



Safety Data Sheet

acc. to Hazardous Products Regulations (HPR)

2K URETHANE LIGHT GRAY

Version number: GHS 1.0

Date of compilation: 2023-08-30

1 Identification

1.1 Product identifier

Trade name **2K URETHANE LIGHT GRAY**
Product code(s) 43301, 43304, 47401A, 47405

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses Paint

1.3 Details of the supplier of the safety data sheet

P.O.R. Products
38 Portman Road
New Rochelle NY 10801
United States

Telephone: +1 914-636-0700
e-mail: support@porproducts.com
Website: www.porproducts.com

e-mail (competent person) support@porproducts.com

1.4 Emergency telephone number

Emergency information service 1-800-255-3924
ChemTel Inc.

2 Hazard identification

2.1 Classification of the substance or mixture

Classification acc. to GHS

Section	Hazard class	Category	Hazard class and category	Hazard statement
2.6	flammable liquid	3	Flam. Liq. 3	H226
3.2	skin corrosion/irritation	2	Skin Irrit. 2	H315
3.5	germ cell mutagenicity	2	Muta. 2	H341
3.7	reproductive toxicity	1B	Repr. 1B	H360FD
3.9	specific target organ toxicity - repeated exposure	1	STOT RE 1	H372
3.10	aspiration hazard	1	Asp. Tox. 1	H304

For full text of abbreviations: see SECTION 16.

The most important adverse physicochemical, human health and environmental effects

Delayed or immediate effects can be expected after short or long-term exposure. The product is combustible and can be ignited by potential ignition sources.

2.2 Label elements

Labeling

- Signal word danger

2K URETHANE LIGHT GRAY

Version number: GHS 1.0

Date of compilation: 2023-08-30

- Pictograms

GHS02, GHS07, GHS08

**- Hazard statements**

H226	Flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H341	Suspected of causing genetic defects.
H360FD	May damage fertility. May damage the unborn child.
H372	Causes damage to organs through prolonged or repeated exposure.

- Precautionary statements

P201	Obtain special instructions before use.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P233	Keep container tightly closed.
P240	Ground and bond container and receiving equipment.
P241	Use explosion-proof electrical/ventilating/lighting equipment.
P242	Use non-sparking tools.
P243	Take action to prevent static discharges.
P260	Do not breathe dust/fume/gas/mist/vapours/spray.
P270	Do not eat, drink or smoke when using this product.
P280	Wear protective gloves.
P301+P310	IF SWALLOWED: Immediately call a POISON CENTER/doctor.
P302+P352	IF ON SKIN: Wash with plenty of water.
P303+P361+P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.
P308+P313	IF exposed or concerned: Get medical advice/ attention.
P314	Get medical advice/attention if you feel unwell.
P321	Specific treatment (see on this label).
P331	Do NOT induce vomiting.
P332+P313	If skin irritation occurs: Get medical advice/attention.
P362+P364	Take off contaminated clothing and wash it before reuse.
P370+P378	In case of fire: Use sand, carbon dioxide or powder extinguisher to extinguish.
P403+P235	Store in a well-ventilated place. Keep cool.
P405	Store locked up.
P501	Dispose of contents/container to industrial combustion plant.

- Hazardous ingredients for labelling dibutyltin dilaurate, xylene-part, xylene, ethyl benzene

2.3 Other hazards**Results of PBT and vPvB assessment**Does not contain a PBT-/vPvB-substance in a concentration of $\geq 0.1\%$.**Endocrine disrupting properties**Does not contain an endocrine disruptor (EDC) in a concentration of $\geq 0.1\%$.

2K URETHANE LIGHT GRAY

Version number: GHS 1.0

Date of compilation: 2023-08-30

3 Composition/ Information on ingredients

3.1 Substances

Not relevant (mixture)

3.2 Mixtures

Description of the mixture

Name of substance	Identifier	Wt%	Classification acc. to GHS
n-butyl acetate	CAS No 123-86-4	10 - < 30	Flam. Liq. 3 / H226 STOT SE 3 / H336
xylene	CAS No 1330-20-7	5 - < 10	Flam. Liq. 3 / H226 Acute Tox. 4 / H312 Acute Tox. 4 / H332 Skin Irrit. 2 / H315 Asp. Tox. 1 / H304
xylene-part	CAS No 1330-20-7	5 - < 10	Flam. Liq. 3 / H226 Acute Tox. 4 / H312 Acute Tox. 4 / H332 Skin Irrit. 2 / H315 Asp. Tox. 1 / H304
ethyl benzene	CAS No 100-41-4	1 - < 5	Flam. Liq. 3 / H226 Acute Tox. 4 / H332 STOT RE 2 / H373 Asp. Tox. 1 / H304
dibutyltin dilaurate	CAS No 77-58-7	1 - < 5	Muta. 2 / H341 Repr. 1B / H360FD STOT RE 1 / H372
Solvent naphtha (petroleum), light arom.	CAS No 64742-95-6	< 0.1	Flam. Liq. 1 / H224 Muta. 1B / H340 Carc. 1A / H350 Asp. Tox. 1 / H304
1,2,4-trimethylbenzene	CAS No 95-63-6	< 0.1	Flam. Liq. 3 / H226 Acute Tox. 4 / H332 Skin Irrit. 2 / H315 Eye Irrit. 2 / H319 STOT SE 3 / H335 Asp. Tox. 1 / H304
cumene	CAS No 98-82-8	< 0.1	Flam. Liq. 3 / H226 STOT SE 3 / H335 Asp. Tox. 1 / H304
benzene	CAS No 71-43-2	< 0.1	Flam. Liq. 2 / H225 Skin Irrit. 2 / H315 Eye Irrit. 2 / H319 Muta. 1B / H340 Carc. 1A / H350 STOT RE 1 / H372 Asp. Tox. 1 / H304
toluene	CAS No 108-88-3	< 0.1	Flam. Liq. 2 / H225 Skin Irrit. 2 / H315 Repr. 2 / H361d STOT SE 3 / H336 STOT RE 2 / H373 Asp. Tox. 1 / H304

2K URETHANE LIGHT GRAY

Version number: GHS 1.0

Date of compilation: 2023-08-30

Name of substance	Identifier	Wt%	Classification acc. to GHS
naphtha (petroleum), hydrodesulphurized heavy	CAS No 64742-82-1	< 0.1	Flam. Liq. 1 / H224 Muta. 1B / H340 Carc. 1A / H350 STOT RE 1 / H372 Asp. Tox. 1 / H304

For full text of abbreviations: see SECTION 16.

4 First-aid measures

4.1 Description of first-aid measures

General notes

Do not leave affected person unattended. Remove victim out of the danger area. Keep affected person warm, still and covered. Take off immediately all contaminated clothing. In all cases of doubt, or when symptoms persist, seek medical advice. In case of unconsciousness place person in the recovery position. Never give anything by mouth.

Following inhalation

If breathing is irregular or stopped, immediately seek medical assistance and start first aid actions. In case of respiratory tract irritation, consult a physician. Provide fresh air.

Following skin contact

Wash with plenty of soap and water.

Following eye contact

Remove contact lenses, if present and easy to do. Continue rinsing. Irrigate copiously with clean, fresh water for at least 10 minutes, holding the eyelids apart.

Following ingestion

Rinse mouth with water (only if the person is conscious). Do NOT induce vomiting.

4.2 Most important symptoms and effects, both acute and delayed

Symptoms and effects are not known to date.

4.3 Indication of any immediate medical attention and special treatment needed

none

5 Fire-fighting measures

5.1 Extinguishing media

Suitable extinguishing media

Water spray, BC-powder, Carbon dioxide (CO₂)

Unsuitable extinguishing media

Water jet

5.2 Special hazards arising from the substance or mixture

In case of insufficient ventilation and/or in use, may form flammable/explosive vapor-air mixture. Solvent vapors are heavier than air and may spread along floors. Places which are not ventilated, e.g. unventilated below ground level areas such as trenches, conduits and shafts, are particularly prone to the presence of flammable substances or mixtures.

Hazardous combustion products

Carbon monoxide (CO), Carbon dioxide (CO₂)

2K URETHANE LIGHT GRAY

Version number: GHS 1.0

Date of compilation: 2023-08-30

5.3 Advice for firefighters

In case of fire and/or explosion do not breathe fumes. Coordinate firefighting measures to the fire surroundings. Do not allow firefighting water to enter drains or water courses. Collect contaminated firefighting water separately. Fight fire with normal precautions from a reasonable distance.

6 Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

Remove persons to safety.

For emergency responders

Wear breathing apparatus if exposed to vapors/dust/aerosols/gases.

6.2 Environmental precautions

Keep away from drains, surface and ground water. Retain contaminated washing water and dispose of it.

6.3 Methods and material for containment and cleaning up

Advice on how to contain a spill

Covering of drains

Advice on how to clean up a spill

Wipe up with absorbent material (e.g. cloth, fleece). Collect spillage: sawdust, kieselgur (diatomite), sand, universal binder

Appropriate containment techniques

Use of adsorbent materials.

Other information relating to spills and releases

Place in appropriate containers for disposal. Ventilate affected area.

6.4 Reference to other sections

Hazardous combustion products: see section 5. Personal protective equipment: see section 8. Incompatible materials: see section 10. Disposal considerations: see section 13.

7 Handling and storage

7.1 Precautions for safe handling

Recommendations

- Measures to prevent fire as well as aerosol and dust generation

Use local and general ventilation. Avoidance of ignition sources. Keep away from sources of ignition - No smoking. Take precautionary measures against static discharge. Use only in well-ventilated areas. Due to danger of explosion, prevent leakage of vapours into cellars, flues and ditches. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting/equipment. Use only non-sparking tools.

- Specific notes/details

Places which are not ventilated, e.g. unventilated below ground level areas such as trenches, conduits and shafts, are particularly prone to the presence of flammable substances or mixtures. Vapors are heavier than air, spread along floors and form explosive mixtures with air. Vapors may form explosive mixtures with air.

Advice on general occupational hygiene

Wash hands after use. Do not eat, drink and smoke in work areas. Remove contaminated clothing and protective equipment before entering eating areas. Never keep food or drink in the vicinity of chemicals. Never place chemicals in containers that are normally used for food or drink. Keep away from food, drink and animal feedingstuffs.

2K URETHANE LIGHT GRAY

Version number: GHS 1.0

Date of compilation: 2023-08-30

7.2 Conditions for safe storage, including any incompatibilities

Managing of associated risks

- Explosive atmospheres

Keep container tightly closed and in a well-ventilated place. Use local and general ventilation. Keep cool. Protect from sunlight.

- Flammability hazards

Keep away from sources of ignition - No smoking. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Take precautionary measures against static discharge. Protect from sunlight.

- Ventilation requirements

Use local and general ventilation. Ground/bond container and receiving equipment.

- Packaging compatibilities

Only packagings which are approved (e.g. acc. to the Dangerous Goods Regulations) may be used.

7.3 Specific end use(s)

See section 16 for a general overview.

8 Exposure controls/ Personal protection

8.1 Control parameters

Occupational exposure limit values (Workplace Exposure Limits)											
Country	Name of agent	CAS No	Identifier	TWA [ppm]	TWA [mg/m ³]	STEL [ppm]	STEL [mg/m ³]	Ceiling-C [ppm]	Ceiling-C [mg/m ³]	Notation	Source
CA	ethylbenzene	100-41-4	OEL (AB)	100	434	125	543				OHS Code
CA	ethylbenzene	100-41-4	OEL (BC)	20							"BC Regulation"
CA	ethylbenzene	100-41-4	OEL (ON-MoL)	20							MoL
CA	ethylbenzene	100-41-4	PEV/VEA	20							Regulation OHS
CA	toluene	108-88-3	OEL (BC)	20							"BC Regulation"
CA	toluene	108-88-3	OEL (ON-MoL)	20							MoL
CA	toluene	108-88-3	PEV/VEA	20							Regulation OHS
CA	toluene (toluol)	108-88-3	OEL (AB)	50	188					H	OHS Code
CA	n-butyl acetate	123-86-4	OEL (AB)	150	713	200	950				OHS Code
CA	n-butyl acetate	123-86-4	OEL (BC)	50		150					"BC Regulation"

2K URETHANE LIGHT GRAY

Version number: GHS 1.0

Date of compilation: 2023-08-30

Occupational exposure limit values (Workplace Exposure Limits)

Country	Name of agent	CAS No	Identifier	TWA [ppm]	TWA [mg/m ³]	STEL [ppm]	STEL [mg/m ³]	Ceiling-C [ppm]	Ceiling-C [mg/m ³]	Notation	Source
CA	n-butyl acetate	123-86-4	OEL (ON-MoL)	50		150					MoL
CA	n-butyl acetate	123-86-4	PEV/VEA	50		150					Regulation OHS
CA	xylene	1330-20-7	OEL (AB)	100	434	150	651				OHS Code
CA	xylene	1330-20-7	OEL (BC)	100		150					"BC Regulation"
CA	xylene	1330-20-7	OEL (ON-MoL)	100		150					MoL
CA	xylene	1330-20-7	PEV/VEA	100	434	150	651				Regulation OHS
CA	benzene	71-43-2	OEL (AB)	0.5	1.6	2.5	8			H	OHS Code
CA	benzene	71-43-2	OEL (BC)	0.5		2.5				H	"BC Regulation"
CA	benzene	71-43-2	OEL (ON)	0.5		2.5				H	Regulation 833
CA	benzene	71-43-2	OEL (ON-MoL)	0.5		2.5				H	MoL
CA	benzene	71-43-2	PEV/VEA	0.5		2.5				H	Regulation OHS
CA	1,2,4-trimethylbenzene	95-63-6	OEL (BC)	25							"BC Regulation"
CA	cumene	98-82-8	OEL (AB)	50	246						OHS Code
CA	cumene	98-82-8	OEL (BC)	25		75					"BC Regulation"
CA	cumene	98-82-8	OEL (ON-MoL)	50							MoL
CA	cumene	98-82-8	PEV/VEA	50	246						Regulation OHS

Notation

Ceiling-C

H

STEL

TWA

ceiling value is a limit value above which exposure should not occur

absorbed through the skin

short-term exposure limit: a limit value above which exposure should not occur and which is related to a 15-minute period (unless otherwise specified)

time-weighted average (long-term exposure limit): measured or calculated in relation to a reference period of 8 hours time-weighted average (unless otherwise specified)

2K URETHANE LIGHT GRAY

Version number: GHS 1.0

Date of compilation: 2023-08-30

Relevant DNELs of components of the mixture						
Name of substance	CAS No	Endpoint	Threshold level	Protection goal, route of exposure	Used in	Exposure time
xylene	1330-20-7	DNEL	221 mg/m ³	human, inhalatory	worker (industry)	chronic - systemic effects
xylene	1330-20-7	DNEL	442 mg/m ³	human, inhalatory	worker (industry)	acute - systemic effects
xylene	1330-20-7	DNEL	221 mg/m ³	human, inhalatory	worker (industry)	chronic - local effects
xylene	1330-20-7	DNEL	442 mg/m ³	human, inhalatory	worker (industry)	acute - local effects
xylene	1330-20-7	DNEL	212 mg/kg bw/day	human, dermal	worker (industry)	chronic - systemic effects
xylene-part	1330-20-7	DNEL	221 mg/m ³	human, inhalatory	worker (industry)	chronic - systemic effects
xylene-part	1330-20-7	DNEL	442 mg/m ³	human, inhalatory	worker (industry)	acute - systemic effects
xylene-part	1330-20-7	DNEL	221 mg/m ³	human, inhalatory	worker (industry)	chronic - local effects
xylene-part	1330-20-7	DNEL	442 mg/m ³	human, inhalatory	worker (industry)	acute - local effects
xylene-part	1330-20-7	DNEL	212 mg/kg bw/day	human, dermal	worker (industry)	chronic - systemic effects
ethyl benzene	100-41-4	DNEL	77 mg/m ³	human, inhalatory	worker (industry)	chronic - systemic effects
ethyl benzene	100-41-4	DNEL	293 mg/m ³	human, inhalatory	worker (industry)	acute - local effects
ethyl benzene	100-41-4	DNEL	180 mg/kg bw/day	human, dermal	worker (industry)	chronic - systemic effects
dibutyltin dilaurate	77-58-7	DNEL	0.02 mg/m ³	human, inhalatory	worker (industry)	chronic - systemic effects
dibutyltin dilaurate	77-58-7	DNEL	0.059 mg/m ³	human, inhalatory	worker (industry)	acute - systemic effects
dibutyltin dilaurate	77-58-7	DNEL	0.43 mg/kg bw/day	human, dermal	worker (industry)	chronic - systemic effects
dibutyltin dilaurate	77-58-7	DNEL	2.08 mg/kg bw/day	human, dermal	worker (industry)	acute - systemic effects
1,2,4-trimethylbenzene	95-63-6	DNEL	100 mg/m ³	human, inhalatory	worker (industry)	chronic - systemic effects
1,2,4-trimethylbenzene	95-63-6	DNEL	100 mg/m ³	human, inhalatory	worker (industry)	acute - systemic effects
1,2,4-trimethylbenzene	95-63-6	DNEL	100 mg/m ³	human, inhalatory	worker (industry)	chronic - local effects
1,2,4-trimethylbenzene	95-63-6	DNEL	100 mg/m ³	human, inhalatory	worker (industry)	acute - local effects
1,2,4-trimethylbenzene	95-63-6	DNEL	16,171 mg/kg bw/day	human, dermal	worker (industry)	chronic - systemic effects
cumene	98-82-8	DNEL	100 mg/m ³	human, inhalatory	worker (industry)	chronic - systemic effects

2K URETHANE LIGHT GRAY

Version number: GHS 1.0

Date of compilation: 2023-08-30

Relevant DNELs of components of the mixture

Name of substance	CAS No	Endpoint	Threshold level	Protection goal, route of exposure	Used in	Exposure time
cumene	98-82-8	DNEL	250 mg/m ³	human, inhalatory	worker (industry)	acute - local effects
cumene	98-82-8	DNEL	15.4 mg/kg bw/day	human, dermal	worker (industry)	chronic - systemic effects
toluene	108-88-3	DNEL	192 mg/m ³	human, inhalatory	worker (industry)	chronic - systemic effects
toluene	108-88-3	DNEL	384 mg/m ³	human, inhalatory	worker (industry)	acute - systemic effects
toluene	108-88-3	DNEL	192 mg/m ³	human, inhalatory	worker (industry)	chronic - local effects
toluene	108-88-3	DNEL	384 mg/m ³	human, inhalatory	worker (industry)	acute - local effects
toluene	108-88-3	DNEL	384 mg/kg bw/day	human, dermal	worker (industry)	chronic - systemic effects

Relevant PNECs of components of the mixture

Name of substance	CAS No	Endpoint	Threshold level	Organism	Environmental compartment	Exposure time
xylene	1330-20-7	PNEC	0.327 mg/l	aquatic organisms	freshwater	short-term (single instance)
xylene	1330-20-7	PNEC	0.327 mg/l	aquatic organisms	marine water	short-term (single instance)
xylene	1330-20-7	PNEC	6.58 mg/l	aquatic organisms	sewage treatment plant (STP)	short-term (single instance)
xylene	1330-20-7	PNEC	12.46 mg/kg	aquatic organisms	freshwater sediment	short-term (single instance)
xylene	1330-20-7	PNEC	12.46 mg/kg	aquatic organisms	marine sediment	short-term (single instance)
xylene	1330-20-7	PNEC	2.31 mg/kg	terrestrial organisms	soil	short-term (single instance)
xylene-part	1330-20-7	PNEC	0.327 mg/l	aquatic organisms	freshwater	short-term (single instance)
xylene-part	1330-20-7	PNEC	0.327 mg/l	aquatic organisms	marine water	short-term (single instance)
xylene-part	1330-20-7	PNEC	6.58 mg/l	aquatic organisms	sewage treatment plant (STP)	short-term (single instance)
xylene-part	1330-20-7	PNEC	12.46 mg/kg	aquatic organisms	freshwater sediment	short-term (single instance)
xylene-part	1330-20-7	PNEC	12.46 mg/kg	aquatic organisms	marine sediment	short-term (single instance)
xylene-part	1330-20-7	PNEC	2.31 mg/kg	terrestrial organisms	soil	short-term (single instance)

2K URETHANE LIGHT GRAY

Version number: GHS 1.0

Date of compilation: 2023-08-30

Relevant PNECs of components of the mixture						
Name of substance	CAS No	Endpoint	Threshold level	Organism	Environmental compartment	Exposure time
ethyl benzene	100-41-4	PNEC	0.1 mg/l	aquatic organisms	freshwater	short-term (single instance)
ethyl benzene	100-41-4	PNEC	0.01 mg/l	aquatic organisms	marine water	short-term (single instance)
ethyl benzene	100-41-4	PNEC	9.6 mg/l	aquatic organisms	sewage treatment plant (STP)	short-term (single instance)
ethyl benzene	100-41-4	PNEC	13.7 mg/kg	aquatic organisms	freshwater sediment	short-term (single instance)
ethyl benzene	100-41-4	PNEC	1.37 mg/kg	aquatic organisms	marine sediment	short-term (single instance)
ethyl benzene	100-41-4	PNEC	2.68 mg/kg	terrestrial organisms	soil	short-term (single instance)
dibutyltin dilaurate	77-58-7	PNEC	0 mg/l	aquatic organisms	freshwater	short-term (single instance)
dibutyltin dilaurate	77-58-7	PNEC	0 mg/l	aquatic organisms	marine water	short-term (single instance)
dibutyltin dilaurate	77-58-7	PNEC	100 mg/l	aquatic organisms	sewage treatment plant (STP)	short-term (single instance)
dibutyltin dilaurate	77-58-7	PNEC	0.05 mg/kg	aquatic organisms	freshwater sediment	short-term (single instance)
dibutyltin dilaurate	77-58-7	PNEC	0.005 mg/kg	aquatic organisms	marine sediment	short-term (single instance)
dibutyltin dilaurate	77-58-7	PNEC	0.041 mg/kg	terrestrial organisms	soil	short-term (single instance)
1,2,4-trimethylbenzene	95-63-6	PNEC	0.12 mg/l	aquatic organisms	freshwater	short-term (single instance)
1,2,4-trimethylbenzene	95-63-6	PNEC	0.12 mg/l	aquatic organisms	marine water	short-term (single instance)
1,2,4-trimethylbenzene	95-63-6	PNEC	2.41 mg/l	aquatic organisms	sewage treatment plant (STP)	short-term (single instance)
1,2,4-trimethylbenzene	95-63-6	PNEC	13.56 mg/kg	aquatic organisms	freshwater sediment	short-term (single instance)
1,2,4-trimethylbenzene	95-63-6	PNEC	13.56 mg/kg	aquatic organisms	marine sediment	short-term (single instance)
1,2,4-trimethylbenzene	95-63-6	PNEC	2.34 mg/kg	terrestrial organisms	soil	short-term (single instance)
cumene	98-82-8	PNEC	0.035 mg/l	aquatic organisms	freshwater	short-term (single instance)
cumene	98-82-8	PNEC	0.004 mg/l	aquatic organisms	marine water	short-term (single instance)

2K URETHANE LIGHT GRAY

Version number: GHS 1.0

Date of compilation: 2023-08-30

Relevant PNECs of components of the mixture						
Name of substance	CAS No	Endpoint	Threshold level	Organism	Environmental compartment	Exposure time
cumene	98-82-8	PNEC	200 mg/l	aquatic organisms	sewage treatment plant (STP)	short-term (single instance)
cumene	98-82-8	PNEC	3.22 mg/kg	aquatic organisms	freshwater sediment	short-term (single instance)
cumene	98-82-8	PNEC	0.322 mg/kg	aquatic organisms	marine sediment	short-term (single instance)
cumene	98-82-8	PNEC	0.624 mg/kg	terrestrial organisms	soil	short-term (single instance)
toluene	108-88-3	PNEC	0.68 mg/l	aquatic organisms	freshwater	short-term (single instance)
toluene	108-88-3	PNEC	0.68 mg/l	aquatic organisms	marine water	short-term (single instance)
toluene	108-88-3	PNEC	13.61 mg/l	aquatic organisms	sewage treatment plant (STP)	short-term (single instance)
toluene	108-88-3	PNEC	16.39 mg/kg	aquatic organisms	freshwater sediment	short-term (single instance)
toluene	108-88-3	PNEC	16.39 mg/kg	aquatic organisms	marine sediment	short-term (single instance)
toluene	108-88-3	PNEC	2.89 mg/kg	terrestrial organisms	soil	short-term (single instance)
benzene	71-43-2	PNEC	1.9 mg/l	aquatic organisms	freshwater	short-term (single instance)
benzene	71-43-2	PNEC	1.9 mg/l	aquatic organisms	marine water	short-term (single instance)
benzene	71-43-2	PNEC	39 mg/l	aquatic organisms	sewage treatment plant (STP)	short-term (single instance)
benzene	71-43-2	PNEC	33 mg/kg	aquatic organisms	freshwater sediment	short-term (single instance)
benzene	71-43-2	PNEC	33 mg/kg	aquatic organisms	marine sediment	short-term (single instance)
benzene	71-43-2	PNEC	4.8 mg/kg	terrestrial organisms	soil	short-term (single instance)

8.2 Exposure controls

Appropriate engineering controls

General ventilation.

Individual protection measures (personal protective equipment)

Eye/face protection

Wear eye/face protection.

2K URETHANE LIGHT GRAY

Version number: GHS 1.0

Date of compilation: 2023-08-30

Skin protection

- Hand protection

Wear suitable gloves. Chemical protection gloves are suitable, which are tested according to EN 374. Check leak-tightness/impermeability prior to use. In the case of wanting to use the gloves again, clean them before taking off and air them well. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

- Other protection measures

Take recovery periods for skin regeneration. Preventive skin protection (barrier creams/ointments) is recommended. Wash hands thoroughly after handling.

Respiratory protection

In case of inadequate ventilation wear respiratory protection.

Environmental exposure controls

Use appropriate container to avoid environmental contamination. Keep away from drains, surface and ground water.

9 Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state	liquid
Color	not determined
Odor	characteristic
Melting point/freezing point	not determined
Boiling point or initial boiling point and boiling range	126.2 °C at 1,013 hPa
Flammability	flammable liquid in accordance with GHS criteria
Lower and upper explosion limit	1.1 vol% - 7 vol%
Flash point	23 °C at 1,013 hPa
Auto-ignition temperature	≥400 °C (auto-ignition temperature (liquids and gases))
Decomposition temperature	not relevant
pH (value)	not determined
Kinematic viscosity	not determined
Solubility(ies)	not determined

Partition coefficient

Partition coefficient n-octanol/water (log value)	this information is not available
---	-----------------------------------

2K URETHANE LIGHT GRAY

Version number: GHS 1.0

Date of compilation: 2023-08-30

Vapor pressure	0.207 PSI at 85 °F
----------------	--------------------

Density and/or relative density

Density	not determined
Relative vapour density	information on this property is not available

Particle characteristics	not relevant (liquid)
--------------------------	-----------------------

9.2 Other information

Information with regard to physical hazard classes	there is no additional information
--	------------------------------------

Other safety characteristics

Solid content	1 %
---------------	-----

10 Stability and reactivity

10.1 Reactivity

Concerning incompatibility: see below "Conditions to avoid" and "Incompatible materials". The mixture contains reactive substance(s). Risk of ignition.

If heated:

Risk of ignition

10.2 Chemical stability

See below "Conditions to avoid".

10.3 Possibility of hazardous reactions

No known hazardous reactions.

10.4 Conditions to avoid

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Hints to prevent fire or explosion

Use explosion-proof electrical/ventilating/lighting/equipment. Use only non-sparking tools. Take precautionary measures against static discharge.

10.5 Incompatible materials

Oxidizers

10.6 Hazardous decomposition products

Reasonably anticipated hazardous decomposition products produced as a result of use, storage, spill and heating are not known. Hazardous combustion products: see section 5.

2K URETHANE LIGHT GRAY

Version number: GHS 1.0

Date of compilation: 2023-08-30

11 Toxicological information

11.1 Information on toxicological effects

Test data are not available for the complete mixture.

Classification procedure

The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

Classification acc. to GHS

Acute toxicity

Shall not be classified as acutely toxic.

Acute toxicity estimate (ATE) of components of the mixture			
Name of substance	CAS No	Exposure route	ATE
xylene	1330-20-7	dermal	1,100 mg/kg
xylene	1330-20-7	inhalation: vapour	11 mg/l/4h
xylene-part	1330-20-7	dermal	1,100 mg/kg
xylene-part	1330-20-7	inhalation: vapour	11 mg/l/4h
ethyl benzene	100-41-4	inhalation: vapour	11 mg/l/4h
1,2,4-trimethylbenzene	95-63-6	inhalation: vapour	11 mg/l/4h

Skin corrosion/irritation

Causes skin irritation.

Serious eye damage/eye irritation

Shall not be classified as seriously damaging to the eye or eye irritant.

Respiratory or skin sensitization

Shall not be classified as a respiratory or skin sensitizer.

Germ cell mutagenicity

Suspected of causing genetic defects.

Carcinogenicity

Shall not be classified as carcinogenic.

Reproductive toxicity

May damage the unborn child. May damage fertility.

Specific target organ toxicity - single exposure

Shall not be classified as a specific target organ toxicant (single exposure).

Specific target organ toxicity - repeated exposure

Causes damage to organs through prolonged or repeated exposure.

Aspiration hazard

May be fatal if swallowed and enters airways.

2K URETHANE LIGHT GRAY

Version number: GHS 1.0

Date of compilation: 2023-08-30

12 Ecological information

12.1 Toxicity

Harmful to aquatic life.

Aquatic toxicity (acute) of components of the mixture					
Name of substance	CAS No	Endpoint	Value	Species	Exposure time
n-butyl acetate	123-86-4	LC50	18 mg/l	fish	96 h
n-butyl acetate	123-86-4	EC50	18 mg/l	fish	96 h
n-butyl acetate	123-86-4	ErC50	335 mg/l	algae	24 h
xylene	1330-20-7	LC50	8.4 mg/l	fish	96 h
xylene	1330-20-7	EC50	4.9 mg/l	algae	72 h
xylene	1330-20-7	ErC50	4.7 mg/l	algae	72 h
xylene-part	1330-20-7	LC50	8.4 mg/l	fish	96 h
xylene-part	1330-20-7	EC50	4.9 mg/l	algae	72 h
xylene-part	1330-20-7	ErC50	4.7 mg/l	algae	72 h
ethyl benzene	100-41-4	LC50	7 mg/l	fish	24 h
ethyl benzene	100-41-4	EC50	2.4 mg/l	aquatic invertebrates	48 h
dibutyltin dilaurate	77-58-7	LC50	21.2 mg/l	fish	96 h
dibutyltin dilaurate	77-58-7	EC50	3.4 mg/l	aquatic invertebrates	48 h
Solvent naphtha (petroleum), light arom.	64742-95-6	LL50	8.2 mg/l	fish	96 h
Solvent naphtha (petroleum), light arom.	64742-95-6	EL50	4.5 mg/l	aquatic invertebrates	48 h
1,2,4-trimethylbenzene	95-63-6	LC50	7.72 mg/l	fish	96 h
1,2,4-trimethylbenzene	95-63-6	EC50	2.356 mg/l	algae	96 h
cumene	98-82-8	LC50	4.7 mg/l	fish	96 h
cumene	98-82-8	EC50	2.14 mg/l	aquatic invertebrates	48 h
cumene	98-82-8	ErC50	2.01 mg/l	algae	72 h
toluene	108-88-3	LC50	5.5 mg/l	fish	96 h
toluene	108-88-3	EC50	84 mg/l	microorganisms	24 h
benzene	71-43-2	LC50	5.3 mg/l	fish	96 h
benzene	71-43-2	EC50	10 mg/l	aquatic invertebrates	24 h
benzene	71-43-2	ErC50	100 mg/l	algae	72 h

2K URETHANE LIGHT GRAY

Version number: GHS 1.0

Date of compilation: 2023-08-30

Aquatic toxicity (acute) of components of the mixture					
Name of substance	CAS No	Endpoint	Value	Species	Exposure time
naphtha (petroleum), hydrodesulphurized heavy	64742-82-1	LL50	8.2 mg/l	fish	96 h
naphtha (petroleum), hydrodesulphurized heavy	64742-82-1	EL50	4.5 mg/l	aquatic invertebrates	48 h

12.2 Persistence and degradability

Data are not available.

12.3 Bioaccumulative potential

Data are not available.

12.4 Mobility in soil

Data are not available.

12.5 Results of PBT and vPvB assessment

According to the results of its assessment, this substance is not a PBT or a vPvB. Does not contain a PBT-/vPvB-substance in a concentration of $\geq 0.1\%$.

12.6 Endocrine disrupting properties

Does not contain an endocrine disruptor (EDC) in a concentration of $\geq 0.1\%$.

12.7 Other adverse effects

Data are not available.

13 Disposal considerations

13.1 Waste treatment methods

Waste treatment-relevant information

Solvent reclamation/regeneration.

Sewage disposal-relevant information

Do not empty into drains. Avoid release to the environment. Refer to special instructions/safety data sheets.

Waste treatment of containers/packages

Only packagings which are approved (e.g. acc. to the Dangerous Goods Regulations) may be used. Completely emptied packages can be recycled. Handle contaminated packages in the same way as the substance itself.

Remarks

Please consider the relevant national or regional provisions. Waste shall be separated into the categories that can be handled separately by the local or national waste management facilities.

2K URETHANE LIGHT GRAY

Version number: GHS 1.0

Date of compilation: 2023-08-30

14 Transport information

14.1 UN number

UN RTDG	UN 1263
IMDG-Code	UN 1263
ICAO-TI	UN 1263

14.2 UN proper shipping name

UN RTDG	PAINT
IMDG-Code	PAINT
ICAO-TI	Paint

14.3 Transport hazard class(es)

UN RTDG	3
IMDG-Code	3
ICAO-TI	3

14.4 Packing group

UN RTDG	III
IMDG-Code	III
ICAO-TI	III

14.5 Environmental hazards

non-environmentally hazardous acc. to the dangerous goods regulations

14.6 Special precautions for user

There is no additional information.

14.7 Transport in bulk according to IMO instruments

The cargo is not intended to be carried in bulk.

Information for each of the UN Model Regulations

Transport information - National regulations - Additional information (UN RTDG)

UN number	1263
Class	3
Packing group	III
Danger label(s)	3



Special provisions (SP)	163, 223, 367 (UN RTDG)
Excepted quantities (EQ)	E1 (UN RTDG)
Limited quantities (LQ)	5 L (UN RTDG)

2K URETHANE LIGHT GRAY

Version number: GHS 1.0

Date of compilation: 2023-08-30

International Maritime Dangerous Goods Code (IMDG) - Additional information

Marine pollutant -
 Danger label(s) 3



Special provisions (SP) 163, 223, 367, 955
 Excepted quantities (EQ) E1
 Limited quantities (LQ) 5 L
 EmS F-E, S-E
 Stowage category A

International Civil Aviation Organization (ICAO-IATA/DGR) - Additional information

Danger label(s) 3



Special provisions (SP) A3, A72, A192
 Excepted quantities (EQ) E1
 Limited quantities (LQ) 10 L

15 Regulatory information

15.1 Safety, health and environmental regulations specific for the product in question

National regulations (United States)

Toxic Substance Control Act (TSCA) not all ingredients are listed (ACTIVE)

Superfund Amendment and Reauthorization Act (SARA TITLE III)

- The List of Extremely Hazardous Substances and Their Threshold Planning Quantities (EPCRA Section 302, 304)

none of the ingredients are listed

- Specific Toxic Chemical Listings (EPCRA Section 313)

Toxics Release Inventory: Specific Toxic Chemical Listings

Name of substance	CAS No	Remarks	Effective date
ethyl benzene	100-41-4		1986-12-31
benzene	71-43-2		1986-12-31
1,2,4-trimethylbenzene	95-63-6		1986-12-31
cumene	98-82-8		1986-12-31
toluene	108-88-3		1986-12-31
xylene	1330-20-7		1986-12-31



Safety Data Sheet

acc. to Hazardous Products Regulations (HPR)

2K URETHANE LIGHT GRAY

Version number: GHS 1.0

Date of compilation: 2023-08-30

Toxics Release Inventory: Specific Toxic Chemical Listings

Name of substance	CAS No	Remarks	Effective date
xylene-part	1330-20-7		1986-12-31

Comprehensive Environmental Response, Compensation, and Liability Act (CERCLA)

- List of Hazardous Substances and Reportable Quantities (CERCLA section 102a) (40 CFR 302.4)

Name of substance	CAS No	Remarks	Statutory code	Final RQ pounds (Kg)
ethyl benzene	100-41-4		1 2 3	1000 (454)
benzene	71-43-2	a	1 2 3 4	10 (4,54)
cumene	98-82-8		3 4	5000 (2270)
toluene	108-88-3		1 2 3 4	1000 (454)
xylene	1330-20-7		1 3 4	100 (45,4)
n-butyl acetate	123-86-4		1	5000 (2270)
xylene-part	1330-20-7		1 3 4	100 (45,4)

Legend

- 1 "1" indicates that the statutory source is section 311(b)(2) of the Clean Water Act
- 2 "2" indicates that the source is section 307(a) of the Clean Water Act
- 3 "3" indicates that the source is section 112 of the Clean Air Act
- 4 "4" indicates that the source is section 3001 of the Resource Conservation and Recovery Act (RCRA)
- a Benzene was already a CERCLA hazardous substance prior to the CAA Amendments of 1990 and received an adjusted 10-pound RQ based on potential carcinogenicity in an August 14, 1989, final rule (54 FR 33418). The CAA Amendments specify that "benzene (including benzene from gasoline)" is a hazardous air pollutant and, thus, a CERCLA hazardous substance.

Clean Air Act

none of the ingredients are listed

Right to Know Hazardous Substance List

- Cleaning Product Right to Know Act Substance List (CA-RTK)

Name of substance	CAS No	Functionality	Authoritative Lists
xylene	1330-20-7		ATSDR Neurotoxicants CA MCLs CA TACs CDC 4th National Exposure Report IRIS Neurotoxicants OEHA RELs



Safety Data Sheet

acc. to Hazardous Products Regulations (HPR)

2K URETHANE LIGHT GRAY

Version number: GHS 1.0

Date of compilation: 2023-08-30

Name of substance	CAS No	Functionality	Authoritative Lists
xylene-part	1330-20-7		ATSDR Neurotoxicants CA MCLs CA TACs CDC 4th National Exposure Report IRIS Neurotoxicants OEHHA RELs
ethyl benzene	100-41-4		ATSDR Neurotoxicants CA MCLs CA TACs CDC 4th National Exposure Report CWA 303(c) IARC Carcinogens - 2B OEHHA RELs Prop 65
dibutyltin dilaurate	7440-31-5		OSPAR Priority Action Part A
Solvent naphtha (petroleum), light arom.	64742-95-6		EC Annex VI CMRs - Cat. 1B
1,2,4-trimethylbenzene	95-63-6		CA NLS IRIS Neurotoxicants
cumene	98-82-8		CA NLS CA TACs CDC 4th National Exposure Report IARC Carcinogens - 2B NTP 13th RoC - reasonable OEHHA RELs Prop 65
benzene	71-43-2		ATSDR Neurotoxicants CA MCLs CA TACs CDC 4th National Exposure Report CWA 303(c) EC Annex VI CMRs - Cat. 1A EC Annex VI CMRs - Cat. 1B IARC Carcinogens - 1 IRIS Carcinogens - A NTP 13th RoC - known OEHHA RELs Prop 65
toluene	108-88-3		ATSDR Neurotoxicants CA MCLs CA TACs CDC 4th National Exposure Report CWA 303(c) IRIS Neurotoxicants OEHHA RELs Prop 65
naphtha (petroleum), hydrodesulphurized heavy	64742-82-1		Canada PBiTs EC Annex VI CMRs - Cat. 1B

- Toxic or Hazardous Substance List (MA-TURA)



Safety Data Sheet

acc. to Hazardous Products Regulations (HPR)

2K URETHANE LIGHT GRAY

Version number: GHS 1.0

Date of compilation: 2023-08-30

Name of substance	CAS No	DEP CODE	PBT / HHS / LHS	PBT / HHS Threshold	De Minimis Concentration Threshold
ethyl benzene	100-41-4				0.1 %
benzene	71-43-2				1.0 %
1,2,4-trimethylbenzene	95-63-6				1.0 %
cumene	98-82-8				0.1 %
toluene	108-88-3				1.0 %
xylene	1330-20-7				1.0 %
n-butyl acetate	123-86-4		LHS		1.0 %
xylene-part	1330-20-7				1.0 %

- Hazardous Substances List (MN-ERTK)

Name of substance	CAS No	References	Remarks
ethyl benzene	100-41-4	A, O	
dibutyltin dilaurate		N, O	
dibutyltin dilaurate		A	skin
xylene	1330-20-7	A, N, O	
n-butyl acetate	123-86-4	A, O	
xylene-part	1330-20-7	A, N, O	

Legend

- A American Conference of Governmental Industrial Hygienists (ACGIH), "Threshold Limit Values for Chemical Substances and Physical Agents and Biological Exposure Indices for 1992-93", available from ACGIH
- N National Institute for Occupational Safety and Health (NIOSH), "Recommendations for Occupational Safety and Health Standards," August 1988, available from NIOSH, Publications Dissemination Office, Division of Standards Development and Technology Transfer
- O Occupational Safety and Health Administration (OSHA), Safety and Health Standards, Code of Federal Regulations, title 29, part 1910, subpart Z, "Toxic and Hazardous Substances, 1990." General information: Minnesota Department of Labor and Industry, Occupational Safety and Health Division
- skin If a potential for absorption from skin contact merits special consideration, the word "skin" follows the substance name.

- Hazardous Substance List (NJ-RTK)

Name of substance	CAS No	Remarks	Classifications
ethyl benzene	100-41-4		CA F3
naphtha (petroleum), hydrodesulphurized heavy	8052-41-3		F2
benzene	71-43-2		CA MU F3
1,2,4-trimethylbenzene	95-63-6		F2
cumene	98-82-8		F3 R1

2K URETHANE LIGHT GRAY

Version number: GHS 1.0

Date of compilation: 2023-08-30

Name of substance	CAS No	Remarks	Classifications
toluene	108-88-3		TE F3
xylene	1330-20-7		F3
n-butyl acetate	123-86-4		F3
xylene-part	1330-20-7		F3

Legend

CA Carcinogenic
 F2 Flammable - Second Degree
 F3 Flammable - Third Degree
 MU Mutagenic
 R1 Reactive - First Degree
 TE Teratogenic

- Hazardous Substance List (Chapter 323) (PA-RTK)

Name acc. to inventory	CAS No	Classification
BENZENE, ETHYL-	100-41-4	E
BENZENE, DIMETHYL-	1330-20-7	E
ACETIC ACID, BUTYL ESTER	123-86-4	E
BENZENE, DIMETHYL-	1330-20-7	E

Legend

E Environmental hazard

- Hazardous Substance List (RI-RTK)

Name of substance	CAS No	References
ethyl benzene	100-41-4	T, F
naphtha (petroleum), hydrodesulphurized heavy	8052-41-3	T
benzene	71-43-2	T, F, C
dibutyltin dilaurate	7440-31-5	T
1,2,4-trimethylbenzene	25551-13-7	T
cumene	98-82-8	T, F
toluene	108-88-3	T, F
toluene	108-88-3	T, F
toluene	108-88-3	T, F
xylene	1330-20-7	T, F
xylene	1330-20-7	T, F
xylene	1330-20-7	T, F
n-butyl acetate	123-86-4	T, F



Safety Data Sheet

acc. to Hazardous Products Regulations (HPR)

2K URETHANE LIGHT GRAY

Version number: GHS 1.0

Date of compilation: 2023-08-30

Name of substance	CAS No	References
xylene-part	1330-20-7	T, F
xylene-part	1330-20-7	T, F
xylene-part	1330-20-7	T, F

Legend

C Carcinogenicity (IARC)
 F Flammability (NFPA®)
 T Toxicity (ACGIH®)

California Environmental Protection Agency (Cal/EPA): Proposition 65 - Safe Drinking Water and Toxic Enforcement Act of 1987

Proposition 65 List of chemicals			
Name acc. to inventory	CAS No	Remarks	Type of the toxicity
ethylbenzene	100-41-4		cancer
benzene	71-43-2		cancer
benzene	71-43-2		developmental, male
cumene	98-82-8		cancer
toluene	108-88-3		developmental

Industry or sector specific available guidance(s)

NPCA-HMIS® III

Hazardous Materials Identification System. American Coatings Association.

Category	Rating	Description
Chronic	*	chronic (long-term) health effects may result from repeated overexposure
Health	2	temporary or minor injury may occur
Flammability	3	material that can be ignited under almost all ambient temperature conditions
Physical hazard	0	material that is normally stable, even under fire conditions, and will not react with water, polymerize, decompose, condense, or self-react. Non-explosive
Personal protection	-	

NFPA® 704

National Fire Protection Association: Standard System for the Identification of the Hazards of Materials for Emergency Response (United States).



Safety Data Sheet

acc. to Hazardous Products Regulations (HPR)

2K URETHANE LIGHT GRAY

Version number: GHS 1.0

Date of compilation: 2023-08-30

Category	Degree of hazard	Description
Flammability	3	material that can be ignited under almost all ambient temperature conditions
Health	2	material that, under emergency conditions, can cause temporary incapacitation or residual injury
Instability	0	material that is normally stable, even under fire conditions
Special hazard		

National regulations (Canada)

Domestic Substances List (DSL)/Non-domestic Substances List (NDSL)

All ingredients are listed or exempt from listing.

National inventories

Country	Inventory	Status
US	TSCA	not all ingredients are listed

Legend

TSCA Toxic Substance Control Act

15.2 Chemical Safety Assessment

Chemical safety assessments for substances in this mixture were not carried out.

16 Other information

Key literature references and sources for data

Hazardous Products Regulations (HPR)

SOR/2022-272: Regulations Amending the Hazardous Products Regulations (GHS, Seventh Revised Edition)

UN Recommendations on the Transport of Dangerous Good. International Maritime Dangerous Goods Code (IMDG). Dangerous Goods Regulations (DGR) for the air transport (IATA).

Classification procedure

Physical and chemical properties: The classification is based on tested mixture.

Health hazards, Environmental hazards: The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

Disclaimer

This information is based upon the present state of our knowledge. This SDS has been compiled and is solely intended for this product.