



Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

POR-15 2K URETHANE LIGHT GRAY

Version number: GHS 2.0
Replaces version of: 2022-03-28 (GHS 1)

Revision: 2023-12-07

SECTION 1: Identification

1.1 Product identifier

Trade name **POR-15 2K URETHANE LIGHT GRAY**
Product code(s) 43301, 43304, 47401A, 47405

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses Paint

1.3 Details of the supplier of the safety data sheet

P.O.R. Products
38 Portman Road
New Rochelle NY 10801
United States

Telephone: +1 914-636-0700
e-mail: support@porproducts.com
Website: www.porproducts.com

e-mail (competent person) support@porproducts.com

1.4 Emergency telephone number

Emergency information service 1-800-255-3924
ChemTel Inc.

SECTION 2: Hazard(s) identification

2.1 Classification of the substance or mixture

Classification acc. to OSHA "Hazard Communication Standard" (29 CFR 1910.1200)

Section	Hazard class	Category	Hazard class and category	Hazard statement
A.2	skin corrosion/irritation	2	Skin Irrit. 2	H315
A.5	germ cell mutagenicity	2	Muta. 2	H341
A.6	carcinogenicity	2	Carc. 2	H351
A.7	reproductive toxicity	1B	Repr. 1B	H360FD
A.9	specific target organ toxicity - repeated exposure	1	STOT RE 1	H372
A.10	aspiration hazard	1	Asp. Tox. 1	H304
B.6	flammable liquid	3	Flam. Liq. 3	H226

For full text of abbreviations: see SECTION 16.

The most important adverse physicochemical, human health and environmental effects

Delayed or immediate effects can be expected after short or long-term exposure. The product is combustible and can be ignited by potential ignition sources.

2.2 Label elements

POR-15 2K URETHANE LIGHT GRAYVersion number: GHS 2.0
Replaces version of: 2022-03-28 (GHS 1)

Revision: 2023-12-07

Labelling acc. to OSHA "Hazard Communication Standard" (29 CFR 1910.1200)

- Signal word danger

- Pictograms

GHS02, GHS07, GHS08



- Hazard statements

H226	Flammable liquid and vapor.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H341	Suspected of causing genetic defects.
H351	Suspected of causing cancer.
H360FD	May damage fertility. May damage the unborn child.
H372	Causes damage to organs through prolonged or repeated exposure.

- Precautionary statements

P201	Obtain special instructions before use.
P210	Keep away from heat/sparks/open flames/hot surfaces. No smoking.
P233	Keep container tightly closed.
P240	Ground/bond container and receiving equipment.
P241	Use explosion-proof electrical/ventilating/lighting equipment.
P242	Use only non-sparking tools.
P243	Take precautionary measures against static discharge.
P260	Do not breathe dust/fume/gas/mist/vapors/spray.
P270	Do not eat, drink or smoke when using this product.
P280	Wear protective gloves/eye protection/face protection.
P301+P310	If swallowed: Immediately call a poison center/doctor.
P302+P352	If on skin: Wash with plenty of water.
P303+P361+P353	If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
P308+P313	If exposed or concerned: Get medical advice/attention.
P314	Get medical advice/attention if you feel unwell.
P321	Specific treatment (see on this label).
P331	Do NOT induce vomiting.
P332+P313	If skin irritation occurs: Get medical advice/attention.
P362	Take off contaminated clothing and wash before reuse.
P370+P378	In case of fire: Use sand, carbon dioxide or powder extinguisher to extinguish.
P403+P235	Store in a well-ventilated place. Keep cool.
P405	Store locked up.
P501	Dispose of contents/container to industrial combustion plant.

- Hazardous ingredients for labelling ethyl benzene, dibutyltin dilaurate, xylene

2.3 Other hazards

Results of PBT and vPvB assessment

Does not contain a PBT-/vPvB-substance in a concentration of $\geq 0.1\%$.

Endocrine disrupting properties

Does not contain an endocrine disruptor (EDC) in a concentration of $\geq 0.1\%$.



Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

POR-15 2K URETHANE LIGHT GRAY

Version number: GHS 2.0
Replaces version of: 2022-03-28 (GHS 1)

Revision: 2023-12-07

SECTION 3: Composition/information on ingredients

3.1 Substances

Not relevant (mixture)

3.2 Mixtures

Description of the mixture

Name of substance	Identifier	Wt%	Classification acc. to GHS
G-CURE 192BL80/ 27-0192	CAS No n/a	50 - < 75	
n-butyl acetate	CAS No 123-86-4	10 - < 25	STOT SE 3 / H336 Flam. Liq. 3 / H226
xylene	CAS No 1330-20-7	5 - < 10	Acute Tox. 4 / H312 Acute Tox. 4 / H332 Skin Irrit. 2 / H315 Asp. Tox. 1 / H304 Flam. Liq. 3 / H226
xylene	CAS No 1330-20-7	5 - < 10	Acute Tox. 4 / H312 Acute Tox. 4 / H332 Skin Irrit. 2 / H315 Asp. Tox. 1 / H304 Flam. Liq. 3 / H226
ethyl benzene	CAS No 100-41-4	1 - < 5	Acute Tox. 4 / H332 Carc. 2 / H351 STOT RE 2 / H373 Asp. Tox. 1 / H304 Flam. Liq. 3 / H226
dibutyltin dilaurate	CAS No 77-58-7	1 - < 5	Muta. 2 / H341 Repr. 1B / H360FD STOT RE 1 / H372
Solvent naphtha (petroleum), light arom.	CAS No 64742-95-6	0 - < 0.1	Muta. 1B / H340 Carc. 1A / H350 Asp. Tox. 1 / H304 Flam. Liq. 1 / H224
1,2,4-trimethylbenzene	CAS No 95-63-6	0 - < 0.1	Acute Tox. 4 / H332 Skin Irrit. 2 / H315 Eye Irrit. 2 / H319 STOT SE 3 / H335 Asp. Tox. 1 / H304 Flam. Liq. 3 / H226
cumene	CAS No 98-82-8	0 - < 0.1	Carc. 2 / H351 STOT SE 3 / H335 Asp. Tox. 1 / H304 Flam. Liq. 3 / H226
benzene	CAS No 71-43-2	0 - < 0.1	Skin Irrit. 2 / H315 Eye Irrit. 2 / H319 Muta. 1B / H340 Carc. 1A / H350 STOT RE 1 / H372 Asp. Tox. 1 / H304 Flam. Liq. 2 / H225

POR-15 2K URETHANE LIGHT GRAY

Version number: GHS 2.0
Replaces version of: 2022-03-28 (GHS 1)

Revision: 2023-12-07

Name of substance	Identifier	Wt%	Classification acc. to GHS
toluene	CAS No 108-88-3	0 – <0.1	Skin Irrit. 2 / H315 Repr. 2 / H361d STOT SE 3 / H336 STOT RE 2 / H373 Asp. Tox. 1 / H304 Flam. Liq. 2 / H225
Polyacrylat	CAS No N/A	0 – <0.1	

For full text of abbreviations: see SECTION 16.

SECTION 4: First-aid measures

4.1 Description of first-aid measures

General notes

Do not leave affected person unattended. Remove victim out of the danger area. Keep affected person warm, still and covered. Take off immediately all contaminated clothing. In all cases of doubt, or when symptoms persist, seek medical advice. In case of unconsciousness place person in the recovery position. Never give anything by mouth.

Following inhalation

If breathing is irregular or stopped, immediately seek medical assistance and start first aid actions. In case of respiratory tract irritation, consult a physician. Provide fresh air.

Following skin contact

Wash with plenty of soap and water.

Following eye contact

Remove contact lenses, if present and easy to do. Continue rinsing. Irrigate copiously with clean, fresh water for at least 10 minutes, holding the eyelids apart.

Following ingestion

Rinse mouth with water (only if the person is conscious). Do NOT induce vomiting.

4.2 Most important symptoms and effects, both acute and delayed

Symptoms and effects are not known to date.

4.3 Indication of any immediate medical attention and special treatment needed

none

SECTION 5: Fire-fighting measures

5.1 Extinguishing media

Suitable extinguishing media

Water spray, BC-powder, Carbon dioxide (CO₂)

Unsuitable extinguishing media

Water jet

5.2 Special hazards arising from the substance or mixture

In case of insufficient ventilation and/or in use, may form flammable/explosive vapor-air mixture. Solvent vapors are heavier than air and may spread along floors. Places which are not ventilated, e.g. unventilated below ground level areas such as trenches, conduits and shafts, are particularly prone to the presence of flammable substances or mixtures.

POR-15 2K URETHANE LIGHT GRAY

Version number: GHS 2.0
Replaces version of: 2022-03-28 (GHS 1)

Revision: 2023-12-07

Hazardous combustion products
Carbon monoxide (CO), Carbon dioxide (CO₂)

5.3 Advice for firefighters

In case of fire and/or explosion do not breathe fumes. Coordinate firefighting measures to the fire surroundings. Do not allow firefighting water to enter drains or water courses. Collect contaminated firefighting water separately. Fight fire with normal precautions from a reasonable distance.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

Remove persons to safety.

For emergency responders

Wear breathing apparatus if exposed to vapors/dust/aerosols/gases.

6.2 Environmental precautions

Keep away from drains, surface and ground water. Retain contaminated washing water and dispose of it.

6.3 Methods and material for containment and cleaning up

Advice on how to contain a spill

Covering of drains

Advice on how to clean up a spill

Wipe up with absorbent material (e.g. cloth, fleece). Collect spillage: sawdust, kieselgur (diatomite), sand, universal binder

Appropriate containment techniques

Use of adsorbent materials.

Other information relating to spills and releases

Place in appropriate containers for disposal. Ventilate affected area.

6.4 Reference to other sections

Hazardous combustion products: see section 5. Personal protective equipment: see section 8. Incompatible materials: see section 10. Disposal considerations: see section 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Recommendations

- Measures to prevent fire as well as aerosol and dust generation

Use local and general ventilation. Avoidance of ignition sources. Keep away from sources of ignition - No smoking. Take precautionary measures against static discharge. Use only in well-ventilated areas. Due to danger of explosion, prevent leakage of vapours into cellars, flues and ditches. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting/equipment. Use only non-sparking tools.

- Specific notes/details

Places which are not ventilated, e.g. unventilated below ground level areas such as trenches, conduits and shafts, are particularly prone to the presence of flammable substances or mixtures. Vapors are heavier than air, spread along floors and form explosive mixtures with air. Vapors may form explosive mixtures with air.

POR-15 2K URETHANE LIGHT GRAY

Version number: GHS 2.0
Replaces version of: 2022-03-28 (GHS 1)

Revision: 2023-12-07

Advice on general occupational hygiene

Wash hands after use. Do not eat, drink and smoke in work areas. Remove contaminated clothing and protective equipment before entering eating areas. Never keep food or drink in the vicinity of chemicals. Never place chemicals in containers that are normally used for food or drink. Keep away from food, drink and animal feedingstuffs.

7.2 Conditions for safe storage, including any incompatibilities

Managing of associated risks

- Explosive atmospheres

Keep container tightly closed and in a well-ventilated place. Use local and general ventilation. Keep cool. Protect from sunlight.

- Flammability hazards

Keep away from sources of ignition - No smoking. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Take precautionary measures against static discharge. Protect from sunlight.

- Ventilation requirements

Use local and general ventilation. Ground/bond container and receiving equipment.

- Packaging compatibilities

Only packagings which are approved (e.g. acc. to the Dangerous Goods Regulations) may be used.

7.3 Specific end use(s)

See section 16 for a general overview.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limit values (Workplace Exposure Limits)											
Country	Name of agent	CAS No	Identifier	TWA [ppm]	TWA [mg/m ³]	STEL [ppm]	STEL [mg/m ³]	Ceiling-C [ppm]	Ceiling-C [mg/m ³]	Notation	Source
US	ethylbenzene	100-41-4	PEL (CA)	5	22	30	130				Ca/ OSHA PEL
US	ethylbenzene	100-41-4	REL	100 (10 h)	435 (10 h)	125	545				NIOSH REL
US	ethylbenzene	100-41-4	TLV®	20							ACGIH® 2023
US	ethylbenzene	100-41-4	PEL	100	435						29 CFR 1910.1000
US	toluene	108-88-3	REL	100 (10 h)	375 (10 h)	150	560				NIOSH REL
US	toluene	108-88-3	TLV®	20							ACGIH® 2023
US	toluene	108-88-3	PEL	200		500 (10 min)		300			29 CFR 1910.1000



Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

POR-15 2K URETHANE LIGHT GRAY

Version number: GHS 2.0
Replaces version of: 2022-03-28 (GHS 1)

Revision: 2023-12-07

Occupational exposure limit values (Workplace Exposure Limits)

Country	Name of agent	CAS No	Identifier	TWA [ppm]	TWA [mg/m ³]	STEL [ppm]	STEL [mg/m ³]	Ceiling-C [ppm]	Ceiling-C [mg/m ³]	Notation	Source
US	toluene (toluol)	108-88-3	PEL (CA)	10	37	150	560	500			Cal/ OSHA PEL
US	n-butyl acetate	123-86-4	PEL (CA)	150	710	200	950				Cal/ OSHA PEL
US	n-butyl acetate	123-86-4	REL	150 (10 h)	710 (10 h)	200	950				NIOSH REL
US	n-butyl acetate	123-86-4	TLV®	50		150					ACGIH® 2023
US	n-butyl acetate	123-86-4	PEL	150	710						29 CFR 1910.1000
US	xylene, mixture of isomers	1330-20-7	TLV®	20							ACGIH® 2023
US	xylene, mixture of isomers	1330-20-7	PEL	100	435						29 CFR 1910.1000
US	xylene (dimethylbenzene)	1330-20-7	PEL (CA)	100	435	150	655	300			Cal/ OSHA PEL
US	benzene	71-43-2	PEL (CA)	1		5					Cal/ OSHA PEL
US	benzene	71-43-2	PEL	1		5					29 CFR 1910.1000
US	benzene	71-43-2	REL	0.1 (10 h)		1				appx-A	NIOSH REL
US	benzene	71-43-2	TLV®	0.5		2.5				H	ACGIH® 2023
US	benzene	71-43-2	PEL	10		50 (10 min)		25		us-pel-z2a	29 CFR 1910.1000
US	1,2,4-trimethylbenzene	95-63-6	REL	25 (10 h)	125 (10 h)						NIOSH REL
US	1,2,4-trimethylbenzene	95-63-6	TLV®	10							ACGIH® 2023
US	cumene	98-82-8	REL	50 (10 h)	245 (10 h)						NIOSH REL
US	cumene	98-82-8	TLV®	5							ACGIH® 2023



Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

POR-15 2K URETHANE LIGHT GRAY

Version number: GHS 2.0
Replaces version of: 2022-03-28 (GHS 1)

Revision: 2023-12-07

Occupational exposure limit values (Workplace Exposure Limits)

Country	Name of agent	CAS No	Identifier	TWA [ppm]	TWA [mg/m ³]	STEL [ppm]	STEL [mg/m ³]	Ceiling-C [ppm]	Ceiling-C [mg/m ³]	Notation	Source
US	cumene	98-82-8	PEL	50	245						29 CFR 1910.1000
US	cumene (isopropylbenzene)	98-82-8	PEL (CA)	50	245						Cal/OSHA PEL

Notation

appx-A	NIOSH Potential Occupational Carcinogen (Appendix A)
Ceiling-C	ceiling value is a limit value above which exposure should not occur
H	absorbed through the skin
STEL	short-term exposure limit: a limit value above which exposure should not occur and which is related to a 15-minute period (unless otherwise specified)
TWA	time-weighted average (long-term exposure limit): measured or calculated in relation to a reference period of 8 hours time-weighted average (unless otherwise specified)
us-pel-z2a	This standard applies to the industry segments exempt from the 1 ppm 8-hour TWA and 5 ppm STEL of the benzene standard at 1910.1028.

Biological limit values

Country	Name of agent	Parameter	Notation	Identifier	Value	Source
US	ethylbenzene	mandelic acid, benzoylformic acid	crea	BEI®	0.15 g/g	ACGIH® 2023
US	toluene	toluene		BEI®	0.02 mg/l	ACGIH® 2023
US	toluene	toluene		BEI®	0.03 mg/l	ACGIH® 2023
US	toluene	o-cresol	hydr, crea	BEI®	0.3 mg/g	ACGIH® 2023
US	xylene, mixture of isomers	methylhippuric acids	crea	BEI®	1.5 g/g	ACGIH® 2023
US	benzene	S-phenylmercapturic acid	crea	BEI®	25 µg/g	ACGIH® 2023
US	benzene	trans,trans-muconic acid	crea	BEI®	500 µg/g	ACGIH® 2023

Notation

crea	creatinine
hydr	hydrolysis

Relevant DNELs of components of the mixture

Name of substance	CAS No	Endpoint	Threshold level	Protection goal, route of exposure	Used in	Exposure time
xylene	1330-20-7	DNEL	221 mg/m ³	human, inhalatory	worker (industry)	chronic - systemic effects
xylene	1330-20-7	DNEL	442 mg/m ³	human, inhalatory	worker (industry)	acute - systemic effects
xylene	1330-20-7	DNEL	221 mg/m ³	human, inhalatory	worker (industry)	chronic - local effects
xylene	1330-20-7	DNEL	442 mg/m ³	human, inhalatory	worker (industry)	acute - local effects



Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

POR-15 2K URETHANE LIGHT GRAY

Version number: GHS 2.0
Replaces version of: 2022-03-28 (GHS 1)

Revision: 2023-12-07

Relevant DNELs of components of the mixture						
Name of substance	CAS No	Endpoint	Threshold level	Protection goal, route of exposure	Used in	Exposure time
xylene	1330-20-7	DNEL	212 mg/kg bw/day	human, dermal	worker (industry)	chronic - systemic effects
xylene	1330-20-7	DNEL	221 mg/m ³	human, inhalatory	worker (industry)	chronic - systemic effects
xylene	1330-20-7	DNEL	442 mg/m ³	human, inhalatory	worker (industry)	acute - systemic effects
xylene	1330-20-7	DNEL	221 mg/m ³	human, inhalatory	worker (industry)	chronic - local effects
xylene	1330-20-7	DNEL	442 mg/m ³	human, inhalatory	worker (industry)	acute - local effects
xylene	1330-20-7	DNEL	212 mg/kg bw/day	human, dermal	worker (industry)	chronic - systemic effects
ethyl benzene	100-41-4	DNEL	77 mg/m ³	human, inhalatory	worker (industry)	chronic - systemic effects
ethyl benzene	100-41-4	DNEL	293 mg/m ³	human, inhalatory	worker (industry)	acute - local effects
ethyl benzene	100-41-4	DNEL	180 mg/kg bw/day	human, dermal	worker (industry)	chronic - systemic effects
dibutyltin dilaurate	77-58-7	DNEL	0.02 mg/m ³	human, inhalatory	worker (industry)	chronic - systemic effects
dibutyltin dilaurate	77-58-7	DNEL	0.059 mg/m ³	human, inhalatory	worker (industry)	acute - systemic effects
dibutyltin dilaurate	77-58-7	DNEL	0.43 mg/kg bw/day	human, dermal	worker (industry)	chronic - systemic effects
dibutyltin dilaurate	77-58-7	DNEL	2.08 mg/kg bw/day	human, dermal	worker (industry)	acute - systemic effects
1,2,4-trimethylbenzene	95-63-6	DNEL	100 mg/m ³	human, inhalatory	worker (industry)	chronic - systemic effects
1,2,4-trimethylbenzene	95-63-6	DNEL	100 mg/m ³	human, inhalatory	worker (industry)	acute - systemic effects
1,2,4-trimethylbenzene	95-63-6	DNEL	100 mg/m ³	human, inhalatory	worker (industry)	chronic - local effects
1,2,4-trimethylbenzene	95-63-6	DNEL	100 mg/m ³	human, inhalatory	worker (industry)	acute - local effects
1,2,4-trimethylbenzene	95-63-6	DNEL	16,171 mg/kg bw/day	human, dermal	worker (industry)	chronic - systemic effects
cumene	98-82-8	DNEL	100 mg/m ³	human, inhalatory	worker (industry)	chronic - systemic effects
cumene	98-82-8	DNEL	250 mg/m ³	human, inhalatory	worker (industry)	acute - local effects
cumene	98-82-8	DNEL	15.4 mg/kg bw/day	human, dermal	worker (industry)	chronic - systemic effects
toluene	108-88-3	DNEL	192 mg/m ³	human, inhalatory	worker (industry)	chronic - systemic effects



Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

POR-15 2K URETHANE LIGHT GRAY

Version number: GHS 2.0
Replaces version of: 2022-03-28 (GHS 1)

Revision: 2023-12-07

Relevant DNELs of components of the mixture						
Name of substance	CAS No	Endpoint	Threshold level	Protection goal, route of exposure	Used in	Exposure time
toluene	108-88-3	DNEL	384 mg/m ³	human, inhalatory	worker (industry)	acute - systemic effects
toluene	108-88-3	DNEL	192 mg/m ³	human, inhalatory	worker (industry)	chronic - local effects
toluene	108-88-3	DNEL	384 mg/m ³	human, inhalatory	worker (industry)	acute - local effects
toluene	108-88-3	DNEL	384 mg/kg bw/day	human, dermal	worker (industry)	chronic - systemic effects

Relevant PNECs of components of the mixture						
Name of substance	CAS No	Endpoint	Threshold level	Organism	Environmental compartment	Exposure time
xylene	1330-20-7	PNEC	0.327 mg/l	aquatic organisms	freshwater	short-term (single instance)
xylene	1330-20-7	PNEC	0.327 mg/l	aquatic organisms	marine water	short-term (single instance)
xylene	1330-20-7	PNEC	6.58 mg/l	aquatic organisms	sewage treatment plant (STP)	short-term (single instance)
xylene	1330-20-7	PNEC	12.46 mg/kg	aquatic organisms	freshwater sediment	short-term (single instance)
xylene	1330-20-7	PNEC	12.46 mg/kg	aquatic organisms	marine sediment	short-term (single instance)
xylene	1330-20-7	PNEC	2.31 mg/kg	terrestrial organisms	soil	short-term (single instance)
xylene	1330-20-7	PNEC	0.327 mg/l	aquatic organisms	freshwater	short-term (single instance)
xylene	1330-20-7	PNEC	0.327 mg/l	aquatic organisms	marine water	short-term (single instance)
xylene	1330-20-7	PNEC	6.58 mg/l	aquatic organisms	sewage treatment plant (STP)	short-term (single instance)
xylene	1330-20-7	PNEC	12.46 mg/kg	aquatic organisms	freshwater sediment	short-term (single instance)
xylene	1330-20-7	PNEC	12.46 mg/kg	aquatic organisms	marine sediment	short-term (single instance)
xylene	1330-20-7	PNEC	2.31 mg/kg	terrestrial organisms	soil	short-term (single instance)
ethyl benzene	100-41-4	PNEC	0.1 mg/l	aquatic organisms	freshwater	short-term (single instance)
ethyl benzene	100-41-4	PNEC	0.01 mg/l	aquatic organisms	marine water	short-term (single instance)



Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

POR-15 2K URETHANE LIGHT GRAY

Version number: GHS 2.0
Replaces version of: 2022-03-28 (GHS 1)

Revision: 2023-12-07

Relevant PNECs of components of the mixture						
Name of substance	CAS No	Endpoint	Threshold level	Organism	Environmental compartment	Exposure time
ethyl benzene	100-41-4	PNEC	9.6 mg/l	aquatic organisms	sewage treatment plant (STP)	short-term (single instance)
ethyl benzene	100-41-4	PNEC	13.7 mg/kg	aquatic organisms	freshwater sediment	short-term (single instance)
ethyl benzene	100-41-4	PNEC	1.37 mg/kg	aquatic organisms	marine sediment	short-term (single instance)
ethyl benzene	100-41-4	PNEC	2.68 mg/kg	terrestrial organisms	soil	short-term (single instance)
dibutyltin dilaurate	77-58-7	PNEC	0 mg/l	aquatic organisms	freshwater	short-term (single instance)
dibutyltin dilaurate	77-58-7	PNEC	0 mg/l	aquatic organisms	marine water	short-term (single instance)
dibutyltin dilaurate	77-58-7	PNEC	100 mg/l	aquatic organisms	sewage treatment plant (STP)	short-term (single instance)
dibutyltin dilaurate	77-58-7	PNEC	0.05 mg/kg	aquatic organisms	freshwater sediment	short-term (single instance)
dibutyltin dilaurate	77-58-7	PNEC	0.005 mg/kg	aquatic organisms	marine sediment	short-term (single instance)
dibutyltin dilaurate	77-58-7	PNEC	0.041 mg/kg	terrestrial organisms	soil	short-term (single instance)
1,2,4-trimethylbenzene	95-63-6	PNEC	0.12 mg/l	aquatic organisms	freshwater	short-term (single instance)
1,2,4-trimethylbenzene	95-63-6	PNEC	0.12 mg/l	aquatic organisms	marine water	short-term (single instance)
1,2,4-trimethylbenzene	95-63-6	PNEC	2.41 mg/l	aquatic organisms	sewage treatment plant (STP)	short-term (single instance)
1,2,4-trimethylbenzene	95-63-6	PNEC	13.56 mg/kg	aquatic organisms	freshwater sediment	short-term (single instance)
1,2,4-trimethylbenzene	95-63-6	PNEC	13.56 mg/kg	aquatic organisms	marine sediment	short-term (single instance)
1,2,4-trimethylbenzene	95-63-6	PNEC	2.34 mg/kg	terrestrial organisms	soil	short-term (single instance)
cumene	98-82-8	PNEC	0.035 mg/l	aquatic organisms	freshwater	short-term (single instance)
cumene	98-82-8	PNEC	0.004 mg/l	aquatic organisms	marine water	short-term (single instance)
cumene	98-82-8	PNEC	200 mg/l	aquatic organisms	sewage treatment plant (STP)	short-term (single instance)
cumene	98-82-8	PNEC	3.22 mg/kg	aquatic organisms	freshwater sediment	short-term (single instance)

POR-15 2K URETHANE LIGHT GRAY

Version number: GHS 2.0
Replaces version of: 2022-03-28 (GHS 1)

Revision: 2023-12-07

Relevant PNECs of components of the mixture						
Name of substance	CAS No	Endpoint	Threshold level	Organism	Environmental compartment	Exposure time
cumene	98-82-8	PNEC	0.322 mg/kg	aquatic organisms	marine sediment	short-term (single instance)
cumene	98-82-8	PNEC	0.624 mg/kg	terrestrial organisms	soil	short-term (single instance)
toluene	108-88-3	PNEC	0.68 mg/l	aquatic organisms	freshwater	short-term (single instance)
toluene	108-88-3	PNEC	0.68 mg/l	aquatic organisms	marine water	short-term (single instance)
toluene	108-88-3	PNEC	13.61 mg/l	aquatic organisms	sewage treatment plant (STP)	short-term (single instance)
toluene	108-88-3	PNEC	16.39 mg/kg	aquatic organisms	freshwater sediment	short-term (single instance)
toluene	108-88-3	PNEC	16.39 mg/kg	aquatic organisms	marine sediment	short-term (single instance)
toluene	108-88-3	PNEC	2.89 mg/kg	terrestrial organisms	soil	short-term (single instance)
benzene	71-43-2	PNEC	1.9 mg/l	aquatic organisms	freshwater	short-term (single instance)
benzene	71-43-2	PNEC	1.9 mg/l	aquatic organisms	marine water	short-term (single instance)
benzene	71-43-2	PNEC	39 mg/l	aquatic organisms	sewage treatment plant (STP)	short-term (single instance)
benzene	71-43-2	PNEC	33 mg/kg	aquatic organisms	freshwater sediment	short-term (single instance)
benzene	71-43-2	PNEC	33 mg/kg	aquatic organisms	marine sediment	short-term (single instance)
benzene	71-43-2	PNEC	4.8 mg/kg	terrestrial organisms	soil	short-term (single instance)

8.2 Exposure controls

Appropriate engineering controls

General ventilation.

Individual protection measures (personal protective equipment)

Eye/face protection

Wear eye/face protection.

POR-15 2K URETHANE LIGHT GRAY

Version number: GHS 2.0
Replaces version of: 2022-03-28 (GHS 1)

Revision: 2023-12-07

Skin protection

- Hand protection

Wear suitable gloves. Chemical protection gloves are suitable, which are tested according to EN 374. Check leak-tightness/impermeability prior to use. In the case of wanting to use the gloves again, clean them before taking off and air them well. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

- Other protection measures

Take recovery periods for skin regeneration. Preventive skin protection (barrier creams/ointments) is recommended. Wash hands thoroughly after handling.

Respiratory protection

In case of inadequate ventilation wear respiratory protection.

Environmental exposure controls

Use appropriate container to avoid environmental contamination. Keep away from drains, surface and ground water.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance

Physical state	liquid
Color	not determined
Particle	not relevant (liquid)
Odor	characteristic

Other safety parameters

pH (value)	not determined
Melting point/freezing point	not determined
Initial boiling point and boiling range	126.2 °C at 1,013 hPa
Flash point	23 °C at 1,013 hPa
Evaporation rate	Not determined
Flammability (solid, gas)	not relevant, (fluid)

Explosive limits

POR-15 2K URETHANE LIGHT GRAY

Version number: GHS 2.0
Replaces version of: 2022-03-28 (GHS 1)

Revision: 2023-12-07

- Lower explosion limit (LEL)	1.1 vol%
- Upper explosion limit (UEL)	7 vol%
Vapor pressure	0.207 PSI at 85 °F
Density	not determined
Vapor density	this information is not available
Relative density	Information on this property is not available
Solubility(ies)	not determined

Partition coefficient

- n-octanol/water (log KOW)	this information is not available
Auto-ignition temperature	≥400 °C (auto-ignition temperature (liquids and gases))
Viscosity	not determined
Explosive properties	none
Oxidizing properties	none

9.2 Other information

Solid content	1 %
---------------	-----

SECTION 10: Stability and reactivity

10.1 Reactivity

Concerning incompatibility: see below "Conditions to avoid" and "Incompatible materials". The mixture contains reactive substance(s). Risk of ignition.

If heated:

Risk of ignition

10.2 Chemical stability

See below "Conditions to avoid".

10.3 Possibility of hazardous reactions

No known hazardous reactions.

10.4 Conditions to avoid

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Hints to prevent fire or explosion

Use explosion-proof electrical/ventilating/lighting/equipment. Use only non-sparking tools. Take precautionary measures against static discharge.



Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

POR-15 2K URETHANE LIGHT GRAY

Version number: GHS 2.0
Replaces version of: 2022-03-28 (GHS 1)

Revision: 2023-12-07

10.5 Incompatible materials

Oxidizers

10.6 Hazardous decomposition products

Reasonably anticipated hazardous decomposition products produced as a result of use, storage, spill and heating are not known. Hazardous combustion products: see section 5.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Test data are not available for the complete mixture.

Classification procedure

The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

Classification acc. to OSHA "Hazard Communication Standard" (29 CFR 1910.1200)

Acute toxicity

Shall not be classified as acutely toxic.

Acute toxicity estimate (ATE) of components of the mixture

Name of substance	CAS No	Exposure route	ATE
xylene	1330-20-7	dermal	1,100 mg/kg
xylene	1330-20-7	inhalation: vapor	11 mg/l/4h
xylene	1330-20-7	dermal	1,100 mg/kg
xylene	1330-20-7	inhalation: vapor	11 mg/l/4h
ethyl benzene	100-41-4	inhalation: vapor	11 mg/l/4h
1,2,4-trimethylbenzene	95-63-6	inhalation: vapor	11 mg/l/4h

Skin corrosion/irritation

Causes skin irritation.

Serious eye damage/eye irritation

Shall not be classified as seriously damaging to the eye or eye irritant.

Respiratory or skin sensitization

Shall not be classified as a respiratory or skin sensitizer.

Germ cell mutagenicity

Suspected of causing genetic defects.

Carcinogenicity

Suspected of causing cancer.



Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

POR-15 2K URETHANE LIGHT GRAY

Version number: GHS 2.0
Replaces version of: 2022-03-28 (GHS 1)

Revision: 2023-12-07

IARC Monographs on the Evaluation of Carcinogenic Risks to Humans

Name of substance	CAS No	Classification	Number
ethyl benzene	100-41-4	2B	
benzene	71-43-2	1	
cumene	98-82-8	2B	
toluene	108-88-3	3	
xylene	1330-20-7	3	
xylene	1330-20-7	3	

Legend

- 1 Carcinogenic to humans
- 2B Possibly carcinogenic to humans
- 3 Not classifiable as to carcinogenicity in humans

National Toxicology Program (United States): Report on Carcinogens

Name of substance	CAS No	Classification	Number
benzene	71-43-2	Known to be a human carcinogen	1st Report on Carcinogens
cumene	98-82-8	Reasonably anticipated to be a human carcinogen	13th Report on Carcinogens

29 CFR 1910/1915/1926 Occupational Safety and Health Standards: Toxic and Hazardous Substances (carcinogens)

Name of substance	CAS No	Type of registration
benzene	71-43-2	GI §1910.1028, SE §1915.1028, CI §1926.1128

Legend

- CI §1926.1128 Construction Industry (29 CFR 1926.1128)
- GI §1910.1028 General Industry (29 CFR 1910.1028)
- SE §1915.1028 Shipyard Employment (29 CFR 1915.1028)

Reproductive toxicity

May damage the unborn child. May damage fertility.

Specific target organ toxicity - single exposure

Shall not be classified as a specific target organ toxicant (single exposure).

Specific target organ toxicity - repeated exposure

Causes damage to organs through prolonged or repeated exposure.

Aspiration hazard

May be fatal if swallowed and enters airways.

POR-15 2K URETHANE LIGHT GRAY

Version number: GHS 2.0
Replaces version of: 2022-03-28 (GHS 1)

Revision: 2023-12-07

SECTION 12: Ecological information

12.1 Toxicity

Shall not be classified as hazardous to the aquatic environment.

12.2 Persistence and degradability

Data are not available.

12.3 Bioaccumulative potential

Data are not available.

12.4 Mobility in soil

Data are not available.

12.5 Results of PBT and vPvB assessment

According to the results of its assessment, this substance is not a PBT or a vPvB. Does not contain a PBT-/vPvB-substance in a concentration of $\geq 0.1\%$.

12.6 Endocrine disrupting properties

Does not contain an endocrine disruptor (EDC) in a concentration of $\geq 0.1\%$.

12.7 Other adverse effects

Data are not available.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Waste treatment-relevant information

Solvent reclamation/regeneration.

Sewage disposal-relevant information

Do not empty into drains. Avoid release to the environment. Refer to special instructions/safety data sheets.

Waste treatment of containers/packages

Only packagings which are approved (e.g. acc. to DOT) may be used. Completely emptied packages can be recycled. Handle contaminated packages in the same way as the substance itself.

Remarks

Please consider the relevant national or regional provisions. Waste shall be separated into the categories that can be handled separately by the local or national waste management facilities.

SECTION 14: Transport information

14.1 UN number

DOT	UN 1263
IMDG-Code	UN 1263
ICAO-TI	UN 1263

14.2 UN proper shipping name

DOT	Paint
-----	-------

POR-15 2K URETHANE LIGHT GRAY


Version number: GHS 2.0
Replaces version of: 2022-03-28 (GHS 1)

Revision: 2023-12-07

IMDG-Code	PAIN
ICAO-TI	Paint
14.3 Transport hazard class(es)	
DOT	3
IMDG-Code	3
ICAO-TI	3
14.4 Packing group	
DOT	III
IMDG-Code	III
ICAO-TI	III
14.5 Environmental hazards	non-environmentally hazardous acc. to the dangerous goods regulations
14.6 Special precautions for user	
There is no additional information.	
14.7 Transport in bulk according to IMO instruments	
The cargo is not intended to be carried in bulk.	

Information for each of the UN Model Regulations

Transport of dangerous goods by road or rail (49 CFR US DOT) - Additional information

Particulars in the shipper's declaration	UN1263, Paint, 3, III
Reportable quantity (RQ)	1,138 lbs (516.5 kg) (xylene) (xylene)
Danger label(s)	3
	
Special provisions (SP)	367, B1, B52, B131, IB3, T2, TP1, TP29
ERG No	128

International Maritime Dangerous Goods Code (IMDG) - Additional information

Marine pollutant	-
Danger label(s)	3
	
Special provisions (SP)	163, 223, 367, 955
Excepted quantities (EQ)	E1
Limited quantities (LQ)	5 L
EmS	F-E, <u>S-E</u>
Stowage category	A

POR-15 2K URETHANE LIGHT GRAY

Version number: GHS 2.0
Replaces version of: 2022-03-28 (GHS 1)

Revision: 2023-12-07

International Civil Aviation Organization (ICAO-IATA/DGR) - Additional information

Danger label(s) 3



Special provisions (SP) A3, A72, A192

Excepted quantities (EQ) E1

Limited quantities (LQ) 10 L

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations specific for the product in question

National regulations (United States)

Toxic Substance Control Act (TSCA) not all ingredients are listed (ACTIVE)

Superfund Amendment and Reauthorization Act (SARA TITLE III)

- The List of Extremely Hazardous Substances and Their Threshold Planning Quantities (EPCRA Section 302, 304)

none of the ingredients are listed

- Specific Toxic Chemical Listings (EPCRA Section 313)

Toxics Release Inventory: Specific Toxic Chemical Listings

Name of substance	CAS No	Remarks	Effective date
ethyl benzene	100-41-4		1986-12-31
benzene	71-43-2		1986-12-31
1,2,4-trimethylbenzene	95-63-6		1986-12-31
cumene	98-82-8		1986-12-31
toluene	108-88-3		1986-12-31
xylene	1330-20-7		1986-12-31
xylene	1330-20-7		1986-12-31

Comprehensive Environmental Response, Compensation, and Liability Act (CERCLA)

- List of Hazardous Substances and Reportable Quantities (CERCLA section 102a) (40 CFR 302.4)

Name of substance	CAS No	Remarks	Statutory code	Final RQ pounds (Kg)
ethyl benzene	100-41-4		1 2 3	1000 (454)
benzene	71-43-2	a	1 2 3 4	10 (4,54)



Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

POR-15 2K URETHANE LIGHT GRAY

Version number: GHS 2.0
Replaces version of: 2022-03-28 (GHS 1)

Revision: 2023-12-07

Name of substance	CAS No	Remarks	Statutory code	Final RQ pounds (Kg)
cumene	98-82-8		3 4	5000 (2270)
toluene	108-88-3		1 2 3 4	1000 (454)
xylene	1330-20-7		1 3 4	100 (45,4)
n-butyl acetate	123-86-4		1	5000 (2270)
xylene	1330-20-7		1 3 4	100 (45,4)

Legend

- 1 "1" indicates that the statutory source is section 311(b)(2) of the Clean Water Act
- 2 "2" indicates that the source is section 307(a) of the Clean Water Act
- 3 "3" indicates that the source is section 112 of the Clean Air Act
- 4 "4" indicates that the source is section 3001 of the Resource Conservation and Recovery Act (RCRA)
- a Benzene was already a CERCLA hazardous substance prior to the CAA Amendments of 1990 and received an adjusted 10-pound RQ based on potential carcinogenicity in an August 14, 1989, final rule (54 FR 33418). The CAA Amendments specify that "benzene (including benzene from gasoline)" is a hazardous air pollutant and, thus, a CERCLA hazardous substance.

Clean Air Act

none of the ingredients are listed

Right to Know Hazardous Substance List

- Cleaning Product Right to Know Act Substance List (CA-RTK)

Name of substance	CAS No	Functionality	Authoritative Lists
xylene	1330-20-7		ATSDR Neurotoxicants CA MCLs CA TACs CDC 4th National Exposure Report IRIS Neurotoxicants OEHHA RELs
xylene	1330-20-7		ATSDR Neurotoxicants CA MCLs CA TACs CDC 4th National Exposure Report IRIS Neurotoxicants OEHHA RELs
ethyl benzene	100-41-4		ATSDR Neurotoxicants CA MCLs CA TACs CDC 4th National Exposure Report CWA 303(c) IARC Carcinogens - 2B OEHHA RELs Prop 65
dibutyltin dilaurate	7440-31-5		OSPAR Priority Action Part A
Solvent naphtha (petroleum), light arom.	64742-95-6		EC Annex VI CMRs - Cat. 1B



Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

POR-15 2K URETHANE LIGHT GRAY

Version number: GHS 2.0
Replaces version of: 2022-03-28 (GHS 1)

Revision: 2023-12-07

Name of substance	CAS No	Functionality	Authoritative Lists
1,2,4-trimethylbenzene	95-63-6		CA NLS IRIS Neurotoxicants
cumene	98-82-8		CA NLS CA TACs CDC 4th National Exposure Report IARC Carcinogens - 2B NTP 13th RoC - reasonable OEHHA RELs Prop 65
benzene	71-43-2		ATSDR Neurotoxicants CA MCLs CA TACs CDC 4th National Exposure Report CWA 303(c) EC Annex VI CMRs - Cat. 1A EC Annex VI CMRs - Cat. 1B IARC Carcinogens - 1 IRIS Carcinogens - A NTP 13th RoC - known OEHHA RELs Prop 65
toluene	108-88-3		ATSDR Neurotoxicants CA MCLs CA TACs CDC 4th National Exposure Report CWA 303(c) IRIS Neurotoxicants OEHHA RELs Prop 65

- Toxic or Hazardous Substance List (MA-TURA)

Name of substance	CAS No	DEP CODE	PBT / HHS / LHS	PBT / HHS Threshold	De Minimis Concentration Threshold
ethyl benzene	100-41-4				0.1 %
benzene	71-43-2				1.0 %
1,2,4-trimethylbenzene	95-63-6				1.0 %
cumene	98-82-8				0.1 %
toluene	108-88-3				1.0 %
xylene	1330-20-7				1.0 %
n-butyl acetate	123-86-4		LHS		1.0 %
xylene	1330-20-7				1.0 %

- Hazardous Substances List (MN-ERTK)



Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

POR-15 2K URETHANE LIGHT GRAY

Version number: GHS 2.0
Replaces version of: 2022-03-28 (GHS 1)

Revision: 2023-12-07

Name of substance	CAS No	References	Remarks
ethyl benzene	100-41-4	A, O	
dibutyltin dilaurate		N, O	
dibutyltin dilaurate		A	skin
xylene	1330-20-7	A, N, O	
n-butyl acetate	123-86-4	A, O	
xylene	1330-20-7	A, N, O	

Legend

- A American Conference of Governmental Industrial Hygienists (ACGIH), "Threshold Limit Values for Chemical Substances and Physical Agents and Biological Exposure Indices for 1992-93", available from ACGIH
- N National Institute for Occupational Safety and Health (NIOSH), "Recommendations for Occupational Safety and Health Standards," August 1988, available from NIOSH, Publications Dissemination Office, Division of Standards Development and Technology Transfer
- O Occupational Safety and Health Administration (OSHA), Safety and Health Standards, Code of Federal Regulations, title 29, part 1910, subpart Z, "Toxic and Hazardous Substances, 1990." General information: Minnesota Department of Labor and Industry, Occupational Safety and Health Division
- skin If a potential for absorption from skin contact merits special consideration, the word "skin" follows the substance name.

- Hazardous Substance List (NJ-RTK)

Name of substance	CAS No	Remarks	Classifications
ethyl benzene	100-41-4		CA F3
benzene	71-43-2		CA MU F3
1,2,4-trimethylbenzene	95-63-6		F2
cumene	98-82-8		F3 R1
toluene	108-88-3		TE F3
xylene	1330-20-7		F3
n-butyl acetate	123-86-4		F3
xylene	1330-20-7		F3

Legend

- CA Carcinogenic
- F2 Flammable - Second Degree
- F3 Flammable - Third Degree
- MU Mutagenic
- R1 Reactive - First Degree
- TE Teratogenic



Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

POR-15 2K URETHANE LIGHT GRAY

Version number: GHS 2.0
Replaces version of: 2022-03-28 (GHS 1)

Revision: 2023-12-07

- Hazardous Substance List (Chapter 323) (PA-RTK)

Name acc. to inventory	CAS No	Classification
BENZENE, ETHYL-	100-41-4	E
BENZENE, DIMETHYL-	1330-20-7	E
ACETIC ACID, BUTYL ESTER	123-86-4	E
BENZENE, DIMETHYL-	1330-20-7	E

Legend

E Environmental hazard

- Hazardous Substance List (RI-RTK)

Name of substance	CAS No	References
ethyl benzene	100-41-4	T, F
benzene	71-43-2	T, F, C
dibutyltin dilaurate	7440-31-5	T
1,2,4-trimethylbenzene	25551-13-7	T
cumene	98-82-8	T, F
toluene	108-88-3	T, F
toluene	108-88-3	T, F
toluene	108-88-3	T, F
xylene	1330-20-7	T, F
xylene	1330-20-7	T, F
xylene	1330-20-7	T, F
n-butyl acetate	123-86-4	T, F
xylene	1330-20-7	T, F
xylene	1330-20-7	T, F
xylene	1330-20-7	T, F

Legend

C Carcinogenicity (IARC)
F Flammability (NFPA®)
T Toxicity (ACGIH®)

California Environmental Protection Agency (Cal/EPA): Proposition 65 - Safe Drinking Water and Toxic Enforcement Act of 1987



Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

POR-15 2K URETHANE LIGHT GRAY

Version number: GHS 2.0
Replaces version of: 2022-03-28 (GHS 1)

Revision: 2023-12-07

Proposition 65 List of chemicals			
Name acc. to inventory	CAS No	Remarks	Type of the toxicity
ethylbenzene	100-41-4		cancer
benzene	71-43-2		cancer
benzene	71-43-2		developmental, male
cumene	98-82-8		cancer
toluene	108-88-3		developmental

Industry or sector specific available guidance(s)

NPCA-HMIS® III

Hazardous Materials Identification System. American Coatings Association.

Category	Rating	Description
Chronic	*	chronic (long-term) health effects may result from repeated overexposure
Health	2	temporary or minor injury may occur
Flammability	3	material that can be ignited under almost all ambient temperature conditions
Physical hazard	0	material that is normally stable, even under fire conditions, and will not react with water, polymerize, decompose, condense, or self-react. Non-explosive
Personal protection	-	

NFPA® 704

National Fire Protection Association: Standard System for the Identification of the Hazards of Materials for Emergency Response (United States).

Category	Degree of hazard	Description
Flammability	3	material that can be ignited under almost all ambient temperature conditions
Health	2	material that, under emergency conditions, can cause temporary incapacitation or residual injury
Instability	0	material that is normally stable, even under fire conditions
Special hazard		

National inventories

Country	Inventory	Status
US	TSCA	not all ingredients are listed

Legend

TSCA Toxic Substance Control Act



Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

POR-15 2K URETHANE LIGHT GRAY

Version number: GHS 2.0
Replaces version of: 2022-03-28 (GHS 1)

Revision: 2023-12-07

15.2 Chemical Safety Assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information, including date of preparation or last revision

Key literature references and sources for data

OSHA Hazard Communication Standard (HCS), 29 CFR 1910.1200.

Transport of dangerous goods by road or rail (49 CFR US DOT). International Maritime Dangerous Goods Code (IMDG). Dangerous Goods Regulations (DGR) for the air transport (IATA).

Classification procedure

Physical and chemical properties: The classification is based on tested mixture.

Health hazards, Environmental hazards: The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

Disclaimer

This information is based upon the present state of our knowledge. This SDS has been compiled and is solely intended for this product.