

Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 08.16.2018

Page 1 of 15

Caliper Blue

SECTION 1: Identification

Product identifier

Product name: Caliper Blue

Product code: 42706



Recommended use of the product and restriction on use

Relevant identified uses: Paint

Uses advised against: Not determined or not applicable.

Reasons why uses advised against: Not determined or not applicable.

Manufacturer or supplier details

Manufacturer:

United States

P.O.R. Products

38 Portman Road

New Rochelle, NY 10801

914-636-0700

Emergency telephone number:

United States

ChemTel Inc.

+1 800 255 3924

+1 813 248 0585

SECTION 2: Hazard(s) identification

GHS classification:

Flammable liquids, category 3

Eye irritation, category 2A

Skin sensitization, category 1

Aspiration hazard, category 1

Specific target organ toxicity - repeated exposure, category 1

Reproductive toxicity, category 2

Chronic aquatic hazard, category 2

Label elements

Hazard pictograms:



Signal word: Danger

Hazard statements:

H226 Flammable liquid and vapor.

H319 Causes serious eye irritation.

H317 May cause an allergic skin reaction.

H304 May be fatal if swallowed and enters airways.

H372 Causes damage to organs through prolonged or repeated exposure.

H361 Suspected of damaging fertility or the unborn child.

H411 Toxic to aquatic life with long lasting effects.

Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 08.16.2018

Page 2 of 15

Caliper Blue

Precautionary statements:

- P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking.
- P233 Keep container tightly closed.
- P240 Ground/bond container and receiving equipment.
- P241 Use explosion-proof electrical/ventilating/lighting equipment.
- P242 Use only non-sparking tools.
- P243 Take precautionary measures against static discharge.
- P280 Wear protective gloves/protective clothing/eye protection/face protection.
- P264 Wash thoroughly after handling.
- P261 Avoid breathing dust/fume/gas/mist/vapors/spray.
- P272 Contaminated work clothing should not be allowed out of the workplace.
- P260 Do not breathe dust/fume/gas/mist/vapors/spray.
- P270 Do not eat, drink or smoke when using this product.
- P201 Obtain special instructions before use.
- P202 Do not handle until all safety precautions have been read and understood.
- P281 Use personal protective equipment as required.
- P273 Avoid release to the environment.
- P303+P361+P353 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.
- P370+P378 In case of fire: Use appropriate fire extinguishing methods for extinction.
- P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- P337+P313 If eye irritation persists get medical advice/attention
- P321 Specific treatment (see first aid instructions on this label).
- P363 Wash contaminated clothing before reuse
- P302+P352 IF ON SKIN: Wash with plenty of soap and water.
- P333+P313 If skin irritation or a rash occurs: Get medical advice/attention
- P362+P364 Take off contaminated clothing and wash it before reuse.
- P331 Do NOT induce vomiting.
- P301+P310 IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.
- P314 Get medical advice/attention if you feel unwell
- P308+P313 If exposed or concerned: Get medical advice/attention
- P391 Collect spillage
- P403+P235 Store in a well ventilated place. Keep cool.
- P405 Store locked up.
- P501 Dispose of contents/container according to local regulations.

Hazards not otherwise classified: None

SECTION 3: Composition/information on ingredients

Identification	Name	Weight %
CAS number: 64742-48-9	Naphtha (petroleum), hydrotreated heavy	2-5
CAS number: 71-43-2	Benzene	<0.01
CAS number: 100-41-4	Ethyl Benzene	<0.01
CAS number: 64742-95-6	Solvent naphtha (petroleum), light arom.	<0.01

Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 08.16.2018

Page 3 of 15

Caliper Blue

CAS number: 22464-99-9	Zirconium 2-Ethylhexanoate	<0.5
CAS number: 64742-47-8	Distillates (petroleum), hydrotreated light	<0.5
CAS number: 13463-67-7	Titanium Dioxide	<0.5
CAS number: 147-14-8	29H,31H-Phthalocyaninato(2-)-N29,N30,N31,N32 copper	1-3
CAS number: 136-52-7	Cobalt bis(2-ethylhexanoate)	<0.5
CAS number: 108-88-3	Toluene	<0.01
CAS number: 96-29-7	Methyl ethyl ketoxime	<0.1
CAS number: 8052-41-3	Stoddard Solvent	40-45
CAS number: 91-20-3	Naphthalene	<0.01

Additional Information: None

SECTION 4: First aid measures

Description of first aid measures

General notes:

Not determined or not applicable.

After inhalation:

Loosen clothing as necessary and position individual in a comfortable position

Maintain an unobstructed airway

Get medical advice/attention if you feel unwell

After skin contact:

Rinse affected area with soap and water

If symptoms develop or persist, seek medical attention

After eye contact:

Rinse/flush exposed eye(s) gently using water for 15-20 minutes

If symptoms develop or persist, seek medical attention

Rinse eyes cautiously with lukewarm, gently flowing water for several minutes, while holding the eyelids open

Remove contact lenses, if present and easy to do so

Continue rinsing for 15-20 minutes

Get medical advice if eye irritation persists

After swallowing:

Rinse mouth thoroughly

Seek medical attention if irritation, discomfort, or vomiting persists

Most important symptoms and effects, both acute and delayed

Acute symptoms and effects:

Not determined or not applicable.

Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 08.16.2018

Page 4 of 15

Caliper Blue

Delayed symptoms and effects:

Not determined or not applicable.

Immediate medical attention and special treatment

Specific treatment:

Not determined or not applicable.

Notes for the doctor:

Not determined or not applicable.

SECTION 5: Firefighting measures

Extinguishing media

Suitable extinguishing media:

Use Water (fog only), dry chemical, chemical foam, carbon dioxide, or alcohol-resistant foam

Unsuitable extinguishing media:

Do not use a water stream as an extinguisher

Specific hazards during fire-fighting:

Thermal decomposition can lead to release of irritating gases and vapors

Vapors can flow to distant ignition sources and flashback

Liquid is volatile and may generate an explosive atmosphere

Special protective equipment for firefighters:

Use typical firefighting equipment, self-contained breathing apparatus, special tightly sealed suit

Special precautions:

Shut off sources of ignition

Carbon monoxide and carbon dioxide may form upon combustion

Heating causes a rise in pressure, risk of bursting and combustion

SECTION 6: Accidental release measures

Personal precautions, protective equipment and emergency procedures:

Ensure adequate ventilation

Ensure air handling systems are operational

Wear protective eye wear, gloves and clothing

Beware of vapors accumulating to form explosive concentrations

Vapors can accumulate in low areas

Environmental precautions:

Should not be released into the environment

Prevent from reaching drains, sewer or waterway

Methods and material for containment and cleaning up:

Wear protective eye wear, gloves and clothing

Use spark-proof tools and explosion-proof equipment

Absorb with non-combustible liquid-binding material (sand, diatomaceous earth (clay), acid binders, universal binders)

Dispose of contents / container in accordance with local regulations

Reference to other sections:

Not determined or not applicable.

SECTION 7: Handling and storage

Precautions for safe handling:

Use only with adequate ventilation.

Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 08.16.2018

Page 5 of 15

Caliper Blue

Avoid breathing mist or vapor.

Do not eat, drink, smoke or use personal products when handling chemical substances.

Take precautionary measures against electrostatic discharges.

Use only non-sparking tools.

Conditions for safe storage, including any incompatibilities:

Keep container tightly sealed.

Protect from freezing and physical damage.

Store in a cool, well-ventilated area.

Store away from all ignition sources (open flames, hot surfaces, direct sunlight, spark sources).

SECTION 8: Exposure controls/personal protection

Only those substances with limit values have been included below.

Occupational Exposure limit values:

Country (Legal Basis)	Substance	Identifier	Permissible concentration
ACGIH	Stoddard Solvent	8052-41-3	ACGIH TLV TWA: 100 ppm
	Distillates (petroleum), hydrotreated light	64742-47-8	8-Hour Exposure Limit (TLV-TWA): 200 mg/m ³
	Naphthalene	91-20-3	ACGIH TLV TWA 10.0 ppm
	Cobalt bis(2-ethylhexanoate)	136-52-7	ACGIH TLV TWA: 0.02 mg/m ³ , as Co
	Titanium Dioxide	13463-67-7	ACGIH TLV TWA: 10 mg/m ³
	Naphthalene	91-20-3	ACGIH TLV STEL 15.0 ppm
	Zirconium 2-Ethylhexanoate	22464-99-9	ACGIH TLV TWA: 5.0 mg/m ³ , as Zr (long-term)
	Zirconium 2-Ethylhexanoate	22464-99-9	ACGIH STEL 10 mg/m ³ , as Zr (short-term)
	Ethyl Benzene	100-41-4	ACGIH TWA: 20.0 ppm
	Ethyl Benzene	100-41-4	ACGIH STEL: 125.0 ppm
	29H,31H-Phthalocyaninato(2-)-N29,N30,N31,N32 copper	147-14-8	ACGIH TLV TWA: 1.0 mg/m ³ , as Cu
	Benzene	71-43-2	ACGIH TLV TWA 0.5 ppm
	Benzene	71-43-2	ACGIH TLV STEL 2.5 ppm
	Toluene	108-88-3	ACGIH TWA: 20 ppm
United States (OSHA)	Zirconium 2-Ethylhexanoate	22464-99-9	OSHA PEL TWA 5 mg/m ³ , as Zr
	Titanium Dioxide	13463-67-7	OSHA PEL TWA 15 mg/m ³ (Total dust)
	Naphtha (petroleum), hydrotreated heavy	64742-48-9	OSHA Z-1 TWA 500 ppm (2,000 mg/m ³)
	Naphthalene	91-20-3	OSHA PEL TWA 10.0 ppm
	Distillates (petroleum), hydrotreated light	64742-47-8	OSHA TWA: 400 mg/m ³ (100 ppm)
	Naphthalene	91-20-3	OSHA PEL TWA 50.0 mg/m ³
	Stoddard Solvent	8052-41-3	OSHA Z-1 PEL: 500 ppm (2900 mg/m ³)
	Stoddard Solvent	8052-41-3	OSHA Z-1-A TWA: 100 ppm (525 mg/m ³)

Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 08.16.2018

Page 6 of 15

Caliper Blue

Country (Legal Basis)	Substance	Identifier	Permissible concentration
	Zirconium 2-Ethylhexanoate	22464-99-9	OSHA Z-1-A STEL: 10 mg/m ³
	Ethyl Benzene	100-41-4	OSHA PEL (STEL): 125.0 ppm
	Ethyl Benzene	100-41-4	OSHA TWA 100 ppm 435 mg/m ³
	29H,31H-Phthalocyaninato(2-)-N29,N30,N31,N32 copper	147-14-8	OSHA PEL TWA 1.0 mg/m ³ , as Cu
	Benzene	71-43-2	OSHA PEL [1910.1028] TWA 1 ppm
	Benzene	71-43-2	OSHA PEL [1910.1028] ST 5 ppm
	Toluene	108-88-3	OSHA PEL 300 ppm Ceiling
	Toluene	108-88-3	OSHA PEL TWA 200 ppm
	Toluene	108-88-3	OSHA PEL 500 ppm Peak (10 mins)
WEEL	Methyl ethyl ketoxime	96-29-7	WEEL TWA: 10 ppm
NIOSH	Distillates (petroleum), hydrotreated light	64742-47-8	NIOSH Recommended exposure limit (REL) [for up to a 10-hour workday during a 40-hour workweek]: 400 mg/m ³ (100 ppm)
	Stoddard Solvent	8052-41-3	NIOSH REL TWA 350 mg/m ³
	Titanium Dioxide	13463-67-7	IDLH: 5,000 mg/m ³
	Distillates (petroleum), hydrotreated light	64742-47-8	NIOSH Immediately dangerous to life or health (IDLH) concentration: 1000 ppm.
	Stoddard Solvent	8052-41-3	NIOSH REL C 1800 mg/m ³
	Zirconium 2-Ethylhexanoate	22464-99-9	NIOSH REL TWA 5.0 mg/m ³ , as Zr
	Zirconium 2-Ethylhexanoate	22464-99-9	NIOSH ST 10.0 mg/m ³ , as Zr
	Naphthalene	91-20-3	NIOSH REL TWA 10.0 ppm
	Naphthalene	91-20-3	NIOSH REL TWA 50.0 mg/m ³
	Naphthalene	91-20-3	NIOSH REL ST 15.0 ppm
	Naphthalene	91-20-3	NIOSH REL ST 75.0 mg/m ³
	Ethyl Benzene	100-41-4	NIOSH TWA 100.0 ppm 435.0 mg/m ³
	Ethyl Benzene	100-41-4	NIOSH ST 125.0 ppm 545.0 mg/m ³
	29H,31H-Phthalocyaninato(2-)-N29,N30,N31,N32 copper	147-14-8	NIOSH IDLH 100.0 mg/m ³ , as Cu
	Benzene	71-43-2	NIOSH REL Ca TWA 0.1 ppm
	Benzene	71-43-2	NIOSH REL ST 1 ppm
	Toluene	108-88-3	NIOSH TWA 375.0 mg/m ³ ; 100 ppm
	Toluene	108-88-3	NIOSH STEL 560 mg/m ³ ; 150 ppm

Biological limit values:

No biological exposure limits noted for the ingredient(s).

Information on monitoring procedures:

Monitoring of the concentration of substances in the breathing zone of workers or in the general workplace

Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 08.16.2018

Page 7 of 15

Caliper Blue

may be required to confirm compliance with an OEL and adequacy of exposure controls.
Biological monitoring may also be appropriate for some substances.

Appropriate engineering controls:

Emergency eye wash fountains and safety showers should be available in the immediate vicinity of use or handling.

Provide exhaust ventilation or other engineering controls to keep the airborne concentrations of vapor and mists below the applicable workplace exposure limits (Occupational Exposure Limits-OELs) indicated above.
Use explosion-proof ventilation equipment.

Personal protection equipment

Eye and face protection:

Safety goggles or glasses, or appropriate eye protection.

Skin and body protection:

Select glove material impermeable and resistant to the substance.

Wear appropriate clothing to prevent any possibility of skin contact.

Respiratory protection:

If engineering controls do not maintain airborne concentrations below recommended exposure limits (where applicable) or to an acceptable level (in countries where exposure limits have not been established), an approved respirator must be worn.

General hygienic measures:

Avoid contact with skin, eyes and clothing.

Wash hands before breaks and at the end of work.

Wash contaminated clothing before reuse.

SECTION 9: Physical and chemical properties

Information on basic physical and chemical properties

Appearance	Liquid
Odor	Solvent
Odor threshold	Not determined or not available.
pH	Not determined or not available.
Melting point/freezing point	Not determined or not available.
Initial boiling point/range	Not determined or not available.
Flash point (closed cup)	104°F (40°C)
Evaporation rate	Not determined or not available.
Flammability (solid, gas)	Not determined or not available.
Upper flammability/explosive limit	Not determined or not available.
Lower flammability/explosive limit	Not determined or not available.
Vapor pressure	Not determined or not available.
Vapor density	Not determined or not available.
Density	Not determined or not available.
Relative density	Not determined or not available.
Solubilities	Not soluble in water.
Partition coefficient (n-octanol/water)	Not determined or not available.
Auto/Self-ignition temperature	Not determined or not available.
Decomposition temperature	Not determined or not available.
Dynamic viscosity	Not determined or not available.
Kinematic viscosity	Not determined or not available.

Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 08.16.2018

Page 8 of 15

Caliper Blue

Explosive properties	Not determined or not available.
Oxidizing properties	Not determined or not available.

Other information

VOC Content	<430 g/L (Theoretical)
--------------------	------------------------

SECTION 10: Stability and reactivity

Reactivity:

Does not react under normal conditions of use and storage.

Chemical stability:

Stable under normal conditions of use and storage.

Possibility of hazardous reactions:

None under normal conditions of use and storage.

Conditions to avoid:

Avoid heat, sparks, flames or other sources of ignition.

Incompatible materials:

None known.

Hazardous decomposition products:

None known.

SECTION 11: Toxicological information

Acute toxicity

Assessment: Based on available data, the classification criteria are not met.

Product data: No data available.

Substance data:

Name	Route	Result
Ethyl Benzene	inhalation	LCLo - Rat - 4,000 ppm/4 h
Naphthalene	oral	LD50 - Mouse - 316 mg/kg

Skin corrosion/irritation

Assessment: Based on available data, the classification criteria are not met.

Product data:

No data available.

Substance data:

Name	Result
Naphtha (petroleum), hydrotreated heavy	Irritating to the skin.
Cobalt bis(2-ethylhexanoate)	Irritating to the skin.
Zirconium 2-Ethylhexanoate	Irritating to the skin.
Benzene	Irritating to the skin.
Toluene	Irritating to the skin.

Serious eye damage/irritation

Assessment: Causes serious eye irritation

Product data:

No data available.

Substance data:

Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 08.16.2018

Page 9 of 15

Caliper Blue

Name	Result
Methyl ethyl ketoxime	Risk of serious damage to the eyes.
Benzene	Irritating effect on the eyes.

Respiratory or skin sensitization

Assessment: May cause an allergic skin reaction

Product data:

No data available.

Substance data:

Name	Result
Cobalt bis(2-ethylhexanoate)	May cause sensitization by skin contact.
Methyl ethyl ketoxime	May cause sensitization by skin contact

Carcinogenicity

Assessment: Based on available data, the classification criteria are not met.

Product data: No data available.

Substance data:

Name	Species	Result
Stoddard Solvent	Stoddard Solvent	Component may cause cancer.
Naphtha (petroleum), hydrotreated heavy		May cause cancer.
Naphthalene	Not applicable.	Suspected of causing cancer.
Titanium Dioxide		Airborne, unbound particles of respirable size are known to cause cancer.
Methyl ethyl ketoxime		May cause cancer.
Solvent naphtha (petroleum), light arom.	Solvent naphtha (petroleum), light arom.	Component may cause cancer.
Benzene	Benzene	Confirmed human carcinogen.

International Agency for Research on Cancer (IARC):

Name	Classification
Stoddard Solvent	Group 3
Cobalt bis(2-ethylhexanoate)	Group 2B
Ethyl Benzene	Group 2B - Possibly carcinogenic to humans
Naphthalene	Group 2B - Possibly carcinogenic to humans
Distillates (petroleum), hydrotreated light	Group 3 - Not classifiable as to its carcinogenicity to humans
Titanium Dioxide	Group 2B
Benzene	Group 1 - Carcinogenic to humans
Toluene	Group 3 - Not classifiable as to its carcinogenicity to humans

National Toxicology Program (NTP):

Name	Classification
Cobalt bis(2-ethylhexanoate)	Reasonably anticipated to be human carcinogens
Naphthalene	Reasonably anticipated to be human carcinogens
Benzene	Known to be human carcinogens

Germ cell mutagenicity

Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 08.16.2018

Page 10 of 15

Caliper Blue

Assessment: Based on available data, the classification criteria are not met.

Product data:

No data available.

Substance data:

Name	Result
Stoddard Solvent	May cause genetic defects.
Naphtha (petroleum), hydrotreated heavy	May cause genetic defects.
Solvent naphtha (petroleum), light arom.	May cause genetic defects.
Benzene	May cause genetic defects.

Reproductive toxicity

Assessment: Suspected of damaging fertility or the unborn child

Product data:

No data available.

Substance data:

Name	Result
Toluene	Suspected of damaging fertility or the unborn child.

Specific target organ toxicity (single exposure)

Assessment: Based on available data, the classification criteria are not met.

Product data:

No data available.

Substance data:

Name	Result
Naphtha (petroleum), hydrotreated heavy	Component affects the central nervous system.
Ethyl Benzene	Repeated exposure damages the hearing organs.
Benzene	Causes damage to the organs through prolonged or repeated exposure.
Toluene	Component affects the central nervous system.

Specific target organ toxicity (repeated exposure)

Assessment: Causes damage to organs through prolonged or repeated exposure

Product data:

No data available.

Substance data:

Name	Result
Stoddard Solvent	Causes damage to organs through prolonged or repeated exposure.

Aspiration toxicity

Assessment: May be fatal if swallowed and enters airways

Product data:

No data available.

Substance data:

Name	Result
Stoddard Solvent	May be fatal if swallowed and enters airways.

Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 08.16.2018

Page 11 of 15

Caliper Blue

Name	Result
Naphtha (petroleum), hydrotreated heavy	May be fatal if swallowed and enters airway.
Ethyl Benzene	May be fatal if swallowed and enters airway.
Distillates (petroleum), hydrotreated light	May be fatal if swallowed and enters airway.
Solvent naphtha (petroleum), light arom.	May be fatal if swallowed and enters airway.

Information on likely routes of exposure:

No data available.

Symptoms related to the physical, chemical and toxicological characteristics:

No data available.

Other information:

No data available.

SECTION 12: Ecological information

Acute (short-term) toxicity

Assessment: Based on available data, the classification criteria are not met.

Product data: No data available.

Substance data:

Name	Result
Naphthalene	LC50 - Opossum Shrimp - 0.85 mg/L - 96 h
	LC50 - Melanotaenia fluviatilis (Crimson-Spotted Rainbowfish) - 0.213 mg/L - 96 h

Chronic (long-term) toxicity

Product data: No data available.

Substance data:

Name	Result
Stoddard Solvent	NOEC Fish: 0.14 mg/L (96 Hr)
Cobalt bis(2-ethylhexanoate)	NOEC - Pimephales promelas - 0.21 mg/L - 34 d

Persistence and degradability

Product data: No data available.

Substance data: No data available.

Bioaccumulative potential

Product data: No data available.

Substance data: No data available.

Mobility in soil

Product data: No data available.

Substance data: No data available.

Other adverse effects: No data available.

SECTION 13: Disposal considerations

Disposal methods:

It is the responsibility of the waste generator to properly characterize all waste materials according to applicable regulatory entities

SECTION 14: Transport information

Safety Data Sheet



According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 08.16.2018



Page 12 of 15

Caliper Blue



United States Transportation of dangerous goods (49 CFR DOT)

UN number	1263	
UN proper shipping name	PAINT	
UN transport hazard class(es)	3	 
Packing group	III	
Environmental hazards	Marine Pollutant (Stoddard Solvent)	
Special precautions for user	None	
Passenger air/rail	60L	
Cargo aircraft only	220L	
Stowage category	A	

International Maritime Dangerous Goods (IMDG)

UN number	1263	
UN proper shipping name	PAINT	
UN transport hazard class(es)	3	 
Packing group	III	
Environmental hazards	Marine Pollutant (Stoddard Solvent)	
Special precautions for user	None	
EmS number	F-E, S-E	
Excepted quantities	E1	
Limited quantity	5L	

International Air Transport Association Dangerous Goods Regulations (IATA-DGR)

UN number	1263	
UN proper shipping name	PAINT	
UN transport hazard class(es)	3	 
Packing group	III	
Environmental hazards	Marine Pollutant (Stoddard Solvent)	
Special precautions for user	None	
Excepted quantities	E1	
Limited quantity	10L	

SECTION 15: Regulatory information

United States regulations

Inventory listing (TSCA):

8052-41-3	Stoddard Solvent	Listed
-----------	------------------	--------

Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 08.16.2018

Page 13 of 15

Caliper Blue

64742-48-9	Naphtha (petroleum), hydrotreated heavy	Listed
136-52-7	Cobalt bis(2-ethylhexanoate)	Listed
100-41-4	Ethyl Benzene	Listed
91-20-3	Naphthalene	Listed
22464-99-9	Zirconium 2-Ethylhexanoate	Listed
64742-47-8	Distillates (petroleum), hydrotreated light	Listed
96-29-7	Methyl ethyl ketoxime	Listed
147-14-8	29H,31H-Phthalocyaninato(2-)-N29,N30,N31,N32 copper	Listed
13463-67-7	Titanium Dioxide	Listed
64742-95-6	Solvent naphtha (petroleum), light arom.	Listed
71-43-2	Benzene	Listed
108-88-3	Toluene	Listed

Significant New Use Rule (TSCA Section 5): Not determined.

Export notification under TSCA Section 12(b): Not determined.

SARA Section 302 extremely hazardous substances: Not determined.

SARA Section 313 toxic chemicals:

8052-41-3	Stoddard Solvent	Not Listed
64742-48-9	Naphtha (petroleum), hydrotreated heavy	Not Listed
136-52-7	Cobalt bis(2-ethylhexanoate)	Listed
100-41-4	Ethyl Benzene	Listed
91-20-3	Naphthalene	Listed
22464-99-9	Zirconium 2-Ethylhexanoate	Not Listed
64742-47-8	Distillates (petroleum), hydrotreated light	Not Listed
96-29-7	Methyl ethyl ketoxime	Not Listed
13463-67-7	Titanium Dioxide	Not Listed
71-43-2	Benzene	Not Listed
108-88-3	Toluene	Listed

CERCLA:

100-41-4	Ethyl Benzene	Listed	1,000 lb
91-20-3	Naphthalene	Listed	100
108-88-3	Toluene	Listed	1000 lb

RCRA:

91-20-3	Naphthalene	Listed	U165
108-88-3	Toluene	Listed	U220

Section 112(r) of the Clean Air Act (CAA): Not determined.

Massachusetts Right to Know:

8052-41-3	Stoddard Solvent	Listed
-----------	------------------	--------

Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 08.16.2018

Page 14 of 15

Caliper Blue

64742-48-9	Naphtha (petroleum), hydrotreated heavy	Not Listed
136-52-7	Cobalt bis(2-ethylhexanoate)	Not Listed
100-41-4	Ethyl Benzene	Listed
91-20-3	Naphthalene	Listed
22464-99-9	Zirconium 2-Ethylhexanoate	Not Listed
64742-47-8	Distillates (petroleum), hydrotreated light	Listed
96-29-7	Methyl ethyl ketoxime	Not Listed
13463-67-7	Titanium Dioxide	Listed
64742-95-6	Solvent naphtha (petroleum), light arom.	Not Listed
108-88-3	Toluene	Listed

New Jersey Right to Know:

8052-41-3	Stoddard Solvent	Listed
64742-48-9	Naphtha (petroleum), hydrotreated heavy	Not Listed
136-52-7	Cobalt bis(2-ethylhexanoate)	Listed
100-41-4	Ethyl Benzene	Listed
91-20-3	Naphthalene	Listed
22464-99-9	Zirconium 2-Ethylhexanoate	Not Listed
64742-47-8	Distillates (petroleum), hydrotreated light	Listed
96-29-7	Methyl ethyl ketoxime	Not Listed
13463-67-7	Titanium Dioxide	Listed
64742-95-6	Solvent naphtha (petroleum), light arom.	Not Listed
108-88-3	Toluene	Listed

New York Right to Know:

8052-41-3	Stoddard Solvent	Listed
64742-48-9	Naphtha (petroleum), hydrotreated heavy	Listed
136-52-7	Cobalt bis(2-ethylhexanoate)	Listed
100-41-4	Ethyl Benzene	Listed
91-20-3	Naphthalene	Listed
22464-99-9	Zirconium 2-Ethylhexanoate	Not Listed
64742-47-8	Distillates (petroleum), hydrotreated light	Listed
96-29-7	Methyl ethyl ketoxime	Not Listed
13463-67-7	Titanium Dioxide	Listed
64742-95-6	Solvent naphtha (petroleum), light arom.	Not Listed
108-88-3	Toluene	Listed

Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 08.16.2018

Page 15 of 15

Caliper Blue

Pennsylvania Right to Know:

8052-41-3	Stoddard Solvent	Listed
64742-48-9	Naphtha (petroleum), hydrotreated heavy	Listed
136-52-7	Cobalt bis(2-ethylhexanoate)	Listed
100-41-4	Ethyl Benzene	Listed
91-20-3	Naphthalene	Listed
22464-99-9	Zirconium 2-Ethylhexanoate	Not Listed
64742-47-8	Distillates (petroleum), hydrotreated light	Listed
96-29-7	Methyl ethyl ketoxime	Not Listed
13463-67-7	Titanium Dioxide	Listed
64742-95-6	Solvent naphtha (petroleum), light arom.	Not Listed
108-88-3	Toluene	Listed

California Proposition 65:

⚠️WARNING: This product can expose you to chemicals including Ethyl Benzene and Naphthalene, which are known to the State of California to cause cancer, and Toluene, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

⚠️WARNING: This product can expose you to Benzene, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

SECTION 16: Other information

Abbreviations and Acronyms: None

Disclaimer:

This product has been classified in accordance with OSHA HCS 2012 guidelines. The information provided in this SDS is correct, to the best of our knowledge, based on information available. The information given is designed only as a guidance for safe handling, use, storage, transportation and disposal and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials, unless specified in the text. The responsibility to provide a safe workplace remains with the user.

NFPA: 3-2-0

HMIS: 3-2-0

Initial preparation date: 08.16.2018

End of Safety Data Sheet