

# Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 04.24.2018

Page 1 of 12

## Caliper Paint Red

### SECTION 1: Identification

#### Product identifier

**Product name:** Caliper Paint Red

**Product code:** 42806



#### Recommended use of the product and restriction on use

**Relevant identified uses:** Coating compound/ Surface coating/ paint

**Uses advised against:** Not determined or not applicable.

**Reasons why uses advised against:** Not determined or not applicable.

#### Manufacturer or supplier details

##### Manufacturer:

**United States**

P.O.R. Products

38 Portman Road

New Rochelle, NY 10801

914-636-0700

#### Emergency telephone number:

**United States**

**ChemTel Inc.**

+1 800 255 3924

+1 813 248 0585

### SECTION 2: Hazard(s) identification

#### GHS classification:

Flammable liquids, category 3

Skin sensitization, category 1

Specific target organ toxicity - repeated exposure, category 1

Carcinogenicity, category 2

Reproductive toxicity, category 2

#### Label elements

##### Hazard pictograms:



**Signal word:** Danger

#### Hazard statements:

H226 Flammable liquid and vapor.

H317 May cause an allergic skin reaction.

H372 Causes damage to organs through prolonged or repeated exposure.

H351 Suspected of causing cancer.

H361 Suspected of damaging fertility or the unborn child.

#### Precautionary statements:

P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking.

P233 Keep container tightly closed.

P240 Ground/bond container and receiving equipment.

# Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 04.24.2018

Page 2 of 12

## Caliper Paint Red

- P241 Use explosion-proof electrical/ventilating/lighting equipment.
- P242 Use only non-sparking tools.
- P243 Take precautionary measures against static discharge.
- P280 Wear protective gloves/protective clothing/eye protection/face protection.
- P261 Avoid breathing dust/fume/gas/mist/vapors/spray.
- P272 Contaminated work clothing should not be allowed out of the workplace.
- P260 Do not breathe dust/fume/gas/mist/vapors/spray.
- P264 Wash skin thoroughly after handling.
- P270 Do not eat, drink or smoke when using this product.
- P201 Obtain special instructions before use.
- P202 Do not handle until all safety precautions have been read and understood.
- P281 Use personal protective equipment as required.
- P303+P361+P353 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.
- P370+P378 In case of fire: Use appropriate fire extinguishing methods for extinction.
- P321 Specific treatment (see first aid instructions on this label).
- P363 Wash contaminated clothing before reuse
- P302+P352 IF ON SKIN: Wash with plenty of soap and water.
- P333+P313 If skin irritation or a rash occurs: Get medical advice/attention
- P362+P364 Take off contaminated clothing and wash it before reuse.
- P314 Get medical advice/attention if you feel unwell
- P308+P313 If exposed or concerned: Get medical advice/attention
- P403+P235 Store in a well ventilated place. Keep cool.
- P405 Store locked up.
- P501 Dispose of contents/container according to local regulations.

**Hazards not otherwise classified:** None

## SECTION 3: Composition/information on ingredients

Identification	Name	Weight %
CAS number: 64742-48-9	Naphtha (petroleum), hydrotreated heavy	<3
CAS number: 108-65-6	1-Methoxy-2-propanol acetate	<3
CAS number: 1309-37-1	Diiron trioxide	<2
CAS number: 136-52-7	Cobalt bis(2-ethylhexanoate)	<0.3
CAS number: 96-29-7	Methyl ethyl ketoxime	<0.3
CAS number: 8052-41-3	Stoddard Solvent	33-36

**Additional Information:** None

## SECTION 4: First aid measures

### Description of first aid measures

**General notes:**

## Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 04.24.2018

Page 3 of 12

### Caliper Paint Red

Not determined or not applicable.

#### After inhalation:

Loosen clothing as necessary and position individual in a comfortable position  
Maintain an unobstructed airway  
Get medical advice/attention if you feel unwell

#### After skin contact:

Rinse affected area with soap and water  
If symptoms develop or persist, seek medical attention

#### After eye contact:

Rinse/flush exposed eye(s) gently using water for 15-20 minutes  
If symptoms develop or persist, seek medical attention

#### After swallowing:

Rinse mouth thoroughly  
Seek medical attention if irritation, discomfort, or vomiting persists

### Most important symptoms and effects, both acute and delayed

#### Acute symptoms and effects:

Not determined or not applicable.

#### Delayed symptoms and effects:

Not determined or not applicable.

### Immediate medical attention and special treatment

#### Specific treatment:

Not determined or not applicable.

#### Notes for the doctor:

Not determined or not applicable.

## SECTION 5: Firefighting measures

### Extinguishing media

#### Suitable extinguishing media:

Use Water (fog only), dry chemical, chemical foam, carbon dioxide, or alcohol-resistant foam

#### Unsuitable extinguishing media:

Do not use a water stream as an extinguisher

### Specific hazards during fire-fighting:

Thermal decomposition can lead to release of irritating gases and vapors  
Vapors can flow to distant ignition sources and flashback  
Liquid is volatile and may generate an explosive atmosphere

### Special protective equipment for firefighters:

Use typical firefighting equipment, self-contained breathing apparatus, special tightly sealed suit

### Special precautions:

Shut off sources of ignition  
Carbon monoxide and carbon dioxide may form upon combustion  
Heating causes a rise in pressure, risk of bursting and combustion

## SECTION 6: Accidental release measures

### Personal precautions, protective equipment and emergency procedures:

Ensure adequate ventilation  
Ensure air handling systems are operational  
Wear protective eye wear, gloves and clothing

# Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 04.24.2018

Page 4 of 12

## Caliper Paint Red

Beware of vapors accumulating to form explosive concentrations  
Vapors can accumulate in low areas

### Environmental precautions:

Should not be released into the environment  
Prevent from reaching drains, sewer or waterway

### Methods and material for containment and cleaning up:

Wear protective eye wear, gloves and clothing  
Use spark-proof tools and explosion-proof equipment  
Absorb with non-combustible liquid-binding material (sand, diatomaceous earth (clay), acid binders, universal binders)  
Dispose of contents / container in accordance with local regulations

### Reference to other sections:

Not determined or not applicable.

## SECTION 7: Handling and storage

### Precautions for safe handling:

Use only with adequate ventilation.  
Avoid breathing mist or vapor.  
Do not eat, drink, smoke or use personal products when handling chemical substances.  
Take precautionary measures against electrostatic discharges.  
Use only non-sparking tools.

### Conditions for safe storage, including any incompatibilities:

Keep container tightly sealed.  
Protect from freezing and physical damage.  
Store in a cool, well-ventilated area.  
Store away from all ignition sources (open flames, hot surfaces, direct sunlight, spark sources).

## SECTION 8: Exposure controls/personal protection

Only those substances with limit values have been included below.

### Occupational Exposure limit values:

Country (Legal Basis)	Substance	Identifier	Permissible concentration
ACGIH	Cobalt bis(2-ethylhexanoate)	136-52-7	ACGIH TLV TWA: 0.02 mg/m <sup>3</sup> , as Co
	Stoddard Solvent	8052-41-3	ACGIH TLV TWA: 100 ppm
	Diiron trioxide	1309-37-1	ACGIH TLV TWA: 5 mg/m <sup>3</sup>
WEEL	Methyl ethyl ketoxime	96-29-7	WEEL TWA: 10 ppm
	1-Methoxy-2-propanol acetate	108-65-6	WEEL TWA 50.0 ppm
United States (OSHA)	Naphtha (petroleum), hydrotreated heavy	64742-48-9	OSHA Z-1 TWA 500 ppm (2,000 mg/m <sup>3</sup> )
	Stoddard Solvent	8052-41-3	OSHA Z-1 PEL: 500 ppm (2900 mg/m <sup>3</sup> )
	Stoddard Solvent	8052-41-3	OSHA Z-1-A TWA: 100 ppm (525 mg/m <sup>3</sup> )
	Diiron trioxide	1309-37-1	OSHA PEL TWA 15 mg/m <sup>3</sup> (total dust)
	Diiron trioxide	1309-37-1	OSHA PEL TWA 5 mg/m <sup>3</sup> (respirable fraction)
	Diiron trioxide	1309-37-1	OSHA PEL TWA 10 mg/m <sup>3</sup> (Fume)

# Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 04.24.2018

Page 5 of 12

## Caliper Paint Red

Country (Legal Basis)	Substance	Identifier	Permissible concentration
NIOSH	Stoddard Solvent	8052-41-3	NIOSH REL TWA 350 mg/m <sup>3</sup>
	Stoddard Solvent	8052-41-3	NIOSH REL C 1800 mg/m <sup>3</sup>
	Diiron trioxide	1309-37-1	NIOSH REL TWA 5.0 mg/m <sup>3</sup>
Australia	Diiron trioxide	1309-37-1	TWA: 5 mg/m <sup>3</sup>
	1-Methoxy-2-propanol acetate	108-65-6	TWA: 274 mg/m <sup>3</sup> (50 ppm); STEL: 548 mg/m <sup>3</sup> (100 ppm)

### Biological limit values:

No biological exposure limits noted for the ingredient(s).

### Information on monitoring procedures:

Monitoring of the concentration of substances in the breathing zone of workers or in the general workplace may be required to confirm compliance with an OEL and adequacy of exposure controls.

Biological monitoring may also be appropriate for some substances.

### Appropriate engineering controls:

Emergency eye wash fountains and safety showers should be available in the immediate vicinity of use or handling.

Provide exhaust ventilation or other engineering controls to keep the airborne concentrations of vapor and mists below the applicable workplace exposure limits (Occupational Exposure Limits-OELs) indicated above.

Use explosion-proof ventilation equipment.

### Personal protection equipment

#### Eye and face protection:

Safety goggles or glasses, or appropriate eye protection.

#### Skin and body protection:

Select glove material impermeable and resistant to the substance.

Wear appropriate clothing to prevent any possibility of skin contact.

#### Respiratory protection:

If engineering controls do not maintain airborne concentrations below recommended exposure limits (where applicable) or to an acceptable level (in countries where exposure limits have not been established), an approved respirator must be worn.

### General hygienic measures:

Avoid contact with skin, eyes and clothing.

Wash hands before breaks and at the end of work.

Wash contaminated clothing before reuse.

## SECTION 9: Physical and chemical properties

### Information on basic physical and chemical properties

Appearance	Red Colored Liquid
Odor	Solvent-like
Odor threshold	Not determined or not available.
pH	Not determined or not available.
Melting point/freezing point	Not determined or not available.
Initial boiling point/range	>284°F (>140°C)
Flash point (closed cup)	>105°F (>41°C)
Evaporation rate	Not determined or not available.
Flammability (solid, gas)	Not determined or not available.

# Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 04.24.2018

Page 6 of 12

## Caliper Paint Red

<b>Upper flammability/explosive limit</b>	Not determined or not available.
<b>Lower flammability/explosive limit</b>	Not determined or not available.
<b>Vapor pressure</b>	Not determined or not available.
<b>Vapor density</b>	Not determined or not available.
<b>Density</b>	0.848-0.945 g/cm <sup>3</sup>
<b>Relative density</b>	Not determined or not available.
<b>Solubilities</b>	Not miscible.
<b>Partition coefficient (n-octanol/water)</b>	Not determined or not available.
<b>Auto/Self-ignition temperature</b>	Product is not self-igniting
<b>Decomposition temperature</b>	Not determined or not available.
<b>Dynamic viscosity</b>	Not determined or not available.
<b>Kinematic viscosity</b>	Not determined or not available.
<b>Explosive properties</b>	Product is not explosive. However, formation of explosive air/vapor mixtures are possible.
<b>Oxidizing properties</b>	Not determined or not available.

### Other information

<b>VOC Content</b>	60-68% (Max - < 430 g/L)
--------------------	--------------------------

## SECTION 10: Stability and reactivity

### Reactivity:

Does not react under normal conditions of use and storage.

### Chemical stability:

Stable under normal conditions of use and storage.

### Possibility of hazardous reactions:

Develops readily flammable gases/fumes.

Can form explosive mixtures in air if heated above flash point and/or when sprayed or atomised.

Can react violently with oxygen rich (oxidizing) materials.

Toxic fumes may be released if heated above the decomposition point.

Used empty containers may contain product gases which form explosive mixtures with air.

### Conditions to avoid:

Keep away from open flames, hot surfaces and sources of ignition.

Store away from oxidizing agents.

### Incompatible materials:

None known.

### Hazardous decomposition products:

CO, CO<sub>2</sub>.

Hydrocarbons.

## SECTION 11: Toxicological information

### Acute toxicity

**Assessment:** Based on available data, the classification criteria are not met.

**Product data:** No data available.

**Substance data:** No data available.

### Skin corrosion/irritation

**Assessment:** Based on available data, the classification criteria are not met.

**Product data:**

# Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 04.24.2018

Page 7 of 12

## Caliper Paint Red

No data available.

### Substance data:

Name	Result
Naphtha (petroleum), hydrotreated heavy	Irritating to the skin.
Cobalt bis(2-ethylhexanoate)	Irritating to the skin.

### Serious eye damage/irritation

**Assessment:** Based on available data, the classification criteria are not met.

### Product data:

No data available.

### Substance data:

Name	Result
Methyl ethyl ketoxime	Risk of serious damage to the eyes.

### Respiratory or skin sensitization

**Assessment:** May cause an allergic skin reaction

### Product data:

No data available.

### Substance data:

Name	Result
Cobalt bis(2-ethylhexanoate)	May cause sensitization by skin contact.
Methyl ethyl ketoxime	May cause sensitization by skin contact

### Carcinogenicity

**Assessment:** Suspected of causing cancer

**Product data:** No data available.

### Substance data:

Name	Species	Result
Stoddard Solvent	Stoddard Solvent	Component may cause cancer.
Naphtha (petroleum), hydrotreated heavy		May cause cancer.
Methyl ethyl ketoxime		May cause cancer.

### International Agency for Research on Cancer (IARC):

Name	Classification
Stoddard Solvent	Group 3
Cobalt bis(2-ethylhexanoate)	Group 2B
Diiron trioxide	Group 3 - Not classifiable as to its carcinogenicity to humans

### National Toxicology Program (NTP):

Name	Classification
Cobalt bis(2-ethylhexanoate)	Reasonably anticipated to be human carcinogens

### Germ cell mutagenicity

**Assessment:** Based on available data, the classification criteria are not met.

### Product data:

No data available.

### Substance data:

# Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 04.24.2018

Page 8 of 12

## Caliper Paint Red

Name	Result
Stoddard Solvent	May cause genetic defects.
Naphtha (petroleum), hydrotreated heavy	May cause genetic defects.

### Reproductive toxicity

**Assessment:** Suspected of damaging fertility or the unborn child

**Product data:**

No data available.

**Substance data:** No data available.

### Specific target organ toxicity (single exposure)

**Assessment:** Based on available data, the classification criteria are not met.

**Product data:**

No data available.

**Substance data:**

Name	Result
Naphtha (petroleum), hydrotreated heavy	Component affects the central nervous system.

### Specific target organ toxicity (repeated exposure)

**Assessment:** Causes damage to organs through prolonged or repeated exposure

**Product data:**

No data available.

**Substance data:**

Name	Result
Stoddard Solvent	Causes damage to organs through prolonged or repeated exposure.

### Aspiration toxicity

**Assessment:** Based on available data, the classification criteria are not met.

**Product data:**

No data available.

**Substance data:**

Name	Result
Stoddard Solvent	May be fatal if swallowed and enters airways.
Naphtha (petroleum), hydrotreated heavy	May be fatal if swallowed and enters airway.

### Information on likely routes of exposure:

No data available.

### Symptoms related to the physical, chemical and toxicological characteristics:

No data available.

### Other information:

No data available.

## SECTION 12: Ecological information

### Acute (short-term) toxicity

**Assessment:** Based on available data, the classification criteria are not met.

**Product data:** No data available.

**Substance data:** No data available.



# Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 04.24.2018

Page 9 of 12

## Caliper Paint Red

### Chronic (long-term) toxicity

**Product data:** No data available.

**Substance data:**

Name	Result
Stoddard Solvent	NOEC Fish: 0.14 mg/L (96 Hr)
Cobalt bis(2-ethylhexanoate)	NOEC - Pimephales promelas - 0.21 mg/L - 34 d

### Persistence and degradability

**Product data:** No data available.

**Substance data:** No data available.

### Bioaccumulative potential

**Product data:** No data available.

**Substance data:** No data available.

### Mobility in soil

**Product data:** No data available.

**Substance data:** No data available.

**Other adverse effects:** No data available.


## SECTION 13: Disposal considerations

### Disposal methods:


It is the responsibility of the waste generator to properly characterize all waste materials according to applicable regulatory entities

## SECTION 14: Transport information

### United States Transportation of dangerous goods (49 CFR DOT)

UN number	1263
UN proper shipping name	Paint
UN transport hazard class(es)	3 
Packing group	III
Environmental hazards	Marine Pollutant (Stoddard Solvent, Naphtha (petroleum), hydrotreated heavy)
Special precautions for user	None
Excepted quantities	E1
Passenger air/rail	60L
Cargo aircraft only	220L
Stowage category	A

### International Maritime Dangerous Goods (IMDG)

UN number	1263
UN proper shipping name	Paint
UN transport hazard class(es)	3 
Packing group	III

# Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200



Initial preparation date: 04.24.2018

Page 10 of 12

## Caliper Paint Red

<b>Environmental hazards</b>	Marine Pollutant (Stoddard Solvent, Naphtha (petroleum), hydrotreated heavy)
<b>Special precautions for user</b>	None
<b>EmS number</b>	F-E, S-E
<b>Stowage category</b>	A
<b>Excepted quantities</b>	E1
<b>Limited quantity</b>	5L

### International Air Transport Association Dangerous Goods Regulations (IATA-DGR)

<b>UN number</b>	1263
<b>UN proper shipping name</b>	Paint
<b>UN transport hazard class(es)</b>	3  
<b>Packing group</b>	III
<b>Environmental hazards</b>	Marine Pollutant (Stoddard Solvent, Naphtha (petroleum), hydrotreated heavy)
<b>Special precautions for user</b>	None
<b>ERG code</b>	3L
<b>Excepted quantities</b>	E1
<b>Passenger and cargo</b>	60L
<b>Cargo aircraft only</b>	220L
<b>Limited quantity</b>	10L

## SECTION 15: Regulatory information

### United States regulations

#### Inventory listing (TSCA):

8052-41-3	Stoddard Solvent	Listed
64742-48-9	Naphtha (petroleum), hydrotreated heavy	Listed
136-52-7	Cobalt bis(2-ethylhexanoate)	Listed
96-29-7	Methyl ethyl ketoxime	Listed
1309-37-1	Diiron trioxide	Listed
108-65-6	1-Methoxy-2-propanol acetate	Listed

**Significant New Use Rule (TSCA Section 5):** Not determined.

**Export notification under TSCA Section 12(b):** Not determined.

**SARA Section 302 extremely hazardous substances:** Not determined.

#### SARA Section 313 toxic chemicals:

8052-41-3	Stoddard Solvent	Not Listed
64742-48-9	Naphtha (petroleum), hydrotreated heavy	Not Listed
136-52-7	Cobalt bis(2-ethylhexanoate)	Listed
96-29-7	Methyl ethyl ketoxime	Not Listed

**CERCLA:** Not determined.

# Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 04.24.2018

Page 11 of 12

## Caliper Paint Red

**RCRA:** Not determined.

**Section 112(r) of the Clean Air Act (CAA):** Not determined.

### Massachusetts Right to Know:

8052-41-3	Stoddard Solvent	Listed
64742-48-9	Naphtha (petroleum), hydrotreated heavy	Not Listed
136-52-7	Cobalt bis(2-ethylhexanoate)	Not Listed
96-29-7	Methyl ethyl ketoxime	Not Listed
1309-37-1	Diiron trioxide	Listed
108-65-6	1-Methoxy-2-propanol acetate	Not Listed

### New Jersey Right to Know:

8052-41-3	Stoddard Solvent	Listed
64742-48-9	Naphtha (petroleum), hydrotreated heavy	Not Listed
136-52-7	Cobalt bis(2-ethylhexanoate)	Listed
96-29-7	Methyl ethyl ketoxime	Not Listed
1309-37-1	Diiron trioxide	Not Listed
108-65-6	1-Methoxy-2-propanol acetate	Not Listed

### New York Right to Know:

8052-41-3	Stoddard Solvent	Listed
64742-48-9	Naphtha (petroleum), hydrotreated heavy	Listed
136-52-7	Cobalt bis(2-ethylhexanoate)	Listed
96-29-7	Methyl ethyl ketoxime	Not Listed
1309-37-1	Diiron trioxide	Listed
108-65-6	1-Methoxy-2-propanol acetate	Not Listed

### Pennsylvania Right to Know:

8052-41-3	Stoddard Solvent	Listed
64742-48-9	Naphtha (petroleum), hydrotreated heavy	Listed
136-52-7	Cobalt bis(2-ethylhexanoate)	Listed
96-29-7	Methyl ethyl ketoxime	Not Listed
1309-37-1	Diiron trioxide	Listed
108-65-6	1-Methoxy-2-propanol acetate	Not Listed

**California Proposition 65:** None of the ingredients are listed.

## SECTION 16: Other information

**Abbreviations and Acronyms:** None

## Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 04.24.2018

Page 12 of 12

### Caliper Paint Red

**Disclaimer:**

This product has been classified in accordance with OSHA HCS 2012 guidelines. The information provided in this SDS is correct, to the best of our knowledge, based on information available. The information given is designed only as a guidance for safe handling, use, storage, transportation and disposal and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials, unless specified in the text. The responsibility to provide a safe workplace remains with the user.

**NFPA:** 2-2-0

**HMIS:** 2-2-0

**Initial preparation date:** 04.24.2018

**End of Safety Data Sheet**