

acc. to Hazardous Products Regulations (HPR)

POR-15 Detail Spray

Version number: GHS 2.0
Replaces version of: 2021-05-14 (GHS 1)
Replaces version of: 2021-05-14 (GHS 1)

SECTION 1: Identification

1.1 Product identifier

Trade name POR-15 Detail Spray

Product code(s) 53020, 253020

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses general use

1.3 Details of the supplier of the safety data sheet

P.O.R. Products 38 Portman Road New Rochelle New York 10801 United States

Telephone: +1-914-636-0700 e-mail: support@porproducts.com Website: www.porproducts.com

e-mail (competent person) support@porproducts.com

1.4 Emergency telephone number

Emergency information service 1.800.255.3924 ChemTel Inc.

SECTION 2: Hazard identification

2.1 Classification of the substance or mixture

Classification acc. to GHS

Section	Hazard class	Category	Hazard class and cat- egory	Hazard state- ment
2.6	flammable liquid	4	Flam. Liq. 4	H227
3.4S	skin sensitization	1	Skin Sens. 1	H317

For full text of abbreviations: see SECTION 16.

The most important adverse physicochemical, human health and environmental effects
The product is combustible and can be ignited by potential ignition sources.

2.2 Label elements

Labeling

- Signal word warning

- Pictograms

GHS07



- Hazard statements

H227 Combustible liquid.

H317 May cause an allergic skin reaction.

Canada: en Page: 1 / 14



acc. to Hazardous Products Regulations (HPR)

POR-15 Detail Spray

Version number: GHS 2.0 Revision: 2021-06-18 Replaces version of: 2021-05-14 (GHS 1)

- Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P272 Contaminated work clothing should not be allowed out of the workplace.
P280 Wear protective gloves/protective clothing/eye protection/face protection.

P302+P352 IF ON SKIN: Wash with plenty of water.
P321 Specific treatment (see on this label).

P333+P313 If skin irritation or rash occurs: Get medical advice/attention. P362+P364 Take off contaminated clothing and wash it before reuse.

P370+P378 In case of fire: Use sand, carbon dioxide or powder extinguisher to extinguish.

P403 Store in a well-ventilated place.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

- Hazardous ingredients for labelling

benzotriazole polymer mixture UV Absorber

2.3 Other hazards

This material is combustible, but will not ignite readily.

SECTION 3: Composition/information on ingredients

3.1 Substances

Not relevant (mixture)

3.2 Mixtures

Description of the mixture

Name of substance	Identifier	Wt%	Classification acc. to GHS
dipropylene glycol monomethyl ether	CAS No 34590-94-8	1-<5	Flam. Liq. 4 / H227
benzotriazole polymer mixture UV Absorber	CAS No not available	0.1 - < 1	Skin Irrit. 2 / H315 Eye Dam. 1 / H318 Skin Sens. 1 / H317
isododecane	CAS No 13475-82-6	0.1 - < 1	Flam. Liq. 3 / H226 Acute Tox. 3 / H331 Asp. Tox. 1 / H304

For full text of abbreviations: see SECTION 16.

SECTION 4: First-aid measures

4.1 Description of first-aid measures

General notes

Do not leave affected person unattended. Remove victim out of the danger area. Keep affected person warm, still and covered. Take off immediately all contaminated clothing. In all cases of doubt, or when symptoms persist, seek medical advice. In case of unconsciousness place person in the recovery position. Never give anything by mouth.

Following inhalation

If breathing is irregular or stopped, immediately seek medical assistance and start first aid actions. Provide fresh air.

Following skin contact

Wash with plenty of soap and water.

Following eye contact

Remove contact lenses, if present and easy to do. Continue rinsing. Irrigate copiously with clean, fresh water for at least 10 minutes, holding the eyelids apart.

Canada: en Page: 2 / 14



acc. to Hazardous Products Regulations (HPR)

POR-15 Detail Spray

Version number: GHS 2.0
Replaces version of: 2021-05-14 (GHS 1)
Replaces version of: 2021-05-14 (GHS 1)

Following ingestion

Rinse mouth with water (only if the person is conscious). Do NOT induce vomiting.

4.2 Most important symptoms and effects, both acute and delayed

Symptoms and effects are not known to date.

4.3 Indication of any immediate medical attention and special treatment needed

none

SECTION 5: Fire-fighting measures

5.1 Extinguishing media

Suitable extinguishing media

Water spray, BC-powder, Carbon dioxide (CO2)

Unsuitable extinguishing media

Water jet

5.2 Special hazards arising from the substance or mixture

In case of insufficient ventilation and/or in use, may form flammable/explosive vapor-air mixture. Solvent vapors are heavier than air and may spread along floors. Places which are not ventilated, e.g. unventilated below ground level areas such as trenches, conduits and shafts, are particularly prone to the presence of flammable substances or mixtures.

Hazardous combustion products

Nitrogen oxides (NOx)

5.3 Advice for firefighters

In case of fire and/or explosion do not breathe fumes. Coordinate firefighting measures to the fire surroundings. Do not allow firefighting water to enter drains or water courses. Collect contaminated firefighting water separately. Fight fire with normal precautions from a reasonable distance.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

Remove persons to safety.

For emergency responders

Wear breathing apparatus if exposed to vapors/dust/aerosols/gases.

6.2 Environmental precautions

Keep away from drains, surface and ground water. Retain contaminated washing water and dispose of it.

6.3 Methods and material for containment and cleaning up

Advice on how to contain a spill

Covering of drains

Advice on how to clean up a spill

Wipe up with absorbent material (e.g. cloth, fleece). Collect spillage: sawdust, kieselgur (diatomite), sand, universal binder

Appropriate containment techniques

Use of adsorbent materials.

Other information relating to spills and releases

Place in appropriate containers for disposal. Ventilate affected area.

Canada: en Page: 3 / 14



acc. to Hazardous Products Regulations (HPR)

POR-15 Detail Spray

Version number: GHS 2.0
Replaces version of: 2021-05-14 (GHS 1)
Replaces version of: 2021-05-14 (GHS 1)

,

Hazardous combustion products: see section 5. Personal protective equipment: see section 8. Incompatible materials: see section 10. Disposal considerations: see section 13.

SECTION 7: Handling and storage

Reference to other sections

7.1 Precautions for safe handling

Recommendations

- Measures to prevent fire as well as aerosol and dust generation

Use local and general ventilation. Avoidance of ignition sources. Keep away from sources of ignition - No smoking. Take precautionary measures against static discharge. Use only in well-ventilated areas. Due to danger of explosion, prevent leakage of vapours into cellars, flues and ditches. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting/equipment. Use only non-sparking tools.

- Specific notes/details

Places which are not ventilated, e.g. unventilated below ground level areas such as trenches, conduits and shafts, are particularly prone to the presence of flammable substances or mixtures. Vapors are heavier than air, spread along floors and form explosive mixtures with air.

Advice on general occupational hygiene

Wash hands after use. Do not eat, drink and smoke in work areas. Remove contaminated clothing and protective equipment before entering eating areas. Never keep food or drink in the vicinity of chemicals. Never place chemicals in containers that are normally used for food or drink. Keep away from food, drink and animal feedingstuffs.

7.2 Conditions for safe storage, including any incompatibilities

Managing of associated risks

- Explosive atmospheres

Keep container tightly closed and in a well-ventilated place. Use local and general ventilation. Keep cool. Protect from sunlight.

- Flammability hazards

Keep away from sources of ignition - No smoking. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Take precautionary measures against static discharge. Protect from sunlight.

Control of the effects

Protect against external exposure, such as

frost

- Ventilation requirements

Use local and general ventilation. Ground/bond container and receiving equipment.

(BC)

7.3 Specific end use(s)

See section 16 for a general overview.

methyl ether

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limit values (Workplace Exposure Limits) CAS No Name of agent CA (2-methoxymethyl-34590-94-8 **OEL** 100 150 Н MoL (ONethoxy)propanol (DPM) MoL) CA BC Reg dipropylene glycol 34590-94-8 **OEL** 100 150

ulation

Canada: en Page: 4 / 14



acc. to Hazardous Products Regulations (HPR)

POR-15 Detail Spray

Version number: GHS 2.0
Replaces version of: 2021-05-14 (GHS 1)
Replaces version of: 2021-05-14 (GHS 1)

Occupational exposure limit values (Workplace Exposure Limits)

Coun- try	Name of agent	CAS No	Identifi- er	TWA [ppm]	TWA [mg/m³]	STEL [ppm]	STEL [mg/m³]	Ceiling-C [ppm]	Ceiling-C [mg/m³]	Nota- tion	Source
CA	dipropylene glycol methyl ether ((2- methoxymethyleth- oxy)propanol) (DP- GME)	34590-94-8	OEL (AB)	100	606	150	909				OHS Code
CA	dipropylene glycol monomethyl ether	34590-94-8	PEV/ VEA	100	606	150	909				Regula- tion OHS

Notation

Ceiling-C ceiling value is a limit value above which exposure should not occur

absorbed through the skin

STEL short-term exposure limit: a limit value above which exposure should not occur and which is related to a 15-minute period (unless

otherwise specified)

TWA time-weighted average (long-term exposure limit): measured or calculated in relation to a reference period of 8 hours time-weighted

average (unless otherwise specified

Relevant DNELs of components of the mixture

Name of substance	CAS No	Endpoint	Threshold level	Protection goal, route of exposure	Used in	Exposure time
dipropylene glycol monomethyl ether	34590-94-8	DNEL	950 mg/kg	human, dermal	worker (industry)	chronic - systemic effects
dipropylene glycol monomethyl ether	34590-94-8	DNEL	404 mg/m ³	human, inhalatory	worker (industry)	chronic - systemic effects

Relevant PNECs of components of the mixture

Name of substance	CAS No	Endpoint	Threshold level	Organism	Environmental compartment	Exposure time
dipropylene glycol monomethyl ether	34590-94-8	PNEC	4,168 ^{mg} / _I	microorganisms	sewage treatment plant (STP)	short-term (single instance)
dipropylene glycol monomethyl ether	34590-94-8	PNEC	19.2 ^{mg} / _l	aquatic organisms	freshwater	short-term (single instance)
dipropylene glycol monomethyl ether	34590-94-8	PNEC	1.92 ^{mg} / _l	aquatic organisms	marine water	short-term (single instance)
dipropylene glycol monomethyl ether	34590-94-8	PNEC	4,168 ^{mg} / _I	aquatic organisms	sewage treatment plant (STP)	short-term (single instance)
dipropylene glycol monomethyl ether	34590-94-8	PNEC	2.2 ^{mg} / _{kg}	terrestrial organisms	soil	short-term (single instance)
dipropylene glycol monomethyl ether	34590-94-8	PNEC	192 ^{mg} / _l	aquatic organisms	water	intermittent release

8.2 Exposure controls

Appropriate engineering controls

General ventilation.

Individual protection measures (personal protective equipment)

Eye/face protection

Wear eye/face protection.

Canada: en Page: 5 / 14



acc. to Hazardous Products Regulations (HPR)

POR-15 Detail Spray

Version number: GHS 2.0
Replaces version of: 2021-05-14 (GHS 1)
Replaces version of: 2021-05-14 (GHS 1)

Skin protection

- Hand protection

Wear suitable gloves. Chemical protection gloves are suitable, which are tested according to EN 374. Check leak-tightness/impermeability prior to use. In the case of wanting to use the gloves again, clean them before taking off and air them well. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

Other protection measures

Take recovery periods for skin regeneration. Preventive skin protection (barrier creams/ointments) is recommended. Wash hands thoroughly after handling.

Respiratory protection

In case of inadequate ventilation wear respiratory protection.

Environmental exposure controls

Use appropriate container to avoid environmental contamination. Keep away from drains, surface and ground water.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance

Physical state	liquid
Color	turquoise
Particle	not relevant (liquid)
Odor	citrus

Other safety parameters

pH (value)	5.5 – 6.5 (25 °C)
Melting point/freezing point	-83 °C at 101,325 Pa
Initial boiling point and boiling range	100 °C
Flash point	86 °C at 101.3 kPa
Evaporation rate	not determined
Flammability (solid, gas)	not relevant, (fluid)

Explosive limits

- Lower explosion limit (LEL)	1.1 vol%
- Upper explosion limit (UEL)	3 vol%

Canada: en Page: 6 / 14



acc. to Hazardous Products Regulations (HPR)

POR-15 Detail Spray

Version number: GHS 2.0
Replaces version of: 2021-05-14 (GHS 1)
Replaces version of: 2021-05-14 (GHS 1)

Vapor pressure	31.69 hPa at 25 °C
Density	8.68 lb/ _{gal} at 25 °C 1.03 – 1.04 ^g / _{cm³} at 25 °C
Vapor density	this information is not available
Solubility(ies)	not determined

Partition coefficient

- n-octanol/water (log KOW)	this information is not available
Auto-ignition temperature	270 °C
Viscosity	not determined
Explosive properties	not explosive (GHS of the United Nations, annex 4)
Oxidizing properties	none
	there is no additional information

9.2 there is no additional information

SECTION 10: Stability and reactivity

10.1 Reactivity

Concerning incompatibility: see below "Conditions to avoid" and "Incompatible materials". The mixture contains reactive substance(s). Risk of ignition.

If heated:

Risk of ignition

10.2 Chemical stability

See below "Conditions to avoid".

10.3 Possibility of hazardous reactions

No known hazardous reactions.

10.4 Conditions to avoid

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Hints to prevent fire or explosion

Use explosion-proof electrical/ventilating/lighting/equipment. Use only non-sparking tools. Take precautionary measures against static discharge.

10.5 Incompatible materials

There is no additional information.

10.6 Hazardous decomposition products

Reasonably anticipated hazardous decomposition products produced as a result of use, storage, spill and heating are not known. Hazardous combustion products: see section 5.

Canada: en Page: 7 / 14



acc. to Hazardous Products Regulations (HPR)

POR-15 Detail Spray

Version number: GHS 2.0 Revision: 2021-06-18 Replaces version of: 2021-05-14 (GHS 1)

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Test data are not available for the complete mixture.

Classification procedure

The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

Classification acc. to GHS

Acute toxicity

Shall not be classified as acutely toxic.

Acute toxicity estimate (ATE) of components of the mixture

isododecane	13475-82-6	inhalation: vapour	>4.951 ^{mg} / _l /4h
Name of substance	CAS No	Exposure route	ATE

Skin corrosion/irritation

Shall not be classified as corrosive/irritant to skin.

Serious eye damage/eye irritation

Shall not be classified as seriously damaging to the eye or eye irritant.

Respiratory or skin sensitization

May cause an allergic skin reaction.

Germ cell mutagenicity

Shall not be classified as germ cell mutagenic.

Carcinogenicity

Shall not be classified as carcinogenic.

Reproductive toxicity

Shall not be classified as a reproductive toxicant.

Specific target organ toxicity - single exposure

Shall not be classified as a specific target organ toxicant (single exposure).

Specific target organ toxicity - repeated exposure

Shall not be classified as a specific target organ toxicant (repeated exposure).

Aspiration hazard

Shall not be classified as presenting an aspiration hazard.

SECTION 12: Ecological information

12.1 Toxicity

Toxic to aquatic life.

Aquatic toxicity (acute) of components of the mixture

requality (desire) of components of the mixture								
Name of substance	CAS No	Endpoint	Value	Species	Exposure time			
dipropylene glycol mono- methyl ether	34590-94-8	LC50	>150 ^{mg} / _I	fish	72 h			
dipropylene glycol mono- methyl ether	34590-94-8	ErC50	>969 ^{mg} / _I	algae	72 h			

Canada: en Page: 8 / 14



acc. to Hazardous Products Regulations (HPR)

POR-15 Detail Spray

Version number: GHS 2.0 Revision: 2021-06-18 Replaces version of: 2021-05-14 (GHS 1)

Aquatic toxicity (acute) of components of the mixture

Name of substance	CAS No	Endpoint	Value	Species	Exposure time
benzotriazole polymer mix- ture UV Absorber	not available	LC50	2.8 ^{mg} / _l	fish	96 h
benzotriazole polymer mix- ture UV Absorber	not available	EC50	4 ^{mg} / _l	daphnia magna	48 h
benzotriazole polymer mix- ture UV Absorber	not available	EC50	>100 ^{mg} / _l	algae	72 h
isododecane	13475-82-6	LL50	>1,028 ^{mg} / _I	fish	96 h
isododecane	13475-82-6	EL50	>1,000 ^{mg} / _I	aquatic invertebrates	24 h

Persistence and degradability 12.2

Data are not available.

12.3 **Bioaccumulative potential**

Data are not available.

12.4 Mobility in soil

Data are not available.

Results of PBT and vPvB assessment 12.5

Data are not available.

12.6 **Endocrine disrupting properties**

None of the ingredients are listed.

12.7 Other adverse effects

Data are not available.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Waste treatment-relevant information

Solvent reclamation/regeneration.

Sewage disposal-relevant information

Do not empty into drains. Avoid release to the environment. Refer to special instructions/safety data sheets.

Waste treatment of containers/packages

Completely emptied packages can be recycled. Handle contaminated packages in the same way as the substance itself.

Remarks

Please consider the relevant national or regional provisions. Waste shall be separated into the categories that can be handled separately by the local or national waste management facilities.

Canada: en Page: 9 / 14



acc. to Hazardous Products Regulations (HPR)

POR-15 Detail Spray

Version number: GHS 2.0
Replaces version of: 2021-05-14 (GHS 1)
Replaces version of: 2021-05-14 (GHS 1)

SECTION 14: Transport information

14.1 UN number not subject to transport regulations

14.2 UN proper shipping name not relevant
 14.3 Transport hazard class(es) not assigned
 14.4 Packing group not assigned

14.5 Environmental hazards non-environmentally hazardous acc. to the dangerous

goods regulations

14.6 Special precautions for user

There is no additional information.

14.7 Transport in bulk according to Annex II of MARPOL and the IBC Code

The cargo is not intended to be carried in bulk.

Information for each of the UN Model Regulations

Transport information - National regulations - Additional information (UN RTDG)

Not subject to transport regulations: UN RTDG

International Maritime Dangerous Goods Code (IMDG) - Additional information

Not subject to IMDG.

International Civil Aviation Organization (ICAO-IATA/DGR) - Additional information

Not subject to ICAO-IATA.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations specific for the product in question

National regulations (United States)

Toxic Substance Control Act (TSCA) all ingredients are listed

Superfund Amendment and Reauthorization Act (SARA TITLE III)

- The List of Extremely Hazardous Substances and Their Threshold Planning Quantities (EPCRA Section 302, 304)

none of the ingredients are listed

Clean Air Act

none of the ingredients are listed

Right to Know Hazardous Substance List

- Cleaning Product Right to Know Act Substance List (CA-RTK)

Name of substance	CAS No	Functionality	Authoritative Lists
Water	7732-18-5	solvent	
dipropylene glycol monomethyl ether	34590-94-8	surfactant	
C13-15 alkanes	64742-46-7	solvents	EC Annex VI CMRs - Cat. 1B
2-(2-butoxyethoxy)ethanol		co-solvent	CA TACs
Alcohols, C9-11 ethoxylated	68439-46-3	surfactant	
polyurethane resin	not available	polymer	

Canada: en Page: 10 / 14



acc. to Hazardous Products Regulations (HPR)

POR-15 Detail Spray

Version number: GHS 2.0 Revision: 2021-06-18 Replaces version of: 2021-05-14 (GHS 1)

Name of substance	CAS No	Functionality	Authoritative Lists
benzotriazole polymer mixture UV Absorber	not available	UV absorber	
Oxydipropanol	25265-71-8	fragrance	
isododecane	13475-82-6	solvents	
d-limonene	5989-27-5		EU Fragrance Allergens
benzyl benzoate	120-51-4	fragrance	EU Fragrance Allergens
Citral	5392-40-5	fragrance	
di-Citronellol	106-22-9	fragrance	

- Hazardous Substances List (MN-ERTK)

Name of substance	CAS No	References	Remarks
dipropylene glycol monomethyl ether	34590-94-8	A, O	

Legend

- Hazardous Substance List (NJ-RTK)

Name of substance	CAS No	Remarks	Classifications
dipropylene glycol monomethyl ether	34590-94-8		F2

Legend

Flammable - Second Degree

- Hazardous Substance List (Chapter 323) (PA-RTK)

Name acc. to inventory	CAS No	Classification
PROPANOL, (2-METHOXYMETHYLETHOXY)-	34590-94-8	

- Hazardous Substance List (RI-RTK)

Name of substance	CAS No	References
dipropylene glycol monomethyl ether	34590-94-8	Т

Toxicity (ACGIH®)

California Environmental Protection Agency (Cal/EPA): Proposition 65 - Safe Drinking Water and **Toxic Enforcement Act of 1987**

Proposition 65 List of chemicals					
Name acc. to inventory	CAS No	Wt%	Remarks	Type of the toxicity	
styrene	100-42-5	0.000004542		cancer	

VOC content

- Regulated Volatile Organic Compounds (VOC-EPA)

2.446 %

Canada: en Page: 11 / 14

American Conference of Governmental Industrial Hygienists (ACGIH), "Threshold Limit Values for Chemical Substances and Physical Agents and Biological Exposure Indices for 1992-93", available from ACGIH
Occupational Safety and Health Administration (OSHA), Safety and Health Standards, Code of Federal Regulations, title 29, part 1910, subpart Z, "Toxic and Hazardous Substances, 1990." General information: Minnesota Department of Labor and Industry, Occupational 0 Safety and Health Division



acc. to Hazardous Products Regulations (HPR)

POR-15 Detail Spray

Version number: GHS 2.0
Revision: 2021-06-18
Replaces version of: 2021-05-14 (GHS 1)

- Regulated Volatile Organic Compounds (VOC-Cal ARB)

2.446 %

Industry or sector specific available guidance(s) NPCA-HMIS® III

Hazardous Materials Identification System. American Coatings Association.

Category	Rating	Description
Chronic	*	chronic (long-term) health effects may result from repeated overexposure
Health	2	temporary or minor injury may occur
Flammability	2	material that must be moderately heated or exposed to relatively high ambient temperatures before ignition can occur
Physical hazard	0	material that is normally stable, even under fire conditions, and will not react with water, polymerize, decompose, condense, or self-react. Non-explosive
Personal protection	-	

NFPA® 704

National Fire Protection Association: Standard System for the Identification of the Hazards of Materials for Emergency Response (United States).

Category	Degree of hazard	Description
Flammability	2	material that must be moderately heated or exposed to relatively high ambient temperatures before ignition can occur
Health	2	material that, under emergency conditions, can cause temporary incapacitation or residual injury
Instability	0	material that is normally stable, even under fire conditions
Special hazard		

National regulations (Canada)

Domestic Substances List (DSL)

All ingredients are listed.

National inventories

Country	Inventory	Status
CA	DSL	all ingredients are listed
EU	REACH Reg.	not all ingredients are listed
US	TSCA	all ingredients are listed

Legend

DSL Domestic Substances List (DSL)
REACH Reg.
REACH registered substances
TSCA Toxic Substance Control Act

15.2 Chemical Safety Assessment

Chemical safety assessments for substances in this mixture were not carried out.

Canada: en Page: 12 / 14



acc. to Hazardous Products Regulations (HPR)

POR-15 Detail Spray

Version number: GHS 2.0 Revision: 2021-06-18 Replaces version of: 2021-05-14 (GHS 1)

SECTION 16: Other information

Indication of changes (revised safety data sheet)

Section	Former entry (text/value)	Actual entry (text/value)	Safety-rel- evant
1.1		Product code(s): 53020, 253020	yes

Abbreviations and acronyms

Abbr.	Descriptions of used abbreviations
"BC Regulation"	OHS Regulation: Section 5.48 (British Columbia)
ACGIH®	American Conference of Governmental Industrial Hygienists
Acute Tox.	Acute toxicity
Asp. Tox.	Aspiration hazard
ATE	Acute Toxicity Estimate
Cal ARB	California Air Resources Board
CAS	Chemical Abstracts Service (service that maintains the most comprehensive list of chemical substances)
Ceiling-C	Ceiling value
DGR	Dangerous Goods Regulations (see IATA/DGR)
DNEL	Derived No-Effect Level
EC50	Effective Concentration 50 %. The EC50 corresponds to the concentration of a tested substance causing 50 % changes in response (e.g. on growth) during a specified time interval
EL50	Effective Loading 50 %: the EL50 corresponds to the loading rate required to produce a response in 50% of the test organisms
EPA	Environmental Protection Agency. An agency of the federal government of the United States charged with protecting human health and the environment
ErC50	≡ EC50: in this method, that concentration of test substance which results in a 50 % reduction in either growth (EbC50) or growth rate (ErC50) relative to the control
Eye Dam.	Seriously damaging to the eye
Eye Irrit.	Irritant to the eye
Flam. Liq.	Flammable liquid
GHS	"Globally Harmonized System of Classification and Labelling of Chemicals" developed by the United Nations
IATA	International Air Transport Association
IATA/DGR	Dangerous Goods Regulations (DGR) for the air transport (IATA)
ICAO	International Civil Aviation Organization
IMDG	International Maritime Dangerous Goods Code
LC50	Lethal Concentration 50%: the LC50 corresponds to the concentration of a tested substance causing 50 % lethality during a specified time interval
LL50	Lethal Loading 50 %: the LL50 corresponds to the loading rate causing 50 % lethality
MARPOL	International Convention for the Prevention of Pollution from Ships (abbr. of "Marine Pollutant")
MoL	Ministry of Labor: Current Occupational Exposure Limits for Ontario Workplaces Required under Regulation 833

Canada: en Page: 13 / 14



acc. to Hazardous Products Regulations (HPR)

POR-15 Detail Spray

Version number: GHS 2.0
Replaces version of: 2021-05-14 (GHS 1)
Replaces version of: 2021-05-14 (GHS 1)

Abbr.	Descriptions of used abbreviations
NPCA-HMIS® III	National Paint and Coatings Association: Hazardous Materials Identification System - HMIS® III, Third Edition
OHS Code	Occupational Health and Safety Code: Occupational exposure limits for chemical substances (Alberta)
PBT	Persistent, Bioaccumulative and Toxic
PNEC	Predicted No-Effect Concentration
ppm	Parts per million
Regulation OHS	Regulation respecting occupational health and safety: Permissible exposure values for airborne contaminants (Quebec)
RTECS	Registry of Toxic Effects of Chemical Substances (database of NIOSH with toxicological information)
Skin Corr.	Corrosive to skin
Skin Irrit.	Irritant to skin
Skin Sens.	Skin sensitization
STEL	Short-term exposure limit
TWA	Time-weighted average
UN RTDG	UN Recommendations on the Transport of Dangerous Good
VOC	Volatile Organic Compounds
vPvB	Very Persistent and very Bioaccumulative

Key literature references and sources for data

Hazardous Products Regulations (HPR).

UN Recommendations on the Transport of Dangerous Good. International Maritime Dangerous Goods Code (IMDG). Dangerous Goods Regulations (DGR) for the air transport (IATA).

Classification procedure

Physical and chemical properties: The classification is based on tested mixture.

Health hazards, Environmental hazards: The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

List of relevant phrases (code and full text as stated in chapter 2 and 3)

Code	Text
H226	Flammable liquid and vapour.
H227	Combustible liquid.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H331	Toxic if inhaled.

Disclaimer

This information is based upon the present state of our knowledge. This SDS has been compiled and is solely intended for this product.

Canada: en Page: 14 / 14