



Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

POR-15 ENGINE ENAMEL FORD BLUE

Version number: GHS 3.1
Replaces version of: 2023-12-07 (GHS 2)

Revision: 2024-06-17

SECTION 1: Identification

1.1 Product identifier

Trade name **POR-15 ENGINE ENAMEL FORD BLUE**
Product code(s) 42105, 42158

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses Paint

1.3 Details of the supplier of the safety data sheet

P.O.R. Products
38 Portman Road
New Rochelle NY 10801
United States

Telephone: +1 914-636-0700
e-mail: support@porproducts.com
Website: www.porproducts.com

e-mail (competent person) support@porproducts.com

1.4 Emergency telephone number

Emergency information service 1-800-255-3924
ChemTel Inc.

SECTION 2: Hazard(s) identification

2.1 Classification of the substance or mixture

Classification acc. to OSHA "Hazard Communication Standard" (29 CFR 1910.1200)

Section	Hazard class	Category	Hazard class and category	Hazard statement
A.1I	acute toxicity (inhal.)	4	Acute Tox. 4	H332
A.4S	skin sensitization	1	Skin Sens. 1	H317
A.5	germ cell mutagenicity	1B	Muta. 1B	H340
A.6	carcinogenicity	1A	Carc. 1A	H350
A.9	specific target organ toxicity - repeated exposure	1	STOT RE 1	H372
A.10	aspiration hazard	1	Asp. Tox. 1	H304
B.6	flammable liquid	3	Flam. Liq. 3	H226

For full text of abbreviations: see SECTION 16.

The most important adverse physicochemical, human health and environmental effects

Delayed or immediate effects can be expected after short or long-term exposure. The product is combustible and can be ignited by potential ignition sources.

2.2 Label elements

POR-15 ENGINE ENAMEL FORD BLUE

Version number: GHS 3.1
Replaces version of: 2023-12-07 (GHS 2)

Revision: 2024-06-17

Labelling acc. to OSHA "Hazard Communication Standard" (29 CFR 1910.1200)

- Signal word danger

- Pictograms

GHS02, GHS07, GHS08



- Hazard statements

H226	Flammable liquid and vapor.
H304	May be fatal if swallowed and enters airways.
H317	May cause an allergic skin reaction.
H332	Harmful if inhaled.
H340	May cause genetic defects.
H350	May cause cancer.
H372	Causes damage to organs through prolonged or repeated exposure.

- Precautionary statements

P201	Obtain special instructions before use.
P210	Keep away from heat/sparks/open flames/hot surfaces. No smoking.
P233	Keep container tightly closed.
P240	Ground/bond container and receiving equipment.
P241	Use explosion-proof electrical/ventilating/lighting equipment.
P242	Use only non-sparking tools.
P243	Take precautionary measures against static discharge.
P260	Do not breathe dust/fume/gas/mist/vapors/spray.
P270	Do not eat, drink or smoke when using this product.
P271	Use only outdoors or in a well-ventilated area.
P272	Contaminated work clothing must not be allowed out of the workplace.
P280	Wear protective gloves/eye protection/face protection.
P301+P310	If swallowed: Immediately call a poison center/doctor.
P302+P352	If on skin: Wash with plenty of water.
P303+P361+P353	If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
P304+P340	If inhaled: Remove person to fresh air and keep comfortable for breathing.
P312	Call a poison center/doctor if you feel unwell.
P321	Specific treatment (see on this label).
P331	Do NOT induce vomiting.
P363	Wash contaminated clothing before reuse.
P370+P378	In case of fire: Use sand, carbon dioxide or powder extinguisher to extinguish.
P403+P235	Store in a well-ventilated place. Keep cool.
P405	Store locked up.
P501	Dispose of contents/container to industrial combustion plant.

- Hazardous ingredients for labelling

stoddard solvent, 2-butanone oxime, Naphtha (petroleum), hydrotreated heavy, Distillates (petroleum), hydro-treated light



Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

POR-15 ENGINE ENAMEL FORD BLUE

Version number: GHS 3.1
Replaces version of: 2023-12-07 (GHS 2)

Revision: 2024-06-17

2.3 Other hazards

Hazards not otherwise classified

Contains 2-butanone oxime. May produce an allergic reaction.

Very toxic to aquatic life with long lasting effects (GHS category 1: aquatic toxicity - acute and/or chronic).

Results of PBT and vPvB assessment

Does not contain a PBT-/vPvB-substance at a concentration of $\geq 0.1\%$.

Endocrine disrupting properties

Does not contain an endocrine disruptor (ED) in a concentration of $\geq 0.1\%$.

SECTION 3: Composition/information on ingredients

3.1 Substances

Not relevant (mixture)

3.2 Mixtures

Description of the mixture

Name of substance	Identifier	Wt%	Classification acc. to GHS
alkyd resin	CAS No 63148-69-6	50 - < 75	
stoddard solvent	CAS No 8052-41-3	25 - < 50	Acute Tox. 3 / H331 Muta. 1B / H340 Carc. 1A / H350 STOT RE 1 / H372 Asp. Tox. 1 / H304 Flam. Liq. 3 / H226
Naphtha (petroleum), hydrotreated heavy	CAS No 64742-48-9	5 - < 10	Muta. 1B / H340 Carc. 1A / H350 Asp. Tox. 1 / H304 Flam. Liq. 1 / H224
Titanium dioxide (excluding nano-particle)	CAS No 13463-67-7	1 - < 5	Carc. 2 / H351
29H,31H-phthalocyaninato(2-)-N29,N30,N31,N32 copper	CAS No 147-14-8	0.1 - < 1	
Distillates (petroleum), hydro-treated light	CAS No 64742-47-8	0.1 - < 1	Acute Tox. 3 / H331 Asp. Tox. 1 / H304 Flam. Liq. 3 / H226
Soy Lecithin, Superior # 5, Superior DB	CAS No 8002-43-5	0.1 - < 1	
2-ethylhexanoic acid, zirconium salt	CAS No 22464-99-9	0.1 - < 1	Acute Tox. 4 / H332
Hexanoic acid, 2-ethyl-, cobalt(2+) salt (2:1)	CAS No 136-52-7	0.1 - < 1	



Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

POR-15 ENGINE ENAMEL FORD BLUE

Version number: GHS 3.1
Replaces version of: 2023-12-07 (GHS 2)

Revision: 2024-06-17

Name of substance	Identifier	Wt%	Classification acc. to GHS
2-butanone oxime	CAS No 96-29-7	0.1 – < 1	Acute Tox. 3 / H301 Acute Tox. 4 / H312 Acute Tox. 3 / H331 Skin Irrit. 2 / H315 Eye Dam. 1 / H318 Skin Sens. 1 / H317 Carc. 1B / H350 STOT SE 1 / H370 STOT SE 3 / H336 STOT RE 2 / H373 Flam. Liq. 4 / H227
Carbon black	CAS No 1333-86-4	0 – < 0.1	Carc. 1A / H350
Lecithins, soybean	CAS No 8030-76-0	0 – < 0.1	
2-(2-butoxyethoxy)ethanol	CAS No 112-34-5	0 – < 0.1	Eye Irrit. 2 / H319
ethyl benzene	CAS No 100-41-4	0 – < 0.1	Acute Tox. 4 / H332 Carc. 2 / H351 STOT RE 2 / H373 Asp. Tox. 1 / H304 Flam. Liq. 3 / H226
naphthalene	CAS No 91-20-3	0 – < 0.1	Acute Tox. 4 / H302 Acute Tox. 1 / H330 Carc. 2 / H351
solvent naphtha (petroleum), medium aliph.	CAS No 64742-88-7	0 – < 0.1	Acute Tox. 3 / H331 STOT RE 1 / H372 Asp. Tox. 1 / H304 Flam. Liq. 3 / H226
Solvent naphtha (petroleum), light arom.	CAS No 64742-95-6	0 – < 0.1	Muta. 1B / H340 Carc. 1A / H350 Asp. Tox. 1 / H304 Flam. Liq. 1 / H224
benzene	CAS No 71-43-2	0 – < 0.1	Skin Irrit. 2 / H315 Eye Irrit. 2 / H319 Muta. 1B / H340 Carc. 1A / H350 STOT RE 1 / H372 Asp. Tox. 1 / H304 Flam. Liq. 2 / H225
toluene	CAS No 108-88-3	0 – < 0.1	Skin Irrit. 2 / H315 Repr. 2 / H361d STOT SE 3 / H336 STOT RE 2 / H373 Asp. Tox. 1 / H304 Flam. Liq. 2 / H225

Remarks

For full text of abbreviations: see SECTION 16



Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

POR-15 ENGINE ENAMEL FORD BLUE

Version number: GHS 3.1
Replaces version of: 2023-12-07 (GHS 2)

Revision: 2024-06-17

SECTION 4: First-aid measures

4.1 Description of first-aid measures

General notes

Do not leave affected person unattended. Remove victim out of the danger area. Keep affected person warm, still and covered. Take off immediately all contaminated clothing. In all cases of doubt, or when symptoms persist, seek medical advice. In case of unconsciousness place person in the recovery position. Never give anything by mouth.

Following inhalation

If breathing is irregular or stopped, immediately seek medical assistance and start first aid actions. Provide fresh air.

Following skin contact

Wash with plenty of soap and water.

Following eye contact

Remove contact lenses, if present and easy to do. Continue rinsing. Irrigate copiously with clean, fresh water for at least 10 minutes, holding the eyelids apart.

Following ingestion

Rinse mouth with water (only if the person is conscious). Do NOT induce vomiting.

4.2 Most important symptoms and effects, both acute and delayed

Symptoms and effects are not known to date.

4.3 Indication of any immediate medical attention and special treatment needed

none

SECTION 5: Fire-fighting measures

5.1 Extinguishing media

Suitable extinguishing media

Water spray, BC-powder, Carbon dioxide (CO₂)

Unsuitable extinguishing media

Water jet

5.2 Special hazards arising from the substance or mixture

In case of insufficient ventilation and/or in use, may form flammable/explosive vapor-air mixture. Solvent vapors are heavier than air and may spread along floors. Places which are not ventilated, e.g. unventilated below ground level areas such as trenches, conduits and shafts, are particularly prone to the presence of flammable substances or mixtures.

Hazardous combustion products

Nitrogen oxides (NO_x), Carbon monoxide (CO), Carbon dioxide (CO₂)

5.3 Advice for firefighters

In case of fire and/or explosion do not breathe fumes. Coordinate firefighting measures to the fire surroundings. Do not allow firefighting water to enter drains or water courses. Collect contaminated firefighting water separately. Fight fire with normal precautions from a reasonable distance.

POR-15 ENGINE ENAMEL FORD BLUE

Version number: GHS 3.1
Replaces version of: 2023-12-07 (GHS 2)

Revision: 2024-06-17

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

Remove persons to safety.

For emergency responders

Wear breathing apparatus if exposed to vapors/dust/aerosols/gases.

6.2 Environmental precautions

Keep away from drains, surface and ground water. Retain contaminated washing water and dispose of it. If substance has entered a water course or sewer, inform the responsible authority.

6.3 Methods and material for containment and cleaning up

Advice on how to contain a spill

Covering of drains

Advice on how to clean up a spill

Wipe up with absorbent material (e.g. cloth, fleece). Collect spillage: sawdust, kieselgur (diatomite), sand, universal binder

Appropriate containment techniques

Use of adsorbent materials.

Other information relating to spills and releases

Place in appropriate containers for disposal. Ventilate affected area.

6.4 Reference to other sections

Hazardous combustion products: see section 5. Personal protective equipment: see section 8. Incompatible materials: see section 10. Disposal considerations: see section 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Recommendations

- Measures to prevent fire as well as aerosol and dust generation

Use local and general ventilation. Avoidance of ignition sources. Keep away from sources of ignition - No smoking. Take precautionary measures against static discharge. Use only in well-ventilated areas. Due to danger of explosion, prevent leakage of vapours into cellars, flues and ditches. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting/equipment. Use only non-sparking tools.

- Specific notes/details

Places which are not ventilated, e.g. unventilated below ground level areas such as trenches, conduits and shafts, are particularly prone to the presence of flammable substances or mixtures. Vapors are heavier than air, spread along floors and form explosive mixtures with air. Vapors may form explosive mixtures with air.

Advice on general occupational hygiene

Wash hands after use. Do not eat, drink and smoke in work areas. Remove contaminated clothing and protective equipment before entering eating areas. Never keep food or drink in the vicinity of chemicals. Never place chemicals in containers that are normally used for food or drink. Keep away from food, drink and animal feedingstuffs.

POR-15 ENGINE ENAMEL FORD BLUE

Version number: GHS 3.1
Replaces version of: 2023-12-07 (GHS 2)

Revision: 2024-06-17

7.2 Conditions for safe storage, including any incompatibilities

Managing of associated risks

- Explosive atmospheres

Keep container tightly closed and in a well-ventilated place. Use local and general ventilation. Keep cool. Protect from sunlight.

- Flammability hazards

Keep away from sources of ignition - No smoking. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Take precautionary measures against static discharge. Protect from sunlight.

- Ventilation requirements

Keep any substance that emits harmful vapors or gases in a place that allows these to be permanently extracted. Use local and general ventilation. Ground/bond container and receiving equipment.

- Packaging compatibilities

Only packagings which are approved (e.g. acc. to the Dangerous Goods Regulations) may be used.

7.3 Specific end use(s)

See section 16 for a general overview.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limit values (Workplace Exposure Limits)											
Country	Name of agent	CAS No	Identifier	TWA [ppm]	TWA [mg/m ³]	STEL [ppm]	STEL [mg/m ³]	Ceiling-C [ppm]	Ceiling-C [mg/m ³]	Notation	Source
US	ethylbenzene	100-41-4	PEL (CA)	5	22	30	130				Cal/ OSHA PEL
US	ethylbenzene	100-41-4	REL	100 (10 h)	435 (10 h)	125	545				NIOSH REL
US	ethylbenzene	100-41-4	TLV®	20							ACGIH® 2024
US	ethylbenzene	100-41-4	PEL	100	435						29 CFR 1910.1000
US	toluene	108-88-3	REL	100 (10 h)	375 (10 h)	150	560				NIOSH REL
US	toluene	108-88-3	TLV®	20							ACGIH® 2024
US	toluene	108-88-3	PEL	200		500 (10 min)		300			29 CFR 1910.1000
US	toluene (toluol)	108-88-3	PEL (CA)	10	37	150	560	500		H	Cal/ OSHA PEL
US	diethylene glycol monobutyl ether	112-34-5	TLV®	10						iv	ACGIH® 2024



Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

POR-15 ENGINE ENAMEL FORD BLUE

Version number: GHS 3.1
Replaces version of: 2023-12-07 (GHS 2)

Revision: 2024-06-17

Occupational exposure limit values (Workplace Exposure Limits)

Country	Name of agent	CAS No	Identifier	TWA [ppm]	TWA [mg/m³]	STEL [ppm]	STEL [mg/m³]	Ceiling-C [ppm]	Ceiling-C [mg/m³]	Notation	Source
US	carbon black	1333-86-4	PEL (CA)		3.5						Ca/ OSHA PEL
US	carbon black	1333-86-4	PEL		3.5						29 CFR 1910.1000
US	carbon black	1333-86-4	REL		3.5 (10 h)					appx-A, appx-C	NIOSH REL
US	carbon black	1333-86-4	TLV®		3					i	ACGIH® 2024
US	carbon black in presence of polycyclic aromatic hydrocarbons (PAHs)	1333-86-4	REL		0.1 (10 h)					PAHs, appx-A, appx-C	NIOSH REL
US	titanium dioxide	13463-67-7	PEL		15					dust	29 CFR 1910.1000
US	titanium dioxide	13463-67-7	REL							lowest, appx-A	NIOSH REL
US	titanium dioxide	13463-67-7	TLV®		2.5					r, fine	ACGIH® 2024
US	titanium dioxide	13463-67-7	TLV®		0.2					r, nano	ACGIH® 2024
US	petroleum distillates (naphtha) (rubber solvent)	64742-48-9	PEL	500	2,000						29 CFR 1910.1000
US	benzene	71-43-2	REL	0.1 (10 h)		1				appx-A	NIOSH REL
US	benzene	71-43-2	PEL (CA)	1		5				H	Ca/ OSHA PEL
US	benzene	71-43-2	TLV®	0.02						H	ACGIH® 2024
US	benzene	71-43-2	PEL	1		5				H, i	29 CFR 1910.1000
US	benzene	71-43-2	PEL	10		50 (10 min)		25		us-pel-z2a	29 CFR 1910.1000
US	stoddard solvent	8052-41-3	PEL (CA)	100	525						Ca/ OSHA PEL
US	stoddard solvent	8052-41-3	REL		350 (10 h)				1,800 (15 min)		NIOSH REL



Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

POR-15 ENGINE ENAMEL FORD BLUE

Version number: GHS 3.1
Replaces version of: 2023-12-07 (GHS 2)

Revision: 2024-06-17

Occupational exposure limit values (Workplace Exposure Limits)

Country	Name of agent	CAS No	Identifier	TWA [ppm]	TWA [mg/m ³]	STEL [ppm]	STEL [mg/m ³]	Ceiling-C [ppm]	Ceiling-C [mg/m ³]	Notation	Source
US	stoddard solvent	8052-41-3	TLV®	100							ACGIH® 2024
US	stoddard solvent	8052-41-3	PEL	500	2,900						29 CFR 1910.1000
US	naphthalene	91-20-3	REL	10 (10 h)	50 (10 h)	15	75				NIOSH REL
US	naphthalene	91-20-3	PEL	10	50						29 CFR 1910.1000
US	naphthalene	91-20-3	PEL (CA)	0.1	0.5					H	Cal/ OSHA PEL
US	naphthalene	91-20-3	TLV®	10						H	ACGIH® 2024

Notation

appx-A	NIOSH Potential Occupational Carcinogen (Appendix A)
appx-C	Appendix C - Supplementary Exposure Limits
Ceiling-C	ceiling value is a limit value above which exposure should not occur
dust	as dust
fine	fineparticle
H	absorbed through the skin
i	inhalable fraction
iv	inhalable fraction and vapor
lowest	exposure by all routes should be carefully controlled to levels as low as possible
nano	nanoparticle
PAHs	as polycyclic aromatic hydrocarbons (PAHs)
r	respirable fraction
STEL	short-term exposure limit: a limit value above which exposure should not occur and which is related to a 15-minute period (unless otherwise specified)
TWA	time-weighted average (long-term exposure limit): measured or calculated in relation to a reference period of 8 hours time-weighted average (unless otherwise specified)
us-pel-z2a	This standard applies to the industry segments exempt from the 1 ppm 8-hour TWA and 5 ppm STEL of the benzene standard at 1910.1028.

Biological limit values

Country	Name of agent	Parameter	Notation	Identifier	Value	Source
US	ethylbenzene	Sum of mandelic acid and phenylglyoxylic acid	crea	BEI®	150 mg/g	ACGIH® 2024
US	toluene	toluene		BEI®	0.02 mg/l	ACGIH® 2024
US	toluene	toluene		BEI®	0.03 mg/l	ACGIH® 2024
US	toluene	o-cresol	hydr, crea	BEI®	0.3 mg/g	ACGIH® 2024
US	benzene	S-phenylmercapturic acid	crea	BEI®	25 µg/g	ACGIH® 2024
US	benzene	trans,trans-muconic acid	crea	BEI®	500 µg/g	ACGIH® 2024

Notation

crea	creatinine
------	------------



Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

POR-15 ENGINE ENAMEL FORD BLUE

Version number: GHS 3.1
Replaces version of: 2023-12-07 (GHS 2)

Revision: 2024-06-17

Notation
hydr hydrolysis

Relevant DNELs of components						
Name of substance	CAS No	Endpoint	Threshold level	Protection goal, route of exposure	Used in	Exposure time
stoddard solvent	8052-41-3	DNEL	44 mg/m ³	human, inhalatory	worker (industry)	chronic - systemic effects
stoddard solvent	8052-41-3	DNEL	55 mg/m ³	human, inhalatory	worker (industry)	acute - systemic effects
stoddard solvent	8052-41-3	DNEL	44 mg/m ³	human, inhalatory	worker (industry)	chronic - local effects
stoddard solvent	8052-41-3	DNEL	55 mg/m ³	human, inhalatory	worker (industry)	acute - local effects
stoddard solvent	8052-41-3	DNEL	80 mg/kg bw/day	human, dermal	worker (industry)	chronic - systemic effects
stoddard solvent	8052-41-3	DNEL	30 mg/kg bw/day	human, dermal	worker (industry)	acute - systemic effects
29H,31H-phthalocyaninato(2-)-N29,N30,N31,N32 copper	147-14-8	DNEL	4 mg/m ³	human, inhalatory	worker (industry)	chronic - systemic effects
29H,31H-phthalocyaninato(2-)-N29,N30,N31,N32 copper	147-14-8	DNEL	450 mg/kg bw/day	human, dermal	worker (industry)	chronic - systemic effects
Hexanoic acid, 2-ethyl-, cobalt(2+) salt (2:1)	136-52-7	DNEL	235.1 µg/m ³	human, inhalatory	worker (industry)	chronic - local effects
2-butanone oxime	96-29-7	DNEL	9 mg/m ³	human, inhalatory	worker (industry)	chronic - systemic effects
2-butanone oxime	96-29-7	DNEL	3.33 mg/m ³	human, inhalatory	worker (industry)	chronic - local effects
2-butanone oxime	96-29-7	DNEL	1.3 mg/kg bw/day	human, dermal	worker (industry)	chronic - systemic effects
2-butanone oxime	96-29-7	DNEL	2.5 mg/kg bw/day	human, dermal	worker (industry)	acute - systemic effects
2-(2-butoxyethoxy)ethanol	112-34-5	DNEL	67.5 mg/m ³	human, inhalatory	worker (industry)	chronic - systemic effects
2-(2-butoxyethoxy)ethanol	112-34-5	DNEL	67.5 mg/m ³	human, inhalatory	worker (industry)	chronic - local effects
2-(2-butoxyethoxy)ethanol	112-34-5	DNEL	101.2 mg/m ³	human, inhalatory	worker (industry)	acute - local effects
2-(2-butoxyethoxy)ethanol	112-34-5	DNEL	83 mg/kg bw/day	human, dermal	worker (industry)	chronic - systemic effects
ethyl benzene	100-41-4	DNEL	77 mg/m ³	human, inhalatory	worker (industry)	chronic - systemic effects
ethyl benzene	100-41-4	DNEL	293 mg/m ³	human, inhalatory	worker (industry)	acute - local effects

POR-15 ENGINE ENAMEL FORD BLUE

Version number: GHS 3.1
Replaces version of: 2023-12-07 (GHS 2)

Revision: 2024-06-17

Relevant DNELs of components						
Name of substance	CAS No	Endpoint	Threshold level	Protection goal, route of exposure	Used in	Exposure time
ethyl benzene	100-41-4	DNEL	180 mg/kg bw/day	human, dermal	worker (industry)	chronic - systemic effects
naphthalene	91-20-3	DNEL	25 mg/m ³	human, inhalatory	worker (industry)	chronic - systemic effects
naphthalene	91-20-3	DNEL	25 mg/m ³	human, inhalatory	worker (industry)	chronic - local effects
naphthalene	91-20-3	DNEL	3.57 mg/kg bw/day	human, dermal	worker (industry)	chronic - systemic effects
toluene	108-88-3	DNEL	192 mg/m ³	human, inhalatory	worker (industry)	chronic - systemic effects
toluene	108-88-3	DNEL	384 mg/m ³	human, inhalatory	worker (industry)	acute - systemic effects
toluene	108-88-3	DNEL	192 mg/m ³	human, inhalatory	worker (industry)	chronic - local effects
toluene	108-88-3	DNEL	384 mg/m ³	human, inhalatory	worker (industry)	acute - local effects
toluene	108-88-3	DNEL	384 mg/kg bw/day	human, dermal	worker (industry)	chronic - systemic effects

Relevant PNECs of components						
Name of substance	CAS No	Endpoint	Threshold level	Organism	Environmental compartment	Exposure time
stoddard solvent	8052-41-3	PNEC	0.14 mg/l	aquatic organisms	freshwater	short-term (single instance)
stoddard solvent	8052-41-3	PNEC	0.35 mg/l	aquatic organisms	marine water	short-term (single instance)
stoddard solvent	8052-41-3	PNEC	1.14 mg/kg	aquatic organisms	freshwater sediment	short-term (single instance)
stoddard solvent	8052-41-3	PNEC	0.14 mg/kg	aquatic organisms	marine sediment	short-term (single instance)
29H,31H-phthalocyaninato(2-)-N29,N30,N31,N32 copper	147-14-8	PNEC	10 mg/kg	aquatic organisms	freshwater sediment	short-term (single instance)
29H,31H-phthalocyaninato(2-)-N29,N30,N31,N32 copper	147-14-8	PNEC	1 mg/kg	aquatic organisms	marine sediment	short-term (single instance)
29H,31H-phthalocyaninato(2-)-N29,N30,N31,N32 copper	147-14-8	PNEC	1 mg/kg	terrestrial organisms	soil	short-term (single instance)
Hexanoic acid, 2-ethyl-, cobalt(2+) salt (2:1)	136-52-7	PNEC	0.62 µg/l	aquatic organisms	freshwater	short-term (single instance)



Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

POR-15 ENGINE ENAMEL FORD BLUE

Version number: GHS 3.1
Replaces version of: 2023-12-07 (GHS 2)

Revision: 2024-06-17

Relevant PNECs of components						
Name of substance	CAS No	Endpoint	Threshold level	Organism	Environmental compartment	Exposure time
Hexanoic acid, 2-ethyl-, cobalt(2+) salt (2:1)	136-52-7	PNEC	2.36 mg/l	aquatic organisms	marine water	short-term (single instance)
Hexanoic acid, 2-ethyl-, cobalt(2+) salt (2:1)	136-52-7	PNEC	0.37 mg/l	aquatic organisms	sewage treatment plant (STP)	short-term (single instance)
Hexanoic acid, 2-ethyl-, cobalt(2+) salt (2:1)	136-52-7	PNEC	53.8 mg/kg	aquatic organisms	freshwater sediment	short-term (single instance)
Hexanoic acid, 2-ethyl-, cobalt(2+) salt (2:1)	136-52-7	PNEC	69.8 mg/kg	aquatic organisms	marine sediment	short-term (single instance)
Hexanoic acid, 2-ethyl-, cobalt(2+) salt (2:1)	136-52-7	PNEC	10.9 mg/kg	terrestrial organisms	soil	short-term (single instance)
2-butanone oxime	96-29-7	PNEC	0.256 mg/l	aquatic organisms	freshwater	short-term (single instance)
2-butanone oxime	96-29-7	PNEC	177 mg/l	aquatic organisms	sewage treatment plant (STP)	short-term (single instance)
2-(2-butoxyethoxy)ethanol	112-34-5	PNEC	1.1 mg/l	aquatic organisms	freshwater	short-term (single instance)
2-(2-butoxyethoxy)ethanol	112-34-5	PNEC	0.11 mg/l	aquatic organisms	marine water	short-term (single instance)
2-(2-butoxyethoxy)ethanol	112-34-5	PNEC	200 mg/l	aquatic organisms	sewage treatment plant (STP)	short-term (single instance)
2-(2-butoxyethoxy)ethanol	112-34-5	PNEC	4.4 mg/kg	aquatic organisms	freshwater sediment	short-term (single instance)
2-(2-butoxyethoxy)ethanol	112-34-5	PNEC	0.44 mg/kg	aquatic organisms	marine sediment	short-term (single instance)
2-(2-butoxyethoxy)ethanol	112-34-5	PNEC	0.32 mg/kg	terrestrial organisms	soil	short-term (single instance)
ethyl benzene	100-41-4	PNEC	0.1 mg/l	aquatic organisms	freshwater	short-term (single instance)
ethyl benzene	100-41-4	PNEC	0.01 mg/l	aquatic organisms	marine water	short-term (single instance)
ethyl benzene	100-41-4	PNEC	9.6 mg/l	aquatic organisms	sewage treatment plant (STP)	short-term (single instance)
ethyl benzene	100-41-4	PNEC	13.7 mg/kg	aquatic organisms	freshwater sediment	short-term (single instance)
ethyl benzene	100-41-4	PNEC	1.37 mg/kg	aquatic organisms	marine sediment	short-term (single instance)
ethyl benzene	100-41-4	PNEC	2.68 mg/kg	terrestrial organisms	soil	short-term (single instance)
toluene	108-88-3	PNEC	0.68 mg/l	aquatic organisms	freshwater	short-term (single instance)

POR-15 ENGINE ENAMEL FORD BLUE

Version number: GHS 3.1
Replaces version of: 2023-12-07 (GHS 2)

Revision: 2024-06-17

Relevant PNECs of components						
Name of substance	CAS No	Endpoint	Threshold level	Organism	Environmental compartment	Exposure time
toluene	108-88-3	PNEC	0.68 mg/l	aquatic organisms	marine water	short-term (single instance)
toluene	108-88-3	PNEC	13.61 mg/l	aquatic organisms	sewage treatment plant (STP)	short-term (single instance)
toluene	108-88-3	PNEC	16.39 mg/kg	aquatic organisms	freshwater sediment	short-term (single instance)
toluene	108-88-3	PNEC	16.39 mg/kg	aquatic organisms	marine sediment	short-term (single instance)
toluene	108-88-3	PNEC	2.89 mg/kg	terrestrial organisms	soil	short-term (single instance)
benzene	71-43-2	PNEC	1.9 mg/l	aquatic organisms	freshwater	short-term (single instance)
benzene	71-43-2	PNEC	1.9 mg/l	aquatic organisms	marine water	short-term (single instance)
benzene	71-43-2	PNEC	39 mg/l	aquatic organisms	sewage treatment plant (STP)	short-term (single instance)
benzene	71-43-2	PNEC	33 mg/kg	aquatic organisms	freshwater sediment	short-term (single instance)
benzene	71-43-2	PNEC	33 mg/kg	aquatic organisms	marine sediment	short-term (single instance)
benzene	71-43-2	PNEC	4.8 mg/kg	terrestrial organisms	soil	short-term (single instance)

8.2 Exposure controls

Appropriate engineering controls

General ventilation.

Individual protection measures (personal protective equipment)

Eye/face protection

Wear eye/face protection.

Skin protection

- Hand protection

Wear suitable gloves. Chemical protection gloves are suitable, which are tested according to EN 374. Check leak-tightness/impermeability prior to use. In the case of wanting to use the gloves again, clean them before taking off and air them well. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

- Other protection measures

Take recovery periods for skin regeneration. Preventive skin protection (barrier creams/ointments) is recommended. Wash hands thoroughly after handling.

Respiratory protection

In case of inadequate ventilation wear respiratory protection.



Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

POR-15 ENGINE ENAMEL FORD BLUE

Version number: GHS 3.1
Replaces version of: 2023-12-07 (GHS 2)

Revision: 2024-06-17

Environmental exposure controls

Use appropriate container to avoid environmental contamination. Keep away from drains, surface and ground water.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance

Physical state	liquid
Color	not determined
Particle	not relevant (liquid)
Odor	characteristic

Other safety parameters

pH (value)	not determined
Melting point/freezing point	not determined
Initial boiling point and boiling range	≥-20 °C at 101.3 kPa
Flash point	43.4 °C
Evaporation rate	Not determined
Flammability (solid, gas)	not relevant, (fluid)

Explosive limits

- Lower explosion limit (LEL)	1.4 vol%
- Upper explosion limit (UEL)	7.6 vol%

Vapor pressure	≤240 kPa at 37.8 °C
Density	not determined
Vapor density	this information is not available
Relative density	Information on this property is not available
Solubility(ies)	not determined

Partition coefficient

- n-octanol/water (log KOW)	this information is not available
-----------------------------	-----------------------------------



Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

POR-15 ENGINE ENAMEL FORD BLUE

Version number: GHS 3.1
Replaces version of: 2023-12-07 (GHS 2)

Revision: 2024-06-17

Auto-ignition temperature	232 °C (auto-ignition temperature (liquids and gases))
Viscosity	not determined
Explosive properties	none
Oxidizing properties	none
9.2 VOC Content g/L	236

SECTION 10: Stability and reactivity

10.1 Reactivity

Concerning incompatibility: see below "Conditions to avoid" and "Incompatible materials". The mixture contains reactive substance(s). Risk of ignition.

If heated:

Risk of ignition

10.2 Chemical stability

See below "Conditions to avoid".

10.3 Possibility of hazardous reactions

No known hazardous reactions.

10.4 Conditions to avoid

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Hints to prevent fire or explosion

Use explosion-proof electrical/ventilating/lighting/equipment. Use only non-sparking tools. Take precautionary measures against static discharge.

10.5 Incompatible materials

Oxidizers

10.6 Hazardous decomposition products

Reasonably anticipated hazardous decomposition products produced as a result of use, storage, spill and heating are not known. Hazardous combustion products: see section 5.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Test data are not available for the complete mixture.

Classification procedure

The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

Classification acc. to OSHA "Hazard Communication Standard" (29 CFR 1910.1200)

Acute toxicity

Harmful if inhaled.

POR-15 ENGINE ENAMEL FORD BLUE

Version number: GHS 3.1
Replaces version of: 2023-12-07 (GHS 2)

Revision: 2024-06-17

- Acute toxicity estimate (ATE)

Inhalation: vapor >15.12 mg/l/4h

Acute toxicity estimate (ATE) of components

Name of substance	CAS No	Exposure route	ATE
stoddard solvent	8052-41-3	inhalation: vapor	>5.5 mg/l/4h
Distillates (petroleum), hydro-treated light	64742-47-8	inhalation: vapor	>5.28 mg/l/4h
2-ethylhexanoic acid, zirconium salt	22464-99-9	inhalation: dust/mist	>4.3 mg/l/4h
2-butanone oxime	96-29-7	dermal	>1,000 mg/kg
2-butanone oxime	96-29-7	inhalation: vapor	>4.83 mg/l/4h
ethyl benzene	100-41-4	inhalation: vapor	11 mg/l/4h
naphthalene	91-20-3	oral	710 mg/kg
naphthalene	91-20-3	inhalation: vapor	>0.4 mg/l/4h
naphthalene	91-20-3	inhalation: dust/mist	>0.005 mg/l/4h
solvent naphtha (petroleum), medium aliph.	64742-88-7	inhalation: vapor	>5.28 mg/l/4h

Skin corrosion/irritation

Shall not be classified as corrosive/irritant to skin.

Serious eye damage/eye irritation

Shall not be classified as seriously damaging to the eye or eye irritant.

Respiratory or skin sensitization

May cause an allergic skin reaction.

Germ cell mutagenicity

May cause genetic defects.

Carcinogenicity

May cause cancer.

IARC Monographs on the Evaluation of Carcinogenic Risks to Humans

Name of substance	CAS No	Classification	Number
ethyl benzene	100-41-4	2B	
Titanium dioxide (excluding nanoparticle)	13463-67-7	2B	
benzene	71-43-2	1	
naphthalene	91-20-3	2B	
toluene	108-88-3	3	
Carbon black	1333-86-4	2B	



Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

POR-15 ENGINE ENAMEL FORD BLUE

Version number: GHS 3.1
Replaces version of: 2023-12-07 (GHS 2)

Revision: 2024-06-17

Legend

- 1 Carcinogenic to humans
- 2B Possibly carcinogenic to humans
- 3 Not classifiable as to carcinogenicity in humans

National Toxicology Program (United States): Report on Carcinogens

Name of substance	CAS No	Classification	Number
benzene	71-43-2	Known to be a human carcinogen	1st Report on Carcinogens
naphthalene	91-20-3	Reasonably anticipated to be a human carcinogen	11th Report on Carcinogens
Carbon black	1333-86-4	Known to be human carcinogens	1st Report on Carcinogens

29 CFR 1910/1915/1926 Occupational Safety and Health Standards: Toxic and Hazardous Substances (carcinogens)

Name of substance	CAS No	Type of registration
benzene	71-43-2	GI §1910.1028, SE §1915.1028, CI §1926.1128

Legend

- CI §1926.1128 Construction Industry (29 CFR 1926.1128)
- GI §1910.1028 General Industry (29 CFR 1910.1028)
- SE §1915.1028 Shipyard Employment (29 CFR 1915.1028)

Reproductive toxicity

Shall not be classified as a reproductive toxicant.

Specific target organ toxicity - single exposure

Shall not be classified as a specific target organ toxicant (single exposure).

Specific target organ toxicity - repeated exposure

Causes damage to organs through prolonged or repeated exposure.

Aspiration hazard

May be fatal if swallowed and enters airways.

SECTION 12: Ecological information

12.1 Toxicity

Very toxic to aquatic life with long lasting effects.

Aquatic toxicity (acute) of components

Name of substance	CAS No	Endpoint	Value	Species	Exposure time
stoddard solvent	8052-41-3	LC50	0.18 mg/l	fish	96 h
stoddard solvent	8052-41-3	LL50	41.4 mg/l	fish	96 h



Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

POR-15 ENGINE ENAMEL FORD BLUE

Version number: GHS 3.1
Replaces version of: 2023-12-07 (GHS 2)

Revision: 2024-06-17

Aquatic toxicity (acute) of components					
Name of substance	CAS No	Endpoint	Value	Species	Exposure time
stoddard solvent	8052-41-3	EL50	2.5 mg/l	algae	96 h
stoddard solvent	8052-41-3	EC50	0.58 mg/l	algae	96 h
Naphtha (petroleum), hydro-treated heavy	64742-48-9	LL50	8.2 mg/l	fish	96 h
Naphtha (petroleum), hydro-treated heavy	64742-48-9	EL50	4.5 mg/l	aquatic invertebrates	48 h
29H,31H-phthalocyaninato(2-)-N29,N30,N31,N32 copper	147-14-8	LC50	>100 mg/l	fish	96 h
29H,31H-phthalocyaninato(2-)-N29,N30,N31,N32 copper	147-14-8	EC50	>500 mg/l	aquatic invertebrates	48 h
29H,31H-phthalocyaninato(2-)-N29,N30,N31,N32 copper	147-14-8	ErC50	>100 mg/l	algae	72 h
Distillates (petroleum), hydro-treated light	64742-47-8	LL50	5 mg/l	fish	96 h
Distillates (petroleum), hydro-treated light	64742-47-8	EL50	1.4 mg/l	aquatic invertebrates	48 h
2-ethylhexanoic acid, zirconium salt	22464-99-9	LC50	>100 mg/l	fish	96 h
2-ethylhexanoic acid, zirconium salt	22464-99-9	LL50	>100 mg/l	fish	96 h
2-ethylhexanoic acid, zirconium salt	22464-99-9	EC50	>0.17 mg/l	aquatic invertebrates	48 h
2-ethylhexanoic acid, zirconium salt	22464-99-9	ErC50	49.3 mg/l	algae	72 h
Hexanoic acid, 2-ethyl-, cobalt(2+) salt (2:1)	136-52-7	LC50	54.1 mg/l	fish	96 h
Hexanoic acid, 2-ethyl-, cobalt(2+) salt (2:1)	136-52-7	EC50	2,618 µg/l	aquatic invertebrates	48 h
Hexanoic acid, 2-ethyl-, cobalt(2+) salt (2:1)	136-52-7	ErC50	71,314 µg/l	algae	96 h
2-butanone oxime	96-29-7	LC50	>100 mg/l	fish	96 h
2-butanone oxime	96-29-7	EC50	201 mg/l	aquatic invertebrates	48 h
2-butanone oxime	96-29-7	ErC50	11.8 mg/l	algae	72 h
Carbon black	1333-86-4	EC50	>5,600 mg/l	aquatic invertebrates	24 h
Carbon black	1333-86-4	ErC50	>10,000 mg/l	algae	72 h



Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

POR-15 ENGINE ENAMEL FORD BLUE

Version number: GHS 3.1
Replaces version of: 2023-12-07 (GHS 2)

Revision: 2024-06-17

Aquatic toxicity (acute) of components					
Name of substance	CAS No	Endpoint	Value	Species	Exposure time
2-(2-butoxyethoxy)ethanol	112-34-5	LC50	1,300 mg/l	fish	96 h
2-(2-butoxyethoxy)ethanol	112-34-5	EC50	>100 mg/l	aquatic invertebrates	48 h
2-(2-butoxyethoxy)ethanol	112-34-5	ErC50	>100 mg/l	algae	96 h
ethyl benzene	100-41-4	LC50	7 mg/l	fish	24 h
ethyl benzene	100-41-4	EC50	2.4 mg/l	aquatic invertebrates	48 h
naphthalene	91-20-3	LC50	1.6 mg/l	fish	96 h
naphthalene	91-20-3	EC50	2.16 mg/l	aquatic invertebrates	48 h
solvent naphtha (petroleum), medium aliph.	64742-88-7	LL50	5 mg/l	fish	96 h
solvent naphtha (petroleum), medium aliph.	64742-88-7	EL50	1.4 mg/l	aquatic invertebrates	48 h
Solvent naphtha (petroleum), light arom.	64742-95-6	LL50	8.2 mg/l	fish	96 h
Solvent naphtha (petroleum), light arom.	64742-95-6	EL50	4.5 mg/l	aquatic invertebrates	48 h
toluene	108-88-3	LC50	5.5 mg/l	fish	96 h
toluene	108-88-3	EC50	84 mg/l	microorganisms	24 h
benzene	71-43-2	LC50	5.3 mg/l	fish	96 h
benzene	71-43-2	EC50	10 mg/l	aquatic invertebrates	24 h
benzene	71-43-2	ErC50	100 mg/l	algae	72 h

Aquatic toxicity (chronic) of components					
Name of substance	CAS No	Endpoint	Value	Species	Exposure time
stoddard solvent	8052-41-3	EL50	1.19 mg/l	aquatic invertebrates	21 d
stoddard solvent	8052-41-3	EC50	0.33 mg/l	aquatic invertebrates	21 d
Naphtha (petroleum), hydrotreated heavy	64742-48-9	EL50	10 mg/l	fish	21 d
Naphtha (petroleum), hydrotreated heavy	64742-48-9	EC50	15.41 mg/l	microorganisms	40 h
29H,31H-phthalocyaninato(2-)-N29,N30,N31,N32 copper	147-14-8	EC50	>1 mg/l	aquatic invertebrates	21 d

POR-15 ENGINE ENAMEL FORD BLUE

Version number: GHS 3.1
Replaces version of: 2023-12-07 (GHS 2)

Revision: 2024-06-17

Aquatic toxicity (chronic) of components					
Name of substance	CAS No	Endpoint	Value	Species	Exposure time
Distillates (petroleum), hydro-treated light	64742-47-8	EL50	0.89 mg/l	aquatic invertebrates	21 d
2-ethylhexanoic acid, zirconium salt	22464-99-9	EC50	75 mg/l	aquatic invertebrates	21 d
Hexanoic acid, 2-ethyl-, cobalt(2+) salt (2:1)	136-52-7	LC50	41,625 µg/l	fish	28 d
Hexanoic acid, 2-ethyl-, cobalt(2+) salt (2:1)	136-52-7	EC50	82.2 µg/l	aquatic invertebrates	21 d
2-butanone oxime	96-29-7	EC50	≥100 mg/l	aquatic invertebrates	21 d
ethyl benzene	100-41-4	LC50	3.6 mg/l	aquatic invertebrates	7 d
naphthalene	91-20-3	EC50	2.96 mg/l	algae	4 h
solvent naphtha (petroleum), medium aliph.	64742-88-7	EL50	0.89 mg/l	aquatic invertebrates	21 d
Solvent naphtha (petroleum), light arom.	64742-95-6	EL50	10 mg/l	fish	21 d
Solvent naphtha (petroleum), light arom.	64742-95-6	EC50	15.41 mg/l	microorganisms	40 h
toluene	108-88-3	LC50	3.78 mg/l	aquatic invertebrates	2 d
toluene	108-88-3	EC50	3.23 mg/l	aquatic invertebrates	7 d

12.2 Persistence and degradability

Data are not available.

12.3 Bioaccumulative potential

Data are not available.

12.4 Mobility in soil

Data are not available.

12.5 Results of PBT and vPvB assessment

According to the results of its assessment, this substance is not a PBT or a vPvB. Does not contain a PBT-/vPvB-substance at a concentration of ≥ 0.1%.

12.6 Endocrine disrupting properties

Does not contain an endocrine disruptor (ED) in a concentration of ≥ 0.1%.

12.7 Other adverse effects

Data are not available.

POR-15 ENGINE ENAMEL FORD BLUE

Version number: GHS 3.1
Replaces version of: 2023-12-07 (GHS 2)

Revision: 2024-06-17

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Waste treatment-relevant information

Solvent reclamation/regeneration.

Sewage disposal-relevant information

Do not empty into drains. Avoid release to the environment. Refer to special instructions/safety data sheets.

Waste treatment of containers/packages

Only packagings which are approved (e.g. acc. to DOT) may be used. Completely emptied packages can be recycled. Handle contaminated packages in the same way as the substance itself.

Remarks

Please consider the relevant national or regional provisions. Waste shall be separated into the categories that can be handled separately by the local or national waste management facilities.

SECTION 14: Transport information

14.1 UN number

DOT	UN 1263
IMDG-Code	UN 1263
ICAO-TI	UN 1263

14.2 UN proper shipping name

DOT	Paint
IMDG-Code	PAINT
ICAO-TI	Paint

14.3 Transport hazard class(es)

DOT	3
IMDG-Code	3
ICAO-TI	3

14.4 Packing group

DOT	III
IMDG-Code	III
ICAO-TI	III

14.5 Environmental hazards

Environmentally hazardous substance (aquatic environment) hazardous to the aquatic environment
stoddard solvent

14.6 Special precautions for user

There is no additional information.

14.7 Transport in bulk according to IMO instruments

The cargo is not intended to be carried in bulk.

POR-15 ENGINE ENAMEL FORD BLUE

Version number: GHS 3.1
Replaces version of: 2023-12-07 (GHS 2)

Revision: 2024-06-17

Information for each of the UN Model Regulations

Transport of dangerous goods by road or rail (49 CFR US DOT) - Additional information

Particulars in the shipper's declaration UN1263, Paint, 3, III, environmentally hazardous
Reportable quantity (RQ) 7,142,857 lbs (3,242,857 kg) (naphthalene) (ethyl benzene)
Danger label(s) 3, fish and tree



Environmental hazards YES (hazardous to the aquatic environment)
Special provisions (SP) 367, B1, B52, B131, IB3, T2, TP1, TP29
ERG No 128

International Maritime Dangerous Goods Code (IMDG) - Additional information

Marine pollutant YES (hazardous to the aquatic environment)
Danger label(s) 3, fish and tree



Special provisions (SP) 163, 223, 367, 955
Excepted quantities (EQ) E1
Limited quantities (LQ) 5 L
EmS F-E, S-E
Stowage category A

International Civil Aviation Organization (ICAO-IATA/DGR) - Additional information

Environmental hazards YES (hazardous to the aquatic environment)
Danger label(s) 3



Special provisions (SP) A3, A72, A192
Excepted quantities (EQ) E1
Limited quantities (LQ) 10 L

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations specific for the product in question

National regulations (United States)

Superfund Amendment and Reauthorization Act (SARA TITLE III)

- The List of Extremely Hazardous Substances and Their Threshold Planning Quantities (EPCRA Section 302, 304)

none of the ingredients are listed



Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

POR-15 ENGINE ENAMEL FORD BLUE

Version number: GHS 3.1
Replaces version of: 2023-12-07 (GHS 2)

Revision: 2024-06-17

- Specific Toxic Chemical Listings (EPCRA Section 313)

Toxics Release Inventory: Specific Toxic Chemical Listings			
Name of substance	CAS No	Remarks	Effective date
ethyl benzene	100-41-4		1986-12-31
benzene	71-43-2		1986-12-31
naphthalene	91-20-3		1986-12-31
toluene	108-88-3		1986-12-31

Comprehensive Environmental Response, Compensation, and Liability Act (CERCLA)

- List of Hazardous Substances and Reportable Quantities (CERCLA section 102a) (40 CFR 302.4)

Name of substance	CAS No	Remarks	Statutory code	Final RQ pounds (Kg)
ethyl benzene	100-41-4		1 2 3	1000 (454)
benzene	71-43-2	a	1 2 3 4	10 (4,54)
naphthalene	91-20-3		1 2 3 4	100 (45,4)
toluene	108-88-3		1 2 3 4	1000 (454)

Legend

- 1 "1" indicates that the statutory source is section 311(b)(2) of the Clean Water Act
- 2 "2" indicates that the source is section 307(a) of the Clean Water Act
- 3 "3" indicates that the source is section 112 of the Clean Air Act
- 4 "4" indicates that the source is section 3001 of the Resource Conservation and Recovery Act (RCRA)
- a Benzene was already a CERCLA hazardous substance prior to the CAA Amendments of 1990 and received an adjusted 10-pound RQ based on potential carcinogenicity in an August 14, 1989, final rule (54 FR 33418). The CAA Amendments specify that "benzene (including benzene from gasoline)" is a hazardous air pollutant and, thus, a CERCLA hazardous substance.

Clean Air Act

none of the ingredients are listed

Right to Know Hazardous Substance List

- Cleaning Product Right to Know Act Substance List (CA-RTK)

Name of substance	CAS No	Functionality	Authoritative Lists
stoddard solvent	8052-41-3		ATSDR Neurotoxicants EC Annex VI CMRs - Cat. 1B
Naphtha (petroleum), hydrotreated heavy	64742-48-9		Canada PBiTs EC Annex VI CMRs - Cat. 1B



Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

POR-15 ENGINE ENAMEL FORD BLUE

Version number: GHS 3.1
Replaces version of: 2023-12-07 (GHS 2)

Revision: 2024-06-17

Name of substance	CAS No	Functionality	Authoritative Lists
Titanium dioxide (excluding nanoparticle)	13463-67-7		IARC Carcinogens - 2B Prop 65
2-butanone oxime	96-29-7		EC Annex VI CMRs - Cat. 1B
Carbon black	1333-86-4		IARC Carcinogens - 2B Prop 65
2-(2-butoxyethoxy)ethanol			CA TACs
ethyl benzene	100-41-4		ATSDR Neurotoxicants CA MCLs CA TACs CWA 303(c) IARC Carcinogens - 2B OEHHA RELs Prop 65
naphthalene	91-20-3		ATSDR Neurotoxicants CA NLS CA TACs CWA 303(c) CWA 303(d) IARC Carcinogens - 2B IRIS Neurotoxicants NTP 13th RoC - reasonable OEHHA RELs Prop 65 U.S. EPA NWMP PBTs
Solvent naphtha (petroleum), light arom.	64742-95-6		EC Annex VI CMRs - Cat. 1B
benzene	71-43-2		ATSDR Neurotoxicants CA MCLs CA TACs CWA 303(c) EC Annex VI CMRs - Cat. 1A EC Annex VI CMRs - Cat. 1B IARC Carcinogens - 1 IRIS Carcinogens - A NTP 13th RoC - known OEHHA RELs Prop 65
toluene	108-88-3		ATSDR Neurotoxicants CA MCLs CA TACs CWA 303(c) IRIS Neurotoxicants OEHHA RELs Prop 65

- Toxic or Hazardous Substance List (MA-TURA)

Name of substance	CAS No	DEP CODE	PBT / HHS / LHS	PBT / HHS Threshold	De Minimis Concentration Threshold
ethyl benzene	100-41-4				0.1 %
29H,31H-phthalocyaninato(2-)-N29,N30,N31,N32 copper		1015			1.0 %
benzene	71-43-2				1.0 %



Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

POR-15 ENGINE ENAMEL FORD BLUE

Version number: GHS 3.1
Replaces version of: 2023-12-07 (GHS 2)

Revision: 2024-06-17

Name of substance	CAS No	DEP CODE	PBT / HHS / LHS	PBT / HHS Threshold	De Minimis Concentration Threshold
naphthalene	91-20-3				0.1 %
2-(2-butoxyethoxy)ethanol		1022			1.0 %
toluene	108-88-3				1.0 %

- Hazardous Substances List (MN-ERTK)

Name of substance	CAS No	References	Remarks
Titanium dioxide (excluding nanoparticle)	13463-67-7	A	
Naphtha (petroleum), hydrotreated heavy	64742-48-9	A, O	
stoddard solvent	8052-41-3	A, N, O	

Legend

- A American Conference of Governmental Industrial Hygienists (ACGIH), "Threshold Limit Values for Chemical Substances and Physical Agents and Biological Exposure Indices for 1992-93", available from ACGIH
- N National Institute for Occupational Safety and Health (NIOSH), "Recommendations for Occupational Safety and Health Standards," August 1988, available from NIOSH, Publications Dissemination Office, Division of Standards Development and Technology Transfer
- O Occupational Safety and Health Administration (OSHA), Safety and Health Standards, Code of Federal Regulations, title 29, part 1910, subpart Z, "Toxic and Hazardous Substances, 1990." General information: Minnesota Department of Labor and Industry, Occupational Safety and Health Division

- Hazardous Substance List (NJ-RTK)

Name of substance	CAS No	Remarks	Classifications
ethyl benzene	100-41-4		CA F3
Titanium dioxide (excluding nanoparticle)	13463-67-7		
29H,31H-phthalocyaninato(2-)-N29,N30,N31,N32 copper			
benzene	71-43-2		CA MU F3
stoddard solvent	8052-41-3		F2
naphthalene	91-20-3		CA F2
2-(2-butoxyethoxy)ethanol			
toluene	108-88-3		TE F3
Carbon black	1333-86-4		CA

Legend

- CA Carcinogenic
- F2 Flammable - Second Degree
- F3 Flammable - Third Degree
- MU Mutagenic
- TE Teratogenic



Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

POR-15 ENGINE ENAMEL FORD BLUE

Version number: GHS 3.1
Replaces version of: 2023-12-07 (GHS 2)

Revision: 2024-06-17

- Hazardous Substance List (Chapter 323) (PA-RTK)

Name acc. to inventory	CAS No	Classification
TITANIUM OXIDE (TIO2)	13463-67-7	
COPPER	7440-50-8	*, E
STODDARD SOLVENT	8052-41-3	
SOOT		S

Legend

- * Any compound of this substance is also an environmental hazard
- E Environmental hazard
- S Special hazardous substance

- Hazardous Substance List (RI-RTK)

Name of substance	CAS No	References
ethyl benzene	100-41-4	T, F
Titanium dioxide (excluding nanoparticle)	13463-67-7	T
benzene	71-43-2	T, F, C
stoddard solvent	8052-41-3	T
naphthalene	91-20-3	T, F
toluene	108-88-3	T, F
toluene	108-88-3	T, F
toluene	108-88-3	T, F
Carbon black	1333-86-4	T

Legend

- C Carcinogenicity (IARC)
- F Flammability (NFPA®)
- T Toxicity (ACGIH®)

California Environmental Protection Agency (Cal/EPA): Proposition 65 - Safe Drinking Water and Toxic Enforcement Act of 1987

Proposition 65 List of chemicals			
Name acc. to inventory	CAS No	Remarks	Type of the toxicity
ethylbenzene	100-41-4		cancer
titanium dioxide	13463-67-7	airborne, unbound particles of respirable size	cancer
benzene	71-43-2		cancer
benzene	71-43-2		developmental, male
naphthalene	91-20-3		cancer



Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

POR-15 ENGINE ENAMEL FORD BLUE

Version number: GHS 3.1
Replaces version of: 2023-12-07 (GHS 2)

Revision: 2024-06-17

Proposition 65 List of chemicals

Name acc. to inventory	CAS No	Remarks	Type of the toxicity
toluene	108-88-3		developmental
carbon black	1333-86-4	airborne, unbound particles of respirable size	cancer

Industry or sector specific available guidance(s)

NPCA-HMIS® III

Hazardous Materials Identification System. American Coatings Association.

Category	Rating	Description
Chronic	*	chronic (long-term) health effects may result from repeated overexposure
Health	2	temporary or minor injury may occur
Flammability	2	material that must be moderately heated or exposed to relatively high ambient temperatures before ignition can occur
Physical hazard	0	material that is normally stable, even under fire conditions, and will not react with water, polymerize, decompose, condense, or self-react. Non-explosive
Personal protection	-	

NFPA® 704

National Fire Protection Association: Standard System for the Identification of the Hazards of Materials for Emergency Response (United States).

Category	Degree of hazard	Description
Flammability	2	material that must be moderately heated or exposed to relatively high ambient temperatures before ignition can occur
Health	2	material that, under emergency conditions, can cause temporary incapacitation or residual injury
Instability	0	material that is normally stable, even under fire conditions
Special hazard		

15.2 Chemical Safety Assessment

Chemical safety assessments for substances in this mixture were not carried out.



Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

POR-15 ENGINE ENAMEL FORD BLUE

Version number: GHS 3.1
Replaces version of: 2023-12-07 (GHS 2)

Revision: 2024-06-17

SECTION 16: Other information, including date of preparation or last revision

Key literature references and sources for data

OSHA Hazard Communication Standard (HCS), 29 CFR 1910.1200.

Transport of dangerous goods by road or rail (49 CFR US DOT). International Maritime Dangerous Goods Code (IMDG). Dangerous Goods Regulations (DGR) for the air transport (IATA).

Classification procedure

Physical and chemical properties: The classification is based on tested mixture.

Health hazards, Environmental hazards: The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

Disclaimer

This information is based upon the present state of our knowledge. This SDS has been compiled and is solely intended for this product.