



# Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

## POR-15 FUEL TANK SEALER

Version number: GHS 4.0  
Replaces version of: 2023-12-07 (GHS 3)

Revision: 2024-08-22

### SECTION 1: Identification

#### 1.1 Product identifier

Trade name **POR-15 FUEL TANK SEALER**  
Product code(s) 49201, 49204, 49204B, 49205, 49208, 49216, 49216B, 49255

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses Paint

#### 1.3 Details of the supplier of the safety data sheet

P.O.R. Products  
38 Portman Road  
New Rochelle NY 10801  
United States

Telephone: +1 914-636-0700  
e-mail: support@porproducts.com  
Website: www.porproducts.com

e-mail (competent person) support@porproducts.com

#### 1.4 Emergency telephone number

Emergency information service 1-800-255-3924  
ChemTel Inc.

### SECTION 2: Hazard(s) identification

#### 2.1 Classification of the substance or mixture

Classification acc. to OSHA "Hazard Communication Standard" (29 CFR 1910.1200)

Section	Hazard class	Category	Hazard class and category	Hazard statement
A.1I	acute toxicity (inhal.)	3	Acute Tox. 3	H331
A.2	skin corrosion/irritation	2	Skin Irrit. 2	H315
A.3	serious eye damage/eye irritation	2	Eye Irrit. 2	H319
A.4R	respiratory sensitization	1	Resp. Sens. 1	H334
A.4S	skin sensitization	1	Skin Sens. 1	H317
A.5	germ cell mutagenicity	1B	Muta. 1B	H340
A.6	carcinogenicity	1A	Carc. 1A	H350
A.8R	specific target organ toxicity - single exposure (respiratory tract irritation)	3	STOT SE 3	H335
A.9	specific target organ toxicity - repeated exposure	2	STOT RE 2	H373
A.10	aspiration hazard	1	Asp. Tox. 1	H304
B.6	flammable liquid	3	Flam. Liq. 3	H226

**POR-15 FUEL TANK SEALER**

Version number: GHS 4.0  
Replaces version of: 2023-12-07 (GHS 3)

Revision: 2024-08-22

For full text of abbreviations: see SECTION 16.

The most important adverse physicochemical, human health and environmental effects

Delayed or immediate effects can be expected after short or long-term exposure. The product is combustible and can be ignited by potential ignition sources.

**2.2 Label elements**

Labelling acc. to OSHA "Hazard Communication Standard" (29 CFR 1910.1200)

- Signal word danger

- Pictograms

GHS02, GHS06, GHS07,  
GHS08



- Hazard statements

H226	Flammable liquid and vapor.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H331	Toxic if inhaled.
H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H335	May cause respiratory irritation.
H340	May cause genetic defects.
H350	May cause cancer.
H373	May cause damage to organs through prolonged or repeated exposure.

- Precautionary statements

P201	Obtain special instructions before use.
P210	Keep away from heat/sparks/open flames/hot surfaces. No smoking.
P240	Ground/bond container and receiving equipment.
P241	Use explosion-proof electrical/ventilating/lighting equipment.
P242	Use only non-sparking tools.
P243	Take precautionary measures against static discharge.
P260	Do not breathe dust/fume/gas/mist/vapors/spray.
P271	Use only outdoors or in a well-ventilated area.
P272	Contaminated work clothing must not be allowed out of the workplace.
P280	Wear protective gloves/eye protection/face protection.
P285	In case of inadequate ventilation wear respiratory protection.
P301+P310	If swallowed: Immediately call a poison center/doctor.
P302+P352	If on skin: Wash with plenty of water.
P303+P361+P353	If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
P304+P340	If inhaled: Remove person to fresh air and keep comfortable for breathing.
P305+P351+P338	If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P321	Specific treatment (see on this label).
P331	Do NOT induce vomiting.
P342+P311	If experiencing respiratory symptoms: Call a poison center/doctor.
P362	Take off contaminated clothing and wash before reuse.
P363	Wash contaminated clothing before reuse.
P370+P378	In case of fire: Use sand, carbon dioxide or powder extinguisher to extinguish.
P403+P233	Store in a well-ventilated place. Keep container tightly closed.



# Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

## POR-15 FUEL TANK SEALER

Version number: GHS 4.0  
Replaces version of: 2023-12-07 (GHS 3)

Revision: 2024-08-22

### - Precautionary statements

P403+P235	Store in a well-ventilated place. Keep cool.
P405	Store locked up.
P501	Dispose of contents/container to industrial combustion plant.

### - Hazardous ingredients for labelling

Methylenediphenyl diisocyanate, Solvent naphtha (petroleum), light arom., 1-isocyanato-2-[(4-isocyanato-3-[(4-isocyanatophenyl)methyl]phenyl)methyl]-4-[(4-isocyanatophenyl)methyl]benzene; 1-isocyanato-2-[(4-isocyanatophenyl)methyl]benzene; 1-isocyanato-4-[(4-isocyanatophenyl)methyl]benzene, 4,4'-diphenylmethanediisocyanate, methylenediphenyl diisocyanate

## 2.3 Other hazards

Hazards not otherwise classified

Contains isocyanates. May produce an allergic reaction.  
Contains epoxy constituents. May produce an allergic reaction.  
Harmful to aquatic life with long lasting effects (GHS category 3: aquatic toxicity - acute and/or chronic).

Results of PBT and vPvB assessment

Does not contain a PBT-/vPvB-substance at a concentration of  $\geq 0.1\%$ .

Endocrine disrupting properties

Does not contain an endocrine disruptor (ED) in a concentration of  $\geq 0.1\%$ .

## SECTION 3: Composition/information on ingredients

### 3.1 Substances

Not relevant (mixture)

### 3.2 Mixtures

Description of the mixture

Name of substance	Identifier	Wt%	Classification acc. to GHS
Methylenediphenyl diisocyanate	CAS No 26447-40-5	50 - < 75	Acute Tox. 4 / H332 Skin Irrit. 2 / H315 Eye Irrit. 2 / H319 Resp. Sens. 1 / H334 Skin Sens. 1 / H317 Carc. 2 / H351 STOT SE 3 / H335 STOT RE 2 / H373
Solvent naphtha (petroleum), light arom.	CAS No 64742-95-6	10 - < 25	Muta. 1B / H340 Carc. 1A / H350 Asp. Tox. 1 / H304 Flam. Liq. 1 / H224



# Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

## POR-15 FUEL TANK SEALER

Version number: GHS 4.0  
Replaces version of: 2023-12-07 (GHS 3)

Revision: 2024-08-22

Name of substance	Identifier	Wt%	Classification acc. to GHS
4,4'-diphenylmethanediisocyanate	CAS No 101-68-8	10 - < 25	Acute Tox. 2 / H330 Skin Irrit. 2 / H315 Eye Irrit. 2 / H319 Resp. Sens. 1 / H334 Skin Sens. 1 / H317 Carc. 2 / H351 STOT SE 3 / H335 STOT RE 2 / H373
1,2,4-trimethylbenzene	CAS No 95-63-6	5 - < 10	Acute Tox. 4 / H332 Skin Irrit. 2 / H315 Eye Irrit. 2 / H319 STOT SE 3 / H335 Asp. Tox. 1 / H304 Flam. Liq. 3 / H226
1-isocyanato-2-((4-isocyanato-3-((4-isocyanatophenyl)methyl]phenyl]methyl)-4-((4-isocyanatophenyl)methyl]benzene; 1-isocyanato-2-((4-isocyanatophenyl)methyl]benzene; 1-isocyanato-4-((4-isocyanatophenyl)methyl]benzene	CAS No 9016-87-9	5 - < 10	Acute Tox. 2 / H330
methylenediphenyl diisocyanate	CAS No 26447-40-5	1 - < 5	Acute Tox. 4 / H332 Skin Irrit. 2 / H315 Eye Irrit. 2 / H319 Resp. Sens. 1 / H334 Skin Sens. 1 / H317 Carc. 2 / H351 STOT SE 3 / H335 STOT RE 2 / H373
aluminium powder (pyrophoric)	CAS No 7429-90-5	1 - < 5	Acute Tox. 3 / H331 Pyr. Sol. 1 / H250 Water-react. 2 / H261
Naphtha (petroleum), hydrotreated heavy	CAS No 64742-48-9	1 - < 5	Muta. 1B / H340 Carc. 1A / H350 Asp. Tox. 1 / H304 Flam. Liq. 1 / H224
cumene	CAS No 98-82-8	0.1 - < 1	Carc. 2 / H351 STOT SE 3 / H335 Asp. Tox. 1 / H304 Flam. Liq. 3 / H226
acetaldehyde	CAS No 75-07-0	0 - < 0.1	Eye Irrit. 2 / H319 Muta. 2 / H341 Carc. 1A / H350 STOT SE 3 / H335 Flam. Liq. 1 / H224
propylene oxide	CAS No 75-56-9	0 - < 0.1	Acute Tox. 4 / H302 Acute Tox. 3 / H311 Acute Tox. 3 / H331 Eye Irrit. 2 / H319 Muta. 1B / H340 Carc. 2 / H351 STOT SE 3 / H335 Flam. Liq. 1 / H224



# Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

## POR-15 FUEL TANK SEALER

Version number: GHS 4.0  
Replaces version of: 2023-12-07 (GHS 3)

Revision: 2024-08-22

### Remarks

For full text of abbreviations: see SECTION 16

## SECTION 4: First-aid measures

### 4.1 Description of first-aid measures

#### General notes

Do not leave affected person unattended. Remove victim out of the danger area. Keep affected person warm, still and covered. Take off immediately all contaminated clothing. In all cases of doubt, or when symptoms persist, seek medical advice. In case of unconsciousness place person in the recovery position. Never give anything by mouth.

#### Following inhalation

If breathing is irregular or stopped, immediately seek medical assistance and start first aid actions. In case of respiratory tract irritation, consult a physician. Provide fresh air.

#### Following skin contact

Wash with plenty of soap and water.

#### Following eye contact

Remove contact lenses, if present and easy to do. Continue rinsing. Irrigate copiously with clean, fresh water for at least 10 minutes, holding the eyelids apart.

#### Following ingestion

Rinse mouth with water (only if the person is conscious). Do NOT induce vomiting.

### 4.2 Most important symptoms and effects, both acute and delayed

Symptoms and effects are not known to date.

### 4.3 Indication of any immediate medical attention and special treatment needed

none

## SECTION 5: Fire-fighting measures

### 5.1 Extinguishing media

#### Suitable extinguishing media

Water spray, D-Powder, Carbon dioxide (CO<sub>2</sub>)

#### Unsuitable extinguishing media

Water jet

### 5.2 Special hazards arising from the substance or mixture

In case of insufficient ventilation and/or in use, may form flammable/explosive vapor-air mixture. Solvent vapors are heavier than air and may spread along floors. Places which are not ventilated, e.g. unventilated below ground level areas such as trenches, conduits and shafts, are particularly prone to the presence of flammable substances or mixtures.

#### Hazardous combustion products

Nitrogen oxides (NO<sub>x</sub>), Carbon monoxide (CO), Carbon dioxide (CO<sub>2</sub>)

### 5.3 Advice for firefighters

In case of fire and/or explosion do not breathe fumes. Coordinate firefighting measures to the fire surroundings. Do not allow firefighting water to enter drains or water courses. Collect contaminated firefighting water separately. Fight fire with normal precautions from a reasonable distance.

## POR-15 FUEL TANK SEALER

Version number: GHS 4.0  
Replaces version of: 2023-12-07 (GHS 3)

Revision: 2024-08-22

### SECTION 6: Accidental release measures

#### 6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

Remove persons to safety.

For emergency responders

Wear breathing apparatus if exposed to vapors/dust/aerosols/gases.

#### 6.2 Environmental precautions

Keep away from drains, surface and ground water. Retain contaminated washing water and dispose of it. If substance has entered a water course or sewer, inform the responsible authority.

#### 6.3 Methods and material for containment and cleaning up

Advice on how to contain a spill

Covering of drains

Advice on how to clean up a spill

Wipe up with absorbent material (e.g. cloth, fleece). Collect spillage: sawdust, kieselgur (diatomite), sand, universal binder

Appropriate containment techniques

Use of adsorbent materials.

Other information relating to spills and releases

Place in appropriate containers for disposal. Ventilate affected area.

#### 6.4 Reference to other sections

Hazardous combustion products: see section 5. Personal protective equipment: see section 8. Incompatible materials: see section 10. Disposal considerations: see section 13.

### SECTION 7: Handling and storage

#### 7.1 Precautions for safe handling

Recommendations

- Measures to prevent fire as well as aerosol and dust generation

Use local and general ventilation. Avoidance of ignition sources. Keep away from sources of ignition - No smoking. Take precautionary measures against static discharge. Use only in well-ventilated areas. Due to danger of explosion, prevent leakage of vapours into cellars, flues and ditches. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting/equipment. Use only non-sparking tools.

- Specific notes/details

Places which are not ventilated, e.g. unventilated below ground level areas such as trenches, conduits and shafts, are particularly prone to the presence of flammable substances or mixtures. Vapors are heavier than air, spread along floors and form explosive mixtures with air. Vapors may form explosive mixtures with air.

Advice on general occupational hygiene

Wash hands after use. Do not eat, drink and smoke in work areas. Remove contaminated clothing and protective equipment before entering eating areas. Never keep food or drink in the vicinity of chemicals. Never place chemicals in containers that are normally used for food or drink. Keep away from food, drink and animal feedingstuffs.

## POR-15 FUEL TANK SEALER

Version number: GHS 4.0  
Replaces version of: 2023-12-07 (GHS 3)

Revision: 2024-08-22

### 7.2 Conditions for safe storage, including any incompatibilities

Managing of associated risks

- Explosive atmospheres

Keep container tightly closed and in a well-ventilated place. Use local and general ventilation. Keep cool. Protect from sunlight.

- Flammability hazards

Keep away from sources of ignition - No smoking. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Take precautionary measures against static discharge. Protect from sunlight.

- Ventilation requirements

Keep any substance that emits harmful vapors or gases in a place that allows these to be permanently extracted. Use local and general ventilation. Ground/bond container and receiving equipment.

- Packaging compatibilities

Only packagings which are approved (e.g. acc. to the Dangerous Goods Regulations) may be used.

### 7.3 Specific end use(s)

See section 16 for a general overview.

## SECTION 8: Exposure controls/personal protection

### 8.1 Control parameters

Occupational exposure limit values (Workplace Exposure Limits)											
Country	Name of agent	CAS No	Identifier	TWA [ppm]	TWA [mg/m <sup>3</sup> ]	STEL [ppm]	STEL [mg/m <sup>3</sup> ]	Ceiling-C [ppm]	Ceiling-C [mg/m <sup>3</sup> ]	Notation	Source
US	methylbis(phenylisocyanate) (4,4'-MDI)	101-68-8	PEL					0.02	0.2		29 CFR 1910.1000
US	methylenebis(p-phenyl isocyanate)	101-68-8	REL	0.005 (10 h)	0.05 (10 h)			0.02 (10 min)	0.2 (10 min)		NIOSH REL
US	methylenebis(p-phenyl isocyanate)	101-68-8	TLV®	0.005							ACGIH® 2024
US	methylenebis(p-phenyl isocyanate) (4,4'-MDI) (4,4'-diphenylmethanediisocyanate)	101-68-8	PEL (CA)	0.005	0.051						Cal/ OSHA PEL
US	petroleum distillates (naphtha) (rubber solvent)	64742-48-9	PEL	500	2,000						29 CFR 1910.1000
US	aluminium	7429-90-5	REL		10 (10 h)						NIOSH REL
US	aluminium	7429-90-5	PEL (CA)		10					dust	Cal/ OSHA PEL
US	aluminium	7429-90-5	PEL		15					dust	29 CFR 1910.1000



# Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

## POR-15 FUEL TANK SEALER

Version number: GHS 4.0  
Replaces version of: 2023-12-07 (GHS 3)

Revision: 2024-08-22

Occupational exposure limit values (Workplace Exposure Limits)											
Country	Name of agent	CAS No	Identifier	TWA [ppm]	TWA [mg/m <sup>3</sup> ]	STEL [ppm]	STEL [mg/m <sup>3</sup> ]	Ceiling-C [ppm]	Ceiling-C [mg/m <sup>3</sup> ]	Notation	Source
US	aluminium	7429-90-5	PEL (CA)		5					fume_weld	Cal/ OSHA PEL
US	aluminium	7429-90-5	REL		5 (10 h)					fume_weld	NIOSH REL
US	aluminium	7429-90-5	PEL (CA)		5					pyro_p	Cal/ OSHA PEL
US	aluminium	7429-90-5	REL		5 (10 h)					pyro_p	NIOSH REL
US	aluminium	7429-90-5	PEL (CA)		5					r	Cal/ OSHA PEL
US	aluminium	7429-90-5	REL		5 (10 h)					r	NIOSH REL
US	aluminium	7429-90-5	TLV®		1					r	ACGIH® 2024
US	aluminium	7429-90-5	PEL		5					r	29 CFR 1910.1000
US	acetaldehyde	75-07-0	PEL (CA)					25	45		Cal/ OSHA PEL
US	acetaldehyde	75-07-0	TLV®					25			ACGIH® 2024
US	acetaldehyde	75-07-0	PEL	200	360						29 CFR 1910.1000
US	acetaldehyde	75-07-0	REL							lowest, appx-A, appx-C	NIOSH REL
US	propylene oxide	75-56-9	TLV®	2							ACGIH® 2024
US	propylene oxide	75-56-9	PEL	100	240						29 CFR 1910.1000
US	propylene oxide	75-56-9	REL							lowest, appx-A	NIOSH REL
US	propylene oxide (1,2-epoxypropane)	75-56-9	PEL (CA)	2	4.75						Cal/ OSHA PEL
US	1,2,4-trimethylbenzene	95-63-6	REL	25 (10 h)	125 (10 h)						NIOSH REL





# Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

## POR-15 FUEL TANK SEALER

Version number: GHS 4.0  
Replaces version of: 2023-12-07 (GHS 3)

Revision: 2024-08-22

### Occupational exposure limit values (Workplace Exposure Limits)

Country	Name of agent	CAS No	Identifier	TWA [ppm]	TWA [mg/m <sup>3</sup> ]	STEL [ppm]	STEL [mg/m <sup>3</sup> ]	Ceiling-C [ppm]	Ceiling-C [mg/m <sup>3</sup> ]	Notation	Source
US	1,2,4-trimethylbenzene	95-63-6	TLV®	10							ACGIH® 2024
US	cumene	98-82-8	TLV®	5							ACGIH® 2024
US	cumene	98-82-8	REL	50 (10 h)	245 (10 h)					H	NIOSH REL
US	cumene	98-82-8	PEL	50	245					H	29 CFR 1910.1000
US	cumene (isopropylbenzene)	98-82-8	PEL (CA)	50	245					H	Cal/OSHA PEL

#### Notation

appx-A	NIOSH Potential Occupational Carcinogen (Appendix A)
appx-C	Appendix C - Supplementary Exposure Limits
Ceiling-C	ceiling value is a limit value above which exposure should not occur
dust	as dust
fume_weld	as welding fumes
H	absorbed through the skin
lowest	exposure by all routes should be carefully controlled to levels as low as possible
pyro_p	as pyrophoric powder
r	respirable fraction
STEL	short-term exposure limit: a limit value above which exposure should not occur and which is related to a 15-minute period (unless otherwise specified)
TWA	time-weighted average (long-term exposure limit): measured or calculated in relation to a reference period of 8 hours time-weighted average (unless otherwise specified)

### Relevant DNELs of components

Name of substance	CAS No	Endpoint	Threshold level	Protection goal, route of exposure	Used in	Exposure time
4,4'-diphenylmethanediisocyanate	101-68-8	DNEL	0.05 mg/m <sup>3</sup>	human, inhalatory	worker (industry)	chronic - local effects
4,4'-diphenylmethanediisocyanate	101-68-8	DNEL	0.1 mg/m <sup>3</sup>	human, inhalatory	worker (industry)	acute - local effects
1,2,4-trimethylbenzene	95-63-6	DNEL	100 mg/m <sup>3</sup>	human, inhalatory	worker (industry)	chronic - systemic effects
1,2,4-trimethylbenzene	95-63-6	DNEL	100 mg/m <sup>3</sup>	human, inhalatory	worker (industry)	acute - systemic effects
1,2,4-trimethylbenzene	95-63-6	DNEL	100 mg/m <sup>3</sup>	human, inhalatory	worker (industry)	chronic - local effects
1,2,4-trimethylbenzene	95-63-6	DNEL	100 mg/m <sup>3</sup>	human, inhalatory	worker (industry)	acute - local effects
1,2,4-trimethylbenzene	95-63-6	DNEL	16,171 mg/kg bw/day	human, dermal	worker (industry)	chronic - systemic effects



# Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

## POR-15 FUEL TANK SEALER

Version number: GHS 4.0  
Replaces version of: 2023-12-07 (GHS 3)

Revision: 2024-08-22

### Relevant DNELs of components

Name of substance	CAS No	Endpoint	Threshold level	Protection goal, route of exposure	Used in	Exposure time
1-isocyanato-2-({4-isocyanato-3-[(4-isocyanatophenyl)methyl]phenyl)methyl)-4-[(4-isocyanatophenyl)methyl]benzene; 1-isocyanato-2-[(4-isocyanatophenyl)methyl]benzene; 1-isocyanato-4-[(4-isocyanatophenyl)methyl]benzene	9016-87-9	DNEL	0.05 mg/m <sup>3</sup>	human, inhalatory	worker (industry)	chronic - local effects
1-isocyanato-2-({4-isocyanato-3-[(4-isocyanatophenyl)methyl]phenyl)methyl)-4-[(4-isocyanatophenyl)methyl]benzene; 1-isocyanato-2-[(4-isocyanatophenyl)methyl]benzene; 1-isocyanato-4-[(4-isocyanatophenyl)methyl]benzene	9016-87-9	DNEL	0.1 mg/m <sup>3</sup>	human, inhalatory	worker (industry)	acute - local effects
cumene	98-82-8	DNEL	100 mg/m <sup>3</sup>	human, inhalatory	worker (industry)	chronic - systemic effects
cumene	98-82-8	DNEL	250 mg/m <sup>3</sup>	human, inhalatory	worker (industry)	acute - local effects
cumene	98-82-8	DNEL	15.4 mg/kg bw/day	human, dermal	worker (industry)	chronic - systemic effects
propylene oxide	75-56-9	DNEL	2.4 mg/m <sup>3</sup>	human, inhalatory	worker (industry)	chronic - local effects
propylene oxide	75-56-9	DNEL	170 mg/m <sup>3</sup>	human, inhalatory	worker (industry)	acute - local effects

### Relevant PNECs of components

Name of substance	CAS No	Endpoint	Threshold level	Organism	Environmental compartment	Exposure time
4,4'-diphenylmethanediisocyanate	101-68-8	PNEC	1 mg/l	aquatic organisms	freshwater	short-term (single instance)
4,4'-diphenylmethanediisocyanate	101-68-8	PNEC	0.1 mg/l	aquatic organisms	marine water	short-term (single instance)
4,4'-diphenylmethanediisocyanate	101-68-8	PNEC	1 mg/l	aquatic organisms	sewage treatment plant (STP)	short-term (single instance)
4,4'-diphenylmethanediisocyanate	101-68-8	PNEC	1 mg/kg	terrestrial organisms	soil	short-term (single instance)
1,2,4-trimethylbenzene	95-63-6	PNEC	0.12 mg/l	aquatic organisms	freshwater	short-term (single instance)



# Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

## POR-15 FUEL TANK SEALER

Version number: GHS 4.0  
Replaces version of: 2023-12-07 (GHS 3)

Revision: 2024-08-22

Relevant PNECs of components						
Name of substance	CAS No	Endpoint	Threshold level	Organism	Environmental compartment	Exposure time
1,2,4-trimethylbenzene	95-63-6	PNEC	0.12 mg/l	aquatic organisms	marine water	short-term (single instance)
1,2,4-trimethylbenzene	95-63-6	PNEC	2.41 mg/l	aquatic organisms	sewage treatment plant (STP)	short-term (single instance)
1,2,4-trimethylbenzene	95-63-6	PNEC	13.56 mg/kg	aquatic organisms	freshwater sediment	short-term (single instance)
1,2,4-trimethylbenzene	95-63-6	PNEC	13.56 mg/kg	aquatic organisms	marine sediment	short-term (single instance)
1,2,4-trimethylbenzene	95-63-6	PNEC	2.34 mg/kg	terrestrial organisms	soil	short-term (single instance)
1-isocyanato-2-((4-isocyanato-3-((4-isocyanatophenyl)methyl)phenyl)methyl)-4-((4-isocyanatophenyl)methyl)benzene; 1-isocyanato-2-((4-isocyanatophenyl)methyl)benzene; 1-isocyanato-4-((4-isocyanatophenyl)methyl)benzene	9016-87-9	PNEC	1 mg/l	aquatic organisms	freshwater	short-term (single instance)
1-isocyanato-2-((4-isocyanato-3-((4-isocyanatophenyl)methyl)phenyl)methyl)-4-((4-isocyanatophenyl)methyl)benzene; 1-isocyanato-2-((4-isocyanatophenyl)methyl)benzene; 1-isocyanato-4-((4-isocyanatophenyl)methyl)benzene	9016-87-9	PNEC	0.1 mg/l	aquatic organisms	marine water	short-term (single instance)
1-isocyanato-2-((4-isocyanato-3-((4-isocyanatophenyl)methyl)phenyl)methyl)-4-((4-isocyanatophenyl)methyl)benzene; 1-isocyanato-2-((4-isocyanatophenyl)methyl)benzene; 1-isocyanato-4-((4-isocyanatophenyl)methyl)benzene	9016-87-9	PNEC	1 mg/l	aquatic organisms	sewage treatment plant (STP)	short-term (single instance)



# Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

## POR-15 FUEL TANK SEALER

Version number: GHS 4.0  
Replaces version of: 2023-12-07 (GHS 3)

Revision: 2024-08-22

Relevant PNECs of components						
Name of substance	CAS No	Endpoint	Threshold level	Organism	Environmental compartment	Exposure time
1-isocyanato-2-[(4-isocyanato-3-[(4-isocyanatophenyl)methyl]phenyl)methyl]-4-[(4-isocyanatophenyl)methyl]benzene; 1-isocyanato-2-[(4-isocyanatophenyl)methyl]benzene; 1-isocyanato-4-[(4-isocyanatophenyl)methyl]benzene	9016-87-9	PNEC	1 mg/kg	terrestrial organisms	soil	short-term (single instance)
cumene	98-82-8	PNEC	0.035 mg/l	aquatic organisms	freshwater	short-term (single instance)
cumene	98-82-8	PNEC	0.004 mg/l	aquatic organisms	marine water	short-term (single instance)
cumene	98-82-8	PNEC	200 mg/l	aquatic organisms	sewage treatment plant (STP)	short-term (single instance)
cumene	98-82-8	PNEC	3.22 mg/kg	aquatic organisms	freshwater sediment	short-term (single instance)
cumene	98-82-8	PNEC	0.322 mg/kg	aquatic organisms	marine sediment	short-term (single instance)
cumene	98-82-8	PNEC	0.624 mg/kg	terrestrial organisms	soil	short-term (single instance)
propylene oxide	75-56-9	PNEC	0.052 mg/l	aquatic organisms	freshwater	short-term (single instance)
propylene oxide	75-56-9	PNEC	0.005 mg/l	aquatic organisms	marine water	short-term (single instance)
propylene oxide	75-56-9	PNEC	10 mg/l	aquatic organisms	sewage treatment plant (STP)	short-term (single instance)
propylene oxide	75-56-9	PNEC	0.245 mg/kg	aquatic organisms	freshwater sediment	short-term (single instance)
propylene oxide	75-56-9	PNEC	0.025 mg/kg	aquatic organisms	marine sediment	short-term (single instance)
propylene oxide	75-56-9	PNEC	0.019 mg/kg	terrestrial organisms	soil	short-term (single instance)

### 8.2 Exposure controls

Appropriate engineering controls

General ventilation.

Individual protection measures (personal protective equipment)

Eye/face protection

Wear eye/face protection.



# Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

## POR-15 FUEL TANK SEALER

Version number: GHS 4.0  
Replaces version of: 2023-12-07 (GHS 3)

Revision: 2024-08-22

### Skin protection

#### - Hand protection

Wear suitable gloves. Chemical protection gloves are suitable, which are tested according to EN 374. Check leak-tightness/impermeability prior to use. In the case of wanting to use the gloves again, clean them before taking off and air them well. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

#### - Other protection measures

Take recovery periods for skin regeneration. Preventive skin protection (barrier creams/ointments) is recommended. Wash hands thoroughly after handling.

### Respiratory protection

In case of inadequate ventilation wear respiratory protection.

### Environmental exposure controls

Use appropriate container to avoid environmental contamination. Keep away from drains, surface and ground water.

## SECTION 9: Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

#### Appearance

Physical state	liquid
Color	not determined
Particle	not relevant (liquid)
Odor	characteristic

#### Other safety parameters

pH (value)	not determined
Melting point/freezing point	not determined
Initial boiling point and boiling range	≥37.7 °C at 101.3 kPa
Flash point	52.1 °C
Evaporation rate	Not determined
Flammability (solid, gas)	not relevant, (fluid)

#### Explosive limits

## POR-15 FUEL TANK SEALER

Version number: GHS 4.0  
Replaces version of: 2023-12-07 (GHS 3)

Revision: 2024-08-22

- Lower explosion limit (LEL)	1.4 vol%
- Upper explosion limit (UEL)	7.6 vol%
Vapor pressure	≤240 kPa at 37.8 °C
Density	not determined
Vapor density	this information is not available
Relative density	Information on this property is not available
Solubility(ies)	not determined
Partition coefficient	
- n-octanol/water (log KOW)	this information is not available
Auto-ignition temperature	≥280 °C (auto-ignition temperature (liquids and gases))
Viscosity	not determined
Explosive properties	none
Oxidizing properties	none
<b>9.2 VOC Content g/L</b>	239

### SECTION 10: Stability and reactivity

#### 10.1 Reactivity

Concerning incompatibility: see below "Conditions to avoid" and "Incompatible materials". The mixture contains reactive substance(s). Risk of ignition.

If heated:

Risk of ignition

#### 10.2 Chemical stability

See below "Conditions to avoid".

#### 10.3 Possibility of hazardous reactions

No known hazardous reactions.

#### 10.4 Conditions to avoid

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Hints to prevent fire or explosion

Use explosion-proof electrical/ventilating/lighting/equipment. Use only non-sparking tools. Take precautionary measures against static discharge.

## POR-15 FUEL TANK SEALER

Version number: GHS 4.0  
Replaces version of: 2023-12-07 (GHS 3)

Revision: 2024-08-22

### 10.5 Incompatible materials

Oxidizers

### 10.6 Hazardous decomposition products

Reasonably anticipated hazardous decomposition products produced as a result of use, storage, spill and heating are not known. Hazardous combustion products: see section 5.

## SECTION 11: Toxicological information

### 11.1 Information on toxicological effects

Test data are not available for the complete mixture.

#### Classification procedure

The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

#### Classification acc. to OSHA "Hazard Communication Standard" (29 CFR 1910.1200)

#### Acute toxicity

Toxic if inhaled.

#### - Acute toxicity estimate (ATE)

Inhalation: vapor 6.164 mg<sub>i</sub>/4h

Acute toxicity estimate (ATE) of components			
Name of substance	CAS No	Exposure route	ATE
Methylenediphenyl diisocyanate	26447-40-5	inhalation: vapor	11 mg <sub>i</sub> /4h
4,4'-diphenylmethanediisocyanate	101-68-8	inhalation: dust/mist	0.368 mg <sub>i</sub> /4h
1,2,4-trimethylbenzene	95-63-6	inhalation: vapor	11 mg <sub>i</sub> /4h
1-isocyanato-2-((4-isocyanato-3-((4-isocyanatophenyl)methyl)phenyl)methyl)-4-((4-isocyanatophenyl)methyl)benzene; 1-isocyanato-2-((4-isocyanatophenyl)methyl)benzene; 1-isocyanato-4-((4-isocyanatophenyl)methyl)benzene	9016-87-9	inhalation: vapor	0.5 mg <sub>i</sub> /4h
1-isocyanato-2-((4-isocyanato-3-((4-isocyanatophenyl)methyl)phenyl)methyl)-4-((4-isocyanatophenyl)methyl)benzene; 1-isocyanato-2-((4-isocyanatophenyl)methyl)benzene; 1-isocyanato-4-((4-isocyanatophenyl)methyl)benzene	9016-87-9	inhalation: dust/mist	0.368 mg <sub>i</sub> /4h
methylenediphenyl diisocyanate	26447-40-5	inhalation: vapor	11 mg <sub>i</sub> /4h
aluminium powder (pyrophoric)	7429-90-5	inhalation: dust/mist	>0.888 mg <sub>i</sub> /4h
propylene oxide	75-56-9	oral	382 mg/kg
propylene oxide	75-56-9	dermal	300 mg/kg
propylene oxide	75-56-9	inhalation: vapor	3 mg <sub>i</sub> /4h

#### Skin corrosion/irritation

Causes skin irritation.

## POR-15 FUEL TANK SEALER

Version number: GHS 4.0  
Replaces version of: 2023-12-07 (GHS 3)

Revision: 2024-08-22

### Serious eye damage/eye irritation

Causes serious eye irritation.

### Respiratory or skin sensitization

May cause allergy or asthma symptoms or breathing difficulties if inhaled. May cause an allergic skin reaction.

### Germ cell mutagenicity

May cause genetic defects.

### Carcinogenicity

May cause cancer.

#### IARC Monographs on the Evaluation of Carcinogenic Risks to Humans

Name of substance	CAS No	Classification	Number
methylenediphenyl diisocyanate	101-68-8	3	
acetaldehyde	75-07-0	2B	
acetaldehyde	75-07-0	1	
propylene oxide	75-56-9	2B	
1-isocyanato-2-[(4-isocyanato-3-[(4-isocyanatophenyl)methyl]phenyl)methyl]-4-[(4-isocyanatophenyl)methyl]benzene; 1-isocyanato-2-[(4-isocyanatophenyl)methyl]benzene; 1-isocyanato-4-[(4-isocyanatophenyl)methyl]benzene	9016-87-9	3	
cumene	98-82-8	2B	
4,4'-diphenylmethanediisocyanate	101-68-8	3	
Methylenediphenyl diisocyanate	101-68-8	3	

#### Legend

1	Carcinogenic to humans
2B	Possibly carcinogenic to humans
3	Not classifiable as to carcinogenicity in humans

#### National Toxicology Program (United States): Report on Carcinogens

Name of substance	CAS No	Classification	Number
acetaldehyde	75-07-0	Reasonably anticipated to be a human carcinogen	6th Report on Carcinogens
propylene oxide	75-56-9	Reasonably anticipated to be a human carcinogen	6th Report on Carcinogens
cumene	98-82-8	Reasonably anticipated to be a human carcinogen	13th Report on Carcinogens

### Reproductive toxicity

Shall not be classified as a reproductive toxicant.





# Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

## POR-15 FUEL TANK SEALER

Version number: GHS 4.0  
Replaces version of: 2023-12-07 (GHS 3)

Revision: 2024-08-22

### Specific target organ toxicity - single exposure

May cause respiratory irritation.

### Specific target organ toxicity - repeated exposure

May cause damage to organs through prolonged or repeated exposure.

### Aspiration hazard

May be fatal if swallowed and enters airways.

## SECTION 12: Ecological information

### 12.1 Toxicity

Harmful to aquatic life with long lasting effects.

Aquatic toxicity (acute) of components					
Name of substance	CAS No	Endpoint	Value	Species	Exposure time
Solvent naphtha (petroleum), light arom.	64742-95-6	LL50	8.2 mg/l	fish	96 h
Solvent naphtha (petroleum), light arom.	64742-95-6	EL50	4.5 mg/l	aquatic invertebrates	48 h
4,4'-diphenylmethane diisocyanate	101-68-8	LC50	>1,000 mg/l	fish	96 h
4,4'-diphenylmethane diisocyanate	101-68-8	EC50	129.7 mg/l	aquatic invertebrates	24 h
1,2,4-trimethylbenzene	95-63-6	LC50	7.72 mg/l	fish	96 h
1,2,4-trimethylbenzene	95-63-6	EC50	2.356 mg/l	algae	96 h
1-isocyanato-2-[(4-isocyanato-3-[(4-isocyanatophenyl)methyl]phenyl)methyl]-4-[(4-isocyanatophenyl)methyl]benzene; 1-isocyanato-2-[(4-isocyanatophenyl)methyl]benzene; 1-isocyanato-4-[(4-isocyanatophenyl)methyl]benzene	9016-87-9	LC50	>1,000 mg/l	fish	96 h
1-isocyanato-2-[(4-isocyanato-3-[(4-isocyanatophenyl)methyl]phenyl)methyl]-4-[(4-isocyanatophenyl)methyl]benzene; 1-isocyanato-2-[(4-isocyanatophenyl)methyl]benzene; 1-isocyanato-4-[(4-isocyanatophenyl)methyl]benzene	9016-87-9	EC50	129.7 mg/l	aquatic invertebrates	24 h
Naphtha (petroleum), hydrotreated heavy	64742-48-9	LL50	8.2 mg/l	fish	96 h



# Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

## POR-15 FUEL TANK SEALER

Version number: GHS 4.0  
Replaces version of: 2023-12-07 (GHS 3)

Revision: 2024-08-22

Aquatic toxicity (acute) of components					
Name of substance	CAS No	Endpoint	Value	Species	Exposure time
Naphtha (petroleum), hydrotreated heavy	64742-48-9	EL50	4.5 mg/l	aquatic invertebrates	48 h
cumene	98-82-8	LC50	4.7 mg/l	fish	96 h
cumene	98-82-8	EC50	2.14 mg/l	aquatic invertebrates	48 h
cumene	98-82-8	ErC50	2.01 mg/l	algae	72 h
acetaldehyde	75-07-0	EC50	48.3 mg/l	aquatic invertebrates	48 h
propylene oxide	75-56-9	LC50	52 mg/l	fish	96 h
propylene oxide	75-56-9	EC50	650 mg/l	aquatic invertebrates	24 h
propylene oxide	75-56-9	ErC50	240 mg/l	algae	96 h

Aquatic toxicity (chronic) of components					
Name of substance	CAS No	Endpoint	Value	Species	Exposure time
Solvent naphtha (petroleum), light arom.	64742-95-6	EL50	10 mg/l	fish	21 d
Solvent naphtha (petroleum), light arom.	64742-95-6	EC50	15.41 mg/l	microorganisms	40 h
4,4'-diphenylmethane diisocyanate	101-68-8	ErC50	>1,640 mg/l	algae	3 d
4,4'-diphenylmethane diisocyanate	101-68-8	EC50	>100 mg/l	microorganisms	3 h
1-isocyanato-2-[(4-isocyanato-3-[(4-isocyanatophenyl)methyl]phenyl)methyl]-4-[(4-isocyanatophenyl)methyl]benzene; 1-isocyanato-2-[(4-isocyanatophenyl)methyl]benzene; 1-isocyanato-4-[(4-isocyanatophenyl)methyl]benzene	9016-87-9	ErC50	>1,640 mg/l	algae	3 d
1-isocyanato-2-[(4-isocyanato-3-[(4-isocyanatophenyl)methyl]phenyl)methyl]-4-[(4-isocyanatophenyl)methyl]benzene; 1-isocyanato-2-[(4-isocyanatophenyl)methyl]benzene; 1-isocyanato-4-[(4-isocyanatophenyl)methyl]benzene	9016-87-9	EC50	>100 mg/l	microorganisms	3 h
Naphtha (petroleum), hydrotreated heavy	64742-48-9	EL50	10 mg/l	fish	21 d

## POR-15 FUEL TANK SEALER

Version number: GHS 4.0  
Replaces version of: 2023-12-07 (GHS 3)

Revision: 2024-08-22

Aquatic toxicity (chronic) of components					
Name of substance	CAS No	Endpoint	Value	Species	Exposure time
Naphtha (petroleum), hydrotreated heavy	64742-48-9	EC50	15.41 mg/l	microorganisms	40 h
cumene	98-82-8	EC50	1.5 mg/l	aquatic invertebrates	21 d
cumene	98-82-8	LC50	>3 mg/l	aquatic invertebrates	21 d
acetaldehyde	75-07-0	ErC50	≤249 mg/l	algae	5 d

### 12.2 Persistence and degradability

Data are not available.

### 12.3 Bioaccumulative potential

Data are not available.

### 12.4 Mobility in soil

Data are not available.

### 12.5 Results of PBT and vPvB assessment

According to the results of its assessment, this substance is not a PBT or a vPvB. Does not contain a PBT-/vPvB-substance at a concentration of ≥ 0.1%.

### 12.6 Endocrine disrupting properties

Does not contain an endocrine disruptor (ED) in a concentration of ≥ 0.1%.

### 12.7 Other adverse effects

Data are not available.

## SECTION 13: Disposal considerations

### 13.1 Waste treatment methods

Waste treatment-relevant information

Solvent reclamation/regeneration.

Sewage disposal-relevant information

Do not empty into drains. Avoid release to the environment. Refer to special instructions/safety data sheets.

Waste treatment of containers/packages

Only packagings which are approved (e.g. acc. to DOT) may be used. Completely emptied packages can be recycled. Handle contaminated packages in the same way as the substance itself.

#### Remarks

Please consider the relevant national or regional provisions. Waste shall be separated into the categories that can be handled separately by the local or national waste management facilities.

## POR-15 FUEL TANK SEALER

Version number: GHS 4.0  
Replaces version of: 2023-12-07 (GHS 3)

Revision: 2024-08-22

### SECTION 14: Transport information

#### 14.1 UN number

DOT	UN 1263
IMDG-Code	UN 1263
ICAO-TI	UN 1263

#### 14.2 UN proper shipping name

DOT	Paint
IMDG-Code	PAINT
ICAO-TI	Paint

#### 14.3 Transport hazard class(es)

DOT	3
IMDG-Code	3
ICAO-TI	3

#### 14.4 Packing group

DOT	III
IMDG-Code	III
ICAO-TI	III

#### 14.5 Environmental hazards

non-environmentally hazardous acc. to the dangerous goods regulations

#### 14.6 Special precautions for user


There is no additional information.

#### 14.7 Transport in bulk according to IMO instruments

The cargo is not intended to be carried in bulk.

### Information for each of the UN Model Regulations

#### **Transport of dangerous goods by road or rail (49 CFR US DOT) - Additional information**

Particulars in the shipper's declaration	UN1263, Paint, 3, III
Reportable quantity (RQ)	45,204 lbs (20,523 kg) (4,4'-diphenylmethanediisocyanate) (cumene)
Danger label(s)	3
	
Special provisions (SP)	367, B1, B52, B131, IB3, T2, TP1, TP29
ERG No	128

## POR-15 FUEL TANK SEALER

Version number: GHS 4.0  
Replaces version of: 2023-12-07 (GHS 3)

Revision: 2024-08-22

### International Maritime Dangerous Goods Code (IMDG) - Additional information

Marine pollutant -  
Danger label(s) 3



Special provisions (SP) 163, 223, 367, 955  
 Excepted quantities (EQ) E1  
 Limited quantities (LQ) 5 L  
 EmS F-E, S-E  
 Stowage category A

### International Civil Aviation Organization (ICAO-IATA/DGR) - Additional information

Danger label(s) 3



Special provisions (SP) A3, A72, A192  
 Excepted quantities (EQ) E1  
 Limited quantities (LQ) 10 L

## SECTION 15: Regulatory information

### 15.1 Safety, health and environmental regulations specific for the product in question

#### National regulations (United States)

**Toxic Substance Control Act (TSCA)** all ingredients are listed (ACTIVE) or exempt from listing

#### Superfund Amendment and Reauthorization Act (SARA TITLE III )

- The List of Extremely Hazardous Substances and Their Threshold Planning Quantities (EPCRA Section 302, 304)

The List of Extremely Hazardous Substances and Their Threshold Planning Quantities				
Name of substance	CAS No	Notes	Reportable quantity (pounds)	Threshold planning quantity (pounds)
propylene oxide	75-56-9	f	100	10000

#### Legend

f Chemical on the original list that does not meet toxicity criteria but because of its acute lethality, high production volume and known risk is considered chemical of concern ("Other chemicals"). (November 17, 1986, and February 15, 1990.)



# Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

## POR-15 FUEL TANK SEALER

Version number: GHS 4.0  
Replaces version of: 2023-12-07 (GHS 3)

Revision: 2024-08-22

### - Specific Toxic Chemical Listings (EPCRA Section 313)

Toxics Release Inventory: Specific Toxic Chemical Listings			
Name of substance	CAS No	Remarks	Effective date
methylenediphenyl diisocyanate	101-68-8		1986-12-31
aluminium powder (pyrophoric)	7429-90-5	fume or dust	1986-12-31
acetaldehyde	75-07-0		1986-12-31
propylene oxide	75-56-9		1986-12-31
1-isocyanato-2-[(4-isocyanato-3-[(4-isocyanatophenyl)methyl]phenyl)methyl]-4-[(4-isocyanatophenyl)methyl]benzene; 1-isocyanato-2-[(4-isocyanatophenyl)methyl]benzene; 1-isocyanato-4-[(4-isocyanatophenyl)methyl]benzene	9016-87-9		1994-12-31
1,2,4-trimethylbenzene	95-63-6		1986-12-31
cumene	98-82-8		1986-12-31
4,4'-diphenylmethanediisocyanate	101-68-8		1986-12-31
Methylenediphenyl diisocyanate	101-68-8		1986-12-31

### Comprehensive Environmental Response, Compensation, and Liability Act (CERCLA)

#### - List of Hazardous Substances and Reportable Quantities (CERCLA section 102a) (40 CFR 302.4)

Name of substance	CAS No	Remarks	Statutory code	Final RQ pounds (Kg)
acetaldehyde	75-07-0		1 3 4	1000 (454)
propylene oxide	75-56-9		1 3	100 (45,4)
cumene	98-82-8		3 4	5000 (2270)
4,4'-diphenylmethanediisocyanate	101-68-8		3	5000 (2270)

#### Legend

- 1 "1" indicates that the statutory source is section 311(b)(2) of the Clean Water Act
- 3 "3" indicates that the source is section 112 of the Clean Air Act
- 4 "4" indicates that the source is section 3001 of the Resource Conservation and Recovery Act (RCRA)

### Clean Air Act

Name of substance	CAS No	Type of registration	Basis for listing	Threshold quantity (lbs)
acetaldehyde	75-07-0	Flammable substance	g	10000
propylene oxide	75-56-9	Toxic substance	b	10000

#### Legend

- b On EHS list, vapor pressure 10 mmHg or greater.
- g Volatile flammable liquid



# Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

## POR-15 FUEL TANK SEALER

Version number: GHS 4.0  
Replaces version of: 2023-12-07 (GHS 3)

Revision: 2024-08-22

### Right to Know Hazardous Substance List

- Cleaning Product Right to Know Act Substance List (CA-RTK)

Name of substance	CAS No	Functionality	Authoritative Lists
Methylenediphenyl diisocyanate	26447-40-5		EC Annex VI Resp. Sens. - Cat. 1 Hazard Traits identified by DTSC
Solvent naphtha (petroleum), light arom.	64742-95-6		EC Annex VI CMRs - Cat. 1B
4,4'-diphenylmethanediisocyanate	101-68-8		CA TACs EC Annex VI Resp. Sens. - Cat. 1 Hazard Traits identified by DTSC IRIS Neurotoxicants OEHA RELS
1,2,4-trimethylbenzene	95-63-6		CA NLS IRIS Neurotoxicants OEHA RELS
1-isocyanato-2-((4-isocyanato-3-((4-isocyanatophenyl)methyl)phenyl)methyl)-4-((4-isocyanatophenyl)methyl)benzene; 1-isocyanato-2-((4-isocyanatophenyl)methyl)benzene; 1-isocyanato-4-((4-isocyanatophenyl)methyl)benzene	9016-87-9		OEHA RELS
methylenediphenyl diisocyanate	26447-40-5		EC Annex VI Resp. Sens. - Cat. 1 Hazard Traits identified by DTSC
aluminium powder (pyrophoric)	7429-90-5		ATSDR Neurotoxicants CA MCLs CWA 303(d)
Naphtha (petroleum), hydrotreated heavy	64742-48-9		Canada PBITs EC Annex VI CMRs - Cat. 1B
cumene	98-82-8		CA NLS CA TACs IARC Carcinogens - 2B NTP 13th RoC - reasonable OEHA RELS Prop 65
acetaldehyde	75-07-0		CA TACs EC Annex VI CMRs - Cat. 1B IARC Carcinogens - 2B IRIS Carcinogens - B2 IRIS Neurotoxicants NTP 13th RoC - reasonable OEHA RELS Prop 65
propylene oxide	75-56-9		CA TACs EC Annex VI CMRs - Cat. 1B IARC Carcinogens - 2B IRIS Carcinogens - B2 NTP 13th RoC - reasonable OEHA RELS Prop 65

## POR-15 FUEL TANK SEALER

Version number: GHS 4.0  
Replaces version of: 2023-12-07 (GHS 3)

Revision: 2024-08-22

### - Toxic or Hazardous Substance List (MA-TURA)

Name of substance	CAS No	DEP CODE	PBT / HHS / LHS	PBT / HHS Threshold	De Minimis Concentration Threshold
aluminium powder (pyrophoric)	7429-90-5				1.0 %
acetaldehyde	75-07-0				0.1 %
propylene oxide	75-56-9				1.0 %
1-isocyanato-2-((4-isocyanato-3-((4-isocyanatophenyl)methyl)phenyl)methyl)-4-((4-isocyanatophenyl)methyl)benzene; 1-isocyanato-2-((4-isocyanatophenyl)methyl)benzene; 1-isocyanato-4-((4-isocyanatophenyl)methyl)benzene		1050			1.0 %
1,2,4-trimethylbenzene	95-63-6				1.0 %
cumene	98-82-8				0.1 %

### - Hazardous Substances List (MN-ERTK)

Name of substance	CAS No	References	Remarks
methylenediphenyl diisocyanate		N	
Naphtha (petroleum), hydrotreated heavy	64742-48-9	A, O	
aluminium powder (pyrophoric)	7429-90-5	A	
aluminium powder (pyrophoric)	7429-90-5	A	fume
aluminium powder (pyrophoric)	7429-90-5	A	dust
1-isocyanato-2-((4-isocyanato-3-((4-isocyanatophenyl)methyl)phenyl)methyl)-4-((4-isocyanatophenyl)methyl)benzene; 1-isocyanato-2-((4-isocyanatophenyl)methyl)benzene; 1-isocyanato-4-((4-isocyanatophenyl)methyl)benzene		N	
1,2,4-trimethylbenzene	25551-13-7	A	
4,4'-diphenylmethanediisocyanate	101-68-8	A, N, O	
4,4'-diphenylmethanediisocyanate		N	
Methylenediphenyl diisocyanate		N	

#### Legend

- A American Conference of Governmental Industrial Hygienists (ACGIH), "Threshold Limit Values for Chemical Substances and Physical Agents and Biological Exposure Indices for 1992-93", available from ACGIH
- dust If the substance poses an airborne particulate exposure hazard, the substance is followed by the word "dust."
- fume Small solid particles formed by the condensation of vapors of solid materials.
- N National Institute for Occupational Safety and Health (NIOSH), "Recommendations for Occupational Safety and Health Standards," August 1988, available from NIOSH, Publications Dissemination Office, Division of Standards Development and Technology Transfer
- O Occupational Safety and Health Administration (OSHA), Safety and Health Standards, Code of Federal Regulations, title 29, part 1910, subpart Z, "Toxic and Hazardous Substances, 1990." General information: Minnesota Department of Labor and Industry, Occupational Safety and Health Division





# Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

## POR-15 FUEL TANK SEALER

Version number: GHS 4.0  
Replaces version of: 2023-12-07 (GHS 3)

Revision: 2024-08-22

### - Hazardous Substance List (NJ-RTK)

Name of substance	CAS No	Remarks	Classifications
methylenediphenyl diisocyanate			
aluminium powder (pyrophoric)	7429-90-5		F3 R1
acetaldehyde	75-07-0		CA MU TE F4 R2
propylene oxide	75-56-9		CA MU F4 R2
1-isocyanato-2-((4-isocyanato-3-((4-isocyanatophenyl)methyl)phenyl)methyl)-4-((4-isocyanatophenyl)methyl)benzene; 1-isocyanato-2-((4-isocyanatophenyl)methyl)benzene; 1-isocyanato-4-((4-isocyanatophenyl)methyl)benzene	9016-87-9		
1,2,4-trimethylbenzene	95-63-6		F2
cumene	98-82-8		F3 R1
4,4'-diphenylmethanediisocyanate	101-68-8		R1
4,4'-diphenylmethanediisocyanate			
Methylenediphenyl diisocyanate			

#### Legend

CA Carcinogenic  
 F2 Flammable - Second Degree  
 F3 Flammable - Third Degree  
 F4 Flammable - Fourth Degree  
 MU Mutagenic  
 R1 Reactive - First Degree  
 R2 Reactive - Second Degree  
 TE Teratogenic

### - Hazardous Substance List (Chapter 323) (PA-RTK)

Name acc. to inventory	CAS No	Classification
BENZENE, 1,1'-METHYLENEBIS[4-ISOCYANATO-	101-68-8	E
ALUMINUM	7429-90-5	E
PSEUDOCUMENE	95-63-6	E
BENZENE, (1-METHYLETHYL)-	98-82-8	E
BENZENE, 1,1'-METHYLENEBIS[4-ISOCYANATO-	101-68-8	E
BENZENE, 1,1'-METHYLENEBIS[4-ISOCYANATO-	101-68-8	E

#### Legend

E Environmental hazard



# Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

## POR-15 FUEL TANK SEALER

Version number: GHS 4.0  
Replaces version of: 2023-12-07 (GHS 3)

Revision: 2024-08-22

### - Hazardous Substance List (RI-RTK)

Name of substance	CAS No	References
methylenediphenyl diisocyanate	101-68-8	T
methylenediphenyl diisocyanate	101-68-8	T
methylenediphenyl diisocyanate	101-68-8	T
aluminium powder (pyrophoric)	7429-90-5	T, F
acetaldehyde	75-07-0	T, F
propylene oxide	75-56-9	T, F
1,2,4-trimethylbenzene	25551-13-7	T
cumene	98-82-8	T, F
4,4'-diphenylmethanediisocyanate	101-68-8	T
4,4'-diphenylmethanediisocyanate	101-68-8	T
4,4'-diphenylmethanediisocyanate	101-68-8	T
Methylenediphenyl diisocyanate	101-68-8	T
Methylenediphenyl diisocyanate	101-68-8	T
Methylenediphenyl diisocyanate	101-68-8	T

#### Legend

F Flammability (NFPA®)  
T Toxicity (ACGIH®)

### California Environmental Protection Agency (Cal/EPA): Proposition 65 - Safe Drinking Water and Toxic Enforcement Act of 1987

Proposition 65 List of chemicals			
Name acc. to inventory	CAS No	Remarks	Type of the toxicity
acetaldehyde	75-07-0		cancer
propylene oxide	75-56-9		cancer
cumene	98-82-8		cancer

### Industry or sector specific available guidance(s)

#### NPCA-HMIS® III

Hazardous Materials Identification System. American Coatings Association.



# Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

## POR-15 FUEL TANK SEALER

Version number: GHS 4.0  
Replaces version of: 2023-12-07 (GHS 3)

Revision: 2024-08-22

Category	Rating	Description
Chronic	*	chronic (long-term) health effects may result from repeated overexposure
Health	2	temporary or minor injury may occur
Flammability	2	material that must be moderately heated or exposed to relatively high ambient temperatures before ignition can occur
Physical hazard	0	material that is normally stable, even under fire conditions, and will not react with water, polymerize, decompose, condense, or self-react. Non-explosive
Personal protection	-	

### NFPA® 704

National Fire Protection Association: Standard System for the Identification of the Hazards of Materials for Emergency Response (United States).

Category	Degree of hazard	Description
Flammability	2	material that must be moderately heated or exposed to relatively high ambient temperatures before ignition can occur
Health	2	material that, under emergency conditions, can cause temporary incapacitation or residual injury
Instability	0	material that is normally stable, even under fire conditions
Special hazard		

### National inventories

Country	Inventory	Status
US	TSCA	all ingredients are listed (ACTIVE)
AU	AiIC	all ingredients are listed
CA	DSL	all ingredients are listed
CN	IECSC	all ingredients are listed
EU	ECSI	all ingredients are listed
EU	REACH Reg.	all ingredients are listed
JP	CSCL-ENCS	not all ingredients are listed
KR	KECI	all ingredients are listed
MX	INSQ	all ingredients are listed
NZ	NZIoC	all ingredients are listed
PH	PICCS	all ingredients are listed
TR	CICR	not all ingredients are listed
TW	TCSI	all ingredients are listed
VN	NCI	all ingredients are listed



# Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

## POR-15 FUEL TANK SEALER

Version number: GHS 4.0  
Replaces version of: 2023-12-07 (GHS 3)

Revision: 2024-08-22

### Legend

AIIC	Australian Inventory of Industrial Chemicals
CICR	Chemical Inventory and Control Regulation
CSSL-ENCS	List of Existing and New Chemical Substances (CSSL-ENCS)
DSL	Domestic Substances List (DSL)
ECSI	EC Substance Inventory (EINECS, ELINCS, NLP)
IECSC	Inventory of Existing Chemical Substances Produced or Imported in China
INSQ	National Inventory of Chemical Substances
KECI	Korea Existing Chemicals Inventory
NCI	National Chemical Inventory
NZIoC	New Zealand Inventory of Chemicals
PICCS	Philippine Inventory of Chemicals and Chemical Substances (PICCS)
REACH Reg.	REACH registered substances
TCSI	Taiwan Chemical Substance Inventory
TSCA	Toxic Substance Control Act

### 15.2 Chemical Safety Assessment

Chemical safety assessments for substances in this mixture were not carried out.

## SECTION 16: Other information, including date of preparation or last revision

### Key literature references and sources for data

OSHA Hazard Communication Standard (HCS), 29 CFR 1910.1200.

Transport of dangerous goods by road or rail (49 CFR US DOT). International Maritime Dangerous Goods Code (IMDG). Dangerous Goods Regulations (DGR) for the air transport (IATA).

### Classification procedure

Physical and chemical properties: The classification is based on tested mixture.

Health hazards, Environmental hazards: The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

### Disclaimer

This information is based upon the present state of our knowledge. This SDS has been compiled and is solely intended for this product.