



Safety Data Sheet

POR-15 Fuel Tank Sealer

1. Identification

Product identifier: POR-15 Fuel Tank Sealer
Product code: 249201, 249204, 249208 and 249216
Supplier Name: P.O.R. Products
38, Portman Road
New Rochelle, New-York
10801 USA
Telephone: 914 636-0700
Emergency tel. number: 914 636-0700
Available hours: 8h-17h
Recommended use: Paint and coating of fuel tank. Stops rust, corrosion & leaks.
Restriction on use: Do not use on plastics.

2. Hazard identification

Signal word: DANGER

Product classification:



Flammable liquids - Category 3.

Acute toxicity-inhalation - Category 3.

Respiratory sensitization - Category 1. Carcinogenicity - Category 2. Specific target organ (kidneys, CNS) toxicity – repeated exposure - Category 2.

Skin irritation - Category 2. Serious eye irritation - Category 2A. Skin sensitization - Category 1. Specific target organ toxicity – single exposure - Category 3 Narcotic effects. Specific target organ toxicity – single exposure - Category 3 Respiratory tract irritation.

Hazard statement(s):

- H226 - Flammable liquid and vapour.
- H331 - Toxic if inhaled.
- H334 - May cause allergy or asthma symptoms or breathing difficulties if inhaled.
- H351 - Suspected of causing cancer.
- H373 - May cause damage to organs (kidneys, CNS) through prolonged or repeated exposure.
- H315 - Causes skin irritation.
- H319 - Causes serious eye irritation.
- H317 - May cause an allergic skin reaction.
- H336 - May cause drowsiness or dizziness.
- H335 - May cause respiratory irritation.



Safety Data Sheet

POR-15 Fuel Tank Sealer

Precautionary statement(s)

Prevention: Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Keep container tightly closed. For large container, ground and bond container and receiving equipment. Use explosion-proof electrical, ventilating and lightning equipment. Use non-sparking tools. Take action to prevent static discharges. Do not breathe mist, vapors and spray. Wear protective gloves, protective clothing, eye and face protection. Use only outdoors or in a well-ventilated area. In case of inadequate ventilation, wear respiratory protection. Wash hands thoroughly after handling and any other part of the body that may have been exposed to the product. Contaminated work clothing should not be allowed out of the workplace.

Response: IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER or a doctor. If experiencing respiratory symptoms: Call a POISON CENTER or a doctor. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower. If skin irritation or a rash occurs: Get medical advice. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice. IF exposed or concerned: Get medical advice. Get medical advice if you feel unwell. In case of fire: Use an appropriate extinguisher. Take off contaminated clothing and wash it before reuse.

Storage: Store in a well ventilated place. Keep container tightly closed. Keep cool. Store locked up.

Disposal: Dispose of contents/container in accordance with local, regional, national and/or international regulations in force.

Other hazards: No other effects shown.

See toxicological information, section 11

3. Composition/ Information on ingredients

No	CAS No :	Common name and synonyms	Concentration % (w/w)
1	67815-87-6	Aromatic polyisocyanate MDI based	30.00 - 60.00
2	64742-95-6	Naphtha, light aromatic fraction C8-C10	28.42
3	101-68-8	4,4'-Diphenylmethane diisocyanate monomer. MDI monomer	10.00 - 30.00
4	9016-87-9	Polymethylene polyphenyl isocyanate. PMDI polymeric	5.00 - 10.00
5	64742-48-9	Naphtha hydrotreated, heavy fraction	1.06
6	26447-40-5	4,4'-Dipheylmethane diisocyanate. MDI polymeric	0.10 - 1.00

The actual concentration range is withheld as a trade secret.

4. First-aid measures

If swallowed, irritation, any type of overexposure or symptoms of overexposure occur during use of the product or persists after use, immediately contact a POISON CENTER, an EMERGENCY ROOM or a PHYSICIAN; ensure that the product safety data sheet is available.

Eye contact: Check for and remove any contact lenses. Immediately flush eyes with plenty of water for at least 15 minutes, occasionally lifting the upper and lower eyelids. Get medical attention as soon as possible.

Skin contact: Remove contaminated clothing immediately. Wash the skin with soap and water. Thoroughly wet contaminated clothing. If irritation persists, consult a doctor.

Inhalation: Move exposed person to fresh air. Keep this person warm and lying down. Loosen tight clothing such as a collar, tie, belt or waistband. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. Get medical attention immediately.

Ingestion: Wash out mouth with water. Do not induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. Get medical attention immediately.

Symptoms: This product is irritating to skin, eyes, respiratory and digestive tracts. The severity of symptoms can vary depending on the exposure conditions (contact time, product concentration, etc.). The main symptoms of intoxication include headache, nausea, vomiting, weakness, loss of



Safety Data Sheet

POR-15 Fuel Tank Sealer

appetite, fatigue, sweating, fever, tachycardia and dyspnea. In the most severe cases, convulsions, hyperthermic coma, liver damage are reported and sometimes death. The worker may develop skin hypersensitivity as well as allergic or asthma symptoms or breathing difficulties if inhaled. Repeated exposures lead to the chronic form whose symptoms are dyspnea to exercise, cough with sputum, fatigue and weight loss.

Effects (acute or delayed): This product is a serious irritant that may cause reversible damages to the cornea. May cause skin irritation. Following repeated or prolonged contact, it has a degreasing effect on the skin. In high concentration, can cause depression of the central nervous system. May cause kidney damage. Narcotic effect by inhalation. This product is a respiratory and skin sensitizer. Repeated exposure of this product may lead to the development of cancerous tumors.

Immediate medical attention and special treatment: No specific treatment. Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.

5. Fire-fighting measures

Suitable extinguishing media: Use dry chemical, CO₂, water spray (fog) or foam.

Unsuitable extinguishing media: Jets of water can facilitate the spread of fire.

Specific hazards arising from the hazardous product: Combustible. If heated, vapors may form explosive mixtures with air. The vapors are heavier than air and may travel to an ignition source.

Hazardous combustion products: Carbon monoxide and dioxide. Nitrogen oxides. Hydrocyanic acid.

Special protective equipment and precautions for fire-fighters: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

6. Accidental release measures

Personal precautions: No action shall be taken involving any personal risk or if you do not have suitable training or protection. Evacuate surrounding areas. Do not touch or walk through spilled material. Shut off all heating and ignition sources. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment (see Section 8).

Protective equipment and emergency procedures: Avoid dispersal of spilled material, runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution. Use inert absorbent or retention tubes in the event of a large spill.

Methods and materials for containment and cleaning up: Stop leak if without risk. Move containers from spill area. Contain leaks and pick up with non-combustible absorbent materials such as sand, earth or vermiculite. Then, place in an appropriate waste disposal container according to local regulations. Dispose of via a licensed waste disposal contractor.

7. Handling and storage

Precautions for safe handling: Put on appropriate personal protective equipment (see Section 8). Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. Avoid exposure - obtain special instructions before use. Avoid contact with eyes, skin and clothing. Do not ingest. Do not breath vapor or mist. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not enter storage areas and confined spaces unless adequately ventilated. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Store and use away from heat, sparks, open flame or any other ignition source. Use non-sparking tools. Take precautionary measures against electrostatic discharges. To avoid fire or explosion, dissipate static electricity during transfer by grounding and bonding containers and equipment before transferring material. Empty containers retain product residue and can be hazardous. Do not reuse container.

Conditions for safe storage: Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and



Safety Data Sheet

POR-15 Fuel Tank Sealer

well-ventilated area, away from incompatible materials (see section 10) and food and drink. Eliminate all ignition sources. Separate from oxidizing materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

Incompatibility: Strong oxidizing agents. Ammonia. Alcohols. Amines. Oxidizers.

8. Exposure Controls/ Personal protection

Alberta

No	CAS No :	Common name and synonyms	8-hour occupational exposure limit (TWA)		15-minute occupational exposure limit (STEL)		Ceiling occupational exposure limit	
			ppm	mg/m ³	ppm	mg/m ³	ppm	mg/m ³
1	67815-87-6	Aromatic polyisocyanate MDI based	N/A	N/A	N/A	N/A	N/A	N/A
2	64742-95-6	Naphtha, light aromatic fraction C8-C10	N/A	N/A	N/A	N/A	N/A	N/A
3	101-68-8	4,4'-Diphenylmethane diisocyanate monomer. MDI monomer	0.005	0.05	N/A	N/A	N/A	N/A
4	9016-87-9	Polymethylene polyphenyl isocyanate. PMDI polymeric	0.005	0.07	N/A	N/A	N/A	N/A
5	64742-48-9	Naphtha hydrotreated, heavy fraction	N/A	N/A	N/A	N/A	N/A	N/A
6	26447-40-5	4,4'-Dipheylmethane diisocyanate. MDI polymeric	N/A	N/A	N/A	N/A	N/A	N/A

British-Columbia

No	CAS No :	Common name and synonyms	8-hour occupational exposure limit (TWA)		15-minute occupational exposure limit (STEL)		Ceiling occupational exposure limit	
			ppm	mg/m ³	ppm	mg/m ³	ppm	mg/m ³
1	67815-87-6	Aromatic polyisocyanate MDI based	N/A	N/A	N/A	N/A	N/A	N/A
2	64742-95-6	Naphtha, light aromatic fraction C8-C10	N/A	N/A	N/A	N/A	N/A	N/A
3	101-68-8	4,4'-Diphenylmethane diisocyanate monomer. MDI monomer	0.005	N/A	N/A	N/A	0.01	N/A
4	9016-87-9	Polymethylene polyphenyl isocyanate. PMDI polymeric	N/A	N/A	N/A	N/A	N/A	N/A
5	64742-48-9	Naphtha hydrotreated, heavy fraction	N/A	N/A	N/A	N/A	N/A	N/A
6	26447-40-5	4,4'-Dipheylmethane diisocyanate. MDI polymeric	N/A	N/A	N/A	N/A	N/A	N/A



Safety Data Sheet

POR-15 Fuel Tank Sealer

Ontario

No	CAS No :	Common name and synonyms	8-hour occupational exposure limit (TWA)		15-minute occupational exposure limit (STEL)		Ceiling occupational exposure limit	
			ppm	mg/m ³	ppm	mg/m ³	ppm	mg/m ³
1	67815-87-6	Aromatic polyisocyanate MDI based	N/A	N/A	N/A	N/A	N/A	N/A
2	64742-95-6	Naphtha, light aromatic fraction C8-C10	N/A	N/A	N/A	N/A	N/A	N/A
3	101-68-8	4,4'-Diphenylmethane diisocyanate monomer. MDI monomer	0.005	N/A	N/A	N/A	0.02	N/A
4	9016-87-9	Polymethylene polyphenyl isocyanate. PMDI polymeric	N/A	N/A	N/A	N/A	N/A	N/A
5	64742-48-9	Naphtha hydrotreated, heavy fraction	N/A	N/A	N/A	N/A	N/A	N/A
6	26447-40-5	4,4'-Dipheylmethane diisocyanate. MDI polymeric	N/A	N/A	N/A	N/A	N/A	N/A

Quebec

No	CAS No :	Common name and synonyms	8-hour occupational exposure limit (TWA)		15-minute occupational exposure limit (STEL)		Ceiling occupational exposure limit	
			ppm	mg/m ³	ppm	mg/m ³	ppm	mg/m ³
1	67815-87-6	Aromatic polyisocyanate MDI based	N/A	N/A	N/A	N/A	N/A	N/A
2	64742-95-6	Naphtha, light aromatic fraction C8-C10	N/A	N/A	N/A	N/A	N/A	N/A
3	101-68-8	4,4'-Diphenylmethane diisocyanate monomer. MDI monomer	0.005	0.051	N/A	N/A	N/A	N/A
4	9016-87-9	Polymethylene polyphenyl isocyanate. PMDI polymeric	N/A	N/A	N/A	N/A	N/A	N/A
5	64742-48-9	Naphtha hydrotreated, heavy fraction	N/A	N/A	N/A	N/A	N/A	N/A
6	26447-40-5	4,4'-Dipheylmethane diisocyanate. MDI polymeric	N/A	N/A	N/A	N/A	N/A	N/A

Saskatchewan

No	CAS No :	Common name and synonyms	8-hour occupational exposure limit (TWA)		15-minute occupational exposure limit (STEL)		Ceiling occupational exposure limit	
			ppm	mg/m ³	ppm	mg/m ³	ppm	mg/m ³
1	67815-87-6	Aromatic polyisocyanate MDI based	N/A	N/A	N/A	N/A	N/A	N/A
2	64742-95-6	Naphtha, light aromatic fraction C8-C10	N/A	N/A	N/A	N/A	N/A	N/A
3	101-68-8	4,4'-Diphenylmethane diisocyanate monomer. MDI monomer	0.005	N/A	0.015	0.015	N/A	N/A
4	9016-87-9	Polymethylene polyphenyl isocyanate. PMDI polymeric	N/A	N/A	N/A	N/A	N/A	N/A
5	64742-48-9	Naphtha hydrotreated, heavy fraction	N/A	N/A	N/A	N/A	N/A	N/A
6	26447-40-5	4,4'-Dipheylmethane diisocyanate. MDI polymeric	N/A	N/A	N/A	N/A	N/A	N/A



Safety Data Sheet

POR-15 Fuel Tank Sealer

United States

No	CAS No :	Common name and synonyms	IDLH NIOSH	Regulatory Limits			Recommended Limits	
				OSHA PEL		California / OSHA PEL	NIOSH REL	ACGIH ® 2019 TLV ®
				ppm	mg/m ³	8-hour TWA (ST) STEL (C) Ceiling	Up to 10-hour TWA (ST) STEL (C) Ceiling	8-hour TWA (ST) STEL (C) Ceiling
1	67815-87-6	Aromatic polyisocyanate MDI based	N/A	N/A	N/A	N/A	N/A	N/A
2	64742-95-6	Naphtha, light aromatic fraction C8-C10	N/A	N/A	N/A	N/A	N/A	N/A
3	101-68-8	4,4'-Diphenylmethane diisocyanate monomer. MDI monomer	75	(C) 0.02	(C) 0.2	0.005 ppm	0.05 mg/m ³ (C) 0.2 mg/m ³ [10-min]	0.005 ppm
4	9016-87-9	Polymethylene polyphenyl isocyanate. PMDI polymeric	N.R.	N/A	N/A	N/A	N/A	N/A
5	64742-48-9	Naphtha hydrotreated, heavy fraction	N/A	N/A	N/A	N/A	N/A	N/A
6	26447-40-5	4,4'-Dipheylmethane diisocyanate. MDI polymeric	N/A	N/A	N/A	N/A	N/A	N/A

IDHL: Immediately Dangerous to Life or Health Concentrations

NIOSH: National Institute for Occupational Safety and Health

OSHA: Occupational Safety and Health Administration

PEL: Permissible Exposure Limits

California / OSHA: California Division of Occupational Safety and Health

REL: Recommended Exposure Limits

ACGIH ®: American Conference of Governmental Industrial Hygienists

TLV ®: Threshold Limit Values

Appropriate engineering controls: Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapor or dust concentrations below any lower explosive limits.

Individual protection measures: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Eyes: DO NOT WEAR CONTACT LENSES Wear anti-splash safety goggles.

Hands: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties.

Respiratory: If workers are exposed to concentrations above the exposure limit, they must use appropriate, certified respirators. Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.

Others: Wear protective clothing with long sleeves and appropriate safety shoes at all times.



Safety Data Sheet

POR-15 Fuel Tank Sealer

9. Physical and chemical properties

Physical state: Liquid

Colour: Silver

Odour: Solvent

Odour threshold: Not available

pH: Not applicable

Melting/Freezing point: < 0 °C (32 °F)

Initial boiling point/boiling range: > 140 °C (284 °F)

Flash point: > 38 °C (100.4 °F) Closed cup

Flammability: Not applicable

Lower flammable/explosive limit: 0,6 % at 25 °C

Upper flammable/explosive limit: 7,0 % at 25 °C

Auto-ignition temperature: 349 °C (660.2 °F)

Evaporation rate: Not available

Vapour pressure: Not available

Vapour density: > 1 (air = 1)

Specific gravity: 1,040 kg/L at 20 °C (water = 1)

Solubility in water: Insoluble

Partition coefficient – n-octanol/water: Not available

Decomposition temperature: Not applicable

Kinematic viscosity: > 20,5 mm²/s (at 40 °C)

10. Stability and reactivity

Reactivity: Stable under recommended conditions of storage and handling.

Chemical stability: The product is chemically stable under normal conditions of use.

Possibility of hazardous reactions: Danger of explosion when heated. No dangerous or polymerization reactions will occur under normal conditions of use.

Conditions to avoid: Avoid electrical discharge. Keep away from sources of ignition, open flames and sparks, Keep away from incompatible products (see section 7).

Incompatible materials: This product can attack certain types of plastic, rubber or coatings.

Hazardous decomposition products: Carbon monoxide and dioxide. Nitrogen oxides. Hydrocyanic acid.



Safety Data Sheet

POR-15 Fuel Tank Sealer

11. Toxicological information

	Oral	Dermal	Inhalation gases	Inhalation vapours	Inhalation dusts/mists
ATE _{mix}	> 5 000 mg/kg	75685.9 mg/kg	N/A	8.1 mg/l	1.34 mg/l

No	CAS No :	Common name and synonyms	LD ₅₀ oral mg/kg	LD ₅₀ skin mg/kg	LC ₅₀ inhalation ppmV 4h - gases	LC ₅₀ inhalation mg/l 4h - vapours	LC ₅₀ inhalation mg/l 4h - dusts-mist
1	67815-87-6	Aromatic polyisocyanate MDI based	> 5000	> 5000	N/A	N/A	1.5
2	64742-95-6	Naphtha, light aromatic fraction C8-C10	8400	> 5000	N/A	> 20.00	> 5.00
3	101-68-8	4,4'-Diphenylmethane diisocyanate monomer. MDI monomer	31600	> 10000	N/A	N/A	0.37
4	9016-87-9	Polymethylene polyphenyl isocyanate. PMDI polymeric	> 10000	9400	N/A	0.5	0.49
5	64742-48-9	Naphtha hydrotreated, heavy fraction	> 5000	> 3200	N/A	> 20.00	8.5
6	26447-40-5	4,4'-Dipheylmethane diisocyanate. MDI polymeric	31600	> 10000	N/A	11	1.01

Routes of exposure: This product is absorbed through the respiratory tract, skin and gastrointestinal tract.

Symptoms: This product is irritating to skin, eyes, respiratory and digestive tracts. The severity of symptoms can vary depending on the exposure conditions (contact time, product concentration, etc.). The main symptoms of intoxication include headache, nausea, vomiting, weakness, loss of appetite, fatigue, sweating, fever, tachycardia and dyspnea. In the most severe cases, convulsions, hyperthermic coma, liver damage are reported and sometimes death. The worker may develop skin hypersensitivity as well as allergic or asthma symptoms or breathing difficulties if inhaled. Repeated exposures lead to the chronic form whose symptoms are dyspnea to exercise, cough with sputum, fatigue and weight loss.

Delayed and immediate effects: This product is a serious irritant that may cause reversible damages to the cornea. May cause skin irritation. Following repeated or prolonged contact, it has a degreasing effect on the skin. In high concentration, can cause depression of the central nervous system. May cause kidney damage. Narcotic effect by inhalation. This product is a respiratory and skin sensitizer. Repeated exposure of this product may lead to the development of cancerous tumors.

Aspiration hazard	N/A
Skin corrosion - Skin irritation	Yes
Serious eye damage - Serious eye irritation	Yes
Skin sensitization	Yes
Respiratory sensitization	Yes
Specific target organ toxicity – single exposure	N/A
Specific target organ toxicity – single exposure Category 3 Narcotic effects	Yes
Specific target organ toxicity – single exposure Category 3 Respiratory tract irritation	Yes
Specific target organ toxicity – repeated exposure	Yes



Safety Data Sheet

POR-15 Fuel Tank Sealer

No	CAS No :	Common name and synonyms	IARC	ACGIH	Mutagenicity	Effect on reproduction
1	67815-87-6	Aromatic polyisocyanate MDI based	N/A	N/A	No effects shown.	No effects shown.
2	64742-95-6	Naphtha, light aromatic fraction C8-C10	N/A	N/A	No effects shown.	No effects shown.
3	101-68-8	4,4'-Diphenylmethane diisocyanate monomer. MDI monomer	3	A4	The data do not allow for an adequate assessment of mutagenic effects.	The data do not allow for an adequate evaluation of the effects on development.
4	9016-87-9	Polymethylene polyphenyl isocyanate. PMDI polymeric	3	A4	No effects shown.	No effects shown.
5	64742-48-9	Naphtha hydrotreated, heavy fraction	N/A	N/A	No effects shown.	No effects shown.
6	26447-40-5	4,4'-Dipheylmethane diisocyanate. MDI polymeric	2B	A3	No effects shown.	No effects shown.

Cancer classification under IARC (International Agency for Research on Cancer)

Group 1: carcinogenic to humans.

Group 2A: probably carcinogenic to humans.

Group 2B: possibly carcinogenic to humans.

Group 3: not classifiable as to its carcinogenicity to humans.

Group 4: probably not carcinogenic to humans.

Cancer classification under ACGIH (American Conference of Governmental Industrial Hygienists)

Group A1: confirmed human carcinogen.

Group A2: suspected human carcinogen.

Group A3: confirmed animal carcinogen with unknown relevance to humans.

Group A4: not classifiable as a human carcinogen.

Group A5: not suspected as a human carcinogen.



Safety Data Sheet

POR-15 Fuel Tank Sealer

12. Ecological information

Ecotoxicity

No	CAS No :	Common name and synonyms	%	Aquatic Ecotoxicity short term	Aquatic Ecotoxicity long term	Terrestrial Ecotoxicity
1	67815-87-6	Aromatic polyisocyanate MDI based	30.00 - 60.00	No known adverse effect to aquatic life.	No known adverse effect to aquatic life.	No known adverse effect to the environment.
2	64742-95-6	Naphtha, light aromatic fraction C8-C10	28.42	No known adverse effect to aquatic life.	No known adverse effect to aquatic life.	No known adverse effect to the environment.
3	101-68-8	4,4'-Diphenylmethane diisocyanate monomer. MDI monomer	10.00 - 30.00	No known adverse effect to aquatic life.	No known adverse effect to aquatic life.	No known adverse effect to the environment.
4	9016-87-9	Polymethylene polyphenyl isocyanate. PMDI polymeric	5.00 - 10.00	Not available.	Very toxic to aquatic life with long lasting effects.	No known adverse effect to the environment.
5	64742-48-9	Naphtha hydrotreated, heavy fraction	1.06	No known adverse effect to aquatic life.	No known adverse effect to aquatic life.	No known adverse effect to the environment.
6	26447-40-5	4,4'-Dipheylmethane diisocyanate. MDI polymeric	0.10 - 1.00	No known adverse effect to aquatic life.	No known adverse effect to aquatic life.	No known adverse effect to the environment.

Persistence and degradability. Bioaccumulative potential. Other adverse effects

No	CAS No :	Common name and synonyms	%	Persistent	Bio-accumulation	Aquatic ecotoxicity
1	67815-87-6	Aromatic polyisocyanate MDI based	30.00 - 60.00	Yes	No	No
2	64742-95-6	Naphtha, light aromatic fraction C8-C10	28.42	No	No	No
3	101-68-8	4,4'-Diphenylmethane diisocyanate monomer. MDI monomer	10.00 - 30.00	No	No	No
4	9016-87-9	Polymethylene polyphenyl isocyanate. PMDI polymeric	5.00 - 10.00	No	No	No
5	64742-48-9	Naphtha hydrotreated, heavy fraction	1.06	Yes	Yes	Yes
6	26447-40-5	4,4'-Dipheylmethane diisocyanate. MDI polymeric	0.10 - 1.00	No	No	No

Degradability: N/A

Mobility in soil: N/A



Safety Data Sheet

POR-15 Fuel Tank Sealer

13. Disposal considerations

Methods of disposal: The generation of waste should be avoided or minimized wherever possible. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Empty containers or liners may retain some product residues. Vapor from product residues may create a highly flammable or explosive atmosphere inside the container. Do not cut, weld or grind used containers unless they have been cleaned thoroughly internally.

14. Transport information

	TDG	DOT	IMDG	IATA
UN Number	1263	1263	1263	1263
Proper shipping name	PAINT	PAINT	PAINT	PAINT
Transport hazard class(es)	3	3	3	3
Packing group	III	III	III	III

United States - Reportable Quantities (RQ)

No	CAS No :	Common name and synonyms	RQ lbs (kg)
1	101-68-8	4,4'-Diphenylmethane diisocyanate monomer. MDI monomer	5000 (2270)

Transport in bulk (according to Annex II of the International Convention for the Prevention of Pollution From Ships, 1973, as modified by the Protocol of 1978 (MARPOL 73/78), and the International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk (IBC Code)): N/A

Marine pollutant: No

Exemption for limited quantity: 5 L

In accordance with the Canadian Transport of Dangerous Goods regulations by Road, we use the 1.17 exemption when applicable. In accordance with 49 CFR article 172.315 for transportation by a mode other than air, we use the Limited quantities exemption when applicable.

Special precautions: Not applicable

Other exemptions: In Canada, containers of 450 Liters or less are EXEMPTED to transport of dangerous goods on a road vehicle, a railway vehicle or a vessel on a domestic voyage under 1,33 article.

In USA, a flammable liquid with a flash point at or above 38 °C (100 °F) that does not meet the definition of any other hazard class may be reclassified as a combustible liquid under article 173.150 (f). This provision does not apply to transportation by vessel or aircraft, except where other means of transportation is impracticable.



Safety Data Sheet

POR-15 Fuel Tank Sealer

15. Regulatory information

Canada

No	CAS No :	Common name and synonyms	%	DSL	NDSL	NPRI
1	67815-87-6	Aromatic polyisocyanate MDI based	30.00 - 60.00	X		
2	64742-95-6	Naphtha, light aromatic fraction C8-C10	28.42	X		X
3	101-68-8	4,4'-Diphenylmethane diisocyanate monomer. MDI monomer	10.00 - 30.00	X		X
4	9016-87-9	Polymethylene polyphenyl isocyanate. PMDI polymeric	5.00 - 10.00	X		X
5	64742-48-9	Naphtha hydrotreated, heavy fraction	1.06	X		X
6	26447-40-5	4,4'-Dipheylmethane diisocyanate. MDI polymeric	0.10 - 1.00	X		

United States

No	CAS No :	Common name and synonyms	%	TSCA	PROP-65	RTK
1	67815-87-6	Aromatic polyisocyanate MDI based	30.00 - 60.00	X		
2	64742-95-6	Naphtha, light aromatic fraction C8-C10	28.42	X		
3	101-68-8	4,4'-Diphenylmethane diisocyanate monomer. MDI monomer	10.00 - 30.00	X		
4	9016-87-9	Polymethylene polyphenyl isocyanate. PMDI polymeric	5.00 - 10.00	X		
5	64742-48-9	Naphtha hydrotreated, heavy fraction	1.06	X		
6	26447-40-5	4,4'-Dipheylmethane diisocyanate. MDI polymeric	0.10 - 1.00	X		

The customer is responsible for determining the PPE (personal protection equipment) code for this material.

The classification of the product and the SDS were developed in accordance with HPR and HazCom 2012.

16. Other information

Date: 2021-06-08

Version: 2

Notice to reader: The manufacturer hereby declares that the information disclosed herein have been based on governmental sites and/or raw material supplier's. The manufacturer has no control over the nature and content of such information. The manufacturer fully reproduces all the information it holds on the constituent of the product, at the time it is manufactured. The manufacturer does not assume any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. By this data sheet, the manufacturer hereby discloses all the potential dangers it has knowledge of and which might be related to the using or manipulation of the product in order to allow the proper care to be brought and use with regard to the product. Although certain hazards are described herein, we cannot guarantee that these are the only hazards which exist and notification is hereby given to the user. Notice is hereby given that injury can derive therefrom if the foregoing is not respected. The manufacturer assumes no responsibility for personal and/or material damage, lost or injury of whichever nature caused or which may occur following the wrongful, inappropriate, negligent or abusive use or handling of the product or from not having read the herein contained information.