

acc. to Hazardous Products Regulations (HPR)

### POR PATCH WHITE

Version number: GHS 1.0 Date of compilation: 2024-06-20

### 1 Identification

#### **Product identifier** 1.1

Trade name **POR PATCH WHITE** 

Product code(s) 49023, 49025

#### Relevant identified uses of the substance or mixture and uses advised against 1.2

Relevant identified uses General use

#### 1.3 Details of the supplier of the safety data sheet

P.O.R. Products 38 Portman Road New Rochelle NY 10801 **United States** 

Telephone: +1 914-636-0700 e-mail: support@porproducts.com Website: www.porproducts.com

e-mail (competent person) support@porproducts.com

#### **Emergency telephone number** 1.4

1-800-255-3924 **Emergency information service** 

ChemTel Inc.

### 2 Hazard identification

#### 2.1 Classification of the substance or mixture

Classification acc. to GHS

Section	Hazard class	Category	Hazard class and cat- egory	Hazard state- ment
2.6	flammable liquid	4	Flam. Liq. 4	H227
3.2	skin corrosion/irritation	2	Skin Irrit. 2	H315
3.3	serious eye damage/eye irritation	2	Eye Irrit. 2	H319
3.4R	respiratory sensitization	1	Resp. Sens. 1	H334
3.45	skin sensitization	1	Skin Sens. 1	H317
3.5	germ cell mutagenicity	1B	Muta. 1B	H340
3.6	carcinogenicity	1A	Carc. 1A	H350
3.8R	specific target organ toxicity - single exposure (respiratory tract irritation)	3	STOT SE 3	H335
3.9	specific target organ toxicity - repeated exposure	2	STOT RE 2	H373
3.10	aspiration hazard	1	Asp. Tox. 1	H304

For full text of abbreviations: see SECTION 16.

Canada: en Page: 1 / 21



acc. to Hazardous Products Regulations (HPR)

### POR PATCH WHITE

Version number: GHS 1.0 Date of compilation: 2024-06-20

The most important adverse physicochemical, human health and environmental effects

Delayed or immediate effects can be expected after short or long-term exposure. The product is combustible and can be ignited by potential ignition sources.

#### 2.2 Label elements

#### Labeling

- Signal word danger

- Pictograms

GHS07, GHS08



#### - Hazard statements

H227 Combustible liquid.

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

H335 May cause respiratory irritation. H340 May cause genetic defects.

H350 May cause cancer.

H373 May cause damage to organs through prolonged or repeated exposure.

#### - Precautionary statements

P201 Obtain special instructions before use.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P260 Do not breathe dust/fume/gas/mist/vapours/spray.
P271 Use only outdoors or in a well-ventilated area.

P272 Contaminated work clothing should not be allowed out of the workplace.

P280 Wear protective gloves/protective clothing/eve protection/face protection/hearing protection.

P284 In case of inadequate ventilation wear respiratory protection.
P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/doctor.

P302+P352 IF ON SKIN: Wash with plenty of water.

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present

and easy to do. Continue rinsing.

P312 Call a POISON CENTER/doctor if you feel unwell.

P321 Specific treatment (see on this label).

P331 Do NOT induce vomiting.

P342+P311 If experiencing respiratory symptoms: Call a POISON CENTER/doctor.

P362+P364 Take off contaminated clothing and wash it before reuse.

P370+P378 In case of fire: Use sand, carbon dioxide or powder extinguisher to extinguish.

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

P405 Store locked up.

P501 Dispose of contents/container to industrial combustion plant.

- Hazardous ingredients for labelling

4,4'-methylenediphenyl diisocyanate, Solvent naphtha (petroleum), light arom., o-(p-

isocyanatobenzyl)phenyl isocyanate, 2,2'-methyle-

nediphenyl diisocyanate

Canada: en Page: 2 / 21



acc. to Hazardous Products Regulations (HPR)

### **POR PATCH WHITE**

Version number: GHS 1.0 Date of compilation: 2024-06-20

#### 2.3 Other hazards

This material is combustible, but will not ignite readily.

Results of PBT and vPvB assessment

Does not contain a PBT-/vPvB-substance at a concentration of  $\geq$  0.1%.

**Endocrine disrupting properties** 

Does not contain an endocrine disruptor (ED) in a concentration of  $\geq$  0.1%.

## 3 Composition/ Information on ingredients

#### 3.1 Substances

Not relevant (mixture)

#### 3.2 Mixtures

Description of the mixture

Name of substance	Identifier	Wt%	Classification acc. to GHS
4,4'-methylenediphenyl diisocy- anate	CAS No 101-68-8	10 - < 30	Acute Tox. 2 / H330 Skin Irrit. 2 / H315 Eye Irrit. 2 / H319 Resp. Sens. 1 / H334 Skin Sens. 1 / H317 Carc. 2 / H351 STOT SE 3 / H335 STOT RE 2 / H373
o-(p-isocyanatobenzyl)phenyl isocy- anate	CAS No 5873-54-1	10 - < 30	Acute Tox. 2 / H330 Skin Irrit. 2 / H315 Eye Irrit. 2 / H319 Resp. Sens. 1 / H334 Skin Sens. 1 / H317 Carc. 2 / H351 STOT SE 3 / H373
Titanium dioxide (excluding nano- particle)	CAS No 13463-67-7	5 – < 10	Carc. 2 / H351
Confidential Organoclay	CAS No 68953-58-2 92704-41-1	5 – < 10	Acute Tox. 4 / H332
Solvent naphtha (petroleum), light arom.	CAS No 64742-95-6	5 – < 10	Flam. Liq. 1 / H224 Muta. 1B / H340 Carc. 1A / H350 Asp. Tox. 1 / H304
1,2,4-trimethylbenzene	CAS No 95-63-6	1-<5	Flam. Liq. 3 / H226 Acute Tox. 4 / H332 Skin Irrit. 2 / H315 Eye Irrit. 2 / H319 STOT SE 3 / H335 Asp. Tox. 1 / H304

Canada: en Page: 3 / 21



acc. to Hazardous Products Regulations (HPR)

### POR PATCH WHITE

Version number: GHS 1.0 Date of compilation: 2024-06-20

Name of substance	Identifier	Wt%	Classification acc. to GHS
2,2'-methylenediphenyl diisocy- anate	CAS No 2536-05-2	0.1 – < 1	Acute Tox. 2 / H330 Skin Irrit. 2 / H315 Eye Irrit. 2 / H319 Resp. Sens. 1 / H334 Skin Sens. 1 / H317 Carc. 2 / H351 STOT SE 3 / H335 STOT RE 2 / H373
cumene	CAS No 98-82-8	0.1 - < 1	Flam. Liq. 3 / H226 Carc. 1B / H350 STOT SE 3 / H335 Asp. Tox. 1 / H304

#### Remarks

For full text of abbreviations: see SECTION 16

#### 4 First-aid measures

#### 4.1 Description of first-aid measures

#### General notes

Do not leave affected person unattended. Remove victim out of the danger area. Keep affected person warm, still and covered. Take off immediately all contaminated clothing. In all cases of doubt, or when symptoms persist, seek medical advice. In case of unconsciousness place person in the recovery position. Never give anything by mouth.

#### Following inhalation

If breathing is irregular or stopped, immediately seek medical assistance and start first aid actions. In case of respiratory tract irritation, consult a physician. Provide fresh air.

#### Following skin contact

Wash with plenty of soap and water.

#### Following eye contact

Remove contact lenses, if present and easy to do. Continue rinsing. Irrigate copiously with clean, fresh water for at least 10 minutes, holding the eyelids apart.

#### Following ingestion

Rinse mouth with water (only if the person is conscious). Do NOT induce vomiting.

#### 4.2 Most important symptoms and effects, both acute and delayed

Symptoms and effects are not known to date.

#### 4.3 Indication of any immediate medical attention and special treatment needed

none

Canada: en Page: 4 / 21



acc. to Hazardous Products Regulations (HPR)

#### POR PATCH WHITE

Version number: GHS 1.0 Date of compilation: 2024-06-20

### 5 Fire-fighting measures

#### 5.1 Extinguishing media

Suitable extinguishing media

Water spray, BC-powder, Carbon dioxide (CO2)

Unsuitable extinguishing media

Water jet

#### 5.2 Special hazards arising from the substance or mixture

In case of insufficient ventilation and/or in use, may form flammable/explosive vapor-air mixture. Solvent vapors are heavier than air and may spread along floors. Places which are not ventilated, e.g. unventilated below ground level areas such as trenches, conduits and shafts, are particularly prone to the presence of flammable substances or mixtures.

Hazardous combustion products

Nitrogen oxides (NOx), Carbon monoxide (CO), Carbon dioxide (CO2)

#### 5.3 Advice for firefighters

In case of fire and/or explosion do not breathe fumes. Coordinate firefighting measures to the fire surroundings. Do not allow firefighting water to enter drains or water courses. Collect contaminated firefighting water separately. Fight fire with normal precautions from a reasonable distance.

#### **6 Accidental release measures**

### 6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

Remove persons to safety.

For emergency responders

Wear breathing apparatus if exposed to vapors/dust/aerosols/gases.

#### 6.2 Environmental precautions

Keep away from drains, surface and ground water. Retain contaminated washing water and dispose of it.

#### 6.3 Methods and material for containment and cleaning up

Advice on how to contain a spill

Covering of drains

Advice on how to clean up a spill

Wipe up with absorbent material (e.g. cloth, fleece). Collect spillage: sawdust, kieselgur (diatomite), sand, universal binder

Appropriate containment techniques

Use of adsorbent materials.

Other information relating to spills and releases

Place in appropriate containers for disposal. Ventilate affected area.

#### 6.4 Reference to other sections

Hazardous combustion products: see section 5. Personal protective equipment: see section 8. Incompatible materials: see section 10. Disposal considerations: see section 13.

Canada: en Page: 5 / 21



acc. to Hazardous Products Regulations (HPR)

#### POR PATCH WHITE

Version number: GHS 1.0 Date of compilation: 2024-06-20

### 7 Handling and storage

#### 7.1 Precautions for safe handling

#### Recommendations

- Measures to prevent fire as well as aerosol and dust generation

Use local and general ventilation. Avoidance of ignition sources. Keep away from sources of ignition - No smoking. Take precautionary measures against static discharge. Use only in well-ventilated areas. Due to danger of explosion, prevent leakage of vapours into cellars, flues and ditches. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting/equipment. Use only non-sparking tools.

- Specific notes/details

Places which are not ventilated, e.g. unventilated below ground level areas such as trenches, conduits and shafts, are particularly prone to the presence of flammable substances or mixtures. Vapors are heavier than air, spread along floors and form explosive mixtures with air. Vapors may form explosive mixtures with air.

#### Advice on general occupational hygiene

Wash hands after use. Do not eat, drink and smoke in work areas. Remove contaminated clothing and protective equipment before entering eating areas. Never keep food or drink in the vicinity of chemicals. Never place chemicals in containers that are normally used for food or drink. Keep away from food, drink and animal feedingstuffs.

#### 7.2 Conditions for safe storage, including any incompatibilities

Managing of associated risks

- Explosive atmospheres

Keep container tightly closed and in a well-ventilated place. Use local and general ventilation. Keep cool. Protect from sunlight.

- Flammability hazards

Keep away from sources of ignition - No smoking. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Take precautionary measures against static discharge. Protect from sunlight.

- Ventilation requirements

Use local and general ventilation. Ground/bond container and receiving equipment.

#### 7.3 Specific end use(s)

See section 16 for a general overview.

#### 8 Exposure controls/ Personal protection

#### 8.1 Control parameters

### Occupational exposure limit values (Workplace Exposure Limits)

	•		•	•	•	•				
Coun- try	Name of agent	CAS No	Identi- fier	TWA [ppm]	TWA [mg/m³]	STEL [ppm]	STEL [mg/m³]	Ceiling-C [ppm]	Ceiling-C [mg/m³]	Source
CA	diphenylmethane- 4,4'-diisocyanate (methylbis(phenyl- isocyanate)) (4,4'- MDI)	101-68-8	OEL (AB)	0.005	0.05					OHS Code
CA	methylbis(phenyl- isocyanate) (4,4'- MDI)	101-68-8	OEL (BC)	0.005				0.01		"BC Reg- ulation"

Canada: en Page: 6 / 21



acc. to Hazardous Products Regulations (HPR)

## **POR PATCH WHITE**

Version number: GHS 1.0 Date of compilation: 2024-06-20

## Occupational exposure limit values (Workplace Exposure Limits)

Coun- try	Name of agent	CAS No	Identi- fier	TWA [ppm]	TWA [mg/m³]	STEL [ppm]	STEL [mg/m³]	Ceiling-C [ppm]	Ceiling-C [mg/m³]	Nota- tion	Source
CA	methylbis(phenyl- isocyanate) (4,4'- MDI)	101-68-8	OEL (ON)	0.005				0.02			Regula- tion 833
CA	methylbis(phenyl- isocyanate) (4,4'- MDI)	101-68-8	OEL (ON- MoL)	0.005				0.02			MoL
CA	methylenebis(p- phenyl isocyanate) (4,4'-MDI)	101-68-8	PEV/ VEA	0.005	0.051						Regula- tion OHS
CA	carbon black	1333-86-4	OEL (AB)		3.5						OHS Code
CA	carbon black	1333-86-4	PEV/ VEA		3					dust, i	Regula- tion OHS
CA	carbon black	1333-86-4	OEL (BC)		3					i	"BC Reg- ulation"
CA	carbon black	1333-86-4	OEL (ON- MoL)		3					i	MoL
CA	titanium dioxide	13463-67-7	OEL (AB)		10						OHS Code
CA	titanium dioxide	13463-67-7	OEL (ON- MoL)		10						MoL
CA	titanium dioxide	13463-67-7	OEL (BC)		10					dust	"BC Reg- ulation"
CA	titanium dioxide	13463-67-7	PEV/ VEA		10					dust, noAsb_l ess1Sil	Regula- tion OHS
CA	titanium dioxide	13463-67-7	OEL (BC)		3					r	"BC Reg- ulation"
CA	diisocyanates	2536-05-2	OEL (BC)	0.005				0.01			"BC Reg- ulation"
CA	1,2,4-trimethylben- zene	95-63-6	OEL (BC)	25							"BC Reg- ulation"
CA	cumene	98-82-8	OEL (AB)	50	246						OHS Code
CA	cumene	98-82-8	OEL (BC)	25		75					"BC Reg- ulation"
CA	cumene	98-82-8	OEL (ON- MoL)	50							MoL
CA	cumene	98-82-8	PEV/ VEA	50	246						Regula- tion OHS

Canada: en Page: 7 / 21



acc. to Hazardous Products Regulations (HPR)

### **POR PATCH WHITE**

Version number: GHS 1.0 Date of compilation: 2024-06-20

Notation

ceiling value is a limit value above which exposure should not occur as dust Ceiling-C

dust

inhalable fraction

. noAsb\_less1S contains no asbestos and less than 1% free crystalline silica il

respirable fraction

STEL short-term exposure limit: a limit value above which exposure should not occur and which is related to a 15-minute period

(unless otherwise specified)

time-weighted average (long-term exposure limit): measured or calculated in relation to a reference period of 8 hours time-weighted average (unless otherwise specified TWA

### Relevant DNELs of components

4.4'-methylenediphen-yl diisocyanate  101-68-8 DNEL 0.05 mg/m³ human, inhalatory worker (industry) chronic - local o-(p-isocyanatobenzyl)phen yl socyanatobenzyl)phen yl socya		•					
4,4'-methylenediphen-yl diisocyanate 4,4'-methylenediphen-yl diisocyanate 4,4'-methylenediphen-yl diisocyanate 4,4'-methylenediphen-yl diisocyanate  101-68-8  DNEL  DNEL  0.05 mg/m³  human, inhalatory  worker (industry)  chronic - local  boxpanatobenzylphen yl isocyanate  5873-54-1  DNEL  0.1 mg/m³  human, inhalatory  worker (industry)  worker (industry)  chronic - local  chronic - local  acute - local  boxpanatobenzylphen yl isocyanate  Confidential Organo- clay  Confidential Organo- clay  DNEL  DNEL  3 mg/m³  human, inhalatory  worker (industry)  worker (industry)  chronic - syste fects  Confidential Organo- clay  DNEL  3 mg/m³  human, inhalatory  worker (industry)  chronic - local  macute - local  human, inhalatory  worker (industry)  chronic - local  macute - local  human, inhalatory  worker (industry)  chronic - local  macute - local  human, inhalatory  worker (industry)  chronic - local  macute - local  human, inhalatory  worker (industry)  chronic - local  macute - local  human, inhalatory  worker (industry)  chronic - local  macute - local  human, inhalatory  worker (industry)  chronic - local  macute - local  human, inhalatory  worker (industry)  chronic - syste  macute - local  human, inhalatory  worker (industry)  chronic - syste  macute - local  human, inhalatory  worker (industry)  chronic - syste  macute - local  human, inhalatory  worker (industry)  chronic - syste  macute - local  human, inhalatory  worker (industry)  chronic - syste  macute - local  human, inhalatory  worker (industry)  chronic - syste  macute - local  human, inhalatory  worker (industry)  chronic - syste  macute - local  human, inhalatory  worker (industry)  chronic - syste  macute - local  human, inhalatory  worker (industry)  chronic - syste  macute - local  human, inhalatory  worker (industry)  chronic - syste  macute - local  human, inhalatory  worker (industry)  chronic - syste  macute - local  human, inhalatory  worker (industry)  chronic - syste  macute - local  human, inhalatory  worker (industry)  chronic - syste  mac	Name of substance	CAS No	Endpoint			Used in	Exposure time
yl diisocyanate  o-(p- isocyanatobenzyl)phen yl isocyanate  o-(p- isocyanatobenzyl)phen yl isocyanate  o-(p- isocyanatobenzyl)phen yl isocyanate  confidential Organo- clay  c		101-68-8	DNEL	0.05 mg/m <sup>3</sup>	human, inhalatory	worker (industry)	chronic - local effects
isocyanatobenzyl)phen yl isocyanate  O-(p- isocyanatobenzyl)phen yl isocyanate  Confidential Organo- clay  Confidential Organo- c	4,4'-methylenediphen- yl diisocyanate	101-68-8	DNEL	0.1 mg/m <sup>3</sup>	human, inhalatory	worker (industry)	acute - local effects
Confidential Organo-   Clay   Clay   Clay   Clay   Clay	isocyanatobenzyl)phen	5873-54-1	DNEL	0.05 mg/m <sup>3</sup>	human, inhalatory	worker (industry)	chronic - local effects
Confidential Organo- clay 92704-41-1 DNEL 3 mg/m³ human, inhalatory worker (industry) acute - syste fects  Confidential Organo- clay 92704-41-1 DNEL 3 mg/m³ human, inhalatory worker (industry) chronic - local display for the clay 92704-41-1 DNEL 3 mg/m³ human, inhalatory worker (industry) chronic - local display fects fects  Confidential Organo- clay 92704-41-1 DNEL 3 mg/m³ human, inhalatory worker (industry) acute - local display fects fects  1,2,4-trimethylbenzene 95-63-6 DNEL 100 mg/m³ human, inhalatory worker (industry) chronic - syste fects  1,2,4-trimethylbenzene 95-63-6 DNEL 100 mg/m³ human, inhalatory worker (industry) chronic - local display fects fects  1,2,4-trimethylbenzene 95-63-6 DNEL 100 mg/m³ human, inhalatory worker (industry) acute - local display fects  1,2,4-trimethylbenzene 95-63-6 DNEL 100 mg/m³ human, inhalatory worker (industry) chronic - local display fects  2,2'-methylenediphen- yl diisocyanate 2536-05-2 DNEL 0.05 mg/m³ human, inhalatory worker (industry) chronic - local display fects  2,2'-methylenediphen- yl diisocyanate 2536-05-2 DNEL 0.1 mg/m³ human, inhalatory worker (industry) chronic - local display diisocyanate 2536-05-2 DNEL 0.1 mg/m³ human, inhalatory worker (industry) chronic - local display fects  Cumene 98-82-8 DNEL 100 mg/m³ human, inhalatory worker (industry) chronic - systematic display fects worker (industry) chronic - systematic display fects worker (industry) chronic - local display fects worker (industry) chronic - systematic fects worker (industry) chronic - local display fects worker (industry) chronic - local display fects worker (industry) chronic - local display fects worker (industry) chronic - systematic fects worker (industry) chronic - local display fects worker (industry) chronic - systematic fects worker (industry) chronic - local display fects worker (industry) chro	isocyanatobenzyl)phen	5873-54-1	DNEL	0.1 mg/m³	human, inhalatory	worker (industry)	acute - local effects
Confidential Organo- clay 92704-41-1 DNEL 3 mg/m³ human, inhalatory worker (industry) chronic - local  Confidential Organo- clay 92704-41-1 DNEL 3 mg/m³ human, inhalatory worker (industry) acute - local  Confidential Organo- clay 92704-41-1 DNEL 3 mg/m³ human, inhalatory worker (industry) acute - local  1,2,4-trimethylbenzene 95-63-6 DNEL 100 mg/m³ human, inhalatory worker (industry) chronic - syste fects  1,2,4-trimethylbenzene 95-63-6 DNEL 100 mg/m³ human, inhalatory worker (industry) chronic - local  1,2,4-trimethylbenzene 95-63-6 DNEL 100 mg/m³ human, inhalatory worker (industry) acute - local  1,2,4-trimethylbenzene 95-63-6 DNEL 16,171 mg/kg human, inhalatory worker (industry) chronic - syste fects  2,2'-methylenediphen- yl diisocyanate 2536-05-2 DNEL 0.05 mg/m³ human, inhalatory worker (industry) chronic - local  2,2'-methylenediphen- yl diisocyanate 2536-05-2 DNEL 0.1 mg/m³ human, inhalatory worker (industry) acute - local  Cumene 98-82-8 DNEL 100 mg/m³ human, inhalatory worker (industry) chronic - syste fects			DNEL	3 mg/m³	human, inhalatory	worker (industry)	chronic - systemic ef- fects
Confidential Organo- clay 92704-41-1  DNEL 3 mg/m³ human, inhalatory worker (industry) acute - local  1,2,4-trimethylbenzene 95-63-6  DNEL 100 mg/m³ human, inhalatory worker (industry) acute - syste fects  1,2,4-trimethylbenzene 95-63-6  DNEL 100 mg/m³ human, inhalatory worker (industry) acute - syste fects  1,2,4-trimethylbenzene 95-63-6  DNEL 100 mg/m³ human, inhalatory worker (industry) chronic - local  1,2,4-trimethylbenzene 95-63-6  DNEL 100 mg/m³ human, inhalatory worker (industry) acute - local  1,2,4-trimethylbenzene 95-63-6  DNEL 16,171 mg/kg human, inhalatory worker (industry) chronic - syste fects  2,2'-methylenediphen- yl diisocyanate 2536-05-2  DNEL 0.05 mg/m³ human, inhalatory worker (industry) chronic - local  2,2'-methylenediphen- yl diisocyanate 2536-05-2  DNEL 0.1 mg/m³ human, inhalatory worker (industry) acute - local  100 mg/m³ human, inhalatory worker (industry) chronic - local			DNEL	3 mg/m³	human, inhalatory	worker (industry)	acute - systemic ef- fects
clay 92704-41-1  1,2,4-trimethylbenzene 95-63-6  DNEL 100 mg/m³ human, inhalatory worker (industry) chronic - syste fects  1,2,4-trimethylbenzene 95-63-6  DNEL 100 mg/m³ human, inhalatory worker (industry) acute - syste fects  1,2,4-trimethylbenzene 95-63-6  DNEL 100 mg/m³ human, inhalatory worker (industry) chronic - local 1,2,4-trimethylbenzene 95-63-6  DNEL 100 mg/m³ human, inhalatory worker (industry) acute - local 1,2,4-trimethylbenzene 95-63-6  DNEL 16,171 mg/kg human, dermal worker (industry) chronic - syste fects  2,2'-methylenediphen-yl diisocyanate 2536-05-2  DNEL 0.05 mg/m³ human, inhalatory worker (industry) chronic - local 1,2,4-trimethylenediphen-yl diisocyanate 2536-05-2  DNEL 0.1 mg/m³ human, inhalatory worker (industry) chronic - local 1,2,4-trimethylenediphen-yl diisocyanate 2536-05-2  DNEL 0.1 mg/m³ human, inhalatory worker (industry) chronic - local 1,2,4-trimethylenediphen-yl diisocyanate 2536-05-2  DNEL 0.1 mg/m³ human, inhalatory worker (industry) chronic - local 1,2,4-trimethylenediphen-yl diisocyanate 2536-05-2  DNEL 0.1 mg/m³ human, inhalatory worker (industry) chronic - local 1,2,4-trimethylenediphen-yl diisocyanate 2,2'-methylenediphen-yl diisocyana			DNEL	3 mg/m³	human, inhalatory	worker (industry)	chronic - local effects
1,2,4-trimethylbenzene 95-63-6 DNEL 100 mg/m³ human, inhalatory worker (industry) acute - syste fects 1,2,4-trimethylbenzene 95-63-6 DNEL 100 mg/m³ human, inhalatory worker (industry) chronic - local 1,2,4-trimethylbenzene 95-63-6 DNEL 100 mg/m³ human, inhalatory worker (industry) acute - local 1,2,4-trimethylbenzene 95-63-6 DNEL 16,171 mg/kg human, dermal worker (industry) chronic - syste bw/day human, inhalatory worker (industry) chronic - syste fects 2,2'-methylenediphen-yl diisocyanate 2536-05-2 DNEL 0.05 mg/m³ human, inhalatory worker (industry) acute - local 2,2'-methylenediphen-yl diisocyanate DNEL 0.1 mg/m³ human, inhalatory worker (industry) acute - local 2,2'-methylenediphen-yl diisocyanate DNEL 100 mg/m³ human, inhalatory worker (industry) chronic - syste fects 2,2'-methylenediphen-yl diisocyanate 2536-05-2 DNEL 0.1 mg/m³ human, inhalatory worker (industry) acute - local 2,2'-methylenediphen-yl diisocyanate 2536-05-2 DNEL 100 mg/m³ human, inhalatory worker (industry) chronic - syste 6.			DNEL	3 mg/m³	human, inhalatory	worker (industry)	acute - local effects
1,2,4-trimethylbenzene 95-63-6 DNEL 100 mg/m³ human, inhalatory worker (industry) chronic - local 1,2,4-trimethylbenzene 95-63-6 DNEL 100 mg/m³ human, inhalatory worker (industry) acute - local 1,2,4-trimethylbenzene 95-63-6 DNEL 16,171 mg/kg human, dermal worker (industry) chronic - system fects 2,2'-methylenediphenyl diisocyanate 2536-05-2 DNEL 0.05 mg/m³ human, inhalatory worker (industry) chronic - local 2,2'-methylenediphenyl diisocyanate 2536-05-2 DNEL 0.1 mg/m³ human, inhalatory worker (industry) acute - local 2,2'-methylenediphenyl diisocyanate 2536-05-2 DNEL 0.1 mg/m³ human, inhalatory worker (industry) chronic - system fects 2,2'-methylenediphenyl diisocyanate 2536-05-2 DNEL 0.1 mg/m³ human, inhalatory worker (industry) chronic - system fects 2,2'-methylenediphenyl diisocyanate 2536-05-2 DNEL 0.1 mg/m³ human, inhalatory worker (industry) chronic - system fects 2,2'-methylenediphenyl diisocyanate 2536-05-2 DNEL 0.1 mg/m³ human, inhalatory worker (industry) chronic - system fects 2,2'-methylenediphenyl diisocyanate 2536-05-2 DNEL 0.1 mg/m³ human, inhalatory worker (industry) chronic - system fects 2,2'-methylenediphenyl diisocyanate 2536-05-2 DNEL 0.1 mg/m³ human, inhalatory worker (industry) chronic - system fects 2,2'-methylenediphenyl diisocyanate 2536-05-2 DNEL 0.1 mg/m³ human, inhalatory worker (industry) chronic - system fects 2,2'-methylenediphenyl diisocyanate 2536-05-2 DNEL 0.1 mg/m³ human, inhalatory worker (industry) chronic - system fects 2,2'-methylenediphenyl diisocyanate 2536-05-2 DNEL 100 mg/m³ human, inhalatory worker (industry) chronic - system fects 2,2'-methylenediphenyl diisocyanate 2536-05-2 DNEL 100 mg/m³ human, inhalatory worker (industry) chronic - system fects 2,2'-methylenediphenyl diisocyanate	1,2,4-trimethylbenzene	95-63-6	DNEL	100 mg/m <sup>3</sup>	human, inhalatory	worker (industry)	chronic - systemic ef- fects
1,2,4-trimethylbenzene95-63-6DNEL100 mg/m³ human, inhalatoryworker (industry)acute - local1,2,4-trimethylbenzene95-63-6DNEL16,171 mg/kg bw/dayhuman, dermalworker (industry)chronic - system fects2,2'-methylenediphenyl diisocyanate2536-05-2DNEL0.05 mg/m³ human, inhalatoryworker (industry)chronic - local worker (industry)2,2'-methylenediphenyl diisocyanate2536-05-2DNEL0.1 mg/m³ human, inhalatoryworker (industry)acute - local worker (industry)cumene98-82-8DNEL100 mg/m³ human, inhalatoryworker (industry)chronic - system	1,2,4-trimethylbenzene	95-63-6	DNEL	100 mg/m <sup>3</sup>	human, inhalatory	worker (industry)	acute - systemic ef- fects
1,2,4-trimethylbenzene95-63-6DNEL16,171 mg/kg bw/dayhuman, dermal bw/dayworker (industry)chronic - system fects2,2'-methylenediphen-yl diisocyanate2536-05-2DNEL0.05 mg/m³ human, inhalatoryworker (industry)chronic - local worker (industry)2,2'-methylenediphen-yl diisocyanate2536-05-2DNEL0.1 mg/m³ human, inhalatoryworker (industry)acute - local worker (industry)cumene98-82-8DNEL100 mg/m³ human, inhalatoryworker (industry)chronic - system	1,2,4-trimethylbenzene	95-63-6	DNEL	100 mg/m <sup>3</sup>	human, inhalatory	worker (industry)	chronic - local effects
bw/day fects  2,2'-methylenediphen-yl diisocyanate  2,2'-methylenediphen-yl diisocyanate  2,2'-methylenediphen-yl diisocyanate  2,3'-methylenediphen-yl diisocyanate  DNEL 0.1 mg/m³ human, inhalatory worker (industry) acute - local worker (industry)  cumene  98-82-8 DNEL 100 mg/m³ human, inhalatory worker (industry) chronic - systematical sys	1,2,4-trimethylbenzene	95-63-6	DNEL	100 mg/m <sup>3</sup>	human, inhalatory	worker (industry)	acute - local effects
yl diisocyanate  2,2'-methylenediphen- yl diisocyanate  DNEL 0.1 mg/m³ human, inhalatory worker (industry) acute - local  cumene 98-82-8 DNEL 100 mg/m³ human, inhalatory worker (industry) chronic - syste	1,2,4-trimethylbenzene	95-63-6	DNEL		human, dermal	worker (industry)	chronic - systemic ef- fects
yl diisocyanate  cumene 98-82-8 DNEL 100 mg/m³ human, inhalatory worker (industry) chronic - syste		2536-05-2	DNEL	0.05 mg/m <sup>3</sup>	human, inhalatory	worker (industry)	chronic - local effects
		2536-05-2	DNEL	0.1 mg/m³	human, inhalatory	worker (industry)	acute - local effects
	cumene	98-82-8	DNEL	100 mg/m <sup>3</sup>	human, inhalatory	worker (industry)	chronic - systemic ef- fects
cumene 98-82-8 DNEL 250 mg/m³ human, inhalatory worker (industry) acute - local	cumene	98-82-8	DNEL	250 mg/m <sup>3</sup>	human, inhalatory	worker (industry)	acute - local effects

Canada: en Page: 8 / 21



acc. to Hazardous Products Regulations (HPR)

## **POR PATCH WHITE**

Version number: GHS 1.0 Date of compilation: 2024-06-20

## Relevant DNELs of components

Name of substance	CAS No	Endpoint	Threshold level	Protection goal, route of exposure	Used in	Exposure time
cumene	98-82-8	DNEL	15.4 mg/kg bw/day	human, dermal	worker (industry)	chronic - systemic ef- fects

## Relevant PNECs of components

	·					
Name of substance	CAS No	Endpoint	Threshold level	Organism	Environmental com- partment	Exposure time
4,4'-methylenediphen- yl diisocyanate	101-68-8	PNEC	1 <sup>mg</sup> / <sub>l</sub>	aquatic organisms	freshwater	short-term (single in- stance)
4,4'-methylenediphen- yl diisocyanate	101-68-8	PNEC	0.1 <sup>mg</sup> / <sub>l</sub>	aquatic organisms	marine water	short-term (single in- stance)
4,4'-methylenediphen- yl diisocyanate	101-68-8	PNEC	1 <sup>mg</sup> / <sub>l</sub>	aquatic organisms	sewage treatment plant (STP)	short-term (single in- stance)
4,4'-methylenediphen- yl diisocyanate	101-68-8	PNEC	1 <sup>mg</sup> / <sub>kg</sub>	terrestrial organ- isms	soil	short-term (single in- stance)
o-(p- isocyanatobenzyl)phen yl isocyanate	5873-54-1	PNEC	1 <sup>mg</sup> / <sub>l</sub>	aquatic organisms	freshwater	short-term (single in- stance)
o-(p- isocyanatobenzyl)phen yl isocyanate	5873-54-1	PNEC	0.1 <sup>mg</sup> / <sub>l</sub>	aquatic organisms	marine water	short-term (single in- stance)
o-(p- isocyanatobenzyl)phen yl isocyanate	5873-54-1	PNEC	1 <sup>mg</sup> / <sub>l</sub>	aquatic organisms	sewage treatment plant (STP)	short-term (single in- stance)
o-(p- isocyanatobenzyl)phen yl isocyanate	5873-54-1	PNEC	1 <sup>mg</sup> / <sub>kg</sub>	terrestrial organ- isms	soil	short-term (single in- stance)
Confidential Organo- clay	68953-58-2 92704-41-1	PNEC	4.1 <sup>mg</sup> / <sub>l</sub>	aquatic organisms	freshwater	short-term (single in- stance)
Confidential Organo- clay	68953-58-2 92704-41-1	PNEC	0.41 <sup>mg</sup> / <sub>l</sub>	aquatic organisms	marine water	short-term (single in- stance)
Confidential Organo- clay	68953-58-2 92704-41-1	PNEC	1,400 <sup>mg</sup> / <sub>l</sub>	aquatic organisms	sewage treatment plant (STP)	short-term (single in- stance)
1,2,4-trimethylbenzene	95-63-6	PNEC	0.12 <sup>mg</sup> / <sub>l</sub>	aquatic organisms	freshwater	short-term (single in- stance)
1,2,4-trimethylbenzene	95-63-6	PNEC	0.12 <sup>mg</sup> / <sub>l</sub>	aquatic organisms	marine water	short-term (single in- stance)
1,2,4-trimethylbenzene	95-63-6	PNEC	2.41 <sup>mg</sup> / <sub>l</sub>	aquatic organisms	sewage treatment plant (STP)	short-term (single in- stance)
1,2,4-trimethylbenzene	95-63-6	PNEC	13.56 <sup>mg</sup> / <sub>kg</sub>	aquatic organisms	freshwater sediment	short-term (single in- stance)
1,2,4-trimethylbenzene	95-63-6	PNEC	13.56 <sup>mg</sup> / <sub>kg</sub>	aquatic organisms	marine sediment	short-term (single in- stance)

Canada: en Page: 9 / 21



acc. to Hazardous Products Regulations (HPR)

### POR PATCH WHITE

Version number: GHS 1.0 Date of compilation: 2024-06-20

#### Relevant PNECs of components

Name of substance	CAS No	Endpoint	Threshold level	Organism	Environmental compartment	Exposure time
1,2,4-trimethylbenzene	95-63-6	PNEC	2.34 <sup>mg</sup> / <sub>kg</sub>	terrestrial organ- isms	soil	short-term (single in- stance)
2,2'-methylenediphen- yl diisocyanate	2536-05-2	PNEC	1 <sup>mg</sup> / <sub>l</sub>	aquatic organisms	freshwater	short-term (single in- stance)
2,2'-methylenediphen- yl diisocyanate	2536-05-2	PNEC	0.1 <sup>mg</sup> / <sub>l</sub>	aquatic organisms	marine water	short-term (single in- stance)
2,2'-methylenediphen- yl diisocyanate	2536-05-2	PNEC	1 <sup>mg</sup> / <sub>l</sub>	aquatic organisms	sewage treatment plant (STP)	short-term (single in- stance)
2,2'-methylenediphen- yl diisocyanate	2536-05-2	PNEC	1 <sup>mg</sup> / <sub>kg</sub>	terrestrial organ- isms	soil	short-term (single in- stance)
cumene	98-82-8	PNEC	0.035 <sup>mg</sup> / <sub>l</sub>	aquatic organisms	freshwater	short-term (single in- stance)
cumene	98-82-8	PNEC	0.004 <sup>mg</sup> / <sub>l</sub>	aquatic organisms	marine water	short-term (single in- stance)
cumene	98-82-8	PNEC	200 <sup>mg</sup> / <sub>l</sub>	aquatic organisms	sewage treatment plant (STP)	short-term (single in- stance)
cumene	98-82-8	PNEC	3.22 <sup>mg</sup> / <sub>kg</sub>	aquatic organisms	freshwater sediment	short-term (single in- stance)
cumene	98-82-8	PNEC	0.322 <sup>mg</sup> / <sub>kg</sub>	aquatic organisms	marine sediment	short-term (single in- stance)
cumene	98-82-8	PNEC	0.624 <sup>mg</sup> / <sub>kg</sub>	terrestrial organ- isms	soil	short-term (single in- stance)

### 8.2 Exposure controls

Appropriate engineering controls

General ventilation.

Individual protection measures (personal protective equipment)

Eye/face protection

Wear eye/face protection.

Skin protection

- Hand protection

Wear suitable gloves. Chemical protection gloves are suitable, which are tested according to EN 374. Check leak-tightness/impermeability prior to use. In the case of wanting to use the gloves again, clean them before taking off and air them well. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

- Other protection measures

Take recovery periods for skin regeneration. Preventive skin protection (barrier creams/ointments) is recommended. Wash hands thoroughly after handling.

#### Respiratory protection

In case of inadequate ventilation wear respiratory protection.

Canada: en Page: 10 / 21



acc. to Hazardous Products Regulations (HPR)

### **POR PATCH WHITE**

Version number: GHS 1.0 Date of compilation: 2024-06-20

#### Environmental exposure controls

Use appropriate container to avoid environmental contamination. Keep away from drains, surface and ground water.

## 9 Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

Physical state	liquid
Color	not determined
Odor	characteristic
Melting point/freezing point	not determined
Boiling point or initial boiling point and boiling range	≥-20 °C at 101.3 kPa
Flammability	flammable liquid in accordance with GHS criteria
Lower and upper explosion limit	1.4 vol% - 7.6 vol%
Flash point	80 °C
Auto-ignition temperature	183 °C (auto-ignition temperature (liquids and gases))
Decomposition temperature	not relevant
pH (value)	not determined
Kinematic viscosity	not determined
Solubility(ies)	not determined

#### Partition coefficient

Partition coefficient n-octanol/water (log value)	this information is not available
---	-----------------------------------

Vapor pressure	≤240 kPa at 37.8 °C
----------------	---------------------

Density and/or relative density

Canada: en Page: 11 / 21



acc. to Hazardous Products Regulations (HPR)

#### POR PATCH WHITE

Version number: GHS 1.0 Date of compilation: 2024-06-20

Density	not determined
Relative vapour density	information on this property is not available

Particle characteristics	not relevant (liquid)
--------------------------	-----------------------

97.71

#### 9.2 VOC Content g/L

Information with regard to physical hazard classes	there is no additional information
Other safety characteristics	there is no additional information

### 10 Stability and reactivity

#### 10.1 Reactivity

Concerning incompatibility: see below "Conditions to avoid" and "Incompatible materials". The mixture contains reactive substance(s). Risk of ignition.

If heated:

Risk of ignition

#### 10.2 Chemical stability

See below "Conditions to avoid".

#### 10.3 Possibility of hazardous reactions

No known hazardous reactions.

#### 10.4 Conditions to avoid

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Hints to prevent fire or explosion

Use explosion-proof electrical/ventilating/lighting/equipment. Use only non-sparking tools. Take precautionary measures against static discharge.

#### 10.5 Incompatible materials

Oxidizers

#### 10.6 Hazardous decomposition products

Reasonably anticipated hazardous decomposition products produced as a result of use, storage, spill and heating are not known. Hazardous combustion products: see section 5.

### 11 Toxicological information

#### 11.1 Information on toxicological effects

Test data are not available for the complete mixture.

#### Classification procedure

The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

Canada: en Page: 12 / 21



acc. to Hazardous Products Regulations (HPR)

### **POR PATCH WHITE**

Version number: GHS 1.0 Date of compilation: 2024-06-20

#### Classification acc. to GHS

Acute toxicity

Shall not be classified as acutely toxic.

### Acute toxicity estimate (ATE) of components

Name of substance	CAS No	Exposure route	ATE
4,4'-methylenediphenyl diisocyanate	101-68-8	inhalation: dust/mist	0.368 <sup>mg</sup> / <sub>l</sub> /4h
o-(p-isocyanatobenzyl)phenyl isocyanate	5873-54-1	inhalation: dust/mist	0.368 <sup>mg</sup> / <sub>l</sub> /4h
Confidential Organoclay	68953-58-2 92704-41-1	inhalation: dust/mist	>2.07 <sup>mg</sup> / <sub>I</sub> /4h
1,2,4-trimethylbenzene	95-63-6	inhalation: vapour	11 <sup>mg</sup> / <sub>l</sub> /4h
2,2'-methylenediphenyl diisocyanate	2536-05-2	inhalation: dust/mist	0.368 <sup>mg</sup> / <sub>l</sub> /4h

#### Skin corrosion/irritation

Causes skin irritation.

#### Serious eye damage/eye irritation

Causes serious eye irritation.

#### Respiratory or skin sensitization

May cause allergy or asthma symptoms or breathing difficulties if inhaled. May cause an allergic skin reaction.

#### Germ cell mutagenicity

May cause genetic defects.

#### Carcinogenicity

May cause cancer.

#### Reproductive toxicity

Shall not be classified as a reproductive toxicant.

#### Specific target organ toxicity - single exposure

May cause respiratory irritation.

#### Specific target organ toxicity - repeated exposure

May cause damage to organs through prolonged or repeated exposure.

#### Aspiration hazard

May be fatal if swallowed and enters airways.

### **12 Ecological information**

#### 12.1 Toxicity

Harmful to aquatic life with long lasting effects.

Canada: en Page: 13 / 21



acc. to Hazardous Products Regulations (HPR)

## **POR PATCH WHITE**

Version number: GHS 1.0 Date of compilation: 2024-06-20

## Aquatic toxicity (acute) of components

, , , ,					
Name of substance	CAS No	Endpoint	Value	Species	Exposure time
4,4'-methylenediphenyl diisocyanate	101-68-8	LC50	>1,000 <sup>mg</sup> / <sub>l</sub>	fish	96 h
4,4'-methylenediphenyl diisocyanate	101-68-8	EC50	129.7 <sup>mg</sup> / <sub>l</sub>	aquatic invertebrates	24 h
o-(p- isocyanatobenzyl)phenyl isocyanate	5873-54-1	LC50	>1,000 <sup>mg</sup> / <sub>l</sub>	fish	96 h
o-(p- isocyanatobenzyl)phenyl isocyanate	5873-54-1	EC50	129.7 <sup>mg</sup> / <sub>l</sub>	aquatic invertebrates	24 h
Confidential Organoclay	68953-58-2 92704-41-1	LC50	>100 <sup>mg</sup> / <sub>l</sub>	fish	96 h
Confidential Organoclay	68953-58-2 92704-41-1	EC50	>100 <sup>mg</sup> / <sub>l</sub>	aquatic invertebrates	48 h
Confidential Organoclay	68953-58-2 92704-41-1	ErC50	2,500 <sup>mg</sup> / <sub>l</sub>	algae	72 h
Solvent naphtha (petro- leum), light arom.	64742-95-6	LL50	8.2 <sup>mg</sup> / <sub>l</sub>	fish	96 h
Solvent naphtha (petro- leum), light arom.	64742-95-6	EL50	4.5 <sup>mg</sup> / <sub>l</sub>	aquatic invertebrates	48 h
1,2,4-trimethylbenzene	95-63-6	LC50	7.72 <sup>mg</sup> / <sub>l</sub>	fish	96 h
1,2,4-trimethylbenzene	95-63-6	EC50	2.356 <sup>mg</sup> / <sub>l</sub>	algae	96 h
2,2'-methylenediphenyl diisocyanate	2536-05-2	LC50	>1,000 <sup>mg</sup> / <sub>l</sub>	fish	96 h
2,2'-methylenediphenyl diisocyanate	2536-05-2	EC50	129.7 <sup>mg</sup> / <sub>l</sub>	aquatic invertebrates	24 h
cumene	98-82-8	LC50	4.7 <sup>mg</sup> / <sub>l</sub>	fish	96 h
cumene	98-82-8	EC50	2.14 <sup>mg</sup> / <sub>l</sub>	aquatic invertebrates	48 h
cumene	98-82-8	ErC50	2.01 <sup>mg</sup> / <sub>l</sub>	algae	72 h

## Aquatic toxicity (chronic) of components

Name of substance	CAS No	Endpoint	Value	Species	Exposure time
4,4'-methylenediphenyl diisocyanate	101-68-8	ErC50	>1,640 <sup>mg</sup> / <sub>l</sub>	algae	3 d
4,4'-methylenediphenyl diisocyanate	101-68-8	EC50	>100 <sup>mg</sup> / <sub>l</sub>	microorganisms	3 h
o-(p- isocyanatobenzyl)phenyl isocyanate	5873-54-1	ErC50	>1,640 <sup>mg</sup> / <sub>I</sub>	algae	3 d

Canada: en Page: 14 / 21



acc. to Hazardous Products Regulations (HPR)

### **POR PATCH WHITE**

Version number: GHS 1.0 Date of compilation: 2024-06-20

### Aquatic toxicity (chronic) of components

CAS No	Endpoint	Value	Species	Exposure time
5873-54-1	EC50	>100 <sup>mg</sup> / <sub>l</sub>	microorganisms	3 h
68953-58-2 92704-41-1	EC50	2,800 <sup>mg</sup> / <sub>l</sub>	microorganisms	16 h
64742-95-6	EL50	10 <sup>mg</sup> / <sub>l</sub>	fish	21 d
64742-95-6	EC50	15.41 <sup>mg</sup> / <sub>l</sub>	microorganisms	40 h
2536-05-2	ErC50	>1,640 <sup>mg</sup> / <sub>l</sub>	algae	3 d
2536-05-2	EC50	>100 <sup>mg</sup> / <sub>l</sub>	microorganisms	3 h
98-82-8	EC50	1.5 <sup>mg</sup> / <sub>l</sub>	aquatic invertebrates	21 d
98-82-8	LC50	>3 <sup>mg</sup> / <sub>l</sub>	aquatic invertebrates	21 d
	5873-54-1  68953-58-2 92704-41-1  64742-95-6  64742-95-6  2536-05-2  2536-05-2  98-82-8	5873-54-1       EC50         68953-58-2       92704-41-1         64742-95-6       EL50         64742-95-6       EC50         2536-05-2       ErC50         98-82-8       EC50	5873-54-1       EC50       >100 mg/ <sub>I</sub> 68953-58-2 92704-41-1       EC50       2,800 mg/ <sub>I</sub> 64742-95-6       EL50       10 mg/ <sub>I</sub> 64742-95-6       EC50       15.41 mg/ <sub>I</sub> 2536-05-2       ErC50       >1,640 mg/ <sub>I</sub> 2536-05-2       EC50       >100 mg/ <sub>I</sub> 98-82-8       EC50       1.5 mg/ <sub>I</sub>	5873-54-1         EC50         >100 mg/ <sub>I</sub> microorganisms           68953-58-2 92704-41-1         EC50         2,800 mg/ <sub>I</sub> microorganisms           64742-95-6         EL50         10 mg/ <sub>I</sub> fish           64742-95-6         EC50         15.41 mg/ <sub>I</sub> microorganisms           2536-05-2         ErC50         >1,640 mg/ <sub>I</sub> algae           2536-05-2         EC50         >100 mg/ <sub>I</sub> microorganisms           98-82-8         EC50         1.5 mg/ <sub>I</sub> aquatic invertebrates

#### 12.2 Persistence and degradability

Data are not available.

#### 12.3 Bioaccumulative potential

Data are not available.

#### 12.4 Mobility in soil

Data are not available.

#### 12.5 Results of PBT and vPvB assessment

According to the results of its assessment, this substance is not a PBT or a vPvB. Does not contain a PBT-/vPvB-substance at a concentration of  $\geq 0.1\%$ .

#### 12.6 Endocrine disrupting properties

Does not contain an endocrine disruptor (ED) in a concentration of  $\geq$  0.1%.

#### 12.7 Other adverse effects

Data are not available.

### 13 Disposal considerations

#### 13.1 Waste treatment methods

Waste treatment-relevant information

Solvent reclamation/regeneration.

Sewage disposal-relevant information

Do not empty into drains. Avoid release to the environment. Refer to special instructions/safety data sheets.

Waste treatment of containers/packages

Completely emptied packages can be recycled. Handle contaminated packages in the same way as the substance itself.

Canada: en Page: 15 / 21



acc. to Hazardous Products Regulations (HPR)

#### POR PATCH WHITE

Version number: GHS 1.0 Date of compilation: 2024-06-20

#### Remarks

Please consider the relevant national or regional provisions. Waste shall be separated into the categories that can be handled separately by the local or national waste management facilities.

### 14 Transport information

**14.1 UN number** not subject to transport regulations

**14.2 UN proper shipping name** not relevant

**14.3 Transport hazard class(es)** none

**14.4 Packing group** not assigned

**14.5 Environmental hazards** non-environmentally hazardous acc. to the danger-

ous goods regulations

14.6 Special precautions for user

There is no additional information.

#### 14.7 Transport in bulk according to IMO instruments

The cargo is not intended to be carried in bulk.

#### Information for each of the UN Model Regulations

Transport information - National regulations - Additional information (UN RTDG)

Not subject to transport regulations: UN RTDG

International Maritime Dangerous Goods Code (IMDG) - Additional information

Not subject to IMDG.

International Civil Aviation Organization (ICAO-IATA/DGR) - Additional information

Not subject to ICAO-IATA.

#### 15 Regulatory information

#### 15.1 Safety, health and environmental regulations specific for the product in question

**National regulations (United States)** 

**Toxic Substance Control Act (TSCA)** all ingredients are listed (ACTIVE) or exempt from

listing

#### Superfund Amendment and Reauthorization Act (SARA TITLE III )

- The List of Extremely Hazardous Substances and Their Threshold Planning Quantities (EPCRA Section 302, 304)

none of the ingredients are listed

- Specific Toxic Chemical Listings (EPCRA Section 313)

Canada: en Page: 16 / 21



acc. to Hazardous Products Regulations (HPR)

### **POR PATCH WHITE**

Version number: GHS 1.0 Date of compilation: 2024-06-20

## Toxics Release Inventory: Specific Toxic Chemical Listings

Name of substance	CAS No	Remarks	Effective date
1,2,4-trimethylbenzene	95-63-6		1986-12-31
cumene	98-82-8		1986-12-31
4,4'-methylenediphenyl diisocyanate	101-68-8		1986-12-31

### Comprehensive Environmental Response, Compensation, and Liability Act (CERCLA)

- List of Hazardous Substances and Reportable Quantities (CERCLA section 102a) (40 CFR 302.4)

Name of substance	CAS No	Remarks	Statutory code	Final RQ pounds (Kg)
cumene	98-82-8		3 4	5000 (2270)
4,4'-methylenediphenyl diisocyanate	101-68-8		3	5000 (2270)

#### Legend

"3" indicates that the source is section 112 of the Clean Air Act

#### **Clean Air Act**

none of the ingredients are listed

#### **Right to Know Hazardous Substance List**

- Cleaning Product Right to Know Act Substance List (CA-RTK)

Name of substance	CAS No	Functionality	Authoritative Lists
4,4'-methylenediphenyl diisocyanate	101-68-8		CA TACs EC Annex VI Resp. Sens Cat. 1 Hazard Traits identified by DTSC IRIS Neurotoxicants OEHHA RELs
o-(p-isocyanatobenzyl)phenyl isocyanate	5873-54-1		EC Annex VI Resp. Sens Cat. 1
Titanium dioxide (excluding nanoparticle)	13463-67-7		IARC Carcinogens - 2B Prop 65
Solvent naphtha (petroleum), light arom.	64742-95-6		EC Annex VI CMRs - Cat. 1B
1,2,4-trimethylbenzene	95-63-6		CA NLs IRIS Neurotoxicants OEHHA RELs
2,2'-methylenediphenyl diisocyanate	2536-05-2		EC Annex VI Resp. Sens Cat. 1
cumene	98-82-8		CA NLs CA TACs IARC Carcinogens - 2B NTP 13th RoC - reasonable OEHHA RELs Prop 65

Canada: en Page: 17 / 21

<sup>4 &</sup>quot;4" indicates that the source is section 3001 of the Resource Conservation and Recovery Act (RCRA)



acc. to Hazardous Products Regulations (HPR)

### **POR PATCH WHITE**

Version number: GHS 1.0 Date of compilation: 2024-06-20

#### - Toxic or Hazardous Substance List (MA-TURA)

Name of substance	CAS No	DEP CODE	PBT / HHS / LHS	PBT / HHS Threshold	
2,2'-methylenediphenyl diisocyanate		1050			1.0 %
o-(p-isocyanatobenzyl)phenyl isocyanate		1050			1.0 %
1,2,4-trimethylbenzene	95-63-6				1.0 %
cumene	98-82-8				0.1 %

#### - Hazardous Substances List (MN-ERTK)

Name of substance	CAS No	References	Remarks
Titanium dioxide (excluding nanoparticle)	13463-67-7	А	
o-(p-isocyanatobenzyl)phenyl isocyanate		N	
1,2,4-trimethylbenzene	25551-13-7	А	
4,4'-methylenediphenyl diisocyanate	101-68-8	A, N, O	
4,4'-methylenediphenyl diisocyanate		N	

#### Legend

American Conference of Governmental Industrial Hygienists (ACGIH), "Threshold Limit Values for Chemical Substances and Physical Agents and Biological Exposure Indices for 1992-93", available from ACGIH

National Institute for Occupational Safety and Health (NIOSH), "Recommendations for Occupational Safety and Health Standards,"

N National Institute for Occupational Safety and Health (NIOSH), "Recommendations for Occupational Safety and Health Standards," August 1988, available from NIOSH, Publications Dissemination Office, Division of Standards Development and Technology Transfer

O Occupational Safety and Health Administration (OSHA), Safety and Health Standards, Code of Federal Regulations, title 29, part 1910, subpart Z, "Toxic and Hazardous Substances, 1990." General information: Minnesota Department of Labor and Industry, Occupational Safety and Health Division

#### - Hazardous Substance List (NJ-RTK)

Name of substance	CAS No	Remarks	Classifications
Titanium dioxide (excluding nanoparticle)	13463-67-7		
2,2'-methylenediphenyl diisocyanate			
o-(p-isocyanatobenzyl)phenyl isocyanate			
1,2,4-trimethylbenzene	95-63-6		F2
cumene	98-82-8		F3 R1
4,4'-methylenediphenyl diisocyanate	101-68-8		R1
4,4'-methylenediphenyl diisocyanate			

#### Legend

F2 Flammable - Second Degree F3 Flammable - Third Degree R1 Reactive - First Degree

Canada: en Page: 18 / 21



acc. to Hazardous Products Regulations (HPR)

### **POR PATCH WHITE**

Version number: GHS 1.0 Date of compilation: 2024-06-20

### - Hazardous Substance List (Chapter 323) (PA-RTK)

Name acc. to inventory	CAS No	Classification
TITANIUM OXIDE (TIO2)	13463-67-7	
BENZENE, 1,1'-METHYLENEBIS[4-ISOCYANATO-	101-68-8	E
BENZENE, 1,1'-METHYLENEBIS[4-ISOCYANATO-	101-68-8	E
PSEUDOCUMENE	95-63-6	E
BENZENE, (1-METHYLETHYL)-	98-82-8	E
BENZENE, 1,1'-METHYLENEBIS[4-ISOCYANATO-	101-68-8	E

Legend

E Environmental hazard

#### - Hazardous Substance List (RI-RTK)

Name of substance	CAS No	References
Titanium dioxide (excluding nanoparticle)	13463-67-7	Т
2,2'-methylenediphenyl diisocyanate	101-68-8	Т
2,2'-methylenediphenyl diisocyanate	101-68-8	Т
2,2'-methylenediphenyl diisocyanate	101-68-8	Т
o-(p-isocyanatobenzyl)phenyl isocyanate	101-68-8	Т
o-(p-isocyanatobenzyl)phenyl isocyanate	101-68-8	Т
o-(p-isocyanatobenzyl)phenyl isocyanate	101-68-8	Т
1,2,4-trimethylbenzene	25551-13-7	Т
cumene	98-82-8	T, F
4,4'-methylenediphenyl diisocyanate	101-68-8	Т
4,4'-methylenediphenyl diisocyanate	101-68-8	Т
4,4'-methylenediphenyl diisocyanate	101-68-8	Т

Legend

F Flammability (NFPA®)
T Toxicity (ACGIH®)

# California Environmental Protection Agency (Cal/EPA): Proposition 65 - Safe Drinking Water and Toxic Enforcement Act of 1987

Proposition 65 List of chemicals			
Name acc. to inventory	CAS No	Remarks	Type of the toxicity
titanium dioxide	13463-67-7	airborne, unbound particles of respirable size	cancer
cumene	98-82-8		cancer

Canada: en Page: 19 / 21



acc. to Hazardous Products Regulations (HPR)

### **POR PATCH WHITE**

Version number: GHS 1.0 Date of compilation: 2024-06-20

### Industry or sector specific available guidance(s)

#### **NPCA-HMIS® III**

Hazardous Materials Identification System. American Coatings Association.

Category	Rating	Description
Chronic	*	chronic (long-term) health effects may result from repeated overexposure
Health	2	temporary or minor injury may occur
Flammability	2	material that must be moderately heated or exposed to relatively high ambient temper- atures before ignition can occur
Physical hazard	0	material that is normally stable, even under fire conditions, and will not react with water, polymerize, decompose, condense, or self-react. Non-explosive
Personal protection	-	

#### **NFPA® 704**

National Fire Protection Association: Standard System for the Identification of the Hazards of Materials for Emergency Response (United States).

Category	Degree of hazard	Description
Flammability	2	material that must be moderately heated or exposed to relatively high ambient temper- atures before ignition can occur
Health	2	material that, under emergency conditions, can cause temporary incapacitation or residual injury
Instability	0	material that is normally stable, even under fire conditions
Special hazard		

#### **National regulations (Canada)**

#### Domestic Substances List (DSL)/Non-domestic Substances List (NDSL)

All ingredients are listed or exempt from listing.

#### **National inventories**

Country	Inventory	Status
US	TSCA	all ingredients are listed (ACTIVE)

Legend

TSCA Toxic Substance Control Act

#### 15.2 Chemical Safety Assessment

Chemical safety assessments for substances in this mixture were not carried out.

Canada: en Page: 20 / 21



acc. to Hazardous Products Regulations (HPR)

#### POR PATCH WHITE

Version number: GHS 1.0 Date of compilation: 2024-06-20

## 16 Other information

#### Key literature references and sources for data

Hazardous Products Regulations (HPR)

SOR/2022-272: Regulations Amending the Hazardous Products Regulations (GHS, Seventh Revised Edition)

UN Recommendations on the Transport of Dangerous Good. International Maritime Dangerous Goods Code (IMDG). Dangerous Goods Regulations (DGR) for the air transport (IATA).

#### **Classification procedure**

Physical and chemical properties: The classification is based on tested mixture. Health hazards, Environmental hazards: The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

#### Disclaimer

This information is based upon the present state of our knowledge. This SDS has been compiled and is solely intended for this product.

Canada: en Page: 21 / 21