

Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 10.30.2017

Page 1 of 12

Rubberized Under Coating - Aerosol

SECTION 1: Identification

Product identifier

Product name: Rubberized Under Coating - Aerosol

Product code: 49308



Recommended use of the product and restriction on use

Relevant identified uses: Underbody coating

Uses advised against: Not determined or not applicable.

Reasons why uses advised against: Not determined or not applicable.

Manufacturer or supplier details

Manufacturer:

United States

P.O.R. Products

38 Portman Road

New Rochelle, NY 10801

914-636-0700

Emergency telephone number:

United States

ChemTel Inc.

+1 800 255 3924

+1 813 248 0585

SECTION 2: Hazard(s) identification

GHS classification:

Flammable aerosols, category 1

Compressed gases

Skin irritation, category 2

Eye irritation, category 2A


Reproductive toxicity, category 2

Specific target organ toxicity - single exposure, category 3, central nervous system

Specific target organ toxicity - repeated exposure, category 2

Label elements

Hazard pictograms:



Signal word: Danger

Hazard statements:

H222 Extremely flammable aerosol

H280 Contains gas under pressure; may explode if heated

H229 Pressurized container: may burst if heated.

H315 Causes skin irritation

H319 Causes serious eye irritation

H361 Suspected of damaging fertility or the unborn child

H336 May cause drowsiness or dizziness

Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 10.30.2017

Page 2 of 12

Rubberized Under Coating - Aerosol

H373 May cause damage to organs through prolonged or repeated exposure
H315+H320 Causes skin and eye irritation.

Precautionary statements:

P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking
P211 Do not spray on an open flame or other ignition source
P251 Pressurized container. Do not pierce or burn, even after use
P264 Wash skin thoroughly after handling
P280 Wear protective gloves/protective clothing/eye protection/face protection
P201 Obtain special instructions before use
P202 Do not handle until all safety precautions have been read and understood
P271 Use only outdoors or in a well-ventilated area
P260 Do not breathe dust/fume/gas/mist/vapors/spray
P281 Use personal protective equipment as required.
P261 Avoid breathing dust/fume/gas/mist/vapors/spray.
P321 Specific treatment (see supplemental first aid instructions on this label).
P362 Take off contaminated clothing and wash before reuse
P302+P352 If on skin: Wash with soap and water
P332+P313 If skin irritation occurs: Get medical advice/attention
P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do. Continue rinsing
P308+P313 If exposed or concerned: Get medical advice/attention
P304+P340+P312 If inhaled: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a poison center or doctor/physician if you feel unwell
P362+P364 Take off contaminated clothing and wash it before reuse.
P337+P313 If eye irritation persists get medical advice/attention
P312 Call a POISON CENTER or doctor/physician if you feel unwell.
P304+P340 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
P314 Get medical advice/attention if you feel unwell
P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F
P410+P403 Protect from sunlight. Store in a well ventilated place
P405 Store locked up
P403+P233 Store in a well ventilated place. Keep container tightly closed
P501 Dispose of contents and container as instructed in Section 13

Hazards not otherwise classified: None

SECTION 3: Composition/information on ingredients

Identification	Name	Weight %
CAS number: 108-88-3	Toluene	10-30
CAS number: 67-64-1	Acetone	5-10
CAS number: 74-98-6	Propane	10-30
CAS number: 540-88-5	T-Butyl Acetate	10-30
CAS number: 79-20-9	Methyl acetate	10-30

Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 10.30.2017

Page 3 of 12

Rubberized Under Coating - Aerosol

Additional Information: None

SECTION 4: First aid measures

Description of first aid measures

General notes:

Not determined or not applicable.

After inhalation:

Loosen clothing as necessary and position individual in a comfortable position

Maintain an unobstructed airway

Get medical advice/attention if you feel unwell

After skin contact:

Rinse affected area with soap and water

If symptoms develop or persist, seek medical attention

Take off all contaminated clothing

Gently blot or brush away excess product

Wash with plenty of lukewarm, gently flowing water

Get medical advice if skin irritation occurs or you feel unwell

After eye contact:

Rinse/flush exposed eye(s) gently using water for 15-20 minutes

If symptoms develop or persist, seek medical attention

Rinse eyes cautiously with lukewarm, gently flowing water for several minutes, while holding the eyelids open

Remove contact lenses, if present and easy to do so

Continue rinsing for 15-20 minutes

Get medical advice if eye irritation persists

After swallowing:

Rinse mouth thoroughly

Seek medical attention if irritation, discomfort, or vomiting persists

Most important symptoms and effects, both acute and delayed

Acute symptoms and effects:

Not determined or not applicable.

Delayed symptoms and effects:

Not determined or not applicable.

Immediate medical attention and special treatment

Specific treatment:

Not determined or not applicable.

Notes for the doctor:

Not determined or not applicable.

SECTION 5: Firefighting measures

Extinguishing media

Suitable extinguishing media:

Use Water (fog only), dry chemical, chemical foam, carbon dioxide, or alcohol-resistant foam

Unsuitable extinguishing media:

Not determined or not applicable.

Specific hazards during fire-fighting:

Thermal decomposition can lead to release of irritating gases and vapors

Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 10.30.2017

Page 4 of 12

Rubberized Under Coating - Aerosol

Contents under pressure

In a fire or if heated, a pressure increase will occur and the container may burst or explode

Vapors can flow to distant ignition sources and flashback

Liquid is volatile and may generate an explosive atmosphere

Special protective equipment for firefighters:

Use typical firefighting equipment, self-contained breathing apparatus, special tightly sealed suit

Special precautions:

Shut off sources of ignition

Carbon monoxide and carbon dioxide may form upon combustion

Heating causes a rise in pressure, risk of bursting and combustion

SECTION 6: Accidental release measures

Personal precautions, protective equipment and emergency procedures:

Ensure adequate ventilation

Ensure air handling systems are operational

Wear protective eye wear, gloves and clothing

Beware of vapors accumulating to form explosive concentrations

Vapors can accumulate in low areas

Environmental precautions:

Should not be released into the environment

Prevent from reaching drains, sewer or waterway

Methods and material for containment and cleaning up:

Wear protective eye wear, gloves and clothing

Use spark-proof tools and equipment

Absorb with non-combustible liquid-binding material (sand, diatomaceous earth (clay), acid binders, universal binders)

Dispose of contents / container in accordance with local regulations

Reference to other sections:

Not determined or not applicable.

SECTION 7: Handling and storage

Precautions for safe handling:

Use only with adequate ventilation.

Avoid breathing mist or vapor.

Do not eat, drink, smoke or use personal products when handling chemical substances.

Do not puncture, crush, or incinerate containers, even when empty.

Protect cylinders from physical damage.

Conditions for safe storage, including any incompatibilities:

Protect from freezing and physical damage.

Protect from direct sunlight.

Store in a cool, well-ventilated area.

Store cylinders upright.

Store away from all ignition sources (open flames, hot surfaces, direct sunlight, spark sources).

SECTION 8: Exposure controls/personal protection

Only those substances with limit values have been included below.

Occupational Exposure limit values:

Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 10.30.2017

Page 5 of 12

Rubberized Under Coating - Aerosol

Country (Legal Basis)	Substance	Identifier	Permissible concentration
ACGIH	Propane	74-98-6	ACGIH TLV TWA 2,500 ppm
	Methyl acetate	79-20-9	STEL 15-min: 250 ppm
	Methyl acetate	79-20-9	TLV TWA 8-hr: 200 ppm
	T-Butyl Acetate	540-88-5	TLV TWA 8-hr: 50 ppm; STEL 15-min: 150 ppm
	Acetone	67-64-1	8-hour Exposure Limit (TLV-TWA): 250 ppm
	Acetone	67-64-1	15-minute STEL: 500 ppm
	Toluene	108-88-3	ACGIH TWA: 20 ppm
United States (OSHA)	Propane	74-98-6	OSHA PEL TWA 1,000 ppm (1,800 mg/m ³)
	Methyl acetate	79-20-9	PEL TWA: 610 mg/m ³ (200 ppm)
	T-Butyl Acetate	540-88-5	PEL: 950 mg/m ³ (200 ppm)
	Acetone	67-64-1	TWA: 750 ppm (1800 mg/m ³)
	Acetone	67-64-1	STEL: 1000 ppm (2400 mg/m ³)
	Toluene	108-88-3	OSHA PEL 300 ppm Ceiling
	Toluene	108-88-3	OSHA PEL TWA 200 ppm
	Toluene	108-88-3	OSHA PEL 500 ppm Peak (10 mins)
NIOSH	Propane	74-98-6	NIOSH REL TWA 1,000 ppm (1,800 mg/m ³)
	Methyl acetate	79-20-9	REL: 610 mg/m ³ (200 ppm)
	Methyl acetate	79-20-9	STEL: 760 mg/m ³ (250 ppm)
	T-Butyl Acetate	540-88-5	REL: 950 mg/m ³ (200 ppm)
	Acetone	67-64-1	REL (for up to a 10-hour workday during a 40-hour workweek): 250 ppm (590 mg/m ³)
	Acetone	67-64-1	IDLH: 2500 ppm
	Toluene	108-88-3	NIOSH TWA 375.0 mg/m ³ ; 100 ppm
	Toluene	108-88-3	NIOSH STEL 560 mg/m ³ ; 150 ppm
Australia	Toluene	108-88-3	TWA: 191 mg/m ³ (50 ppm) ; STEL: 574 mg/m ³ (150 ppm)
	T-Butyl Acetate	540-88-5	TWA: 950 mg/m ³ (200 ppm)
	Methyl acetate	79-20-9	TWA 8-hr: 606 mg/m ³ (200 ppm); STEL 15-min: 757 mg/m ³ (250 ppm)
	Acetone	67-64-1	TWA: 1185 mg/m ³ (500 ppm) ; STEL: 2375 mg/m ³ (1000 ppm)

Biological limit values:

No biological exposure limits noted for the ingredient(s).

Information on monitoring procedures:

Monitoring of the concentration of substances in the breathing zone of workers or in the general workplace may be required to confirm compliance with an OEL and adequacy of exposure controls.

Biological monitoring may also be appropriate for some substances.

Appropriate engineering controls:

Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 10.30.2017

Page 6 of 12

Rubberized Under Coating - Aerosol

Emergency eye wash fountains and safety showers should be available in the immediate vicinity of use or handling.

Provide exhaust ventilation or other engineering controls to keep the airborne concentrations of vapor and mists below the applicable workplace exposure limits (Occupational Exposure Limits-OELs) indicated above. Use explosion-proof ventilation equipment.

Personal protection equipment

Eye and face protection:

Safety goggles or glasses, or appropriate eye protection.

Skin and body protection:

Select glove material impermeable and resistant to the substance.

Wear appropriate clothing to prevent any possibility of skin contact.

Respiratory protection:

If engineering controls do not maintain airborne concentrations below recommended exposure limits (where applicable) or to an acceptable level (in countries where exposure limits have not been established), an approved respirator must be worn.

General hygienic measures:

Avoid contact with skin, eyes and clothing.

Wash hands before breaks and at the end of work.

Wash contaminated clothing before reuse.

SECTION 9: Physical and chemical properties

Information on basic physical and chemical properties

Appearance	Black Pressurized Product
Odor	Paint-like
Odor threshold	Not determined or not available.
pH	Not determined or not available.
Melting point/freezing point	Not determined or not available.
Initial boiling point/range	> 57.00 °C
Flash point (closed cup)	> -20.00 °C (Liquid); -104.40 °C (Propellant)
Evaporation rate	Not determined or not available.
Flammability (solid, gas)	Extremely Flammable Aerosol
Upper flammability/explosive limit	16.0 Vol %
Lower flammability/explosive limit	1.5 Vol %
Vapor pressure	Not determined or not available.
Vapor density	Not determined or not available.
Density	0.793 g/cm ³
Relative density	Not determined or not available.
Solubilities	Not determined or not available.
Partition coefficient (n-octanol/water)	Not determined or not available.
Auto/Self-ignition temperature	354.00 °C
Decomposition temperature	Not determined or not available.
Dynamic viscosity	Not determined or not available.
Kinematic viscosity	Not determined or not available.
Explosive properties	Not determined or not available.
Oxidizing properties	Not determined or not available.

Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 10.30.2017

Page 7 of 12

Rubberized Under Coating - Aerosol

Other information

Percent Volatile	83.20 % wt
Percent VOC	42.15 % wt
Percent HAP	17.18 % wt
Global Warming Potential	1.16 GWP
Ozone Depletion Potential	0.00 ODP
VOC Regulatory/Actual	632.41 g/L (5.28 lbs/gal) / 334.24 g/L (2.79 lbs/gal)
HAP Content	136.24 g/L (1.14 lbs/gal)
Maximum Incremental Reactivity	0.9450 g O ₃ /g

SECTION 10: Stability and reactivity

Reactivity:

Does not react under normal conditions of use and storage.

Chemical stability:

Stable under normal conditions of use and storage.

Possibility of hazardous reactions:

None under normal conditions of use and storage.

Conditions to avoid:

Electrostatic Discharge, Other Ignition Sources, Heat, Flames, Sparks.

Incompatible materials:

Strong Oxidizing Agents, Strong Acids, Potassium t-Butoxide.

Hazardous decomposition products:

Methanol, Acetic Acid.

SECTION 11: Toxicological information

Acute toxicity

Assessment: Based on available data, the classification criteria are not met.

Product data: No data available.

Substance data: No data available.

Skin corrosion/irritation

Assessment: Causes skin irritation

Product data:

No data available.

Substance data:

Name	Result
Toluene	Irritating to the skin.

Serious eye damage/irritation

Assessment: Causes serious eye irritation

Product data:

No data available.

Substance data:

Name	Result
Methyl acetate	Irritating to the eyes.
Acetone	Causes serious eye irritation.

Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 10.30.2017

Page 8 of 12

Rubberized Under Coating - Aerosol

Respiratory or skin sensitization

Assessment: Based on available data, the classification criteria are not met.

Product data:

No data available.

Substance data: No data available.

Carcinogenicity

Assessment: Based on available data, the classification criteria are not met.

Product data: No data available.

Substance data: No data available.

International Agency for Research on Cancer (IARC):

Name	Classification
Toluene	Group 3 - Not classifiable as to its carcinogenicity to humans

National Toxicology Program (NTP): None of the ingredients are listed.

Germ cell mutagenicity

Assessment: Based on available data, the classification criteria are not met.

Product data:

No data available.

Substance data: No data available.

Reproductive toxicity

Assessment: Suspected of damaging fertility or the unborn child

Product data:

No data available.

Substance data:

Name	Result
Toluene	Suspected of damaging fertility or the unborn child.

Specific target organ toxicity (single exposure)

Assessment: May cause drowsiness or dizziness

Product data:

No data available.

Substance data:

Name	Result
Toluene	Component affects the central nervous system.
Methyl acetate	May cause drowsiness or dizziness through single exposure.
Acetone	Specific Target Organ Toxicity, Single Exposure - May cause drowsiness or dizziness.

Specific target organ toxicity (repeated exposure)

Assessment: May cause damage to organs through prolonged or repeated exposure

Product data:

No data available.

Substance data: No data available.

Aspiration toxicity

Assessment: Based on available data, the classification criteria are not met.

Product data:

No data available.

Substance data: No data available.

Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 10.30.2017

Page 9 of 12

Rubberized Under Coating - Aerosol

Information on likely routes of exposure:

No data available.

Symptoms related to the physical, chemical and toxicological characteristics:

No data available.

Other information:

No data available.

SECTION 12: Ecological information

Acute (short-term) toxicity

Assessment: Based on available data, the classification criteria are not met.

Product data: No data available.

Substance data: No data available.

Chronic (long-term) toxicity

Product data: No data available.

Substance data: No data available.

Persistence and degradability

Product data: No data available.

Substance data: No data available.

Bioaccumulative potential

Product data: No data available.

Substance data: No data available.

Mobility in soil

Product data: No data available.

Substance data: No data available.

Other adverse effects: No data available.


SECTION 13: Disposal considerations

Disposal methods:

It is the responsibility of the waste generator to properly characterize all waste materials according to applicable regulatory entities

SECTION 14: Transport information

United States Transportation of dangerous goods (49 CFR DOT)

UN number	1950
UN proper shipping name	Aerosols, flammable, Limited Quantity
UN transport hazard class(es)	2.1 
Packing group	None
Environmental hazards	None
Special precautions for user	None
Passenger air/rail	75 kg
Cargo aircraft only	150 kg

International Maritime Dangerous Goods (IMDG)

UN number	1950
------------------	------


Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200


Initial preparation date: 10.30.2017

Page 10 of 12

Rubberized Under Coating - Aerosol

UN proper shipping name	Aerosols, Limited Quantity	
UN transport hazard class(es)	2.1	
Packing group	None	
Environmental hazards	None	
Special precautions for user	None	
EmS number	F-D, S-U	
Stowage category	For AEROSOLS with a maximum capacity of 1 litre: Category A. Segregation as for class 9 but "Separated from" class 1 except division 1.4. For AEROSOLS with a capacity above 1 litre: Category B. Segregation as for the appropriate sub-division of class 2. For WASTE AEROSOLS: Category C. Clear of living quarters. Segregation as for the appropriate sub-division of class 2.	
Excepted quantities	E0	

International Air Transport Association Dangerous Goods Regulations (IATA-DGR)

UN number	1950	
UN proper shipping name	Aerosols, flammable, Limited Quantity	
UN transport hazard class(es)	2.1	
Packing group	None	
Environmental hazards	None	
Special precautions for user	None	
ERG code	10L	
Excepted quantities	E0	
Passenger and cargo	75 kg	
Cargo aircraft only	150 kg	
Limited quantity	30 kg G	

SECTION 15: Regulatory information

United States regulations

Inventory listing (TSCA):

540-88-5	T-Butyl Acetate	Listed
74-98-6	Propane	Listed
108-88-3	Toluene	Listed
79-20-9	Methyl acetate	Listed
67-64-1	Acetone	Listed

Significant New Use Rule (TSCA Section 5): Not determined.

Export notification under TSCA Section 12(b): Not determined.

SARA Section 302 extremely hazardous substances: Not determined.

SARA Section 313 toxic chemicals:

108-88-3	Toluene	Listed
67-64-1	Acetone	Listed

Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 10.30.2017

Page 11 of 12

Rubberized Under Coating - Aerosol

CERCLA:

540-88-5	T-Butyl Acetate	Listed	5,000 lb
108-88-3	Toluene	Listed	1000 lb
67-64-1	Acetone	Listed	5,000

RCRA:

108-88-3	Toluene	Listed	U220
67-64-1	Acetone	Listed	U002

Section 112(r) of the Clean Air Act (CAA):

74-98-6	Propane	Listed
---------	---------	--------

Massachusetts Right to Know:

540-88-5	T-Butyl Acetate	Listed
74-98-6	Propane	Listed
108-88-3	Toluene	Listed
79-20-9	Methyl acetate	Listed
67-64-1	Acetone	Listed

New Jersey Right to Know:

540-88-5	T-Butyl Acetate	Not Listed
74-98-6	Propane	Listed
108-88-3	Toluene	Listed
79-20-9	Methyl acetate	Not Listed
67-64-1	Acetone	Listed

New York Right to Know:

540-88-5	T-Butyl Acetate	Listed
74-98-6	Propane	Listed
108-88-3	Toluene	Listed
79-20-9	Methyl acetate	Listed
67-64-1	Acetone	Listed

Pennsylvania Right to Know:

540-88-5	T-Butyl Acetate	Listed
74-98-6	Propane	Listed
108-88-3	Toluene	Listed
79-20-9	Methyl acetate	Listed
67-64-1	Acetone	Listed

California Proposition 65:

⚠ WARNING: This product can expose you to Toluene, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

SECTION 16: Other information

Abbreviations and Acronyms: None

Disclaimer:

This product has been classified in accordance with OSHA HCS 2012 guidelines. The information provided in this SDS is correct, to the best of our knowledge, based on information available. The information given is designed only as a guidance for safe handling, use, storage, transportation and disposal and is not to be

Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 10.30.2017

Page 12 of 12

Rubberized Under Coating - Aerosol

considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials, unless specified in the text. The responsibility to provide a safe workplace remains with the user.

NFPA: 2-4-3

HMIS: 2-4-3

Initial preparation date: 10.30.2017

End of Safety Data Sheet