

## POR-15 TOPCOAT SAFET RED AEROSOL

Version number: GHS 3.0  
Replaces version of: 2023-07-03 (GHS 2)

Revision: 2024-02-15

### 1 Identification

#### 1.1 Product identifier

Trade name **POR-15 TOPCOAT SAFET RED AEROSOL**  
Product code(s) 46118

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses Paint

#### 1.3 Details of the supplier of the safety data sheet

P.O.R. Products  
38 Portman Road  
New Rochelle NY 10801  
United States

Telephone: +1 914-636-0700  
e-mail: support@porproducts.com  
Website: www.porproducts.com

e-mail (competent person) support@porproducts.com

#### 1.4 Emergency telephone number

Emergency information service 1-800-255-3924  
ChemTel Inc.

### 2 Hazard identification

#### 2.1 Classification of the substance or mixture

Classification acc. to GHS

Section	Hazard class	Category	Hazard class and category	Hazard statement
2.3	aerosols	1	Aerosol 1	H222,H229
3.3	serious eye damage/eye irritation	2	Eye Irrit. 2	H319
3.5	germ cell mutagenicity	1B	Muta. 1B	H340
3.6	carcinogenicity	1A	Carc. 1A	H350
3.8D	specific target organ toxicity - single exposure (narcotic effects, drowsiness)	3	STOT SE 3	H336

For full text of abbreviations: see SECTION 16.

#### 2.2 Label elements

Labeling

- Signal word danger

- Pictograms

GHS02, GHS07, GHS08



## POR-15 TOPCOAT SAFET RED AEROSOL

Version number: GHS 3.0  
Replaces version of: 2023-07-03 (GHS 2)

Revision: 2024-02-15

### - Hazard statements

H222	Extremely flammable aerosol.
H229	Pressurized container: may burst if heated.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.
H340	May cause genetic defects.
H350	May cause cancer.

### - Precautionary statements

P201	Obtain special instructions before use.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211	Do not spray on an open flame or other ignition source.
P251	Do not pierce or burn, even after use.
P261	Avoid breathing dust/fume/gas/mist/vapours/spray.
P271	Use only outdoors or in a well-ventilated area.
P280	Wear eye protection/face protection.
P304+P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P312	Call a POISON CENTER/doctor if you feel unwell.
P403+P233	Store in a well-ventilated place. Keep container tightly closed.
P405	Store locked up.
P410+P412	Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.
P501	Dispose of contents/container to industrial combustion plant.

- Hazardous ingredients for labelling n-butane, acetone, propane, n-butyl acetate

### 2.3 Other hazards

#### Results of PBT and vPvB assessment

Does not contain a PBT-/vPvB-substance at a concentration of  $\geq 0.1\%$ .

#### Endocrine disrupting properties

Does not contain an endocrine disruptor (ED) in a concentration of  $\geq 0.1\%$ .

## 3 Composition/ Information on ingredients

### 3.1 Substances

Not relevant (mixture)

### 3.2 Mixtures

#### Description of the mixture

Name of substance	Identifier	Wt%	Classification acc. to GHS
acetone	CAS No 67-64-1	10 – < 30	Flam. Liq. 2 / H225 Eye Irrit. 2 / H319 STOT SE 3 / H336
propane	CAS No 78-93-3	10 – < 30	Flam. Liq. 2 / H225 Eye Irrit. 2 / H319 STOT SE 3 / H336

## POR-15 TOPCOAT SAFET RED AEROSOL

Version number: GHS 3.0  
Replaces version of: 2023-07-03 (GHS 2)

Revision: 2024-02-15

Name of substance	Identifier	Wt%	Classification acc. to GHS
n-butane	CAS No 106-97-8	10 - < 30	Flam. Gas 1 / H220 Press. Gas C / H280 Muta. 1B / H340 Carc. 1A / H350
glycol ether EP	CAS No 2807-30-9	5 - < 10	Flam. Liq. 3 / H226 Acute Tox. 4 / H312 Eye Irrit. 2 / H319
n-butyl acetate	CAS No 123-86-4	1 - < 5	Flam. Liq. 3 / H226 STOT SE 3 / H336
PM acetate	CAS No 108-65-6	1 - < 5	Flam. Liq. 3 / H226 STOT SE 3 / H336
METHYL PROPYL KETONE	CAS No 107-87-9	1 - < 5	Flam. Liq. 2 / H225 Acute Tox. 4 / H302 Eye Irrit. 2 / H319

### Remarks

For full text of abbreviations: see SECTION 16

## 4 First-aid measures

### 4.1 Description of first-aid measures

#### General notes

Do not leave affected person unattended. Remove victim out of the danger area. Keep affected person warm, still and covered. Take off immediately all contaminated clothing. In all cases of doubt, or when symptoms persist, seek medical advice. In case of unconsciousness place person in the recovery position. Never give anything by mouth.

#### Following inhalation

If breathing is irregular or stopped, immediately seek medical assistance and start first aid actions. Provide fresh air.

#### Following skin contact

Wash with plenty of soap and water.

#### Following eye contact

Remove contact lenses, if present and easy to do. Continue rinsing. Irrigate copiously with clean, fresh water for at least 10 minutes, holding the eyelids apart.

#### Following ingestion

Rinse mouth with water (only if the person is conscious). Do NOT induce vomiting.

### 4.2 Most important symptoms and effects, both acute and delayed

Narcotic effects.

### 4.3 Indication of any immediate medical attention and special treatment needed

none

## POR-15 TOPCOAT SAFET RED AEROSOL

Version number: GHS 3.0  
Replaces version of: 2023-07-03 (GHS 2)

Revision: 2024-02-15

### 5 Fire-fighting measures

#### 5.1 Extinguishing media

Suitable extinguishing media

Water spray, BC-powder

Unsuitable extinguishing media

Water jet

#### 5.2 Special hazards arising from the substance or mixture

Hazardous combustion products

Carbon monoxide (CO), Carbon dioxide (CO<sub>2</sub>)

#### 5.3 Advice for firefighters

In case of fire and/or explosion do not breathe fumes. Coordinate firefighting measures to the fire surroundings. Do not allow firefighting water to enter drains or water courses. Collect contaminated firefighting water separately. Fight fire with normal precautions from a reasonable distance.

### 6 Accidental release measures

#### 6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

Remove persons to safety.

For emergency responders

Wear breathing apparatus if exposed to vapors/dust/aerosols/gases.

#### 6.2 Environmental precautions

Keep away from drains, surface and ground water. Retain contaminated washing water and dispose of it.

#### 6.3 Methods and material for containment and cleaning up

Advice on how to contain a spill

Covering of drains

Other information relating to spills and releases

Place in appropriate containers for disposal. Ventilate affected area.

#### 6.4 Reference to other sections

Hazardous combustion products: see section 5. Personal protective equipment: see section 8. Incompatible materials: see section 10. Disposal considerations: see section 13.

### 7 Handling and storage

#### 7.1 Precautions for safe handling

Recommendations

- Measures to prevent fire as well as aerosol and dust generation

Use local and general ventilation. Use only in well-ventilated areas.

## POR-15 TOPCOAT SAFET RED AEROSOL

Version number: GHS 3.0  
Replaces version of: 2023-07-03 (GHS 2)

Revision: 2024-02-15

### Advice on general occupational hygiene

Wash hands after use. Do not eat, drink and smoke in work areas. Remove contaminated clothing and protective equipment before entering eating areas. Never keep food or drink in the vicinity of chemicals. Never place chemicals in containers that are normally used for food or drink. Keep away from food, drink and animal feedingstuffs.

### 7.2 Conditions for safe storage, including any incompatibilities

Managing of associated risks

#### - Flammability hazards

Do not spray on an open flame or other ignition source. Protect from sunlight.

#### - Packaging compatibilities

Only packagings which are approved (e.g. acc. to the Dangerous Goods Regulations) may be used.

### 7.3 Specific end use(s)

See section 16 for a general overview.

## 8 Exposure controls/ Personal protection

### 8.1 Control parameters

Occupational exposure limit values (Workplace Exposure Limits)

Country	Name of agent	CAS No	Identifier	TWA [ppm]	TWA [mg/m <sup>3</sup> ]	STEL [ppm]	STEL [mg/m <sup>3</sup> ]	Ceiling-C [ppm]	Ceiling-C [mg/m <sup>3</sup> ]	Notation	Source
CA	butane	106-97-8	OEL (AB)	1,000							OHS Code
CA	butane	106-97-8	PEV/VEA	800	1,900						Regulation OHS
CA	n-butane	106-97-8	OEL (BC)			1,000				E	"BC Regulation"
CA	n-butane	106-97-8	OEL (ON-MoL)			1,000				E	MoL
CA	2-pentanone (methyl propyl ketone)	107-87-9	OEL (AB)	200	705	250	881				OHS Code
CA	methyl propyl ketone	107-87-9	OEL (ON-MoL)			150					MoL
CA	methyl propyl ketone	107-87-9	PEV/VEA	150	530						Regulation OHS
CA	methyl propyl ketone (2-pentanone)	107-87-9	OEL (BC)	150		250					"BC Regulation"
CA	1-methoxy-2-propyl acetate	108-65-6	OEL (BC)	50		75					"BC Regulation"
CA	propylene glycol monomethyl ether acetate	108-65-6	OEL (ON)	50	270						Regulation 833



# Safety Data Sheet

acc. to Hazardous Products Regulations (HPR)

## POR-15 TOPCOAT SAFET RED AEROSOL

Version number: GHS 3.0  
Replaces version of: 2023-07-03 (GHS 2)

Revision: 2024-02-15

### Occupational exposure limit values (Workplace Exposure Limits)

Country	Name of agent	CAS No	Identifier	TWA [ppm]	TWA [mg/m <sup>3</sup> ]	STEL [ppm]	STEL [mg/m <sup>3</sup> ]	Ceiling-C [ppm]	Ceiling-C [mg/m <sup>3</sup> ]	Notation	Source
CA	propylene glycol monomethyl ether acetate	108-65-6	OEL (ON-MoL)	50	270						MoL
CA	n-butyl acetate	123-86-4	OEL (AB)	150	713	200	950				OHS Code
CA	n-butyl acetate	123-86-4	OEL (BC)	50		150					"BC Regulation"
CA	n-butyl acetate	123-86-4	OEL (ON-MoL)	50		150					MoL
CA	n-butyl acetate	123-86-4	PEV/VEA	50		150					Regulation OHS
CA	ethylene glycol mono-n-propyl ether	2807-30-9	OEL (ON)	25	110					H	Regulation 833
CA	ethylene glycol mono-n-propyl ether	2807-30-9	OEL (ON-MoL)	25	110					H	MoL
CA	acetone	67-64-1	OEL (AB)	500	1,200	750	1,800				OHS Code
CA	acetone	67-64-1	OEL (BC)	250		500					"BC Regulation"
CA	acetone	67-64-1	OEL (ON-MoL)	250		500					MoL
CA	acetone	67-64-1	PEV/VEA	250		500					Regulation OHS
CA	barium sulfate	7727-43-7	OEL (AB)		10						OHS Code
CA	barium sulfate	7727-43-7	PEV/VEA		5					dust, i, noAsb, I ess1Sil	Regulation OHS
CA	barium sulfate	7727-43-7	OEL (BC)		5					i, noAsb, I ess1Sil	"BC Regulation"
CA	barium sulfate	7727-43-7	OEL (ON-MoL)		5					i, noAsb, I ess1Sil	MoL
CA	2-butanone (methyl ethyl ketone)	78-93-3	OEL (AB)	200	590	300	885				OHS Code
CA	methyl ethyl ketone (MEK)	78-93-3	OEL (BC)	50		100					"BC Regulation"

## POR-15 TOPCOAT SAFET RED AEROSOL

Version number: GHS 3.0  
Replaces version of: 2023-07-03 (GHS 2)

Revision: 2024-02-15

### Occupational exposure limit values (Workplace Exposure Limits)

Country	Name of agent	CAS No	Identifier	TWA [ppm]	TWA [mg/m <sup>3</sup> ]	STEL [ppm]	STEL [mg/m <sup>3</sup> ]	Ceiling-C [ppm]	Ceiling-C [mg/m <sup>3</sup> ]	Notation	Source
CA	methyl ethyl ketone (MEK)	78-93-3	OEL (ON-MoL)	200		300					MoL
CA	methyl ethyl ketone (MEK)	78-93-3	PEV/VEA	50	150	100	300				Regulation OHS

#### Notation

Ceiling-C	ceiling value is a limit value above which exposure should not occur
dust	as dust
E	explosive
H	absorbed through the skin
i	inhalable fraction
noAsb_less1S	contains no asbestos and less than 1% free crystalline silica
il	
STEL	short-term exposure limit: a limit value above which exposure should not occur and which is related to a 15-minute period (unless otherwise specified)
TWA	time-weighted average (long-term exposure limit): measured or calculated in relation to a reference period of 8 hours time-weighted average (unless otherwise specified)

### Relevant DNELs of components

Name of substance	CAS No	Endpoint	Threshold level	Protection goal, route of exposure	Used in	Exposure time
acetone	67-64-1	DNEL	1,210 mg/m <sup>3</sup>	human, inhalatory	worker (industry)	chronic - systemic effects
acetone	67-64-1	DNEL	2,420 mg/m <sup>3</sup>	human, inhalatory	worker (industry)	acute - local effects
acetone	67-64-1	DNEL	186 mg/kg bw/day	human, dermal	worker (industry)	chronic - systemic effects
propane	78-93-3	DNEL	600 mg/m <sup>3</sup>	human, inhalatory	worker (industry)	chronic - systemic effects
propane	78-93-3	DNEL	1,161 mg/kg bw/day	human, dermal	worker (industry)	chronic - systemic effects
glycol ether EP	2807-30-9	DNEL	36 mg/m <sup>3</sup>	human, inhalatory	worker (industry)	chronic - systemic effects
glycol ether EP	2807-30-9	DNEL	3.4 mg/kg bw/day	human, dermal	worker (industry)	chronic - systemic effects
PM acetate	108-65-6	DNEL	275 mg/m <sup>3</sup>	human, inhalatory	worker (industry)	chronic - systemic effects
PM acetate	108-65-6	DNEL	550 mg/m <sup>3</sup>	human, inhalatory	worker (industry)	acute - local effects
PM acetate	108-65-6	DNEL	796 mg/kg bw/day	human, dermal	worker (industry)	chronic - systemic effects
METHYL PROPYL KETONE	107-87-9	DNEL	209.4 mg/m <sup>3</sup>	human, inhalatory	worker (industry)	chronic - systemic effects
METHYL PROPYL KETONE	107-87-9	DNEL	4,784 mg/m <sup>3</sup>	human, inhalatory	worker (industry)	acute - systemic effects

## POR-15 TOPCOAT SAFET RED AEROSOL

Version number: GHS 3.0  
Replaces version of: 2023-07-03 (GHS 2)

Revision: 2024-02-15

Relevant DNELs of components						
Name of substance	CAS No	Endpoint	Threshold level	Protection goal, route of exposure	Used in	Exposure time
METHYL PROPYL KETONE	107-87-9	DNEL	19.89 mg/kg bw/day	human, dermal	worker (industry)	chronic - systemic effects

Relevant PNECs of components						
Name of substance	CAS No	Endpoint	Threshold level	Organism	Environmental compartment	Exposure time
acetone	67-64-1	PNEC	10.6 mg/l	aquatic organisms	freshwater	short-term (single instance)
acetone	67-64-1	PNEC	1.06 mg/l	aquatic organisms	marine water	short-term (single instance)
acetone	67-64-1	PNEC	100 mg/l	aquatic organisms	sewage treatment plant (STP)	short-term (single instance)
acetone	67-64-1	PNEC	30.4 mg/kg	aquatic organisms	freshwater sediment	short-term (single instance)
acetone	67-64-1	PNEC	3.04 mg/kg	aquatic organisms	marine sediment	short-term (single instance)
acetone	67-64-1	PNEC	29.5 mg/kg	terrestrial organisms	soil	short-term (single instance)
propane	78-93-3	PNEC	55.8 mg/l	aquatic organisms	freshwater	short-term (single instance)
propane	78-93-3	PNEC	55.8 mg/l	aquatic organisms	marine water	short-term (single instance)
propane	78-93-3	PNEC	709 mg/l	aquatic organisms	sewage treatment plant (STP)	short-term (single instance)
propane	78-93-3	PNEC	284.7 mg/kg	aquatic organisms	freshwater sediment	short-term (single instance)
propane	78-93-3	PNEC	284.7 mg/kg	aquatic organisms	marine sediment	short-term (single instance)
propane	78-93-3	PNEC	22.5 mg/kg	terrestrial organisms	soil	short-term (single instance)
glycol ether EP	2807-30-9	PNEC	0.1 mg/l	aquatic organisms	freshwater	short-term (single instance)
glycol ether EP	2807-30-9	PNEC	0.01 mg/l	aquatic organisms	marine water	short-term (single instance)
glycol ether EP	2807-30-9	PNEC	10 mg/l	aquatic organisms	sewage treatment plant (STP)	short-term (single instance)
glycol ether EP	2807-30-9	PNEC	0.594 mg/kg	aquatic organisms	freshwater sediment	short-term (single instance)
glycol ether EP	2807-30-9	PNEC	0.059 mg/kg	aquatic organisms	marine sediment	short-term (single instance)



## POR-15 TOPCOAT SAFET RED AEROSOL

Version number: GHS 3.0  
Replaces version of: 2023-07-03 (GHS 2)

Revision: 2024-02-15

Relevant PNECs of components						
Name of substance	CAS No	Endpoint	Threshold level	Organism	Environmental compartment	Exposure time
glycol ether EP	2807-30-9	PNEC	0.06 mg/kg	terrestrial organisms	soil	short-term (single instance)
PM acetate	108-65-6	PNEC	0.635 mg/l	aquatic organisms	freshwater	short-term (single instance)
PM acetate	108-65-6	PNEC	0.064 mg/l	aquatic organisms	marine water	short-term (single instance)
PM acetate	108-65-6	PNEC	100 mg/l	aquatic organisms	sewage treatment plant (STP)	short-term (single instance)
PM acetate	108-65-6	PNEC	3.29 mg/kg	aquatic organisms	freshwater sediment	short-term (single instance)
PM acetate	108-65-6	PNEC	0.329 mg/kg	aquatic organisms	marine sediment	short-term (single instance)
PM acetate	108-65-6	PNEC	0.29 mg/kg	terrestrial organisms	soil	short-term (single instance)
METHYL PROPYL KETONE	107-87-9	PNEC	0.11 mg/l	aquatic organisms	freshwater	short-term (single instance)
METHYL PROPYL KETONE	107-87-9	PNEC	0.011 mg/l	aquatic organisms	marine water	short-term (single instance)
METHYL PROPYL KETONE	107-87-9	PNEC	0.25 mg/l	aquatic organisms	sewage treatment plant (STP)	short-term (single instance)
METHYL PROPYL KETONE	107-87-9	PNEC	0.717 mg/kg	aquatic organisms	freshwater sediment	short-term (single instance)
METHYL PROPYL KETONE	107-87-9	PNEC	0.072 mg/kg	aquatic organisms	marine sediment	short-term (single instance)
METHYL PROPYL KETONE	107-87-9	PNEC	0.079 mg/kg	terrestrial organisms	soil	short-term (single instance)

### 8.2 Exposure controls

Appropriate engineering controls

General ventilation.

Individual protection measures (personal protective equipment)

Eye/face protection

Wear eye/face protection.

Skin protection

- Hand protection

Wear protective gloves.

- Other protection measures

Take recovery periods for skin regeneration. Preventive skin protection (barrier creams/ointments) is recommended. Wash hands thoroughly after handling.

## POR-15 TOPCOAT SAFET RED AEROSOL

Version number: GHS 3.0  
Replaces version of: 2023-07-03 (GHS 2)

Revision: 2024-02-15

### Respiratory protection

During spraying wear suitable respiratory equipment.

### Environmental exposure controls

Use appropriate container to avoid environmental contamination. Keep away from drains, surface and ground water.

## 9 Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

Physical state	liquid, solid, gaseous (spray aerosol)
Color	not determined
Odor	characteristic
Melting point/freezing point	not determined
Boiling point or initial boiling point and boiling range	-161.5 °C at 1,013 hPa
Flammability	flammable aerosol in accordance with GHS criteria
Lower and upper explosion limit	1.5 vol% - 15 vol%
Flash point	-88.6 °C at 1,013 hPa
Auto-ignition temperature	256 °C (auto-ignition temperature (liquids and gases))
Decomposition temperature	not relevant
pH (value)	not determined
Kinematic viscosity	not relevant
Solubility(ies)	not determined

### Partition coefficient

Partition coefficient n-octanol/water (log value)	this information is not available
---	-----------------------------------

Vapor pressure	240 hPa at 20 °C
----------------	------------------

### Density and/or relative density



# Safety Data Sheet

acc. to Hazardous Products Regulations (HPR)

## POR-15 TOPCOAT SAFET RED AEROSOL

Version number: GHS 3.0  
Replaces version of: 2023-07-03 (GHS 2)

Revision: 2024-02-15

Density	not determined
Relative vapour density	information on this property is not available

Particle characteristics	not relevant (aerosol)
--------------------------	------------------------

### 9.2 Other information

Information with regard to physical hazard classes

Aerosols

- Components (flammable)	80 %
--------------------------	------

Other safety characteristics

Solid content	7 %
Propellant content	13 %

## 10 Stability and reactivity

### 10.1 Reactivity

Concerning incompatibility: see below "Conditions to avoid" and "Incompatible materials". The mixture contains reactive substance(s). Risk of ignition.

### 10.2 Chemical stability

See below "Conditions to avoid".

### 10.3 Possibility of hazardous reactions

No known hazardous reactions.

### 10.4 Conditions to avoid

Do not spray on an open flame or other ignition source. Keep away from heat.

Hints to prevent fire or explosion

Protect from sunlight.

### 10.5 Incompatible materials

Oxidizers

### 10.6 Hazardous decomposition products

Reasonably anticipated hazardous decomposition products produced as a result of use, storage, spill and heating are not known. Hazardous combustion products: see section 5.

## POR-15 TOPCOAT SAFET RED AEROSOL

Version number: GHS 3.0  
Replaces version of: 2023-07-03 (GHS 2)

Revision: 2024-02-15

### 11 Toxicological information

#### 11.1 Information on toxicological effects

Test data are not available for the complete mixture.

##### Classification procedure

The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

##### Classification acc. to GHS

##### Acute toxicity

Shall not be classified as acutely toxic.

##### Acute toxicity estimate (ATE) of components

Name of substance	CAS No	Exposure route	ATE
glycol ether EP	2807-30-9	dermal	1,100 mg/kg
METHYL PROPYL KETONE	107-87-9	oral	>1,600 mg/kg

##### Skin corrosion/irritation

Shall not be classified as corrosive/irritant to skin.

##### Serious eye damage/eye irritation

Causes serious eye irritation.

##### Respiratory or skin sensitization

Shall not be classified as a respiratory or skin sensitizer.

##### Germ cell mutagenicity

May cause genetic defects.

##### Carcinogenicity

May cause cancer.

##### Reproductive toxicity

Shall not be classified as a reproductive toxicant.

##### Specific target organ toxicity - single exposure

May cause drowsiness or dizziness.

##### Specific target organ toxicity - repeated exposure

Shall not be classified as a specific target organ toxicant (repeated exposure).

##### Aspiration hazard

Shall not be classified as presenting an aspiration hazard.

## POR-15 TOPCOAT SAFET RED AEROSOL

Version number: GHS 3.0  
Replaces version of: 2023-07-03 (GHS 2)

Revision: 2024-02-15

### 12 Ecological information

#### 12.1 Toxicity

Harmful to aquatic life.

##### Aquatic toxicity (acute) of components

Name of substance	CAS No	Endpoint	Value	Species	Exposure time
acetone	67-64-1	LC50	8,120 mg/l	fish	96 h
propane	78-93-3	LC50	2,993 mg/l	fish	96 h
propane	78-93-3	EC50	308 mg/l	aquatic invertebrates	48 h
propane	78-93-3	ErC50	2,029 mg/l	algae	96 h
n-butane	106-97-8	LC50	49.9 mg/l	fish	96 h
n-butane	106-97-8	EC50	19.37 mg/l	algae	96 h
glycol ether EP	2807-30-9	LC50	>5,000 mg/l	fish	96 h
glycol ether EP	2807-30-9	ErC50	>100 mg/l	algae	72 h
glycol ether EP	2807-30-9	EC50	>100 mg/l	algae	72 h
n-butyl acetate	123-86-4	LC50	18 mg/l	fish	96 h
n-butyl acetate	123-86-4	EC50	18 mg/l	fish	96 h
n-butyl acetate	123-86-4	ErC50	335 mg/l	algae	24 h
PM acetate	108-65-6	LC50	180 mg/l	fish	96 h
PM acetate	108-65-6	EC50	>500 mg/l	aquatic invertebrates	48 h
PM acetate	108-65-6	ErC50	>1,000 mg/l	algae	96 h
METHYL PROPYL KETONE	107-87-9	LC50	1,240 mg/l	fish	96 h
METHYL PROPYL KETONE	107-87-9	EC50	>110 mg/l	aquatic invertebrates	48 h
METHYL PROPYL KETONE	107-87-9	ErC50	>150 mg/l	algae	72 h

#### 12.2 Persistence and degradability

Data are not available.

#### 12.3 Bioaccumulative potential

Data are not available.

#### 12.4 Mobility in soil

Data are not available.

#### 12.5 Results of PBT and vPvB assessment

According to the results of its assessment, this substance is not a PBT or a vPvB. Does not contain a PBT-/vPvB-substance at a concentration of  $\geq 0.1\%$ .

## POR-15 TOPCOAT SAFET RED AEROSOL

Version number: GHS 3.0  
Replaces version of: 2023-07-03 (GHS 2)

Revision: 2024-02-15

### 12.6 Endocrine disrupting properties

Does not contain an endocrine disruptor (ED) in a concentration of  $\geq 0.1\%$ .

### 12.7 Other adverse effects

Data are not available.

## 13 Disposal considerations

### 13.1 Waste treatment methods

Sewage disposal-relevant information

Do not empty into drains. Avoid release to the environment. Refer to special instructions/safety data sheets.

Waste treatment of containers/packages

Only packagings which are approved (e.g. acc. to the Dangerous Goods Regulations) may be used. Completely emptied packages can be recycled. Handle contaminated packages in the same way as the substance itself.

#### Remarks

Please consider the relevant national or regional provisions. Waste shall be separated into the categories that can be handled separately by the local or national waste management facilities.

## 14 Transport information

### 14.1 UN number

UN RTDG	UN 1950
IMDG-Code	UN 1950
ICAO-TI	UN 1950

### 14.2 UN proper shipping name

UN RTDG	AEROSOLS
IMDG-Code	AEROSOLS
ICAO-TI	Aerosols, flammable

### 14.3 Transport hazard class(es)

UN RTDG	2.1
IMDG-Code	2.1
ICAO-TI	2.1

### 14.4 Packing group

not assigned

### 14.5 Environmental hazards

non-environmentally hazardous acc. to the dangerous goods regulations

### 14.6 Special precautions for user

There is no additional information.

### 14.7 Transport in bulk according to IMO instruments

The cargo is not intended to be carried in bulk.

## POR-15 TOPCOAT SAFET RED AEROSOL

Version number: GHS 3.0  
Replaces version of: 2023-07-03 (GHS 2)

Revision: 2024-02-15

### Information for each of the UN Model Regulations

#### **Transport information - National regulations - Additional information (UN RTDG)**

UN number	1950
Class	2.1
Danger label(s)	2.1



Special provisions (SP)	63, 190, 277, 327, 344, 381, 959 (UN RTDG)
Excepted quantities (EQ)	E0 (UN RTDG)
Limited quantities (LQ)	1 L (UN RTDG)

#### **International Maritime Dangerous Goods Code (IMDG) - Additional information**

Marine pollutant	-
Danger label(s)	2.1



Special provisions (SP)	63, 190, 277, 327, 344, 381, 959
Excepted quantities (EQ)	E0
Limited quantities (LQ)	1 L
EmS	F-D, S-U
Stowage category	-

#### **International Civil Aviation Organization (ICAO-IATA/DGR) - Additional information**

Danger label(s)	2.1
-----------------	-----



Special provisions (SP)	A145, A167
Excepted quantities (EQ)	E0
Limited quantities (LQ)	30 kg

### 15 Regulatory information

#### **15.1 Safety, health and environmental regulations specific for the product in question**

##### **National regulations (United States)**

##### **Superfund Amendment and Reauthorization Act (SARA TITLE III )**

- The List of Extremely Hazardous Substances and Their Threshold Planning Quantities (EPCRA Section 302, 304)

none of the ingredients are listed



# Safety Data Sheet

acc. to Hazardous Products Regulations (HPR)

## POR-15 TOPCOAT SAFET RED AEROSOL

Version number: GHS 3.0  
Replaces version of: 2023-07-03 (GHS 2)

Revision: 2024-02-15

### - Specific Toxic Chemical Listings (EPCRA Section 313)

none of the ingredients are listed

### Comprehensive Environmental Response, Compensation, and Liability Act (CERCLA)

#### - List of Hazardous Substances and Reportable Quantities (CERCLA section 102a) (40 CFR 302.4)

Name of substance	CAS No	Remarks	Statutory code	Final RQ pounds (Kg)
acetone	67-64-1		4	5000 (2270)
propane	78-93-3		4	5000 (2270)
n-butyl acetate	123-86-4		1	5000 (2270)

#### Legend

- 1 "1" indicates that the statutory source is section 311(b)(2) of the Clean Water Act
- 4 "4" indicates that the source is section 3001 of the Resource Conservation and Recovery Act (RCRA)

### Clean Air Act

Name of substance	CAS No	Type of registration	Basis for listing	Threshold quantity (lbs)
n-butane	106-97-8	Flammable substance	f	10000

#### Legend

- f Flammable gas.

### Right to Know Hazardous Substance List

#### - Cleaning Product Right to Know Act Substance List (CA-RTK)

Name of substance	CAS No	Functionality	Authoritative Lists
acetone	67-64-1		ATSDR Neurotoxicants
propane	78-93-3		ATSDR Neurotoxicants CA TACs OEHHA RELs
n-butane	106-97-8		EC Annex VI CMRs - Cat. 1A EC Annex VI CMRs - Cat. 1B
glycol ether EP			CA TACs

#### - Toxic or Hazardous Substance List (MA-TURA)

Name of substance	CAS No	DEP CODE	PBT / HHS / LHS	PBT / HHS Threshold	De Minimis Concentration Threshold
acetone	67-64-1				1.0 %
propane	78-93-3				1.0 %
n-butyl acetate	123-86-4		LHS		1.0 %
glycol ether EP		1022			1.0 %





# Safety Data Sheet

acc. to Hazardous Products Regulations (HPR)

## POR-15 TOPCOAT SAFET RED AEROSOL

Version number: GHS 3.0  
Replaces version of: 2023-07-03 (GHS 2)

Revision: 2024-02-15

### - Hazardous Substances List (MN-ERTK)

Name of substance	CAS No	References	Remarks
acetone	67-64-1	A, N, O	
propane	78-93-3	A, N, O	
n-butyl acetate	123-86-4	A, O	
n-butane		N	
METHYL PROPYL KETONE	107-87-9	A, N, O	

#### Legend

- A American Conference of Governmental Industrial Hygienists (ACGIH), "Threshold Limit Values for Chemical Substances and Physical Agents and Biological Exposure Indices for 1992-93", available from ACGIH  
N National Institute for Occupational Safety and Health (NIOSH), "Recommendations for Occupational Safety and Health Standards," August 1988, available from NIOSH, Publications Dissemination Office, Division of Standards Development and Technology Transfer  
O Occupational Safety and Health Administration (OSHA), Safety and Health Standards, Code of Federal Regulations, title 29, part 1910, subpart Z, "Toxic and Hazardous Substances, 1990." General information: Minnesota Department of Labor and Industry, Occupational Safety and Health Division

### - Hazardous Substance List (NJ-RTK)

Name of substance	CAS No	Remarks	Classifications
acetone	67-64-1		F3
propane	78-93-3		F3
n-butyl acetate	123-86-4		F3
n-butane	106-97-8		F4
glycol ether EP			
METHYL PROPYL KETONE	107-87-9		F3

#### Legend

- F3 Flammable - Third Degree  
F4 Flammable - Fourth Degree

### - Hazardous Substance List (Chapter 323) (PA-RTK)

Name acc. to inventory	CAS No	Classification
2-PROPANONE	67-64-1	E
2-BUTANONE	78-93-3	E
ACETIC ACID, BUTYL ESTER	123-86-4	E
BUTANE	106-97-8	
GLYCOL ETHERS		E
2-PENTANONE	107-87-9	

#### Legend

- E Environmental hazard



# Safety Data Sheet

acc. to Hazardous Products Regulations (HPR)

## POR-15 TOPCOAT SAFET RED AEROSOL

Version number: GHS 3.0  
Replaces version of: 2023-07-03 (GHS 2)

Revision: 2024-02-15

### - Hazardous Substance List (RI-RTK)

Name of substance	CAS No	References
acetone	67-64-1	T, F
propane	78-93-3	T, F
n-butyl acetate	123-86-4	T, F
n-butane	106-97-8	T, F
METHYL PROPYL KETONE	107-87-9	T
METHYL PROPYL KETONE	107-87-9	T

#### Legend

F Flammability (NFPA®)  
T Toxicity (ACGIH®)

### California Environmental Protection Agency (Cal/EPA): Proposition 65 - Safe Drinking Water and Toxic Enforcement Act of 1987

none of the ingredients are listed

### Industry or sector specific available guidance(s)

#### NPCA-HMIS® III

Hazardous Materials Identification System. American Coatings Association.

Category	Rating	Description
Chronic	*	chronic (long-term) health effects may result from repeated overexposure
Health	2	temporary or minor injury may occur
Flammability	4	material that rapidly or completely vaporizes at atmospheric pressure and normal ambient temperature or that is readily dispersed in air and burn readily
Physical hazard	0	material that is normally stable, even under fire conditions, and will not react with water, polymerize, decompose, condense, or self-react. Non-explosive
Personal protection	-	

#### NFPA® 704

National Fire Protection Association: Standard System for the Identification of the Hazards of Materials for Emergency Response (United States).

Category	Degree of hazard	Description
Flammability	4	material that rapidly or completely vaporizes at atmospheric pressure and normal ambient temperature or that is readily dispersed in air and burn readily
Health	0	material that, under emergency conditions, would offer no hazard beyond that of ordinary combustible material
Instability	0	material that is normally stable, even under fire conditions
Special hazard		



# Safety Data Sheet

acc. to Hazardous Products Regulations (HPR)

## POR-15 TOPCOAT SAFET RED AEROSOL

Version number: GHS 3.0  
Replaces version of: 2023-07-03 (GHS 2)

Revision: 2024-02-15

### National regulations (Canada)

#### Domestic Substances List (DSL)/Non-domestic Substances List (NDSL)

All ingredients are listed or exempt from listing.

### 15.2 Chemical Safety Assessment

Chemical safety assessments for substances in this mixture were not carried out.

## 16 Other information

### Key literature references and sources for data

Hazardous Products Regulations (HPR)

SOR/2022-272: Regulations Amending the Hazardous Products Regulations (GHS, Seventh Revised Edition)

UN Recommendations on the Transport of Dangerous Good. International Maritime Dangerous Goods Code (IMDG).  
Dangerous Goods Regulations (DGR) for the air transport (IATA).

### Classification procedure

Physical and chemical properties: The classification is based on tested mixture.

Health hazards, Environmental hazards: The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

### Disclaimer

This information is based upon the present state of our knowledge. This SDS has been compiled and is solely intended for this product.